




WEICON Solutions for the

# Mining Industry





# **Plastic Metal**

WEICON Plastic Metals are two-component epoxy resin systems. They are ideal for providing fast, cost-effective and durable repairs and coatings for many different types of material.



## **WEICON A**

- for general repairs
- pasty, steel-filled

0,5 kg **1**0000005

2,0 kg 10000020

## **WEICON HB 300**

- steel-filled
- pasty, spreadable
- high-temperature-resistant from -35°C to +280°C (-31°F up to +672,8°F)

1,0 kg 10450010

## **WEICON Ceramic BL**

- for lining of heavily stressed parts
- liquid
- high-temperature-resistant from -35°C up to +180°C (-31°F up to +356°F)

0,5 kg **1**0400005

2,0 kg 10400020





## **Plastic Metal**

#### **WEICON SF**

- ideal for quick repairs
- pasty

2,0 kg 🎸 0,5 kg 10250005 10250020

#### **WEICON WR2**

- · highly abrasion-resistant
- pasty
- is particularly suitable for areas where the processing of casting compounds is not possible

10350005


2,0 kg 10350020

#### **WEICON WP**

- extremely high resistance against abrasion and wear
- filled with ceramic beads
- suitable for the protection of heavily used surfaces

2,0 kg 10490020 10490100

10,0 kg 🧭







# **WEICON CBC** Chocking Backing Compound

Specially developed for the shimming and backfilling of systems difficult to align.

- liquid and self-levelling
- vibration resistant
- break and impact resistant

3.0 kg (2,0 l) 10110030

10.0 kg (6,6 l) 😿 10110110



European Exhibition Award for creativity and innovation









# **Repair Sticks**

The simple solution for all repair and maintenance works. Easy to use. Always the right amount, even for small repairs.









# Steel NSF Certified to

- fast-curing, steel-filled
- NSF approval, can be used in drinking water areas





#### **Titanium**

- high-temperature-resistant up to +280°C (+536°F)
- wear-resistant, titanium-filled





# **WEICON Belt Repair Kit**

#### **WEICON Belt Repair Kit**

#### **Content:**

**Urethane 80 Putty** 0.5 kg **Primer M 100** 250 ml **Primer S 300** 250 ml **Cleaner Spray S** 500 ml





## **WEICON Urethanes**

Flexible casting and coating resin with high impact strength and abrasion resistance.

## **Urethane 80**

- shore hardness A 80
- liquid and self-levelling casting and coating mass

0,5 kg 10518005

#### **Urethane 80 Putty**

- shore hardness A 80
- flexible and wear-resistant coating resin with high impact strength and abrasion resistance

0,5 kg 10518505





## **Anti-Seize Assembly Pastes**

All kinds of influencing factors, e.g. moisture, temperature or friction, repeatedly lead to corrosion damage, seizure and wear on machines and installations.

Extensive repair and maintenance works at considerable costs are the consequence.

Especially under extreme conditions of application, e.g.

- · high operation temperatures
- · high pressure loads
- outdoor weather conditions

such consequences frequently occur.







#### **Anti-Seize**

- long-lasting protection against corrosion, seizure and wear
- high-temperature-resistant up to +1.200°C (+2.192°F)
- exceptionally good separating effect



500 g 26000050

Brush top can

10 kg 26000910

## **Copper Paste**

 protecting, separating and lubricating agent for highly stressed parts in high-temperature applications

200 ml 26200200 Press pack 500 g 26200050

Brush top can

10 kg 26200910 Bucket

# Anti-Seize Nickel

- for extreme conditions
- protection against corroding and corrosive solvents
- can be applied at a large temperature range between -30°C to +1450°C (-22°F to 2642°F)

120 g 26050012
Brush top can

400 g 26050040
Cartridge

1,0 kg 26050100 Can 10 kg 26050910 Bucket

## **Allround Lubricant**

WEICON Allround Lubricants provide longlasting protection against friction and wear.

#### AL-M

- strong adhesion
- high-pressure-resistant
- with MoS<sub>2</sub>

400 g 26400040 Cartridge

1,0 kg 26400100 Can 5,0 kg 26400500

25,0 kg 25,0 kg 26400925







# **Technical Sprays and Liquids**

Technical sprays and liquids are employed in almost all industrial sectors. They are used for the maintenance and protection of surfaces, for cleaning and degreasing, lubricating, releasing and separating, and are an essential part in daily work.



#### **Sealant and Adhesive Remover**

- removes residues of hardened sealants and adhesives
- removal of old paints and lacquers



51 🧭

## **Cleaner Spray S**

- powerful
- evaporates without leaving residues
- leaves no oily residues

500 ml 🧭 11202500

15200005









#### **Rust Converter**

- rust converter and base coat in one process
- protects against



#### **Rust Shock**

· the 'chemical wrench'

Multi-Spra

- free of mineral oil, grease and silicone
- · loosens threaded joints within a very short time



#### **Rust Protection 2000 PLUS**

· high corrosion and weathering resistance

11251400 11251550 15251005



400 ml 🥑 11013400 silver arev

# Zinc Spray



- long-term cathodic corrosion protection for all metal surfaces
- · resistant protective layer, even under extreme weather and environmental conditions
- >550 hours salt spray test according to DIN EN ISO 9227

400 ml 🥑 11000400



# Zinc Spray bright grade

- long-term cathodic corrosion protection
- · bright colour shade matching hot-dip galvanization
- >550 hours salt spray test according to DIN EN ISO 9227

400 ml 🧭 11001400

## **Chain and Rope Lube Spray**

- pressure-resistant
- strongly adherent
- · for highly stressed chain and wire ropes

400 ml 🎸 11500400

## **Anti-Spatter Spray**

- · protects work pieces and welding nozzles
- for optimum welding results
- silicone-free



51 😿



Connec

Zink-Spray





# **Technical Sprays and Liquids**

#### **Belt Dressing Spray**

- prevents belt slip
- for all kinds of drive belts
- can also be used during ongoing operation

400 ml 🧭 11511400

## **Smoke Detector Test Spray**

- evaporates without leaving residues
- silicone-free

150 ml 😿 250 ml 😿 11640150 11640250

## Pneuma-Lube

- · lubricant for pneumatic equipment
- high content of PTFE
- excellent weathering resistance
- temperature resistance from

-50°C up to +210°C (-58°F up to +410°F)









# **Crack Testing Agent**









Cleaner, Penetrant and Developer for the non-destructive material testing by way of colour penetration process

## Cleaner/Remover 1 & 3

Material-neutral special cleaner for the colour penetration test. Suitable for metals, many plastics, ceramic materials, glass etc. The suitability for plastic has to be tested in advance.

500 ml 🥑 11692500

# Penetrant 2



Red diffusion agent with excellent capillary action for the nondestructive material testing - washes off with solvent. Suitable for metals, many plastics, ceramic materials, glass etc. The suitability for plastic has to be tested in advance.

500 ml 🥑 11690500

# Developer 4

Colourfast special developer on solvent basis for colour penetration tests. Suitable for metals, many plastics, ceramic materials, glass etc. The suitability for plastic has to be tested in advance.



Standards and regulations Sample-tested according to DIN EN ISO 3452-2. Low sulphur and halogen content, according to DIN EN ISO 3452-2 and ASME-Code, Section V. Article 6. AREVA NP TLV 9017.





## **Elastic Adhesives and Sealants**

Elastic adhesives and sealants are used in many areas of industrial production and assembly today. They combine the advantages of adhesive bonding and sealing technology and are used wherever the elasticity and the sealing of a joint are the most important requirements.

## Flex 310 M® Classic

- suitable for universal use
- free of silicone, isocyanate, halogens or solvents
- ISEGA and LFGB certificated



310 ml 🕥

310 ml (13304310)



#### Black-Seal

Sealing of a cylinder head

- extremely resistant against oil and grease
- high-temperature-resistant from
   -50°C up to +280°C (-58°F up to +536°F)

200 ml 13051200 Press pack 310 ml 310 13051310 Cartridge



## **GMK - Rubber Metal Adhesive**

GMK products are various contact adhesives for bonding rubber and metal.

## **GMK 2510**

- strong
- · permanently elastic
- temperature-resistant



Working package (consisting of 300 g adhesive and 24 g activator)

690 g **o** 

Working package (consisting of 650 g adhesive and 40 g activator)





# **WEICONLOCK® Anaerobic Adhesives and Sealants**

Especially made for economical threadlocking, retaining and sealing of threaded, cylindrical and pipe assemblies. A vibrationand impact resistant adhesive bond is formed after curing, which is resistant to chemicals, solvents and temperatures of -60°C up to +200°C (-76°F up to 392°F).



#### AN 302-43

- threadlocking
- thread connections up to M 36
- drinking water and DVGW approval

higher viscosity medium strength disassembly with normal tools

50 ml 😿 30243150



## AN 302-70



- · locking of threads and stud bolts
- thread connections up to M 36
- drinking water and DVGW approval

medium viscosity high strength hard to disassemble

50 ml 🧭 30270150



# AN 305-77







- · sealing of threaded pipes and fittings
- drinking water and DVGW approval

high viscosity high strength hard to disassemble

50 ml 🧭 30577150 Tested and safety-evaluated by the Federal Institute for Material Research and Testing according to information sheet M 034-1 List of nonmetallic materials supporting document to code of practice M 034e "Oxygen" (DGUV Information 213-074)





# **Contact Cyanoacrylate Adhesive**

WEICON Contact are solvent-free instant adhesives. They bond various materials, such as metal, glass, wood, plastic, ceramic, leather and rubber, within seconds.

#### **VA 100**

- · cyanoacrylate Adhesive for rubber and plastics
- medium viscosity
- slightly longer cure time

30 g 🧭 12050030



## VA 250 Black

- · high peel and impact resistance
- · residual elasticity after curing
- · high-temperature-resistant from -55°C up to +140°C (-67°F up to +284°F)

30 g 🍯 12600030





## **WEICON O-Ring Bonding Set**

#### **Content:**

12603012 Contact VA 30 Black 12 g 11207150 Surface Cleaner 150 ml 12450010 Contact Primer 10 ml 99950243 WEICON Cutter-knife

1 m round cord (NBR) each: Ø 2, 3, 4, 6 and 8 mm






# Plast-o-Seal®

# **Permanently Plastic Universal Sealant**

- no evaporation of solvents
- immediate assembly possible



230 g 🍯 Press pack

300 g 🎷 30000300 Cartridge











#### **WEICON GmbH & Co. KG** (Headquarters)

Königsberger Str. 255 · DE-48157 Münster P.O. Box 84 60 · DE-48045 Münster Germany phone +49 (0) 251 9322 0 info@weicon.de

#### **WEICON Middle East L.L.C.**

Jebel Ali Ind Area 1 P.O. Box 118 216 · Dubai United Arab Emirates phone +971 4 880 25 05 info@weicon.ae

#### WEICON Inc.

20 Steckle Place · Unit 20 Kitchener · Ontario N2E 2C3 · Canada phone +1 877 620 8889 info@weicon.ca

# WEICON Kimya Sanayi Tic. Ltd. Şti. Orhan Gazi Mahallesi 16. Yol Sokak No: 6

34517 Hadımköy-Esenyurt · Istanbul Turkey phone +90 (0) 212 465 33 65 info@weicon.com.tr

## **WEICON Romania SRL**

Orhan Gazi Mahallesi 16. Yol Sokak No: 6 Str. Podului Nr. 1 547176 Budiu Mic (Targu Mures) · Romania phone +40 (0) 3 65 730 763 office@weicon.com

WEICON SA (Pty) Ltd Unit No. D1 · Enterprise Village Capricorn Drive · Capricorn Park Muizenberg 7945 (Cape Town) · South Africa phone +27 (0) 21 709 0088 info@weicon.co.za

#### **WEICON South East Asia Pte Ltd**

7 Soon Lee Street #01-11 iSPACE · Singapore 627608 Phone (+65) 6710 7671 info@weicon.com.sg

# WEICON Czech Republic s.r.o. Teplická 305

CZ-417 61 Teplice-Bystřany Česká republika phone +42 (0) 417 533 013 info@weiconcz.cz

#### WEICON Ibérica S.L.

Av. de Somosierra 18, Nave 6 San Sebastián de los Reyes 28703 Madrid · Spain phone +34 (0) 914 7997 34 info@weicon.es

## WEICON Italia S.r.L.

Via Capitano del Popolo, 20 16156 Genova · Italy phone +39 (0) 329 235 9592 info@weicon.it

www.weicon.com

