

W 44 T®-Fluid



Nonfood Compounds
Program Listed H1
Registration 152619

Multifunctional oil for sensitive areas | NSF registration

W44T Fluid is a physiologically harmless multifunctional oil and has an NSF registration for the food industry. Therefore, it can be used in the food and beverage industry and in the pharmaceuticals and cosmetics industries. The resin- and acid-free oil unites lubrication, water displacement, corrosion protection, cleaning and conservation in one product due to a special active ingredient formula and excellent penetration properties. W44T Fluid loosens seized screw connections, bolts, fittings, locks and valves, and penetrates and dissolves rust. It repels humidity from electrical contacts, prevents leakage currents, and makes it easier to start wet motors. The oil eliminates squeaky and creaky noises on hinges, guides, bearings, and all types of joints and couplings. It cleans soiled metal surfaces and leaves a long-lasting razorthin film, which does not smear or stick and does not attract dust and protects and maintains all types of tools, machines, and electrical and mechanical precision devices. Due to its special formula and the resulting NSF registration, W 44 T Fluid can contribute towards the improvement of workplace safety and health protection.

Approvals / Guidelines

MIL-Spec complies with

MIL-C-1258

Application

Spray the part to be cleaned generously and allow product to take effect; wipe with a clean cloth, if required. Repeat, if necessary. Protect plastic and varnished surfaces.

Storage

Container is pressurised. Protect from direct sunlight and temperatures above +50 °C.

Instructions for use

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

Available sizes

10039113 W 44 T®-Fluid, 400 ml, beige
10059934 W 44 T®-Fluid, 400 ml, beige

To the product detail page:



Technical data

Odour	nearly odourless
Colour	beige
Specific properties	loosens, lubricates, cleans and protects
Silicone-free	yes
Minimum shelf life at room temperature	24 mon.
Kinematic viscosity (40°C)	21 mm ² /s
Kinematic viscosity (100°C)	4 mm ² /s
Temperature resistance	-20°C to +150°C

Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON Middle East L.L.C.
United Arab Emirates
phone +971 4 880 25 05
info@weicon.ae

WEICON Inc.
Canada
phone +1 877 620 8889
info@weicon.ca

WEICON Czech Republic s.r.o.
Czech Republic
phone +42 (0) 417 533 013
info@weicon.cz

WEICON Iberica S.L.
Spain
phone +34 (0) 914 7997 34
info@weicon.es

WEICON GmbH & Co. KG
(Headquarters) Germany
phone +49 (0) 251 9322 0
info@weicon.de

WEICON Italia S.r.l.
Italy
phone +39 (0) 010 2924 871
info@weicon.it

WEICON Romania SRL
Romania
phone +40 (0) 3 65 730 763
office@weicon.com

WEICON SA (Pty) Ltd
South Africa
phone +27 (0) 21 709 0088
info@weicon.co.za

WEICON South East Asia Pte Ltd
Singapore
Phone (+65) 6710 7671
info@weicon.com.sg

WEICON Kimya Sanayi Tic. Ltd. Şti.
Türkiye
phone +90 (0) 212 465 33 65
info@weicon.com.tr