

# Mould Release Agent



## Silicone-free sliding and release agent

High-grade combination of active ingredients with high gliding effect, consisting of pure natural products. Prevents the adhesion to plastics, moulds, metals and tools. WEICON Mould Release Agent can be used in plastic processing and for spraying, pressing, and vacuum deforming.

### Characteristics

Specific properties	silicone-free
Colour	colourless, transparent
Odour	solvent
suitable for processing with	Pump Dispenser   WSD 400   WPS 1500
Minimum shelf life at room temperature	24 mon.
Thermal parameters	
Temperature resistance	-20°C to +130°C
Approvals / Guidelines	
MIL-Spec	complies with
	A-A-59281

### Surface Pre-Treatment

Surfaces must be dry, clean and free of grease.

### Application

Apply Mould Release Agent evenly with a brush or cloth or by spraying (e.g. with an Air Pressure Can).

### Storage

Keep tightly closed in original packaging. Protect from direct sunlight. The storage temperature must not exceed +50 °C. Keep container in a cool, well-ventilated place. Store in a dry place.

### Instructions for use

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our EC safety data sheets ([www.weicon.com](http://www.weicon.com)) must be observed.

### Accessories

10000393	Adapter for WSD 400, 1 PCE
10009303	Spray Set for WSD 400, 1 PCE
10009301	WSD 400 Pressurized-Air Spray Can, 1 PCE
10000398	Adjusting Valve for cans, 1 PCE
10016002	Pump Dispenser WPS 1500, 1 PCE
10016213	Extension tube for WPS 1500, 1 PCE
10000402	Pump Dispenser Special, 1 PCE

### Available sizes

10000363	Mould Release Agent, 5 L, colourless, transparent
10000364	Mould Release Agent, 10 L, colourless, transparent
10007616	Mould Release Agent, 1 L, colourless, transparent
10053498	Mould Release Agent, 28 L, colourless, transparent

To the product detail page:



### Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON Middle East L.L.C.  
United Arab Emirates  
phone +971 4 880 25 05  
info@weicon.ae

WEICON Inc.  
Canada  
phone +1 877 620 8889  
info@weicon.ca

WEICON Czech Republic s.r.o.  
Czech Republic  
phone +42 (0) 417 533 013  
info@weicon.cz

WEICON Iberica S.L.  
Spain  
phone +34 (0) 914 7997 34  
info@weicon.es

WEICON GmbH & Co. KG  
(Headquarters) Germany  
phone +49 (0) 251 9322 0  
info@weicon.de

WEICON Italia S.r.l.  
Italy  
phone +39 (0) 010 2924 871  
info@weicon.it

WEICON Romania SRL  
Romania  
phone +40 (0) 3 65 730 763  
office@weicon.com

WEICON SA (Pty) Ltd  
South Africa  
phone +27 (0) 21 709 0088  
info@weicon.co.za

WEICON South East Asia Pte Ltd  
Singapore  
Phone (+65) 6710 7671  
info@weicon.com.sg

WEICON Kimya Sanayi Tic. Ltd. Şti.  
Türkiye  
phone +90 (0) 212 465 33 65  
info@weicon.com.tr