

Top-Lube



Extremely capillary action

WEICON Top-Lube is a synthetic, transparent adhesive lubricant for the permanent lubrication of all types of highly stressed mechanical parts. WEICON Top-Lube has high adhesive and spinning strength and outstanding capillary action. It is pressure-resistant, water-repellent, temperature-resistant from -40 °C up to +200 °C (-40 °F to +392 °F) and can also be used during on-going operations in compliance with the respective safety regulations. It does not attack the following plastics and elastomers: PTFE, PE, PA, fluorinated, butadiene and silicone rubber, and polychloroprene. The following materials have a limited resistance: PE-LD, POM, PP, NBR. WEICON Top-Lube can be used on force-transmitting bolts, gears and worm gears, high-speed machinery parts, joints and couplings, wheels and bearings and spring assemblies in many industrial sectors.

Application

Shake can before use. Spray on cleaned and dry surfaces from about 15 cm distance. Can afterwards also be used during operation under observation of the respective safety regulations.

Storage

Container is pressurised. Protect from direct sunlight and temperatures above +50 °C.

Instructions for use

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

Available sizes

10000156 Top-Lube, 400 ml

Technical data

| | |
|--|--|
| Odour | mineral oil |
| Specific properties | extremely high capillary action, water-repellent |
| Silicone-free | yes |
| Minimum shelf life at room temperature | 24 mon. |
| Kinematic viscosity (40°C) | 79 mm ² /s |
| Kinematic viscosity (100°C) | 9 mm ² /s |
| Temperature resistance | -40°C to +200°C |

Approvals / Guidelines

| | |
|-----------|-----------|
| ISSA Code | 53.402.12 |
| IMPA Code | 450826 |

To the product detail page:



Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON Middle East L.L.C.
United Arab Emirates
phone +971 4 880 25 05
info@weicon.ae

WEICON Czech Republic s.r.o.
Czech Republic
phone +42 (0) 417 533 013
info@weicon.cz

WEICON GmbH & Co. KG
(Headquarters) Germany
phone +49 (0) 251 9322 0
info@weicon.de

WEICON Romania SRL
Romania
phone +40 (0) 3 65 730 763
office@weicon.com

WEICON South East Asia Pte Ltd
Singapore
Phone (+65) 6710 7671
info@weicon.com.sg

WEICON Inc.
Canada
phone +1 877 620 8889
info@weicon.ca

WEICON Ibérica S.L.
Spain
phone +34 (0) 914 7997 34
info@weicon.es

WEICON Italia S.r.l.
Italy
phone +39 (0) 010 2924 871
info@weicon.it

WEICON SA (Pty) Ltd
South Africa
phone +27 (0) 21 709 0088
info@weicon.co.za

WEICON Kimya Sanayi Tic. Ltd. Şti.
Türkiye
phone +90 (0) 212 465 33 65
info@weicon.com.tr