

## Spray-on Grease white



### All-purpose sprayable grease

WEICON Spray-on Grease white is a multi-purpose sprayable grease with outstanding adhesive strength and excellent resistance to ageing and pressure. By adding special wear-reducing and corrosion-inhibiting additives, temperature stability from -20 °C to +150 °C (-4 to +302 °F) in combination with a long service life can be achieved. As with transparent products, a visual inspection is possible at all times. WEICON Spray-on Grease white can be used for the long-term lubrication of rods, gearwheels, rollers, ball bearings, hinges, guides and all types of joints and couplings in many industrial applications.

#### Technical data

Base	Lithium soap
Odour	solvent
Colour	white
Specific properties	very high adhesive strength and anti-friction properties
Silicone-free	yes
Minimum shelf life at room temperature	24 mon.
Kinematic viscosity (40°C)	110 mm²/s
Kinematic viscosity (100°C)	10 mm²/s
Temperature resistance	-20 °C to +150 °C

#### Approvals / Guidelines

ISSA Code	53.402.50
IMPA Code	450833
MIL-Spec	complies with MIL-PRF-24139

#### Application

Clean the parts to be lubricated thoroughly (Cleaner Spray S). Shake contents before use. Spray on from a distance of approx. 25 cm

#### Storage

Container is pressurised. Protect from direct sunlight and temperatures above +50 °C.

#### Instructions for use

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our EC safety data sheets ([www.weicon.com](http://www.weicon.com)) must be observed.

#### Available sizes

10007039	Spray-on Grease white, 400 ml, white
10059947	Spray-on Grease white, 400 ml, white

#### Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON Middle East L.L.C.  
United Arab Emirates  
phone +971 4 880 25 05  
[info@weicon.ae](mailto:info@weicon.ae)

WEICON Czech Republic s.r.o.  
Czech Republic  
phone +42 (0) 417 533 013  
[info@weicon.cz](mailto:info@weicon.cz)

WEICON GmbH & Co. KG  
(Headquarters) Germany  
phone +49 (0) 251 9322 0  
[info@weicon.de](mailto:info@weicon.de)

WEICON Romania SRL  
Romania  
phone +40 (0) 3 65 730 763  
[office@weicon.com](mailto:office@weicon.com)

WEICON South East Asia Pte Ltd  
Singapore  
Phone (+65) 6710 7671  
[info@weicon.com.sg](mailto:info@weicon.com.sg)

WEICON Inc.  
Canada  
phone +1 877 620 8889  
[info@weicon.ca](mailto:info@weicon.ca)

WEICON Ibérica S.L.  
Spain  
phone +34 (0) 914 7997 34  
[info@weicon.es](mailto:info@weicon.es)

WEICON Italia S.r.l.  
Italy  
phone +39 (0) 010 2924 871  
[info@weicon.it](mailto:info@weicon.it)

WEICON SA (Pty) Ltd  
South Africa  
phone +27 (0) 21 709 0088  
[info@weicon.co.za](mailto:info@weicon.co.za)

WEICON Kimya Sanayi Tic. Ltd. Şti.  
Türkiye  
phone +90 (0) 212 465 33 65  
[info@weicon.com.tr](mailto:info@weicon.com.tr)