

# Universal Spray-on Grease with MoS2



## High-pressure-resistant

WEICON Universal Spray-on Grease with MoS2 is a high-pressure-resistant and strong long-term lubricant, which reduces friction and wear for prolonged periods of time and is temperature-resistant from -20 to +120 °C (-4 to +248 °F). Universal Spray-on Grease with MoS2 is suitable for rolling and slide bearings, joints, levers, sliding guides, spindles, camshafts, spline shafts, springs, exposed gears and worm gears. It is suitable for all slide speeds permissible for grease lubrication. Universal Spray-on Grease with MoS2 can be used in the industrial and building sectors, in rolling mills, machine tools, agricultural and construction machines and in road and rail vehicles.

## Application

Clean surfaces. For a better spray function, warm the product up to room temperature. Shake can before use until mixing pea is audible. Spray on from a distance of approx. 15 cm.

## Storage

Container is pressurised. Protect from direct sunlight and temperatures above +50 °C.

## Instructions for use

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our EC safety data sheets ([www.weicon.com](http://www.weicon.com)) must be observed.

## Available sizes

10019872 Universal Spray-on Grease with MoS2, 400 ml

## Technical data

Odour	nearly odourless
Specific properties	high-pressure-resistant
Silicone-free	yes
Minimum shelf life	at room temperature 24 mon.
Kinematic viscosity (40°C)	160 mm <sup>2</sup> /s
Kinematic viscosity (100°C)	15 mm <sup>2</sup> /s
Temperature resistance	-20 °C to +120 °C

## Approvals / Guidelines

ISSA Code	53.402.51
IMPA Code	450834

To the product detail page:



## Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON Middle East L.L.C.  
United Arab Emirates  
phone +971 4 880 25 05  
info@weicon.ae

WEICON Czech Republic s.r.o.  
Czech Republic  
phone +42 (0) 417 533 013  
info@weicon.cz

WEICON GmbH & Co. KG  
(Headquarters) Germany  
phone +49 (0) 251 9322 0  
info@weicon.de

WEICON Romania SRL  
Romania  
phone +40 (0) 3 65 730 763  
office@weicon.com

WEICON South East Asia Pte Ltd  
Singapore  
Phone (+65) 6710 7671  
info@weicon.com.sg

WEICON Inc.  
Canada  
phone +1 877 620 8889  
info@weicon.ca

WEICON Ibérica S.L.  
Spain  
phone +34 (0) 914 7997 34  
info@weicon.es

WEICON Italia S.r.l.  
Italy  
phone +39 (0) 010 2924 871  
info@weicon.it

WEICON SA (Pty) Ltd  
South Africa  
phone +27 (0) 21 709 0088  
info@weicon.co.za

WEICON Kimya Sanayi Tic. Ltd. Şti.  
Türkiye  
phone +90 (0) 212 465 33 65  
info@weicon.com.tr