

# Isolation Spray

## Transparent insulating and finishing varnish based on acrylic resin

WEICON Isolation Spray is a transparent insulating and finishing varnish based on acrylic resin. It forms a flexible and resistant layer, which shows excellent adhesion to metal, glass, plastic or wood. It is resistant to UV radiation, acids, oils and lyes. It is moisture- and weather-resistant and stands out particularly due to its high dielectric strength. The spray protects against moisture as well as different vapours. It can be used as protective coating for circuit boards, on electrical connections, switches, switchboards, electronic components and coils, as universal sealant in electrical engineering or for the repair of insulations on electric motors, windings and frames.

### Technical data

Base	modified acrylic resin
Odour	solvent
Specific properties	high dielectric strength, material-compatible
Silicone-free	yes
Consumption	per 1.5 crosswise application
	~ 2 m <sup>2</sup>
Dust-dry after	15 min.
Minimum shelf life	at room temperature
	24 mon.
Grid cut	DIN 53151/ISO 2409
	cross cut value 0-1 on steel
Density	0,848 g/cm <sup>3</sup>
Dielectric strength	DIN EN 60243
	67,8 kV/mm
Solid content	50 %
spec. surface resistance	7,59 · 10 <sup>14</sup> Ω
Thermal conductivity	20 °C DIN EN ISO 821
	0,215 W/m·K
Temperature resistance	-40 (-40 °F) to +120 (+248 °F)

### Approvals / Guidelines

MIL-Spec	complies with	MIL-T-83523
----------	---------------	-------------

### Application

Clean and degrease surfaces with WEICON Surface Cleaner. Surfaces should be dry and free from dust and grease. Shake can before use, until the mixing peat is clearly audible. Apply the spray at room temperature (approx. +20 °C) evenly from a distance of approx. 25 cm.

### Storage

Container is pressurised. Protect from direct sunlight and temperatures above +50 °C.

### Instructions for use

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our EC safety data sheets ([www.weicon.com](http://www.weicon.com)) must be observed.

### Available sizes

To the product detail page:



### Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON Middle East L.L.C.  
United Arab Emirates  
phone +971 4 880 25 05  
info@weicon.ae

WEICON Inc.  
Canada  
phone +1 877 620 8889  
info@weicon.ca

WEICON Czech Republic s.r.o.  
Czech Republic  
phone +42 (0) 417 533 013  
info@weicon.cz

WEICON Ibérica S.L.  
Spain  
phone +34 (0) 914 7997 34  
info@weicon.es

WEICON GmbH & Co. KG  
(Headquarters) Germany  
phone +49 (0) 251 9322 0  
info@weicon.de

WEICON Italia S.r.l.  
Italy  
phone +39 (0) 010 2924 871  
info@weicon.it

WEICON Romania SRL  
Romania  
phone +40 (0) 3 65 730 763  
office@weicon.com

WEICON SA (Pty) Ltd  
South Africa  
phone +27 (0) 21 709 0088  
info@weicon.co.za

WEICON South East Asia Pte Ltd  
Singapore  
Phone (+65) 6710 7671  
info@weicon.com.sg

WEICON Kimya Sanayi Tic. Ltd. Şti.  
Türkiye  
phone +90 (0) 212 465 33 65  
info@weicon.com.tr