

Stainless Steel Care Spray A7



Nonfood Compounds
Program Listed A7
Registration 165294

Cleaning, care and protection in sensitive areas

Stainless Steel Care Spray was specially formulated for the cleaning, protection and care of brushed, matt and polished stainless steel surfaces in sensitive areas. The special spray can be used in the food and beverage industry, in canteen kitchens as well as in the pharmaceutical and medical industry. The spray has an NSF registration (A7) and can be used in food processing areas. It removes smudges and fingerprints, reduces oxidation and corrosion, cleans even larger surfaces streak-free, leaves a long-lasting protective layer, and makes water roll off. It has an antistatic effect and adheres even to vertical surfaces.

Technical data

Odour	nearly odourless
Colour	colourless, transparent
Specific properties	antistatic
Minimum shelf life	at room temperature 24 mon.
Temperature resistance	-5°C to +200°C

Approvals / Guidelines

NSF	A7 (FDA 21 CFR)
-----	-----------------

Application

Shake thoroughly before use. Apply Stainless Steel Care Spray from a distance of approx. 20 cm in a thin and even layer and lightly rub in with a dry, soft cloth. Wipe off dirt with a cloth. In case of stubborn soilings, allow to take effect for 30 seconds. Product must not come into direct contact with food.

Storage

Container is pressurised. Protect from direct sunlight and temperatures above +50 °C.

Instructions for use

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

Accessories

10044969 Double Nozzle, 1 PCE

Available sizes

10060669 Stainless Steel Care Spray A7, 400 ml, colourless, transparent

Conversion table

$(^{\circ}\text{C} \times 1.8) + 32 = ^{\circ}\text{F}$	$\text{Nm} \times 8.851 = \text{lb}\cdot\text{in}$
$\text{mm}/25.4 = \text{inch}$	$\text{Nm} \times 0.738 = \text{lb}\cdot\text{ft}$
$\mu\text{m}/25.4 = \text{mil}$	$\text{Nm} \times 141.62 = \text{oz}\cdot\text{in}$
$\text{N} \times 0.225 = \text{lb}$	$\text{mPa}\cdot\text{s} = \text{cP}$
$\text{N}/\text{mm}^2 \times 145 = \text{psi}$	$\text{N}/\text{cm} \times 0.571 = \text{lb}/\text{in}$
$\text{MPa} \times 145 = \text{psi}$	$\text{kV}/\text{mm} \times 25.4 = \text{V}/\text{mil}$

To the product detail page:



Note
The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON Middle East L.L.C.
United Arab Emirates
phone +971 4 880 25 05
info@weicon.ae

WEICON Czech Republic s.r.o.
Czech Republic
phone +42 (0) 417 533 013
info@weicon.cz

WEICON GmbH & Co. KG
(Headquarters) Germany
phone +49 (0) 251 9322 0
info@weicon.de

WEICON Romania SRL
Romania
phone +40 (0) 3 65 730 763
office@weicon.com

WEICON South East Asia Pte Ltd
Singapore
Phone (+65) 6710 7671
info@weicon.com.sg

WEICON Inc.
Canada
phone +1 877 620 8889
info@weicon.ca

WEICON Ibérica S.L.
Spain
phone +34 (0) 914 7997 34
info@weicon.es

WEICON Italia S.r.l.
Italy
phone +39 (0) 010 2924 871
info@weicon.it

WEICON SA (Pty) Ltd
South Africa
phone +27 (0) 21 709 0088
info@weicon.co.za

WEICON Kimya Sanayi Tic. Ltd. Şti.
Türkiye
phone +90 (0) 212 465 33 65
info@weicon.com.tr