WEICON®

Technical Sprays
Adhesive Spray

Adhesive Spray

Universal use

WEICON Adhesive Spray is suitable for all-purpose use and bonds light materials. WEICON Adhesive Spray is suitable for the bonding of numerous materials such as paper, cardboard, pasteboard, wood, thin veneers, cork, leather, textiles, felt, soft foam, rubber, foam rubber, and plastic film (except for PVC and polyethylene). It is especially suited for the bonding of hard foam.

Technische Daten

Base		synthetic rubber
Silicone-free		yes
Processing temperature		+10°C to +30°C
Consumption	per 1.5 crosswise application	~ 13 m²
Evaporation time		5 - 15 min.
Temperature resistance		-20°C to +65°C
Shelf life		12 mon.

Processing

1. Shake can before use. Surfaces must be dry, clean and free of

grease. Spray on one surface at about 15 to 30 cm distance. With

porous materials, Adhesive Spray should be applied on both

surfaces.

2. Depending on surface characteristics and ambient temperature,

let the spray dry for 1 - 15 minutes until the adhesive is no

longer stringy.

3. Position the parts and join them with strong pressure.

4. The spray head can be set to horizontal or vertical spray jet

Storage

Pressurized container. Protect from direct sunlight and temperatures above +50°C.

Instructions for use

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

Available sizes

10059961   Adhesive Spray, 500 ml

To the product detail page: