

Adhesive Spray detachable



Transparent

WEICON Adhesive Spray for detachable joints is especially suited for detachable and adjustable joints. WEICON Adhesive Spray for detachable joints is colourless, does not soak through or cause discolouration, and does not leave a wavy surface, even when used on thin materials. Adhesive Spray for detachable joints can be used to bond paper, cardboard and foils. The joint is detachable when the spray is applied to one side; applying the spray to both sides makes the joint permanent. WEICON Adhesive Spray for detachable joints can be used, for example, to fuse templates, billboards, posters, photos, decorations in trade show construction, layouts and technical drawings.

Technical data

Base	Synthetic chaoutchouc	
Silicone-free		yes
Processing temperature		+10°C to +30°C
Consumption	per 1.5 crosswise application	~13 m ²
Minimum shelf life	at room temperature	12 mon.
Evaporation time		5 - 15 min.
Temperature resistance		-20 °C to +65 °C

Application

1. Shake can before use. Surfaces must be dry, clean and free of grease. Spray onto the surface at about 15 to 30 cm distance. Detachable if a thin adhesive layer is applied on only one surface. For permanent adhesion, Adhesive Spray should be applied either in a thick layer or on both surfaces. 2. Depending on surface characteristics and ambient temperature, let the spray film dry (about 10 minutes) until the adhesive is no longer stringy. 3. Position the parts and join them with strong pressur

Storage

Container is pressurised. Protect from direct sunlight and temperatures above +50 °C.

Instructions for use

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

Available sizes

10024663 Adhesive Spray detachable, 500 ml

To the product detail page:



Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON Middle East L.L.C.
United Arab Emirates
phone +971 4 880 25 05
info@weicon.ae

WEICON Czech Republic s.r.o.
Czech Republic
phone +42 (0) 417 533 013
info@weicon.cz

WEICON GmbH & Co. KG
(Headquarters) Germany
phone +49 (0) 251 9322 0
info@weicon.de

WEICON Romania SRL
Romania
phone +40 (0) 3 65 730 763
office@weicon.com

WEICON South East Asia Pte Ltd
Singapore
Phone (+65) 6710 7671
info@weicon.com.sg

WEICON Inc.
Canada
phone +1 877 620 8889
info@weicon.ca

WEICON Ibérica S.L.
Spain
phone +34 (0) 914 7997 34
info@weicon.es

WEICON Italia S.r.l.
Italy
phone +39 (0) 010 2924 871
info@weicon.it

WEICON SA (Pty) Ltd
South Africa
phone +27 (0) 21 709 0088
info@weicon.co.za

WEICON Kimya Sanayi Tic. Ltd. Şti.
Türkiye
phone +90 (0) 212 465 33 65
info@weicon.com.tr