

## **Technical Sprays**

# **Adhesive Spray**

## Adhesive Spray detachable

#### **Transparent**

WEICON Adhesive Spray for detachable joints is especially suited for detachable and adjustable joints. WEICON Adhesive Spray for detachable joints is colourless, does not soak through or cause discolouration, and does not leave a wavy surface, even when used on thin materials. Adhesive Spray for detachable joints can be used to bond paper, cardboard and foils. The joint is detachable when the spray is applied to one side; applying the spray to both sides makes the joint permanent. WEICON Adhesive Spray for detachable joints can be used, for example, to fuse templates, billboards, posters, photos, decorations in trade show construction, layouts and technical drawings.

#### Technische Daten

| Base                   |                               | Synthetic chaoutchouc |
|------------------------|-------------------------------|-----------------------|
| Silicone-free          |                               | yes                   |
| Processing temperature |                               | +10°C to +30°C        |
| Consumption            | per 1.5 crosswise application | ~13 m²                |
| Evaporation time       |                               | 5 - 15 min.           |
| Temperature resistance |                               | -20°C to +65°C        |
| Shelf life             |                               | 12 mon.               |

### **Processing**

1. Shake can before use. Surfaces must be dry, clean and free of grease. Spray onto the surface at about 15 to 30 cm distance. Detachable if a thin adhesive layer is applied on only one surface. For permanent adhesion, Adhesive Spray should be applied either in a thick layer or on both surfaces. 2. Depending on surface characteristics and ambient temperature, let the spray film dry (about 10 minutes) until the adhesive is no longer stringy. 3. Position the parts and join them with strong pressur

## Storage

Pressurized container. Protect from direct sunlight and temperatures above +50°C.

## Instructions for use

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

#### Available sizes

10024663 Adhesive Spray detachable, 500 ml



The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the requested properties are recommended. A claim cannot be derived from them.

WEICON Romania SRL phone +40 (0) 3 65 730 763

WEICON SA (Pty) Ltd South Africa phone +27 (0) 21 709 0088 info@weicon.co.za

WEICON South East Asia Pte Ltd ne (+65) 6710 7671