

## Rust Loosener



### Sixfold function

WEICON Rust Loosener's six-fold function makes it indispensable for repairs, maintenance and servicing. Thanks to its excellent capillary action, Rust Loosener reaches even the smallest cavities. It loosens rusted and stiff parts, screws, bolts, joints and hinges, permanently protects against corrosion and oxidation. WEICON Rust Loosener durably lubricates sliding surfaces and cleans and cares for metallic surfaces, mechanical parts and electrical systems.

### Characteristics

Specific properties	6-fold function
Colour	beige
Odour	Kerosene
Kinematic viscosity (40°C)	21 mm <sup>2</sup> /s
Kinematic viscosity (100°C)	4 mm <sup>2</sup> /s
suitable for processing with	WSD 400   WPS 1500-V   Pump Dispenser Special
Minimum shelf life at room temperature	24 mon.

### Thermal parameters

Temperature resistance	-20°C to +150°C
------------------------	-----------------

### Approvals / Guidelines

ISSA Code	53.402.43
IMPA Code	551625/26/27

### Application

Richly brush on or spray on (e.g. with an Air Pressure Can). Allow to react for a short time. Repeat if necessary.

### Storage

Keep tightly closed in original packaging. Protect from direct sunlight. The storage temperature must not exceed +50 °C. Keep container in a cool, well-ventilated place. Store in a dry place.

### Instructions for use

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our EC safety data sheets ([www.weicon.com](http://www.weicon.com)) must be observed.

### Accessories

10016002	Pump Dispenser WPS 1500, 1 PCE
10000393	Adapter for WSD 400, 1 PCE
10009303	Spray Set for WSD 400, 1 PCE
10009301	WSD 400 Pressurized-Air Spray Can, 1 PCE
10000398	Adjusting Valve for cans, 1 PCE
10016213	Extension tube for WPS 1500, 1 PCE
10000402	Pump Dispenser Special, 1 PCE

### Available sizes

10000340	Rust Loosener, 5 L, beige
10000233	Rust Loosener, 10 L, beige
10007609	Rust Loosener, 1 L, beige
10053451	Rust Loosener, 28 L, beige

To the product detail page:



### Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON Middle East L.L.C.  
United Arab Emirates  
phone +971 4 880 25 05  
info@weicon.ae

WEICON Czech Republic s.r.o.  
Czech Republic  
phone +42 (0) 417 533 013  
info@weicon.cz

WEICON GmbH & Co. KG  
(Headquarters) Germany  
phone +49 (0) 251 9322 0  
info@weicon.de

WEICON Romania SRL  
Romania  
phone +40 (0) 3 65 730 763  
office@weicon.com

WEICON South East Asia Pte Ltd  
Singapore  
Phone (+65) 6710 7671  
info@weicon.com.sg

WEICON Colombia S.A.S  
Colombia  
Phone: +57 314 793 86 06  
Email: info@weicon.co

WEICON Inc.  
Canada  
phone +1 877 620 8889  
info@weicon.ca

WEICON Ibérica S.L.  
Spain  
phone +34 (0) 914 7997 34  
info@weicon.es

WEICON Italia S.r.L.  
Italy  
phone +39 (0) 010 2924 871  
info@weicon.it

WEICON SA (Pty) Ltd  
South Africa  
phone +27 (0) 21 709 0088  
info@weicon.co.za

WEICON Kimya Sanayi Tic. Ltd. Şti.  
Türkiye  
phone +90 (0) 212 465 33 65  
info@weicon.com.tr