

Cleaners and Degreasers

Cleaner S



Degreases and cleans all metals, glass, ceramics and most plastics

WEICON Cleaner S removes oily and greasy soiling from all metals as well as from ceramics, glass and most plastics. It can, however, attack the surface of thermoplastics such as PVC, Plexiglas, polystyrene and single layers of paint. WEICON Cleaner S evaporates quickly and, in contrast to conventional thinners, without leaving residues. It can be used for cleaning and degreasing before priming and painting, for cleaning machine parts, or before other WEICON products are applied to surfaces where a greasy underground would impair their effect.

Application

Dip in part to be cleaned, or brush or spray on Surface Cleaner sufficiently (e.g. with an Air Pressure Can). Use a clean cloth or nonwoven fabric to wipe off wet residues making sure that impurity and solvent remainders are removed. Repeat the cleaning process if necessary. Let the solvents evaporate until the surfaces have dried.

Storage

Keep tightly closed in original packaging. Protect from direct sunlight. The storage temperature must not exceed +50 °C. Keep container in a cool, well-ventilated place. Store in a dry place.

Instructions for use

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

Accessories

10000393	Adapter for WSD 400, 1 PCE
10009303	Spray Set for WSD 400, 1 PCE
10009301	WSD 400 Pressurized-Air Spray Can, 1 PCE
10000398	Adjusting Valve for cans, 1 PCE
10000402	Pump Dispenser Special, 1 PCE

Available sizes

10000347	Cleaner S, 5 L, colourless, transparent
10007611	Cleaner S, 1 L, colourless, transparent
10053455	Cleaner S, 28 L, colourless, transparent

Characteristics

Specific properties	evaporates without residues
Colour	colourless, transparent
Odour	Orange
suitable for processing with	WSD 400 Pump Dispenser Special
Minimum shelf life	at room temperature
	24 mon.

Chemical properties

AOX-free	yes
----------	-----

Approvals / Guidelines

ISSA Code	53.402.53/54/55
IMPA Code	551571/72/73
MIL-Spec	complies with

To the product detail page:



Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON Middle East L.L.C.
United Arab Emirates
phone +971 4 880 25 05
info@weicon.ae

WEICON Inc.
Canada
phone +1 877 620 8889
info@weicon.ca

WEICON Czech Republic s.r.o.
Czech Republic
phone +42 (0) 417 533 013
info@weicon.cz

WEICON Ibérica S.L.
Spain
phone +34 (0) 914 7997 34
info@weicon.es

WEICON GmbH & Co. KG
(Headquarters) Germany
phone +49 (0) 251 9322 0
info@weicon.de

WEICON Italia S.r.l.
Italy
phone +39 (0) 010 2924 871
info@weicon.it

WEICON Romania SRL
Romania
phone +40 (0) 3 65 730 763
office@weicon.com

WEICON SA (Pty) Ltd
South Africa
phone +27 (0) 21 709 0088
info@weicon.co.za

WEICON South East Asia Pte Ltd
Singapore
Phone (+65) 6710 7671
info@weicon.com.sg

WEICON Kimya Sanayi Tic. Ltd. Şti.
Türkiye
phone +90 (0) 212 465 33 65
info@weicon.com.tr