

AT-44



With PTFE super power | silicone-free

WEICON AT-44 is a high-performance lubrication oil which, thanks to its special formula and very low friction coefficient, combines corrosion protection, cleaning, water repellency, lubrication and conservation in one single product. It loosens seized threads, bolts, fittings and valves, dispels moisture from electrical cables, prevents tracking currents and makes it easier to start wet motors. AT-44 eliminates squeaky and creaky noises on hinges, guides, bearings and all types of joints and couplings. It cleans soiled surfaces and leaves a razor-thin film which does not smear or stick and does not attract dust. It protects and preserves all types of tools, machines, and electrical and mechanical precision devices and keeps them functional. It has almost no limitations in workshop, automotive, shipping, electrical, agricultural, household and hobby applications.

Technische Daten

Colour	yellowish
Specific properties	High-performance lubricating oil with PTFE
Odour	vanilla
Temperature resistance	-50°C to +210°C
suitable for processing with	WSD 400 WPS 1500
Shelf life	24 mon.
Approvals / Guidelines	
IMPA Code	551599/600/621

Processing

Brush or spray the workpieces generously (e.g. with Pressurized-Air Spray Can). Allow to take effect, repeat procedure if necessary.

Storage

Store in tightly closed original container. Protect from direct sunlight. The storage temperature must not exceed +50°C. Keep container in a cool, well-ventilated location. Store in dry place.

Safety and health

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

Accessories

- 15841500-V Pump Dispenser WPS 1500 with VITON seal, 1 PCE
- 15810001 Adapter for WSD 400, 1 PCE
- 15811002 Spray Set for WSD 400, 1 PCE
- 15811400 WSD 400 Pressurized-Air Spray Can, 400 ml
- 15831001 Adjusting Valve for cans, 1 PCE
- 15843001 WEICON Pump Dispenser Special, 1 L

Available sizes:

- 15250005 AT-44, 5 L, yellowish
- 15250010 AT-44, 10 L, yellowish
- 15250001 AT-44, 1 L, yellowish
- 15250028 AT-44, 28 L, yellowish

To the product detail page:



Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.