

# Pneuma-Lube



## Lubricant | corrosion protection | high PTFE content

As a lubricating and corrosion protection agent, WEICON Pneuma-Lube is the universal problemsolver for all moving parts in pneumatic equipment and accessories. Its special product formula with a high content of PTFE makes it a multi-purpose product for: lubrication, corrosion protection, cleaning, water displacing and conservation. The product can not only be used in installation or maintenance of pneumatic equipment and accessories, but also on pneumatic tools in operation. Its excellent weathering resistance allows its use in other sectors as well, e.g. in the on- and offshore industry.

### Technische Daten

Colour	yellowish
Specific properties	High-performance lubricating oil with PTFE
Odour	vanilla
Temperature resistance	-50°C to +210°C
suitable for processing with	WSD 400 WPS 1500
Shelf life	24 mon.

### Processing

Brush or spray the workpieces generously (e.g. with Pressurized-Air Spray Can). Allow to take effect, repeat procedure if necessary.

### Storage

Store in tightly closed original container. Protect from direct sunlight. The storage temperature must not exceed +50°C. Keep container in a cool, well-ventilated location. Store in dry place.

### Safety and health

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our EC safety data sheets ([www.weicon.com](http://www.weicon.com)) must be observed.

### Accessories

- 15810001 Adapter for WSD 400, 1 PCE
- 15811002 Spray Set for WSD 400, 1 PCE
- 15811400 WSD 400 Pressurized-Air Spray Can, 400 ml
- 15831001 Adjusting Valve for cans, 28 PCE
- 15841500 Pump Dispenser WPS 1500, 1,5 L
- 15841501 Extension tube for WPS 1500, 1 PCE
- 15843001 WEICON Pump Dispenser Special, 500 ml

### Available sizes:

- 15260028 Pneuma-Lube, 28 L, yellowish
- 15260010 Pneuma-Lube, 10 L, yellowish
- 15260005 Pneuma-Lube, 5 L, yellowish
- 15260001 Pneuma-Lube, 1 L, yellowish

To the product detail page:



#### Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.