

# Mounting Tape Grey

## Extremely strong adhesion | for smooth surfaces | high flexibility

Mounting Tape Grey is a strong, double-sided adhesive tape made of modified acrylic foam. The tape is particularly suitable for the bonding of low energy plastics, such as PE and PP, as well as for powder-coated surfaces. In combination with WEICON adhesives and sealants, it can be used as a fixing aid for hybrid bondings. The high flexibility of the tape perfectly compensates tensions when bonding curved surfaces. It can be used for permanent bondings both indoors and outdoors. The tape has a temperature resistance of -40 °C to +120 °C and is UV- and moisture-resistant. Mounting Tape Grey can be used in a variety of applications in many sectors, such as car body and vehicle technology, caravanning, metal and apparatus engineering, electronics, mechanical engineering, advertising technology, shipbuilding and marine technology.

### Technical Data

Colour	grey
Width	19 mm
Length	3 m
Thickness	0,9 mm
Elongation at break	ISO 37, S3A
Tensile strength	10 N/cm
Load bearing capacity	85 kg/m
Core size	40 mm
Adhesion on steel	20 N/cm
T-Block tensile strength on aluminium	50 N/cm <sup>2</sup>
Mechanical strength after	24 h
Temperature resistance	-40°C to +120°C
Approvals / Guidelines	

MIL-Spec

complies with

MIL-A-101A

### Surface Pre-Treatment

Clean and degrease surfaces before use.

### Application

The processing temperature should be above 15 °C during the application.

### Instructions for use

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our EC safety data sheets ([www.weicon.com](http://www.weicon.com)) must be observed.

### Available sizes

To the product detail page:



### Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON Middle East L.L.C.  
United Arab Emirates  
phone +971 4 880 25 05  
info@weicon.ae

WEICON Inc.  
Canada  
phone +1 877 620 8889  
info@weicon.ca

WEICON Czech Republic s.r.o.  
Czech Republic  
phone +42 (0) 417 533 013  
info@weicon.cz

WEICON Ibérica S.L.  
Spain  
phone +34 (0) 914 7997 34  
info@weicon.es

WEICON GmbH & Co. KG  
(Headquarters) Germany  
phone +49 (0) 251 9322 0  
info@weicon.de

WEICON Italia S.r.l.  
Italy  
phone +39 (0) 010 2924 871  
info@weicon.it

WEICON Romania SRL  
Romania  
phone +40 (0) 3 65 730 763  
office@weicon.com

WEICON SA (Pty) Ltd  
South Africa  
phone +27 (0) 21 709 0088  
info@weicon.co.za

WEICON South East Asia Pte Ltd  
Singapore  
Phone (+65) 6710 7671  
info@weicon.com.sg

WEICON Kimya Sanayi Tic. Ltd. Şti.  
Türkiye  
phone +90 (0) 212 465 33 65  
info@weicon.com.tr