

## Copper Paste Spray

**Protecting, separating and lubricating agent for highly stressed parts in high-temperature applications**

WEICON Copper Paste Assembly Spray is a protecting, separating and lubricating agent which is high-temperature-resistant, corrosion-resistant and strong. It contains no sulphur, lead or nickel. WEICON Copper Paste Assembly Spray is used as an assembly lubricant for all kinds of threaded joints and sliding surfaces. It forms an effective lubricating and separating film, which protects the functional surfaces on plug-in tools, wear bushings, screws, and all kinds of threaded, plug-in and bayonet joints against corrosion and seizing. It can be used to reduce vibration on brake blocks and guides, brake cams and pins, car and truck battery terminals and other electrical connections, wheel bolts and nuts, and on wear bushings at electrical, compressed air and hydraulic hammers.

### Technische Daten

Base	mineral oil	
Consistency classification	DIN 51818	NLGI grade 1
Density	1,1 g/cm <sup>3</sup>	
Silicone-free	yes	
Four ball weld test weld load	DIN 51350	3.200 N
Cone penetration	DIN ISO 2137	310 - 340 1/10 mm
Temperature resistance	-20°C to 1.100°C	
Thickener	Alu-complex soap	

### Reibwerte

Reibwerte Stahl-blank		
Total friction coefficient	0,13 (min. 0,11)	
Friction coefficients threads	0,14 (min. 0,13)	
Friction coefficient head	0,12 (min. 0,10)	
Reibwert V4A		
Total friction coefficient	0,16 (min. 0,13)	
Friction coefficients threads	0,16 (min. 0,12)	
Friction coefficient head	0,16 (min. 0,13)	
Reibwert Stahl galvanisch verzinkt		
Total friction coefficient	0,10 (min. 0,09)	
Friction coefficient threads	0,11 (min. 0,10)	
Friction coefficient head	0,09 (min. 0,08)	

### Surface pre-treatment

First clean the surface to be lubricated with WEICON Cleaner S, depending on the degree of soiling. If screws have already been used, process with the wire brush and clean with WEICON Cleaner S. For a better spray function, warm the product up to room temperature.

### Processing

Shake can before use and apply evenly from a distance of approx. 15 cm. With screws, it is important to apply the Copper Paste down to the base of the thread. This ensures a good sealing effect. In order not to change the properties, the Copper Paste must not be mixed with greases or oils. Copper Paste does not replace an oil or grease lubrication.

### Storage

Protect from heat and direct sunlight. The storage temperature must not exceed +50°C. Keep container in a cool, well-ventilated location. Store in a cool place.

### Instructions for use

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our EC safety data sheets ([www.weicon.com](http://www.weicon.com)) must be observed.

### Available sizes

To the product detail page:



#### Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON Middle East L.L.C.  
United Arab Emirates  
phone +971 4 880 25 05  
[info@weicon.ae](mailto:info@weicon.ae)

WEICON Czech Republic s.r.o.  
Czech Republic  
phone +42 (0) 417 533 013  
[info@weicon.cz](mailto:info@weicon.cz)

WEICON GmbH & Co. KG  
(Headquarters) Germany  
phone +49 (0) 251 9322 0  
[info@weicon.de](mailto:info@weicon.de)

WEICON Romania SRL  
Romania  
phone +40 (0) 3 65 730 763  
[office@weicon.com](mailto:office@weicon.com)

WEICON South East Asia Pte Ltd  
Singapore  
Phone (+65) 6710 7671  
[info@weicon.com.sg](mailto:info@weicon.com.sg)

WEICON Inc.  
Canada  
phone +1 877 620 8889  
[info@weicon.ca](mailto:info@weicon.ca)

WEICON Ibérica S.L.  
Spain  
phone +34 (0) 914 7997 34  
[info@weicon.es](mailto:info@weicon.es)

WEICON Italia S.r.l.  
Italy  
phone +39 (0) 010 2924 871  
[info@weicon.it](mailto:info@weicon.it)

WEICON SA (Pty) Ltd  
South Africa  
phone +27 (0) 21 709 0088  
[info@weicon.co.za](mailto:info@weicon.co.za)

WEICON Kimya Sanayi Tic. Ltd. Şti.  
Turkey  
phone +90 (0) 212 465 33 65  
[info@weicon.com.tr](mailto:info@weicon.com.tr)