

Threadlocking Varnish

Threadlocking varnish



Fast-drying | non-conductive | excellent media resistance

WEICON Threadlocking Varnish is a solvent-based, fast-drying securing and marking varnish with good adhesion to many materials. It serves as a removable lock, as protection against tampering by unauthorised persons, as a cover for electrically conductive parts and as protection against corrosion and influencing through contact. The product is resistant to water, petrol, diesel, mineral oil, paraffin oil and diluted acids and lyes. Threadlocking Varnish is essential for locking screw connections of all kinds, protecting against manipulation and unauthorised loosening of screws and connections, documenting quality assurance measures, production control and product inspection through a varnish seal and also for the visual inspection of connected, adjusted parts. Available in yellow, green and red.

Processing

Shake can well and apply from a distance of approx. 5 cm, then allow to take effect for approx. 30 seconds.

Storage

Threadlocking Varnish has a shelf life of at least 12 months, when stored at room temperature in closed original container. Protect from heat sources and direct sunlight.

Instructions for use

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

Available sizes

- 10038884 Threadlocking varnish, 30 g, grün (RAL 6010)
- 10046906 Threadlocking varnish, 60 g, grün (RAL 6010)
- 10038883 Threadlocking varnish, 30 g, gelb (RAL 1021)
- 10047485 Threadlocking varnish, 60 g, gelb (RAL 1021)
- 10038882 Threadlocking varnish, 30 g, rot (RAL 3000)
- 10047481 Threadlocking varnish, 60 g, rot (RAL 3000)
- 10045481 Threadlocking varnish, 10 kg, rot (RAL 3000)

Technical Data

Gloss level	matt
Viscosity	1.500 mPa·s
Cured after	60 min.
Gap bridging up to max.	mm mm
Breakaway torque	2,7 Nm
Temperature resistance	-60°C to +120°C
Shelf life	12 mon.

Approvals / Guidelines

IMPA Code	450830
-----------	--------

To the product detail page:



Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON Middle East L.L.C.
United Arab Emirates
phone +971 4 880 25 05
info@weicon.ae

WEICON Czech Republic s.r.o.
Czech Republic
phone +42 (0) 417 533 013
info@weicon.cz

WEICON GmbH & Co. KG
(Headquaters) Germany
phone +49 (0) 251 9322 0
info@weicon.de

WEICON Romania SRL
Romania
phone +40 (0) 3 65 730 763
office@weicon.com

WEICON South East Asia Pte Ltd
Singapore
Phone (+65) 6710 7671
info@weicon.com.sg

WEICON Inc.
Canada
phone +1 877 620 8889
info@weicon.ca

WEICON Ibérica S.L.
Spain
phone +34 (0) 914 7997 34
info@weicon.es

WEICON Italia S.r.l.
Italy
phone +39 (0) 10 2924 871
info@weicon.it

WEICON SA (Pty) Ltd
South Africa
phone +27 (0) 21 709 0088
info@weicon.co.za

WEICON Kimya Sanayi Tic. Ltd. Şti.
Turkey
phone +90 (0) 212 465 33 65
info@weicon.com.tr