## WEICON

### WEICONLOCK® **Threadlocking**

# WEICONLOCK® AN 301-43 Threadlocking







#### Threadlocking | classified as non-hazardous | drinking water and DVGW approval

- · higher viscosity
- · medium strength
- · disassembly with normal tools

#### Technical Data

Colour		blue		
Fluorescent		yes		
For thread connections up t	0	M 36		
Viscosity		2.000 - 8.000 mt mPa·s		
Gap bridging up to max.		0,25 mm		
Breakaway torque		18 - 22 Nm		
Prevail torque		9 - 11 Nm		
Shear strength Nmm <sup>2</sup> (DIN 5	54452)	10 - 13 N/mm <sup>2</sup>		
Handling strength	at room temperature	5 - 15 min.		
Final strength	(100 % strength)	1-3 h		
Temperature resistance		-60°C to +150°C		
Minimum shelf life	at room temperature	24 mon.		
Compressive strength (free cutting steel / grub screw = 8.8)				
M 3x6	max.	1500 bar		
M 4x6	max.	1500 bar		
M 5x8	max.	1500 bar		
M 6x10	max.	1500 bar		
M 8x12	max.	1000 bar		
M 10x16	max.	700 bar		
Approvals / Guidelines				
MIL-Spec	complies with	MIL-T-83523		

#### **Surface Pre-Treatment**

To achieve optimum results, the mounting parts should be degreased and cleaned, e.g. with WEICON Surface (roughen the surfaces, if required). WEICONLOCK can also be used on uncleaned surfaces, e.g. screws as delivered. However, the cleaner the surface, the better the results achieved.

#### **Application**

WEICONLOCK is applied evenly straight from the Pen with the help of the dosing tip; avoid direct contact between dosing tip /metal. For sealing applications, apply WEICONLOCK to the thread in circles. Assemble parts and screw tight. Do not pour any WEICONLOCK back into the bottle that has already come into contact with metal. Even extremely small metal particles cause the adhesive to cure inside the bottle. Therefore, in serial production, the use of dosing devices is recommended.

#### **Storage**

Store WEICONLOCK in the unopened original container at room temperature. Avoid sources of heat and direct sunlight. The air inside the packaging helps maintain storage stability.

#### Instructions for use

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

#### Accessories

10021433 Activator F, 200 ml, green 10001256 Dosing Tip, 1 PCE

ml, blue

#### Available sizes

10026814	WEICONLOCK® AN 301-43 Threadlocking, 50
10026817	ml, blue WEICONLOCK® AN 301-43 Threadlocking, 200
	ml, blue
10026819	WEICONLOCK® AN 301-43 Threadlocking, 20



The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the requested properties are recommended. A claim cannot be derived from them.

WEICON Middle East L.L.C. United Arab Emirates phone +971 4 880 25 05

Canada phone +1 877 620 8889 info@weicon.ca

WEICON Czech Republic s.r.o. phone +42 (0) 417 533 013

Spain phone +34 (0) 914 7997 34

WEICON GmbH & Co. KG ohone +49 (0) 251 9322 0

Italy phone +39 (0) 010 2924 871

WEICON Romania SRL phone +40 (0) 3 65 730 763

WEICON SA (Pty) Ltd South Africa phone +27 (0) 21 709 0088 info@weicon.co.za

WEICON South East Asia Pte Ltd ne (+65) 6710 7671

WEICON Kimya Sanayi Tic. Ltd. Sti. Türkiye phone +90 (0) 212 465 33 65