WEICON

WEICONLOCK®

WEICONLOCK® AN 302-21 Threadlocking



Threadlocking | vibration-proof |classified as non-hazardous

- · low viscosity
- · low strength
- · easy disassembly

M6x10

M8x12

M10x16

Technical Data

Colour		violet
Fluorescent		yes
For thread connections up to		M 12
Viscosity		125 mPa⋅s
Gap bridging up to max.		0,1 mm
Breakaway torque		7 - 10 Nm
Prevail torque		3 - 6 Nm
Shear strength Nmm ² (DIN 544	52)	4 - 7 N/mm²
Handling strength		10 - 20 min.
Final strength	(100 % strength)	3 - 6 h
Temperature resistance		-60°C to +150°C
Compressive strength (free cutting steel / grub screw = 8.8)		
M_3x6	max.	1500 bar
M4x6	max.	1500 bar
M5x8	max.	1500 bar

max

max.

max.

Anaerobic Adhesives and Sealants

Surface pre-treatment

To achieve optimum results, the mounting parts should be degreased and cleaned, e.g. with WEICON Surface (roughen the surfaces, if required). WEICONLOCK can also be used on uncleaned surfaces, e.g. screws as delivered. However, the cleaner the surface, the better the results achieved.

Processing

WEICONLOCK is applied evenly straight from the Pen with the help of the dosing tip; avoid direct contact between dosing tip /metal. For sealing applications, apply WEICONLOCK to the thread in circles. Assemble parts and screw tight. Do not pour any WEICONLOCK back into the bottle that has already come into contact with metal. Even extremely small metal particles cause the adhesive to cure inside the bottle. Therefore, in serial production, the use of dosing devices is recommended.

Storage

WEICONLOCK has a shelf life of at least 24 months, when stored at room temperature in closed original container. Protect from heat sources and direct sunlight. The air contained in the Pen keeps WEICONLOCK liquid.

Instructions for use

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

Available sizes

WEICONLOCK® AN 302-21 Threadlocking, 20 10016416 ml, violet WEICONLOCK® AN 302-21 Threadlocking, 50 10017871

ml, violet

WEICONLOCK® AN 302-21 Threadlocking, 200 10019881

ml, violet



The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the requested properties are recommended. A claim cannot be derived from them.

400 bar

300 bar

300 bar

WEICON Romania SRL phone +40 (0) 3 65 730 763

WEICON SA (Pty) Ltd South Africa phone +27 (0) 21 709 0088 info@weicon.co.za

WEICON South East Asia Pte Ltd ne (+65) 6710 7671