

WEICONLOCK® AN 302-42 Threadlocking



Threadlocker | drinking water approval

- medium viscosity
- medium strength
- disassembly with normal tools

Technical Data

| | | |
|--|--------------------------|----------|
| Colour | blue | |
| Fluorescent | yes | |
| For thread connections up to | M 36 | |
| Viscosity | 1.000 mPa·s | |
| Gap bridging up to max. | 0,2 mm | |
| Breakaway torque | 14 - 18 Nm | |
| Prevail torque | 5 - 8 Nm | |
| Shear strength Nmm ² (DIN 54452) | 8 - 12 N/mm ² | |
| Handling strength | 10 - 20 min. | |
| Final strength (100 % strength) | 3-6 h | |
| Temperature resistance | -60 °C to +150 °C | |
| Minimum shelf life | at room temperature | |
| Compressive strength (free cutting steel / grub screw = 8.8) | 24 mon. | |
| M 3x6 | max. | 1500 bar |
| M 4x6 | max. | 1500 bar |
| M 5x8 | max. | 1500 bar |
| M 6x10 | max. | 1300 bar |
| M 8x12 | max. | 600 bar |
| M 10x16 | max. | 400 bar |

Approvals / Guidelines

| | |
|-------------------|------------------------------|
| Hygiene Institute | UBA KTW-BWGL |
| MIL-Spec | complies with MIL-T-83523 |

Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON Middle East L.L.C.
United Arab Emirates
phone +971 4 880 25 05
info@weicon.ae

WEICON Inc.
Canada
phone +1 877 620 8889
info@weicon.ca

WEICON Czech Republic s.r.o.
Czech Republic
phone +42 (0) 417 533 013
info@weicon.cz

WEICON Ibérica S.L.
Spain
phone +34 (0) 914 7997 34
info@weicon.es

WEICON GmbH & Co. KG
(Headquarters) Germany
phone +49 (0) 511 9322 0
info@weicon.de

WEICON Italia S.r.l.
Italy
phone +39 (0) 010 2924 871
info@weicon.it


WEICON Romania SRL
Romania
phone +40 (0) 3 65 730 763
office@weicon.com

WEICON SA (Pty) Ltd
South Africa
phone +27 (0) 21 709 0088
info@weicon.co.za

WEICON South East Asia Pte Ltd
Singapore
Phone (+65) 6710 7671
info@weicon.com.sg

WEICON Kimya Sanayi Tic. Ltd. Şti.
Türkiye
Phone +90 (0) 212 465 33 65
info@weicon.com.tr


Reaction rate of various materials



Surface Pre-Treatment

To achieve optimum results, the mounting parts should be degreased and cleaned, e.g. with WEICON Surface (roughen the surfaces, if required). WEICONLOCK can also be used on uncleansed surfaces, e.g. screws as delivered. However, the cleaner the surface, the better the results achieved.

Reaction with activator F




Application

WEICONLOCK is applied evenly straight from the Pen with the help of the dosing tip; avoid direct contact between dosing tip /metal. For sealing applications, apply WEICONLOCK to the thread in circles. Assemble parts and screw tight. Do not pour any WEICONLOCK back into the bottle that has already come into contact with metal. Even extremely small metal particles cause the adhesive to cure inside the bottle. Therefore, in serial production, the use of dosing devices is recommended.

WEICONLOCK® AN

302-42 Threadlocking


Reaction speed at temp.



Storage

Store WEICONLOCK in the unopened original container at room temperature. Avoid sources of heat and direct sunlight. The air inside the packaging helps maintain storage stability.


Heat aging



Instructions for use

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

Strength in heat



Accessories

10021433 Activator F, 200 ml, green
 10001256 Dosing Tip, 1 PCE

Available sizes

10017324 WEICONLOCK® AN 302-42 Threadlocking, 20 ml, blue
 10017874 WEICONLOCK® AN 302-42 Threadlocking, 50 ml, blue
 10019966 WEICONLOCK® AN 302-42 Threadlocking, 200 ml, blue

To the product detail page:



Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.