

Smoke Detector Test Spray non-flammable

Special Sprays



non flammable | silicone-free | residue-free evaporation

The test spray is ideal to quickly and reliably test the functionality of optical or photoelectric smoke detectors. The use of the non flammable test aerosol does not soil the smoke detectors, as the spray evaporates completely without leaving any residue. WEICON Smoke Detector Test Spray non-flammable is very easy to apply and can be used wherever photoelectric smoke detectors are installed – for example in the shipping industry, in industrial plants, public institutions or private households.

Application

Shake can well before use and spray the test spray from a distance of approx. 30 cm for up to five seconds into the direction of the smoke detector. If there is no reaction, the test must be repeated. If there is still no reaction after several tests, the smoke detector is defective and must be replaced.

Storage

Container is pressurised. Protect from direct sunlight and temperatures above +50 °C.

Instructions for use

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

Available sizes

10060627 Smoke Detector Test Spray non-flammable, 250 ml, colourless, transparent

Conversion table

$(^{\circ}\text{C} \times 1.8) + 32 = ^{\circ}\text{F}$

$\text{mm}/25.4 = \text{inch}$

$\mu\text{m}/25.4 = \text{mil}$

$\text{N} \times 0.225 = \text{lb}$

$\text{N}/\text{mm}^2 \times 145 = \text{psi}$

$\text{MPa} \times 145 = \text{psi}$

$\text{Nm} \times 8.851 = \text{lb}\cdot\text{in}$

$\text{Nm} \times 0.738 = \text{lb}\cdot\text{ft}$

$\text{Nm} \times 141.62 = \text{oz}\cdot\text{in}$

$\text{mPa}\cdot\text{s} = \text{cP}$

$\text{N}/\text{cm} \times 0.571 = \text{lb}/\text{in}$

$\text{kV}/\text{mm} \times 25.4 = \text{V}/\text{mil}$

Technical data

Odour	Alcohol
Specific properties	Non-flammable, evaporates without residue
Silicone-free	yes
Minimum shelf life at room temperature	24 mon.

Approvals / Guidelines

IMPA Code	331077
-----------	--------

To the product detail page:



Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON Middle East L.L.C.
United Arab Emirates
phone +971 4 880 25 05
info@weicon.ae

WEICON Czech Republic s.r.o.
Czech Republic
phone +42 (0) 417 533 013
info@weicon.cz

WEICON GmbH & Co. KG
(Headquarters) Germany
phone +49 (0) 251 9322 0
info@weicon.de

WEICON Romania SRL
Romania
phone +40 (0) 3 65 730 763
office@weicon.com

WEICON South East Asia Pte Ltd
Singapore
Phone (+65) 6710 7671
info@weicon.com.sg

WEICON Inc.
Canada
phone +1 877 620 8889
info@weicon.ca

WEICON Ibérica S.L.
Spain
phone +34 (0) 914 7997 34
info@weicon.es

WEICON Italia S.r.l.
Italy
phone +39 (0) 010 2924 871
info@weicon.it

WEICON SA (Pty) Ltd
South Africa
phone +27 (0) 21 709 0088
info@weicon.co.za

WEICON Kimya Sanayi Tic. Ltd. Şti.
Türkiye
phone +90 (0) 212 465 33 65
info@weicon.com.tr