

Assembly adhesive



Universal use | fast-curing

Fast and strong contact adhesive based on synthetic rubber for indoor and outdoor bonding. The elastic 1-component assembly adhesive can be used on many materials, such as wood and wood fibreboards, MDF and OSB boards, decorative boards, steel, aluminium, plastic, PVC, plaster, plasterboard, ceramics, masonry, tiles, stone and concrete. The adhesive is suitable for the quick and permanent fixing of skirting boards, panels, flooring elements, wall coverings, window bottoms, door thresholds, wooden door frames, decorative profiles and many other applications.

Technical Data

Base	synthetic rubber (SBR)	
Colour	light beige	
Texture	pasty	
Density	1,1 g/cm ³	
Viscosity	200.000 mPa·s	
Skin-over time	1 min.	
Curing speed	in the first 24 h	2-3 mm
Curing condition	23 °C & 50 % relative air humidity	
Gap bridging up to max.	5 mm	
Processing temperature	+5 °C to +40 °C	
Lap shear strength material thickn. 1,5mm DIN EN 1465		
	MDF	2,7 N/mm ²
Temperature resistance	-40 °C to +100 °C	

Surface Pre-Treatment

Surfaces must be clean and free of grease. Many surface soiling, such as oil, grease, dust and dirt can be removed with WEICON Surface Cleaner. For heavily soiled metal surfaces, we recommend Cleaner Spray S. To remove old colour residues or adhesive residues, WEICON Sealant and Adhesive Remover is ideal. Most materials can be bonded to and among each other. For certain materials or special requirements, we recommend the use of a bonding agent (primer). Mechanical surface pre-treatment, e.g. by grinding or sandblasting, can also improve the adhesion considerably.

Application

Application methods Hand Cartridge gun for 310 ml cartridges, compressed air gun. We recommend an alternative with piston rod (WEICON Compressed Air Cartridge Gun), automatic dosing systems.

Joining the components

In order to guarantee optimal wetting, the components must be joined quickly, before the first skin has formed on the adhesive (skin-forming time).

Storage

Store in the unopened original container at room temperature. Avoid sources of heat and direct sunlight.

Instructions for use

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

Accessories

10025241	V-Joint Nozzle, 1 PCE
10000441	Cartridge Gun, 1 PCE
10020751	Cartridge Gun Special, 1 PCE
10101992	Clip Nozzle Green Tube, 1 PCE, transparent
10059792	Pressure gun Airflow 3, 1 PCE

Available sizes

10060801	Assembly adhesive, 310 ml, light beige
----------	--

Conversion table

(°C x 1.8) + 32 = °F	Nm x 8.851 = lb·in
mm/25.4 = inch	Nm x 0.738 = lb·ft
µm/25.4 = mil	Nm x 141.62 = oz·in
N x 0.225 = lb	mPa·s = cP
N/mm ² x 145 = psi	N/cm x 0.571 = lb/in
MPa x 145 = psi	kV/mm x 25.4 = V/mil

Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

Assembly adhesive

To the product detail page:



Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON Middle East L.L.C.
United Arab Emirates
phone +971 4 880 25 05
info@weicon.ae

WEICON Czech Republic s.r.o.
Czech Republic
phone +42 (0) 417 533 013
info@weicon.cz

WEICON GmbH & Co. KG
(Headquarters) Germany
phone +49 (0) 251 9322 0
info@weicon.de

WEICON Romania SRL
Romania
phone +40 (0) 3 65 730 763
office@weicon.com

WEICON South East Asia Pte Ltd
Singapore
Phone (+65) 6710 7671
info@weicon.com.sg

WEICON Inc.
Canada
phone +1 877 620 8889
info@weicon.ca

WEICON Ibérica S.L.
Spain
phone +34 (0) 914 7997 34
info@weicon.es

WEICON Italia S.r.l.
Italy
phone +39 (0) 010 2924 871
info@weicon.it

WEICON SA (Pty) Ltd
South Africa
phone +27 (0) 21 709 0088
info@weicon.co.za

WEICON Kimya Sanayi Tic. Ltd. Şti.
Türkiye
phone +90 (0) 212 465 33 65
info@weicon.com.tr