

Lubricating and Multifunctional Oils

W 44 T® Multi-Spray



Multifunctional oil with multiple effects

WEICON W 44 T® is a multifunctional product which combines corrosion protection, water repellency, lubrication, conservation and cleaning in a single product due to its special formula and outstanding capillary action. It loosens seized up screw connections, bolts, fittings and valves, and penetrates and dissolves rust. It repels humidity from electrical contacts, prevents leakage currents, and makes it easier to start wet motors. W 44 T® is also suitable for use as cutting oil for drilling and cutting processes. The oil eliminates squeaky and creaky noises on hinges, guides, bearings, and all types of joints and couplings. WEICON W 44 T® cleans soiled metal surfaces and leaves a long-lasting razorthin film, which does not smear or stick and does not attract dust. It protects and maintains all types of tools, machines, and electrical and mechanical precision devices.

Technische Daten

Odour	vanilla
Colour	pale yellow, transparent
Specific properties	Multifunction oil with compound action
Silicone-free	yes
Kinematic viscosity (40°C)	21 mm ² /s
Kinematic viscosity (100°C)	4 mm ² /s
Temperature resistance	-50 °C to +210 °C
Shelf life	24 mon.

Approvals / Guidelines

ISSA Code	53.402.11
IMPA Code	45 08 21

Processing

Shake can before use. Apply W 44 T from a distance of approx. 5 cm and allow to take effect for approx. 30 seconds.

Storage

Pressurized container. Protect from direct sunlight and temperatures above +50 °C.

Instructions for use

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

Available sizes

10001023	W 44 T® Multi-Spray, 400 ml, pale yellow, transparent
10014593	W 44 T® Multi-Spray, 50 ml, pale yellow, transparent
10015286	W 44 T® Multi-Spray, 200 ml, pale yellow, transparent
10039121	W 44 T® Multi-Spray, 500 ml, pale yellow, transparent
10064019	W 44 T® Multi-Spray, 200 ml, pale yellow, transparent

To the product detail page:



Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON Middle East L.L.C.
United Arab Emirates
phone +971 4 880 25 05
info@weicon.ae

WEICON Czech Republic s.r.o.
Czech Republic
phone +42 (0) 417 533 013
info@weicon.cz

WEICON GmbH & Co. KG
(Headquarters) Germany
phone +49 (0) 251 9322 0
info@weicon.de

WEICON Romania SRL
Romania
phone +40 (0) 3 65 730 763
office@weicon.com

WEICON South East Asia Pte Ltd
Singapore
Phone (+65) 6710 7671
info@weicon.com.sg

WEICON Inc.
Canada
phone +1 877 620 8889
info@weicon.ca

WEICON Ibérica S.L.
Spain
phone +34 (0) 914 7997 34
info@weicon.es

WEICON Italia S.r.l.
Italy
phone +39 (0) 010 2924 871
info@weicon.it

WEICON SA (Pty) Ltd
South Africa
phone +27 (0) 21 709 0088
info@weicon.co.za

WEICON Kimya Sanayi Tic. Ltd. Şti.
Turkey
phone +90 (0) 212 465 33 65
info@weicon.com.tr