

WSD 400 Pressurized-Air Spray Can

Dosing and Processing Tools



Aluminium can | versatile use

WSD 400 refillable spray can suitable for processing most WEICON Technical Liquids. Filling with compressed air is done by means of an adapter (accessory) via the compressed air network (optimum operating pressure 7.5 bar). The range of accessories for the WSD 400 includes an adapter for filling on any compressed air system as well as a spray set with four different spray heads and a ball valve with suction pipe.

Application

Before refilling with active ingredient, allow residual air to escape; then unscrew the nut and pull out the spray valve. Hold the can vertically and fill to max. 2/3 (approx. 400 ml). Insert the spray valve and tighten the nut by hand. Fill with compressed air (min. 5 - max. 10 bar). If different fillers are used, clean the container. After filling, only tighten the nut by hand! In case of frequent use, check the seal in the cap. WSD 400 is approved for the use of various WEICON products (see brochure WEICON Technical Liquids). Do not fill with liquids that are alkaline or degrade plastics. Do not use corrosive or toxic gases, vapours or liquids.

Instructions for use

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

Accessories

10009303 Spray Set for WSD 400, 1 PCE
10000393 Adapter for WSD 400, 1 PCE

Available sizes

10009301 WSD 400 Pressurized-Air Spray Can WSD 400
Pressurized-Air Spray Can, 1 PCE 1 PCE
10015366 WSD 400 Pressurized-Air Spray Can, 1 PCE

Technical Data

Filling quantity	400 ml
Container volume	600 ml
Operating pressure	5 - 10 bar
Deformation pressure	26 bar
Bursting pressure	42 bar

Characteristics

Minimum shelf life	at room temperature	∞ mon.
--------------------	---------------------	--------

Approvals / Guidelines

MIL-Spec	complies with	MIL-T-83523
----------	---------------	-------------

To the product detail page:



Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON Middle East L.L.C.
United Arab Emirates
phone +971 4 880 25 05
info@weicon.ae

WEICON Inc.
Canada
phone +1 877 620 8889
info@weicon.ca

WEICON Czech Republic s.r.o.
Czech Republic
phone +42 (0) 417 533 013
info@weicon.cz

WEICON Iberica S.L.
Spain
phone +34 (0) 914 7997 34
info@weicon.es

WEICON GmbH & Co. KG
(Headquarters) Germany
phone +49 (0) 251 9322 0
info@weicon.de

WEICON Italia S.r.l.
Italy
phone +39 (0) 010 2924 871
info@weicon.it

WEICON Romania SRL
Romania
phone +40 (0) 3 65 730 763
office@weicon.com

WEICON SA (Pty) Ltd
South Africa
phone +27 (0) 21 709 0088
info@weicon.co.za

WEICON South East Asia Pte Ltd
Singapore
Phone (+65) 6710 7671
info@weicon.com.sg

WEICON Kimya Sanayi Tic. Ltd. Şti.
Türkiye
phone +90 (0) 212 465 33 65
info@weicon.com.tr

WSD 400 Pressurized-Air Spray Can

