# SAFETY DATA SHEET



### according to Workplace Safety and Health Regulations Singapore

Mould Release Agent

# Section 1. Identification

Product identifier	:	Mould Release Agent
Product code	:	154500

### Relevant identified uses of the substance or mixture and uses advised against

Lubricants, greases, release products

Supplier's details	: WEICON GmbH & Co. KG Königsberger Str. 255 48157 Münster Germany Phone: +49 251 93220 Fax: +49(0)251 / 9322 - 244 Internet: www.weicon.de
e-mail address of person responsible for this SDS	: msds@weicon.de
Emergency telephone number	<ul> <li>EMERGENCY CONTACT – UK, UAE, South Africa (24h): Tel: ++44 1865 407333 (English)</li> <li>TRANSPORT EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel: ++44 1865 407333 (English)</li> </ul>

# Section 2. Hazards identification

Classification of the substance or mixture	: FLAMMABLE LIQUIDS - Category 2 SKIN CORROSION/IRRITATION - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) -
	Category 3
	ASPIRATION HAZARD - Category 1
	AQUATIC HAZARD (LONG-TERM) - Category 2
	AgoAno hAzAND (Long-renar) - odiegory z

### GHS label elements, including precautionary statements

Hazard pictograms	
Signal word	: Danger
Hazard statements	<ul> <li>H225 - Highly flammable liquid and vapor.</li> <li>H304 - May be fatal if swallowed and enters airways.</li> <li>H315 - Causes skin irritation.</li> <li>H336 - May cause drowsiness or dizziness.</li> <li>H411 - Toxic to aquatic life with long lasting effects.</li> </ul>
Precautionary statements	
Prevention	<ul> <li>P280 - Wear protective gloves.</li> <li>P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</li> <li>P241 - Use explosion-proof electrical, ventilating or lighting equipment.</li> <li>P242 - Use non-sparking tools.</li> <li>P243 - Take action to prevent static discharges.</li> <li>P271 - Use only outdoors or in a well-ventilated area.</li> <li>P273 - Avoid release to the environment.</li> <li>P261 - Avoid breathing vapor.</li> <li>P264 - Wash thoroughly after handling.</li> </ul>

# Section 2. Hazards identification

Response	<ul> <li>P391 - Collect spillage.</li> <li>P304 + P312 - IF INHALED: Call a POISON CENTER or doctor if you feel unwell.</li> <li>P301 + P310, P331 - IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.</li> <li>P362 + P364 - Take off contaminated clothing and wash it before reuse.</li> </ul>
Storage	<ul> <li>P405 - Store locked up.</li> <li>P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.</li> <li>P403 + P235 - Keep cool.</li> </ul>
Disposal	: P501 - Dispose of waste according to applicable legislation.
Other hazards which do not result in classification	: None known.

# Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

Ingredient name	%	CAS number
Hydrocarbons, C6-7	≥75 - ≤90	92128-66-0

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Chemical formula

: Not applicable.

## Section 4. First aid measures

<b>Description of necessa</b>	ary first aid measures
Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	<ul> <li>Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.</li> </ul>
Ingestion	: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Most important sympto	oms/effects, acute and delayed

### Potential acute health effects

**Eye contact** : No known significant effects or critical hazards.

 Date of issue/Date of revision
 : 9/30/2021
 Date of previous issue
 : 9/30/2021
 Version
 : 1.06
 2/11

# Section 4. First aid measures

Inhalation	<ul> <li>Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.</li> </ul>
Skin contact	: Causes skin irritation.
Ingestion	<ul> <li>Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.</li> </ul>
<u>Over-exposure signs/sym</u>	<u>ptoms</u>
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: Adverse symptoms may include the following: nausea or vomiting
Indication of immediate me	dical attention and special treatment needed, if necessary
Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

# Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use dry chemical, CO <sub>2</sub> , water spray (fog) or foam.
Unsuitable extinguishing media	: Do not use water jet.
Specific hazards arising from the chemical	: Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Date of issue/Date of revision: 9/30/2021Date of previous issue: 9/30/2021Version: 1.063/11

# Section 6. Accidental release measures

# Personal precautions, protective equipment and emergency proceduresFor non-emergency<br/>personnel: No action shall be taken involving any personal risk or without suitable training.<br/>Evacuate surrounding areas. Keep unnecessary and unprotected personnel from<br/>entering. Do not touch or walk through spilled material. Shut off all ignition sources.<br/>No flares, smoking or flames in hazard area. Avoid breathing vapor or mist.<br/>Provide adequate ventilation. Wear appropriate respirator when ventilation is<br/>inadequate. Put on appropriate personal protective equipment.For emergency responders: If specialized clothing is required to deal with the spillage, take note of any<br/>information in Section 8 on suitable and unsuitable materials. See also the<br/>information in "For non-emergency personnel".

Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways,
-	drains and sewers. Inform the relevant authorities if the product has caused
	environmental pollution (sewers, waterways, soil or air). Water polluting material.
	May be harmful to the environment if released in large quantities. Collect spillage.

### Methods and materials for containment and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

# Section 7. Handling and storage

### Precautions for safe handling

Protective measures	Put on appropriate personal protective equipment (see Section 8). Do not swallow. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well- ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

# Section 8. Exposure controls/personal protection

### **Control parameters**

### **Occupational exposure limits**

None.

Appropriate engineering controls	: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measure	S
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. Recommended : 1 - 4 hours (breakthrough time): nitrile rubber ; 4 - 8 hours (breakthrough time): Viton®/butyl rubber
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended : organic vapor (Type AX) and particulate filter

# Section 9. Physical and chemical properties

<u>Appearance</u>		
Physical state	:	Liquid.
Color	:	Yellowish.
Odor	:	Characteristic.
Odor threshold	:	Not available.
рН	:	Not applicable.
Melting point/freezing point	:	Not available.

Date of issue/Date of revision

# Section 9. Physical and chemical properties

,		
Boiling point, initial boiling point, and boiling range	:	88 to 106°C (190.4 to 222.8°F)
Flash point	:	Closed cup: -9°C (15.8°F) Open cup: Not applicable.
Evaporation rate	:	Not available.
Flammability	:	Not available.
Lower and upper explosion limit/flammability limit	:	Lower: 0.8% Upper: 7.7%
Vapor pressure	:	24.6 kPa (184.52 mm Hg)
Relative vapor density	:	Not available.
Relative density	:	Not available.
Density	:	0.749 g/cm³ [20°C (68°F)]
Solubility(ies) Not available.	:	
Solubility in water	:	Not available.
Miscible with water	:	No.
Partition coefficient: n- octanol/water	:	Not applicable.
Auto-ignition temperature	:	Not applicable.
Decomposition temperature	:	Not available.
Viscosity	:	Kinematic (40°C (104°F)): <20 mm²/s (<20 cSt)
Flow time (ISO 2431)	:	Not available.
Particle characteristics		
Median particle size	:	Not applicable.

# Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
SADT	: Not available.

# Section 11. Toxicological information

### Information on toxicological effects

### Acute toxicity

Not available.

### Irritation/Corrosion

Not available.

### **Sensitization**

Date of issue/Date of revision

# Section 11. Toxicological information

Not available.

**Mutagenicity** 

Not available.

### Carcinogenicity

Not available.

### **Reproductive toxicity**

Not available.

### <u>Teratogenicity</u>

Not available.

### Specific target organ toxicity (single exposure)

Name	·····	Route of exposure	Target organs
Hydrocarbons, C6-7	Category 3	-	Narcotic effects

### Specific target organ toxicity (repeated exposure)

Not available.

### Aspiration hazard

Name	Result
Hydrocarbons, C6-7	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure	: Not available.
Potential acute health effe	<u>cts</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
Skin contact	: Causes skin irritation.
Ingestion	: Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.
Symptoms related to the p	hysical, chemical and toxicological characteristics
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: Adverse symptoms may include the following: nausea or vomiting
Delayed and immediate eff	ects and also chronic effects from short and long term exposure

### <u>Short term exposure</u>

Date of issue/Date of revision

# Section 11. Toxicological information

		•
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Long term exposure		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Potential chronic health eff	ect	<u>S</u>
Not available.		
General	:	No known significant effects or critical hazards.
Carcinogenicity	:	No known significant effects or critical hazards.
Mutagenicity	:	No known significant effects or critical hazards.
Teratogenicity	:	No known significant effects or critical hazards.
Developmental effects	:	No known significant effects or critical hazards.
Fertility effects	:	No known significant effects or critical hazards.

### Numerical measures of toxicity

# Acute toxicity estimates

### Acute toxicity estimates

Not available.

# Section 12. Ecological information

### **Toxicity**

Not available.

### Persistence/degradability

Not available.

### **Bioaccumulative potential**

Date of issue/Date of revision

Not available.

# Mobility in soil Soil/water partition : Not available. coefficient (Koc) : Not available.

**Other adverse effects** : No known significant effects or critical hazards.

: 9/30/2021

# Section 13. Disposal considerations

Disposal methods :	The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling
--------------------	--

Date of previous issue

:9/30/2021

Version : 1.06

8/11

# Section 13. Disposal considerations

emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information					
	UN	IMDG	ΙΑΤΑ	ADR/RID	
UN number	UN3295	UN3295	UN3295	UN3295	
UN proper shipping name	HYDROCARBONS, LIQUID, N.O.S.	HYDROCARBONS, LIQUID, N.O.S. Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	Hydrocarbons, liquid, n.o.s. Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	HYDROCARBONS, LIQUID, N.O.S. Hydrocarbons, C6-C7 n-alkanes, isoalkanes cyclics, <5% n-hexan	
Transport hazard class(es)	3		3		
Packing group	11	11	11	11	
Environmental hazards	Yes. The environmentally hazardous substance mark is not required.	Yes.	Yes. The environmentally hazardous substance mark is not required.	Yes.	
Additional informa	<u>tion</u>				
IMDG		e pollutant mark is not rec <u>y schedules</u> F-E, S-D	quired when transported	in sizes of ≤5 L or ≤5 k	
ΙΑΤΑ	transportati <u>Quantity li</u> Cargo Aircr Passenger	nmentally hazardous sub on regulations. <u>mitation</u> Passenger and aft Only: 60 L. Packaging Aircraft: 1 L. Packaging <u>ovisions</u> A3, A324	Cargo Aircraft: 5 L. Pac g instructions: 364. Limi	kaging instructions: 353	
ADR/RID	<ul> <li>The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.</li> <li>Hazard identification number 33</li> <li>Limited quantity 1 L</li> </ul>				

Special precautions for user	:	<b>Transport within user's premises:</b> always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available. to IMO instruments

Special provisions 640C Tunnel code (D/E)

ADR Classification Code: F1

# Section 15. Regulatory information

### Singapore - hazardous chemicals under government control

None.

### International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals Not listed.

### **Montreal Protocol**

Not listed.

# Stockholm Convention on Persistent Organic Pollutants

Not listed.

### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

### **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

Inventory list	
Australia	: Not determined.
Canada	: Not determined.
China	: Not determined.
Eurasian Economic Union	: Russian Federation inventory: Not determined.
Japan	: Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined.
New Zealand	: All components are listed or exempted.
Philippines	: Not determined.
Republic of Korea	: All components are listed or exempted.
Taiwan	: Not determined.
Thailand	: All components are listed or exempted.
Turkey	: Not determined.
United States	: Not determined.
Viet Nam	: Not determined.

# Section 16. Other information

<u>History</u>	
Date of printing	: 5/14/2023
Date of issue/Date of revision	: 9/30/2021
Date of previous issue	: 9/30/2021
Version	: 1.06
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations
Procedure used to derive t	he classification

### Procedure used to derive the classification

Date of issue/Date of revision	: 9/30/2021	Date of previous issue	: 9/30/2021	Version : 1.06 10/11

# Section 16. Other information

Classification	Justification
FLAMMABLE LIQUIDS - Category 2	On basis of test data
SKIN CORROSION/IRRITATION - Category 2	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) -	Calculation method
Category 3	
ASPIRATION HAZARD - Category 1	Calculation method
AQUATIC HAZARD (LONG-TERM) - Category 2	Calculation method

References

: Not available.

Indicates information that has changed from previously issued version.

### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.