

SAFETY DATA SHEET



WEICON WP Epoxy Hardener

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : WEICON WP Epoxy Hardener
UFI : VKC1-703X-Q00N-XS0Q
Product code : 104902
Color : Black.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Hardener for resins.

1.3 Details of the supplier of the safety data sheet

WEICON GmbH & Co. KG
Königsberger Str. 255
48157 Münster
Germany
Phone: +49 251 93220
Fax: +49(0)251 / 9322 - 244
Internet: www.weicon.de

e-mail address of person responsible for this SDS : msds@weicon.de

1.4 Emergency telephone number

EMERGENCY CONTACT – UK, UAE, South Africa (24h): Tel: ++44 1865 407333 (English)
TRANSPORT EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel: ++44 1865 407333 (English)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Corr. 1B, H314
Eye Dam. 1, H318
Skin Sens. 1, H317
Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : Danger

SECTION 2: Hazards identification

Hazard statements	: H314 - Causes severe skin burns and eye damage. H317 - May cause an allergic skin reaction. H412 - Harmful to aquatic life with long lasting effects.
<u>Precautionary statements</u>	
Prevention	: P280 - Wear protective gloves, protective clothing and eye or face protection. P273 - Avoid release to the environment. P261 - Avoid breathing vapor.
Response	: P304 + P310 - IF INHALED: Immediately call a POISON CENTER or doctor. P301 + P310, P330, P331 - IF SWALLOWED: Immediately call a POISON CENTER or doctor. Rinse mouth. Do NOT induce vomiting. P303 + P361 + P353, P310 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER or doctor. P363 - Wash contaminated clothing before reuse. P302 + P352 - IF ON SKIN: Wash with plenty of water. P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention. P305 + P351 + P338, P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
Storage	: P405 - Store locked up.
Disposal	: P501 - Dispose of waste according to applicable legislation.
Hazardous ingredients	: 2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminated 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine) 3-aminomethyl-3,5,5-trimethylcyclohexylamine Fatty acids, tall-oil, reaction products with bisphenol A, epichlorohydrin, glycidyl tolyl ether and triethylenetetramine 2-piperazin-1-ylethylamine 3-aminopropyltriethoxysilane Orange, sweet, ext. m-phenylenebis(methylamine) Phenol, styrenated
Supplemental label elements	: Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	: None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

WEICON WP Epoxy Hardener

SECTION 3: Composition/information on ingredients

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino] butyl-terminated	CAS: 68683-29-4	≥10 - ≤25	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317	-	[1]
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine)	REACH #: 01-2119965162-39 EC: 500-302-7 CAS: 113930-69-1	≤5	Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 2, H411	-	[1]
benzyl alcohol	REACH #: 01-2119492630-38 EC: 202-859-9 CAS: 100-51-6 Index: 603-057-00-5	≤3	Acute Tox. 4, H302 Acute Tox. 4, H332	ATE [Oral] = 500 mg/kg ATE [Inhalation (dusts and mists)] = 1.5 mg/l	[1] [2]
3-aminomethyl-3,5,5-trimethylcyclohexylamine	EC: 220-666-8 CAS: 2855-13-2	≤3	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412	ATE [Oral] = 500 mg/kg ATE [Dermal] = 1100 mg/kg	[1] [2]
Fatty acids, tall-oil, reaction products with bisphenol A, epichlorohydrin, glycidyl tolyl ether and triethylenetetramine	REACH #: 01-2119983521-35 EC: 606-078-8 CAS: 186321-96-0	<1	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 1 M [Chronic] = 1	[1]
2-piperazin-1-ylethylamine	REACH #: 01-2119471486-30 EC: 205-411-0 CAS: 140-31-8	<1	Acute Tox. 4, H302 Acute Tox. 3, H311 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Repr. 2, H361 STOT RE 1, H372 Aquatic Chronic 3, H412	ATE [Oral] = 500 mg/kg ATE [Dermal] = 300 mg/kg	[1]
3-aminopropyltriethoxysilane	REACH #: 01-2119480479-24 EC: 213-048-4 CAS: 919-30-2	<1	Acute Tox. 4, H332 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1B, H317	ATE [Inhalation (vapours)] = 11 mg/l	[1]
Orange, sweet, ext.	REACH #: 01-2119493353-35 EC: 232-433-8 CAS: 8028-48-6	≤0.3	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Asp. Tox. 1, H304 Aquatic Chronic 2, H411	-	[1]
m-phenylenebis (methylamine)	REACH #: 01-2119480150-50 EC: 216-032-5 CAS: 1477-55-0	≤0.3	Acute Tox. 4, H302 Acute Tox. 4, H332 Skin Corr. 1B, H314 Eye Dam. 1, H318	ATE [Oral] = 500 mg/kg ATE [Inhalation (dusts and mists)]	[1] [2]

SECTION 3: Composition/information on ingredients

Phenol, styrenated	REACH #: 01-2119980970-27 EC: 262-975-0 CAS: 61788-44-1	≤0.3	Skin Sens. 1B, H317 Aquatic Chronic 3, H412 Skin Irrit. 2, H315 Skin Sens. 1A, H317 Aquatic Chronic 2, H411 See Section 16 for the full text of the H statements declared above.	= 1.5 mg/l -	[1]
--------------------	------------------------------------------------------------------	------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	---------------------	-----

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
- Inhalation** : Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

SECTION 4: First aid measures

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
- Ingestion** : Adverse symptoms may include the following:
stomach pains

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides
halogenated compounds
metal oxide/oxides

5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

SECTION 6: Accidental release measures

- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- 6.2 Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
- 6.3 Methods and materials for containment and cleaning up** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- 6.4 Reference to other sections** : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

- Recommendations** : Not available.
- Industrial sector specific solutions** : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

SECTION 8: Exposure controls/personal protection

Product/ingredient name	Exposure limit values
benzyl alcohol	DFG MAC-values list (Germany, 10/2021). Absorbed through skin. PEAK: 44 mg/m ³ , 4 times per shift, 15 minutes. PEAK: 10 ppm, 4 times per shift, 15 minutes. TWA: 22 mg/m ³ 8 hours. TWA: 5 ppm 8 hours. TRGS 900 OEL (Germany, 7/2021). Absorbed through skin. PEAK: 10 ppm 15 minutes. PEAK: 44 mg/m ³ 15 minutes. TWA: 22 mg/m ³ 8 hours. TWA: 5 ppm 8 hours.
3-aminomethyl-3,5,5-trimethylcyclohexylamine	DFG MAC-values list (Germany, 10/2021). Skin sensitizer.
m-phenylenebis(methylamine)	DFG MAC-values list (Germany, 10/2021). Skin sensitizer.

Biological exposure indices

No exposure indices known.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following:
European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine)	DNEL	Long term Oral	50 µg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	50 µg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	74 µg/m ³	General population	Systemic
	DNEL	Long term Dermal	0.14 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	0.493 mg/m ³	Workers	Systemic
benzyl alcohol	DNEL	Long term Oral	4 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	4 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	5.4 mg/m ³	General population	Systemic
	DNEL	Long term Dermal	8 mg/kg bw/day	Workers	Systemic

SECTION 8: Exposure controls/personal protection

	DNEL	Short term Oral	20 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	20 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	22 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	27 mg/m ³	General population	Systemic
	DNEL	Short term Dermal	40 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	110 mg/m ³	Workers	Systemic
3-aminomethyl-3,5,5-trimethylcyclohexylamine	DNEL	Short term Inhalation	0.073 mg/m ³	Workers	Local
	DNEL	Long term Inhalation	0.073 mg/m ³	Workers	Local
	DNEL	Long term Oral	0.526 mg/kg bw/day	General population	Systemic
Fatty acids, tall-oil, reaction products with bisphenol A, epichlorohydrin, glycidyl tolyl ether and triethylenetetramine	DNEL	Long term Oral	0.5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	1 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.74 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	7.05 mg/m ³	Workers	Systemic
2-piperazin-1-ylethylamine	DNEL	Long term Inhalation	15 µg/m ³	Workers	Local
	DNEL	Short term Inhalation	80 µg/m ³	Workers	Local
	DNEL	Long term Dermal	3.33 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	10.6 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	10.6 mg/m ³	Workers	Systemic
3-aminopropyltriethoxysilane	DNEL	Long term Oral	1 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	1 mg/kg bw/day	General population	Systemic

SECTION 8: Exposure controls/personal protection

Orange, sweet, ext.	DNEL	Long term Dermal	2 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	3.5 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	14 mg/m ³	Workers	Systemic
	DNEL	Short term Dermal	0.0929 mg/cm ²	General population	Local
	DNEL	Short term Dermal	0.1858 mg/cm ²	Workers	Local
	DNEL	Long term Oral	4.44 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	4.44 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	7.78 mg/m ³	General population	Systemic
	DNEL	Long term Dermal	8.89 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	31.1 mg/m ³	Workers	Systemic
m-phenylenebis(methylamine)	DNEL	Long term Inhalation	0.2 mg/m ³	Workers	Local
	DNEL	Long term Dermal	0.33 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.2 mg/m ³	Workers	Systemic
Phenol, styrenated	DNEL	Long term Oral	0.29 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	1.01 mg/m ³	General population	Systemic
	DNEL	Long term Dermal	1.46 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	2.92 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	4.11 mg/m ³	Workers	Systemic

PNECs

No PNECs available.

8.2 Exposure controls

Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Individual protection measures

SECTION 8: Exposure controls/personal protection

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. Recommended : 1 - 4 hours (breakthrough time): nitrile rubber ; 4 - 8 hours (breakthrough time): Viton®/butyl rubber
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended : organic vapor (Type AX) and particulate filter
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

- Physical state** : Liquid.
- Color** : Black.
- Odor** : Characteristic.
- Odor threshold** : Not available.
- Melting point/freezing point** : Not available.
- Initial boiling point and boiling range** : Not available.
- Flammability** : Not available.
- Upper/lower flammability or explosive limits** : Not available.
- Flash point** : Closed cup: >100°C (>212°F)
- Auto-ignition temperature** :

WEICON WP Epoxy Hardener

SECTION 9: Physical and chemical properties

Ingredient name	°C	°F	Method
Carbon Black	>140	>284	VDI 2263
Orange, sweet, ext.	235	455	EU A.15
2-piperazin-1-ylethylamine	>300	>572	
decamethylcyclotrasiloxane	372	701.6	ASTM E 659-78
2,4,6-tris(dimethylaminomethyl)phenol	382	719.6	EU A.15
octamethylcyclotetrasiloxane	384 to 387	723.2 to 728.6	ASTM E 659
benzyl alcohol	436	816.8	
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine)	526	978.8	

Decomposition temperature : Not available.

pH : Not applicable.

Viscosity : Not available.

Solubility(ies) :

Not available.

Solubility in water : Not available.

Partition coefficient: n-octanol/ water : Not applicable.

Vapor pressure :

Ingredient name	Vapor Pressure at 20 °C			Vapor pressure at 50 °C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
Orange, sweet, ext.	1.4	0.19				
octamethylcyclotetrasiloxane	0.99	0.13				
decamethylcyclotetrasiloxane	0.25	0.033				
2,4,6-tris(dimethylaminomethyl)phenol	0.06	0.008	EU A.4			
benzyl alcohol	0.05	0.0067				
2-piperazin-1-ylethylamine	0.039	0.0052				
3-aminomethyl-3,5,5-trimethylcyclohexylamine	0.01	0.0013	OECD 104			
m-phenylenebis(methylamine)	0.01	0.0013	OECD 104			

Relative density : Not available.

Density : 2.5 g/cm³ [20°C (68°F)]

Vapor density : Not available.

Explosive properties : Not available.

Oxidizing properties : Not available.

Particle characteristics

Median particle size : Not applicable.

9.2 Other information

SADT : Not available.

SAPT : Not available.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : No specific data.

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
benzyl alcohol	LD50 Dermal	Rabbit	2000 mg/kg	-
	LD50 Oral	Mouse	1360 mg/kg	-
	LD50 Oral	Mouse	1360 mg/kg	-
	LD50 Oral	Rabbit	1040 mg/kg	-
	LD50 Oral	Rabbit	1040 mg/kg	-
	LD50 Oral	Rat	1.5 mL/kg	-
	LD50 Oral	Rat	1230 mg/kg	-
	LD50 Oral	Rat	1660 mg/kg	-
3-aminopropyltriethoxysilane	LD50 Dermal	Rabbit	4.29 g/kg	-
	LD50 Oral	Rat	1.57 g/kg	-

Conclusion/Summary : Not available.

Acute toxicity estimates

Route	
Oral	5137.61 mg/kg
Dermal	8206.86 mg/kg
Inhalation (dusts and mists)	28.72 mg/l

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
benzyl alcohol	Skin - Mild irritant	Man	-	48 hours 16 mg	-
	Skin - Moderate irritant	Pig	-	100 %	-
	Skin - Moderate irritant	Rabbit	-	24 hours 100 mg	-
2-piperazin-1-ylethylamine	Eyes - Moderate irritant	Rabbit	-	24 hours 20 mg	-

SECTION 11: Toxicological information

3-aminopropyltriethoxysilane	Skin - Severe irritant	Rabbit	-	24 hours 5 mg	-
	Skin - Severe irritant	Rabbit	-	24 hours 5 mg	-

Conclusion/Summary : Not available.

Sensitization

Conclusion/Summary : Not available.

Mutagenicity

Conclusion/Summary : Not available.

Carcinogenicity

Conclusion/Summary : Not available.

Reproductive toxicity

Conclusion/Summary : Not available.

Teratogenicity

Conclusion/Summary : Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
2-piperazin-1-ylethylamine	Category 1	-	-

Aspiration hazard

Product/ingredient name	Result
Orange, sweet, ext.	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure : Not available.

Potential acute health effects

Eye contact : Causes serious eye damage.
Inhalation : No known significant effects or critical hazards.
Skin contact : Causes severe burns. May cause an allergic skin reaction.
Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:
 pain
 watering
 redness

Inhalation : No specific data.

Skin contact : Adverse symptoms may include the following:
 pain or irritation
 redness
 blistering may occur

Ingestion : Adverse symptoms may include the following:
 stomach pains

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

SECTION 11: Toxicological information

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary : Not available.

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : No known significant effects or critical hazards.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
benzyl alcohol	Acute LC50 10000 µg/l Fresh water	Fish - <i>Lepomis macrochirus</i>	96 hours
	Acute LC50 15000 µg/l Marine water	Fish - <i>Menidia beryllina</i>	96 hours
	Acute LC50 460000 µg/l Fresh water	Fish - <i>Pimephales promelas</i> - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
2-piperazin-1-ylethylamine	Acute LC50 2190000 µg/l Fresh water	Fish - <i>Pimephales promelas</i>	96 hours

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine)	-	4.77	Low
benzyl alcohol	0.87	-	Low
3-aminomethyl-	0.99	-	Low

SECTION 12: Ecological information

3,5,5-trimethylcyclohexylamine			
2-piperazin-1-ylethylamine	-1.48	-	Low
3-aminopropyltriethoxysilane	1.7	3.4	Low
Orange, sweet, ext.	2.78 to 4.88	1.502 to 2.597	Low
m-phenylenebis (methylamine)	0.18	2.69	Low

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : The classification of the product may meet the criteria for a hazardous waste.

European waste catalogue (EWC)

Waste code	Waste designation
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances




Packaging

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	European waste catalogue (EWC)
15 01 10*	packaging containing residues of or contaminated by hazardous substances

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA
14.1 UN number	UN1760	UN1760	UN1760
14.2 UN proper shipping name	CORROSIVE LIQUID, N.O.S. (4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis (methylamine), 3-aminomethyl-3,5,5-trimethylcyclohexylamine)	CORROSIVE LIQUID, N.O.S. (4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis (methylamine), 3-aminomethyl-3,5,5-trimethylcyclohexylamine)	CORROSIVE LIQUID, N.O.S. (4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis (methylamine), 3-aminomethyl-3,5,5-trimethylcyclohexylamine)
14.3 Transport hazard class(es)	8 	8 	8 
14.4 Packing group	II	II	II
14.5 Environmental hazards	No. Not available.	No. Not available.	No.

Additional information

ADR/RID : **Tunnel code (E)**

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
WEICON WP Epoxy Hardener	≥90	3

Labeling : Not applicable.

Other EU regulations

SECTION 15: Regulatory information

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

Storage class (TRGS 510) : 8A

Hazardous incident ordinance

This product is not controlled under the Germany Hazardous Incident Ordinance.

Hazard class for water : 2

Technical instruction on air quality control : TA-Luft Number 5.2.5: 6.6-11.5%
TA-Luft Class I - Number 5.2.5: 1-2%

AOX : The product contains organically bound halogens and can contribute to the AOX value in waste water.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Australia : Not determined.

Canada : Not determined.

China : Not determined.

Eurasian Economic Union : **Russian Federation inventory:** Not determined.

Japan : **Japan inventory (CSCL):** Not determined.
Japan inventory (ISHL): Not determined.

New Zealand : Not determined.

SECTION 15: Regulatory information

Philippines	: Not determined.
Republic of Korea	: Not determined.
Taiwan	: Not determined.
Thailand	: Not determined.
Turkey	: Not determined.
United States	: Not determined.
Viet Nam	: Not determined.

15.2 Chemical Safety Assessment : This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

Abbreviations and acronyms	: ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number SGG = Segregation Group vPvB = Very Persistent and Very Bioaccumulative
-----------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Corr. 1B, H314	Calculation method
Eye Dam. 1, H318	Calculation method
Skin Sens. 1, H317	Calculation method
Aquatic Chronic 3, H412	Calculation method

Full text of abbreviated H statements

H226	Flammable liquid and vapor.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H361	Suspected of damaging fertility or the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

SECTION 16: Other information

Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	AQUATIC HAZARD (ACUTE) - Category 1
Aquatic Chronic 1	AQUATIC HAZARD (LONG-TERM) - Category 1
Aquatic Chronic 2	AQUATIC HAZARD (LONG-TERM) - Category 2
Aquatic Chronic 3	AQUATIC HAZARD (LONG-TERM) - Category 3
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Eye Dam. 1	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Repr. 2	TOXIC TO REPRODUCTION - Category 2
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITIZATION - Category 1
Skin Sens. 1A	SKIN SENSITIZATION - Category 1A
Skin Sens. 1B	SKIN SENSITIZATION - Category 1B
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

Date of printing : 2/1/2024

Date of issue/ Date of revision : 2/1/2024

Date of previous issue : 11/21/2023

Version : 1.03

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.