SAFETY DATA SHEET



WEICON Ceramic HC 220 Epoxy Hardener

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name UFI Product code Color : WEICON Ceramic HC 220 Epoxy Hardener : 9061-A084-T00G-XK4H

: 105231

: Yellowish.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	
Hardener for resins.	

1.3 Details of the supplier of the safety data sheet

WEICON GmbH & Co. KG Königsberger Str. 255 48157 Münster Germany Phone: +49 251 93220 Fax: +49(0)251 / 9322 - 244 Internet: www.weicon.de e-mail address of person : msds@weicon.de

responsible for this SDS

1.4 Emergency telephone number

EMERGENCY CONTACT – UK, UAE, South Africa (24h): Tel: ++44 1865 407333 (English) TRANSPORT EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel: ++44 1865 407333 (English)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Acute Tox. 4, H302 Acute Tox. 4, H332 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



SECTION 2: Hazards identification

SECTION 2. Hazarus		
Signal word	:	Danger
Hazard statements	:	H302 + H332 - Harmful if swallowed or if inhaled. H314 - Causes severe skin burns and eye damage. H317 - May cause an allergic skin reaction. H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements		
Prevention	:	 P280 - Wear protective gloves, protective clothing and eye or face protection. P271 - Use only outdoors or in a well-ventilated area. P273 - Avoid release to the environment. P261 - Avoid breathing vapor. P270 - Do not eat, drink or smoke when using this product. P264 - Wash thoroughly after handling.
Response	:	 P304 + P310 - IF INHALED: Immediately call a POISON CENTER or doctor. P301 + P310, P330, P331 - IF SWALLOWED: Immediately call a POISON CENTER or doctor. Rinse mouth. Do NOT induce vomiting. P303 + P361 + P353, P310 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER or doctor. P363 - Wash contaminated clothing before reuse. P302 + P352 - IF ON SKIN: Wash with plenty of water. P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention. P305 + P351 + P338, P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
Storage	:	P405 - Store locked up.
Disposal	:	P501 - Dispose of waste according to applicable legislation.
Hazardous ingredients	:	polyethlyenepolyamines m-phenylenebis(methylamine) 3,3,5-trimethylhexylenediamine
Supplemental label elements	:	Contains epoxy constituents. May produce an allergic reaction.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	:	None known.

SECTION 3: Composition/information on ingredients

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Date of issue/Date of revision	: 6/22/2023	Date of previo	us issue : 6/19/2023	Version : 2.0)4 2/1

WEICON Ceramic HC 220 Epoxy Hardener

SECTION 3: Compo	sition/informat	ion on in	gredients		
polyethlyenepolyamines	REACH #: 01-2119487919-13 EC: 292-588-2 CAS: 90640-67-8 Index: 612-065-00-8	≥50 - <55	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412	ATE [Oral] = 500 mg/kg ATE [Dermal] = 1100 mg/kg	[1]
m-phenylenebis (methylamine)	REACH #: 01-2119480150-50 EC: 216-032-5 CAS: 1477-55-0	≥25 - ≤50	Acute Tox. 4, H302 Acute Tox. 4, H332 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1B, H317 Aquatic Chronic 3, H412 EUH071	ATE [Oral] = 500 mg/kg ATE [Inhalation (dusts and mists)] = 1.5 mg/l	[1] [2]
3,3,5-trimethylhexylenediamine	EC: 247-063-2 CAS: 25513-64-8 Index: 1804	<5	Acute Tox. 4, H302 Skin Corr. 1A, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 See Section 16 for the full text of the H statements declared above.	ATE [Oral] = 500 mg/kg	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Type</u>

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

. ...

4.1 Description of first aid m	neasures
Eye contact	: Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
Inhalation	: Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	: Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

SECTION 4: First aid measures

Ingestion	: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur
Ingestion	: Adverse symptoms may include the following: stomach pains

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media					
Suitable extinguishing media	: Use an extingu	ishing agent suitable	for the surrounding	fire.	
Unsuitable extinguishing media	: None known.				
5.2 Special hazards arising	om the substance	e or mixture			
Hazards from the substance or mixture	This material is contaminated v	eated, a pressure incr s harmful to aquatic li with this material mus any waterway, sewer	fe with long lasting e at be contained and p	ffects. Fire water	
Hazardous combustion products	: Decomposition carbon dioxide carbon monoxi nitrogen oxides	de	e the following mate	rials:	
5.3 Advice for firefighters					
Special protective actions for fire-fighters		e the scene by remov No action shall be tal g.			
Date of issue/Date of revision	: 6/22/2023 D	ate of previous issue	: 6/19/2023	Version : 2.0	4/15

SECTION 5: Firefighting measures

Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.
---	---	---

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
6.3 Methods and materials for containment and cleaning up	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s) Recommendations	: Not availabl	e.		
Date of issue/Date of revision	: 6/22/2023	Date of previous issue	: 6/19/2023	Version : 2.04 5/15

SECTION 7: Handling and storage

Industrial sector specific : Not available. solutions

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
m-phenylenebis(methylamine)	DFG MAC-values list (Germany, 10/2021). Skin sensitizer.
procedures Euro asso valu atm of e (Wo for t	ce should be made to monitoring standards, such as the following: n Standard EN 689 (Workplace atmospheres - Guidance for the nent of exposure by inhalation to chemical agents for comparison with limit nd measurement strategy) European Standard EN 14042 (Workplace heres - Guide for the application and use of procedures for the assessment ure to chemical and biological agents) European Standard EN 482 ace atmospheres - General requirements for the performance of procedures heasurement of chemical agents) Reference to national guidance ints for methods for the determination of hazardous substances will also be

DNELs/DMELs

Product/ingredient name	Туре	Exposure	Value	Population	Effects
polyethlyenepolyamines	DNEL	Long term Dermal	0.25 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.57 mg/ kg bw/day	Workers	Systemic
	DNEL	Short term Dermal	8 mg/kg bw/day	General population	Systemic
	DNEL	Short term Oral	20 mg/kg bw/day	General population	Systemic
	DNEL	Short term Inhalation	1600 mg/ m³	General population	Systemic
	DNEL	Short term Inhalation	5380 mg/ m³	Workers	Systemic
	DNEL	Long term Dermal	0.028 mg/ cm²	Workers	Local
	DNEL	Long term Dermal	0.43 mg/ cm²	General population	Local
	DNEL	Short term Dermal	1 mg/cm²	General population	Local
	DNEL	Long term Inhalation	0.096 mg/ m³	General population	Systemic
	DNEL	Long term Oral	0.14 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	0.54 mg/m³	Workers	Systemic
	DNEL	Long term	0.2 mg/m ³	Workers	Local

SECTION 8: Exposure controls/personal protection

J	be now of exposure controls/personal protection					
			Inhalation			
		DNEL	Long term Dermal	0.33 mg/ kg bw/day	Workers	Systemic
		DNEL	Long term Inhalation	1.2 mg/m³	Workers	Systemic
	3,3,5-trimethylhexylenediamine	DNEL	Long term Oral	0.05 mg/ kg bw/day	General population	Systemic

PNECs

No PNECs available.

8.2 Exposure controls Appropriate engineering : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne controls contaminants below any recommended or statutory limits. Individual protection measures : Wash hands, forearms and face thoroughly after handling chemical products, Hygiene measures before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Eye/face protection : Safety evewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists. gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead. Skin protection Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer. check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. Recommended : 1 - 4 hours (breakthrough time): nitrile rubber ; 4 - 8 hours (breakthrough time): Viton®/butyl rubber : Personal protective equipment for the body should be selected based on the task Body protection being performed and the risks involved and should be approved by a specialist before handling this product. : Appropriate footwear and any additional skin protection measures should be Other skin protection selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. **Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended : organic vapor (Type AX) and particulate filter **Environmental exposure** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. controls In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

<u>Appearance</u>		
Physical state	:	Liquid.
Color	:	Yellowish.
Odor	:	Characteristic. [Slight]
Odor threshold	:	Not available.
Melting point/freezing point	:	Not available.
Initial boiling point and boiling range	:	Not available.
Flammability	:	Not available.
Upper/lower flammability or explosive limits	:	Not available.
Flash point	:	Closed cup: >100°C (>212°F)
Auto-ignition temperature	:	Not applicable.
Decomposition temperature	:	Not available.
рН	:	Not applicable.
Viscosity	:	Dynamic: 200 to 400 mPa⋅s
Solubility(ies)	:	
Not available.		
Solubility in water	:	Not available.
Partition coefficient: n-octanol/ water	:	Not applicable.
Vapor pressure	:	0.01 kPa (0.075006 mm Hg)
Relative density	:	Not available.
Density	:	1.02 g/cm³ [25°C (77°F)]
Vapor density	:	Not available.
Explosive properties	:	Not available.
Oxidizing properties	:	Not available.
Particle characteristics		
Median particle size	:	Not applicable.
9.2 Other information		
SADT	:	Not available.
SAPT	:	Not available.

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: No specific data.
10.5 Incompatible materials	: No specific data.

WEICON Ceramic HC 220 Epoxy Hardener

SECTION 10: Stability and reactivity

10.6 Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Conclusion/Summary : Not available.

Acute toxicity estimates

Rou	ite	ATE value
Oral		537.63 mg/kg
Dermal		2095.24 mg/kg
Inhalation (dusts and mist	ts)	4 mg/l
Irritation/Corrosion		
Conclusion/Summary	: Not available.	
Sensitization		
Conclusion/Summary	: Not available.	
<u>Mutagenicity</u>		
Conclusion/Summary	: Not available.	
Carcinogenicity		
Conclusion/Summary	: Not available.	
Reproductive toxicity		
Conclusion/Summary	: Not available.	
Teratogenicity		
Conclusion/Summary	: Not available.	
Specific target organ toxic	<u>city (single exposure)</u>	
Not available.		
Specific target organ toxic Not available.	<u>city (repeated exposu</u>	<u>re)</u>
Aspiration hazard		
Not available.		
nformation on the likely	: Not available.	
routes of exposure		
Potential acute health effect	<u>cts</u>	
Eye contact	: Causes serious e	eye damage.
Inhalation	: Harmful if inhaled	J.
Skin contact	: Causes severe b	urns. May cause an allergic skin reaction.
Ingestion	: Harmful if swallow	wed.
Symptoms related to the pl	hysical, chemical and	toxicological characteristics
Eye contact	-	ns may include the following:
-	pain	
	watering redness	
Inhalation	: No specific data.	
	. NO Specific uala.	

WEICON Ceramic HC 220 Epoxy Hardener

SECTION 11: Toxico	logical information
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur
Ingestion	: Adverse symptoms may include the following: stomach pains
Delayed and immediate effe	cts and also chronic effects from short and long term exposure
<u>Short term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health eff	ects
Not available.	
Conclusion/Summary	: Not available.
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.

11.2 Information on other hazards

- 11.2.1 Endocrine disrupting properties
- Not available.
- 11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
polyethlyenepolyamines	-2.65	-	low
m-phenylenebis (methylamine)	0.18	2.69	low
3,3,5-trimethylhexylenediamine	-0.3	-	low

12.4 Mobility in soil

Date of issue/Date of revision

SECTION 12: Ecological information

Soil/water partition coefficient (Koc) Mobility

: Not available.

: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: The classification of the product may meet the criteria for a hazardous waste.

European waste catalogue (EWC)

Waste code	Waste designation
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances
ackaging	
Methods of disposal	 The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Methods of disposal Type of packaging	packaging should be recycled. Incineration or landfill should only be considered

Special precautions

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG	ΙΑΤΑ
14.1 UN number	UN2735	UN2735	UN2735
14.2 UN proper shipping name	AMINES, LIQUID, CORROSIVE, N.O.S. (Amines, polyethylenepoly-, triethylenetetramine fraction, m-phenylenebis(methylamine))	AMINES, LIQUID, CORROSIVE, N.O.S. (Amines, polyethylenepoly-, triethylenetetramine fraction, m-phenylenebis(methylamine))	Amines, liquid, corrosive, n.o. s. (Amines, polyethylenepoly-, triethylenetetramine fraction, m-phenylenebis (methylamine))
Date of issue/Date of re	vision : 6/22/2023 Date of	previous issue : 6/19/2023	Version : 2.04 11/1

WEICON Ceramic HC 220 Epoxy Hardener

14.3 Transport	8	8	8	
hazard class(es)		all		
14.4 Packing group	11	11	II	
14.5	No.	No.	No.	
Environmental hazards		Not available.		
	Not available.			

1	ADR/RID	: <u>Hazard identification number</u> 80 <u>Limited quantity</u> 1 L <u>Special provisions</u> 274 <u>Tunnel code</u> (E) <u>ADR Classification Code:</u> C7
I	MDG	: <u>Emergency schedules</u> F-A, S-B <u>Special provisions</u> 274
I	ΑΤΑ	: <u>Quantity limitation</u> Passenger and Cargo Aircraft: 1 L. Packaging instructions: 851. Cargo Aircraft Only: 30 L. Packaging instructions: 855. Limited Quantities - Passenger Aircraft: 0.5 L. Packaging instructions: Y840. <u>Special provisions</u> A3, A803
	.6 Special precautions for er	: Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
ac	.7 Transport in bulk cording to IMO struments	: Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU Regulation (EC) No. 1907/2006 (REACH)</u>

Annex XIV - List of substances subject to auth	orization		
Annex XIV			
None of the components are listed.			
Substances of very high concern			
None of the components are listed.			
Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles			
Restrictions on Manufacture, Marketing and U	se		
CountryProduct name	Conc.	Designation	Usage
Other EU regulations			

SECTION 15: Regulatory information

Industrial emissions (integrated pollution prevention and control) -	: Not listed
Air Industrial emissions (integrated pollution prevention and control) -	: Not listed
Water	
Ozone depleting substance Not listed.	<u>}s (1005/2009/EU)</u>
Prior Informed Consent (PI Not listed.	<u>C) (649/2012/EU)</u>
Persistent Organic Polluta Not listed.	<u>nts</u>
Seveso Directive	
•	I under the Seveso Directive.
<u>National regulations</u> Storage class (TRGS 510)	• 80
Hazardous incident ordina	
	under the Germany Hazardous Incident Ordinance.
Hazard class for water	: 2
Technical instruction on air quality control	: TA-Luft Number 5.2.5: 76-100%
ΑΟΧ	: The product does not contain organically bound halogens which could lead to an AOX value in waste water.
International regulations Chemical Weapon Conventi Not listed.	on List Schedules I, II & III Chemicals
Montreal Protocol	
Not listed.	
Stockholm Convention on F	Persistent Organic Pollutants
Not listed.	
Rotterdam Convention on P	Prior Informed Consent (PIC)
Not listed.	
UNECE Aarhus Protocol on	POPs and Heavy Metals
Not listed.	
Inventory list	
Australia	: Not determined.
Canada	: Not determined.
China	: All components are listed or exempted.
	: Russian Federation inventory: All components are listed or exempted.
Japan	 Japan inventory (CSCL): All components are listed or exempted. Japan inventory (ISHL): Not determined.
New Zealand	: All components are listed or exempted.
Philippines	: Not determined.
Date of issue/Date of revision	: 6/22/2023 Date of previous issue : 6/19/2023 Version : 2.04 13/15
L	

SECTION 15: Regulatory information

Republic of Korea	: Not determined.
Taiwan	: Not determined.
Thailand	: All components are listed or exempted.
Turkey	: Not determined.
United States	: Not determined.
Viet Nam	: All components are listed or exempted.
15.2 Chemical Safety Assessment	: This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and	: ATE = Acute Toxicity Estimate
acronyms	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.
	1272/2008]
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = CLP-specific Hazard statement
	N/A = Not available
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
	SGG = Segregation Group
	vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Acute Tox. 4, H302	Calculation method
Acute Tox. 4, H332	Calculation method
Skin Corr. 1B, H314	Calculation method
Eye Dam. 1, H318	Calculation method
Skin Sens. 1, H317	Calculation method
Aquatic Chronic 3, H412	Calculation method

Full text of abbreviated H statements

H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Full text of classifications [CLP/GHS]

WEICON Ceramic HC 220 Epoxy Hardener

SECTION 16: Other information

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.