SAFETY DATA SHEET



WEICON Casting Resin Plus 90 Hardener

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name UFI Product code Color : WEICON Casting Resin Plus 90 Hardener : 3X51-T0JR-H000-87JF

: 105242

: Colorless.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Ide	ntified uses
Hardener for resins.	

1.3 Details of the supplier of the safety data sheet

WEICON GmbH & Co. KG Königsberger Str. 255 48157 Münster Germany Phone: +49 251 93220 Fax: +49(0)251 / 9322 - 244 Internet: www.weicon.de e-mail address of person : msds@weicon.de responsible for this SDS

1.4 Emergency telephone number

Telephone number: EMERGENCY CONTACT – UK, UAE, South Africa (24h): Tel: ++44 1865 407333
(English)
TRANSPORT EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel: ++44
1865 407333 (English)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1B, H314 Eye Dam. 1, H318 Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Signal word

Hazard pictograms



SECTION 2: Hazards identification

Hazard statements	2 + H312 - Harmful if swallowed or in contact v - Causes severe skin burns and eye damage	э.
Precautionary statements	- Toxic to aquatic life with long lasting effects	δ.
Prevention	 Wear protective gloves, protective clothing Avoid release to the environment. Do not eat, drink or smoke when using this Wash thoroughly after handling. 	
Response	 Collect spillage. + P310 - IF INHALED: Immediately call a PC + P310, P330, P331 - IF SWALLOWED: Imm TER or doctor. Rinse mouth. Do NOT induces + P361 + P353, P310 - IF ON SKIN (or hair) aminated clothing. Rinse skin with water. Immediated Wash contaminated clothing before reuse. + P312 - IF ON SKIN: Call a POISON CENT + P351 + P338, P310 - IF IN EYES: Rinse cates. Remove contact lenses, if present and eacediately call a POISON CENTER or doctor. 	mediately call a POISON e vomiting. : Take off immediately all nediately call a POISON CENTER ER or doctor if you feel unwell. autiously with water for several
Storage	i - Store locked up.	
Disposal	- Dispose of waste according to applicable le	egislation.
Hazardous ingredients	oxy(methyl-1,2-ethanediyl)], α-(2-aminomethy ylidynetrimethanol, propoxylated, reaction pro	
Supplemental label elements	applicable.	
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	applicable.	
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	mixture does not contain any substances that	are assessed to be a PBT or a
Other hazards which do not result in classification	e known.	

SECTION 3: Composition/information on ingredients

1,2-ethanediyl)], α-	REACH #: 01-2119557899-12 CAS: 9046-10-0	≥50 - ≤75	Skin Corr. 1B, H314 Eye Dam. 1, H318 Aquatic Chronic 3,	-	[1]
			H412		
propoxylated, reaction 0 products with ammonia E	REACH #: 01-2119556886-20 EC: 500-105-6 CAS: 39423-51-3	≥25 - ≤50	Acute Tox. 4, H302 Acute Tox. 4, H312 Eye Dam. 1, H318 Aquatic Chronic 2, H411	ATE [Oral] = 550 mg/kg ATE [Dermal] = 1100 mg/kg	[1]

SECTION 3: Composition/information on ingredients			
		See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section. <u>Type</u>

[1] Substance classified with a health or environmental hazard

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	:	Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
Inhalation	:	Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	:	Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: No specific data.

SECTION 4: First a	aid measures
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur
Ingestion	: Adverse symptoms may include the following: stomach pains
4.3 Indication of any imm	ediate medical attention and special treatment needed
Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
5.2 Special hazards arising	om the substance or mixture
Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides
5.3 Advice for firefighters	
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures			
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.	
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".	
6.2 Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.	

Date of issue/Date of revision

SECTION 6: Accidental release measures

6.3 Methods and materials for containment and cleaning up	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
6.4 Reference to other sections	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Seveso Directive - Reporting thresholds

<u>Danger criteria</u>

	Notification and MAPP threshold	Safety report threshold
E2	200 tonne	500 tonne

7.3 Specific end use(s)

Recommendations	: Not available.
Industrial sector specific	: Not available.
solutions	

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

SECTION 8: Exposure controls/personal protection

Recommended monitoring : procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
--	--

DNELs/DMELs

Product/ingredient name	Туре	Exposure	Value	Population	Effects
Poly[oxy(methyl-1,2-ethanediyl)], α- (2-aminomethylethyl)-ω- (2-aminomethylethoxy)-	DNEL	Long term Dermal	2.5 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	10.58 mg/ m³	Workers	Systemic
Propylidynetrimethanol, propoxylated, reaction products with ammonia	DNEL	Long term Dermal	1.6 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	14.1 mg/m³	Workers	Systemic

PNECs

No PNECs available.

: If user operations generate dust, fumes, gas, vapor or mist, use process
enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
sures
: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. Recommended : 1 - 4 hours (breakthrough time): nitrile rubber ; 4 - 8 hours (breakthrough time): Viton®/butyl rubber

SECTION 8: Exposure controls/personal protection

Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended : organic vapor (Type AX) and particulate filter
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

÷

9.1 Information on basic physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid.
Color	: Colorless.
Odor	: Alkaline.
Odor threshold	: Not available.
Melting point/freezing point	: Not available.
Initial boiling point and boiling range	: >170°C (>338°F)
Flammability	: Flammable in the presence of the following materials or conditions: open flames, sparks and static discharge. Slightly flammable in the presence of the following materials or conditions: heat.
Upper/lower flammability or	: Not available.

explosive limits

Flash point

		Close	d cup		Оре	n cup
Ingredient name	°C	°F	Method	°C	°F	Method
Poly[oxy(methyl-1,2-ethanediyl)], α-(2-aminomethylethyl)-ω- (2-aminomethylethoxy)-	128	262.4	ISO 2719			

Auto-ignition temperature

Ingredient name		°C	°F	Method	
Propylidynetrimethanol, propoxylated, re products with ammonia	eaction	320	608	EU A.15	
Decomposition temperature	: Not av	ailable.	·		
PH	: Not ap	plicable.			
Viscosity	: Dynan	nic: 41 mPa·s	;		
Solubility(ies)	:				
Not available.					
Solubility in water	: Not av	ailable.			
Miscible with water	: No.				
Partition coefficient: n-octanol/ water	: Not ap	plicable.			
Vapor pressure	:				

	,	Vapor Press	sure at 20°C	\	Vapor pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method	
Propylidynetrimethanol, propoxylated, reaction products with ammonia	5.12	0.68	EU A.4				
Poly[oxy(methyl-1,2-ethanediyl)], α-(2-aminomethylethyl)-ω- (2-aminomethylethoxy)-	0.68	0.091	OECD 104	1.58	0.21	OECD 104	
Relative density	: No	t available.		•			
Density	: 0.9	97 g/cm³ [20°	°C (68°F)]				
Vapor density	: No	t available.					
Explosive properties	: No	t available.					
Oxidizing properties	: No	t available.					
Particle characteristics							
Median particle size	: No	t applicable.					
.2 Other information							
SADT	: No	t available.					
SAPT	: No	t available.					
ECTION 10: Stabilit	y and r	eactivity					
0.1 Reactivity	: No spe	ecific test dat	ta related to reacti	vity available fo	or this produ	ict or its ingredient	
0.2 Chemical stability	: The pr	oduct is stab	ble.				
0.3 Possibility of azardous reactions	: Under	normal conc	litions of storage a	and use, hazaro	lous reactio	ons will not occur.	
0.4 Conditions to avoid	: No spo	ecific data.					
0.5 Incompatible materials	: No spe	ecific data.					
0.6 Hazardous ecomposition products	: React alkalis		patible with the fol	lowing material	s: oxidizing	materials, acids a	

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Dermal			
LD30 Demia	Rabbit	1289 mg/kg	-
LD50 Oral	Rat	733.6 mg/kg	-
LD50 Dermal	Rat	1000 mg/kg	-
LD50 Oral	Rat	550 mg/kg	-
	LD50 Dermal	LD50 Dermal Rat	LD50 Dermal Rat 1000 mg/kg LD50 Oral Rat 550 mg/kg

Acute toxicity estimates

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 - Germany

WEICON Casting Resin Plus 90 Hardener

ECTION 11: Toxicological information				
Route	ATE value			
Oral	733.6 mg/kg			
Dermal	1289 mg/kg			

Irritation/Corrosion

	e	Result	Species	Score	Exposure	Observation
Poly[oxy(methyl- 1,2-ethanediyl)], α- (2-aminomethylethyl)-ω- (2-aminomethylethoxy)-	Eye	s - Severe irritant	Rabbit	-	100 mg	-
Conclusion/Summary	: N	ot available.				
Sensitization						
Conclusion/Summary	: N	ot available.				
<u>Mutagenicity</u>						
Conclusion/Summary	: N	ot available.				
Carcinogenicity						
Conclusion/Summary	: N	ot available.				
Reproductive toxicity						
Conclusion/Summary	: N	ot available.				
Teratogenicity						
Conclusion/Summary	: N	ot available.				
Specific target organ toxi	icity (sir	<u>ngle exposure)</u>				
Not available.						
Specific target organ toxi	city (re	peated exposure)				
Not available.		-				
Aspiration hazard Not available.						
	: N	ot available.				
Not available.		ot available.				
Not available. Information on the likely routes of exposure	<u>cts</u>	ot available. auses serious eye dam	age.			
Not available. Information on the likely routes of exposure Potential acute health effe	<u>cts</u> : C		-	rds.		
Not available. Information on the likely routes of exposure Potential acute health effe Eye contact	<u>cts</u> : C : N	auses serious eye dam	ects or critical haza			
Not available. Information on the likely routes of exposure <u>Potential acute health effe</u> Eye contact Inhalation	<u>cts</u> : C : N : C	auses serious eye dam o known significant effe	ects or critical haza			
Not available. Information on the likely routes of exposure Potential acute health effer Eye contact Inhalation Skin contact	<u>cts</u> : C : N : C : H	auses serious eye dam o known significant effe auses severe burns. H armful if swallowed.	ects or critical hazar armful in contact w	rith skin.		
Not available. Information on the likely routes of exposure Potential acute health effer Eye contact Inhalation Skin contact Ingestion	<u>cts</u> : C : N : C : H : H : A p w	auses serious eye dam o known significant effe auses severe burns. H armful if swallowed.	ects or critical hazan armful in contact w ogical characteris	rith skin. Stics		
Not available. Information on the likely routes of exposure Potential acute health effer Eye contact Inhalation Skin contact Ingestion	<u>cts</u> : C : N : C : H : H : A p w re	auses serious eye dam o known significant effe auses severe burns. H armful if swallowed. <u>chemical and toxicolo</u> dverse symptoms may i ain atering	ects or critical hazan armful in contact w ogical characteris	rith skin. Stics		
Not available. Information on the likely routes of exposure Potential acute health effer Eye contact Inhalation Skin contact Ingestion Symptoms related to the p Eye contact	cts : C : N : C : H : A p w re : A p re	auses serious eye dam o known significant effe auses severe burns. H armful if swallowed. chemical and toxicol dverse symptoms may i ain atering edness	ects or critical hazan armful in contact w ogical characteris include the followin	vith skin. Stics ng:		

SECTION 11: Toxicological information

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure	-
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health effe	<u>its</u>
Not available.	
Conclusion/Summary	: Not available.
General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties
Not available.
11.2.2 Other information
Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
WEICON Casting Resin Plus 90 Hardener	EC50 4.1 mg/l	Algae	72 hours
	EC50 48 mg/l	Daphnia	48 hours
	LC50 >4.1 mg/l	Fish	96 hours
Conclusion/Summary	: Not available.		

Conclusion/Summary

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
WEICON Casting Resin Plus 90 Hardener	-	4 % - Not readily - 28 days	100 mg/l	-

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

SECTION 12: Ecological information

Product/ingredient name	LogPow	BCF	Potential
Poly[oxy(methyl- 1,2-ethanediyl)], α- (2-aminomethylethyl)-ω- (2-aminomethylethoxy)-	1.34	-	low
Propylidynetrimethanol, propoxylated, reaction products with ammonia	-1.13	-	low

12.4 Mobility in soil	
Soil/water partition	: Not available.
coefficient (Koc)	
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product	
Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: The classification of the product may meet the criteria for a hazardous waste.

European waste catalogue (EWC)

Waste code	Waste designation	
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances	
Packaging		

Fackaging

Methods of disposal

: The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

	Type of packaging	European waste catalogue (EWC)
15 01 10* packaging containing residues of or contaminated by hazardous substances		packaging containing residues of or contaminated by hazardous substances
S	pecial precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG	ΙΑΤΑ	
14.1 UN number	UN2735	UN2735	UN2735	
14.2 UN proper shipping name	AMINES, LIQUID, CORROSIVE, N.O.S. (Poly[oxy (methyl-1,2-ethanediyl)], α- (2-aminomethylethyl)-ω- (2-aminomethylethoxy)-)	AMINES, LIQUID, CORROSIVE, N.O.S. (Poly[oxy (methyl-1,2-ethanediyl)], α- (2-aminomethylethyl)-ω- (2-aminomethylethoxy)-)	Amines, liquid, corrosive, n.o. s. (Poly[oxy(methyl- 1,2-ethanediyl)], α- (2-aminomethylethyl)-ω- (2-aminomethylethoxy)-)	
14.3 Transport hazard class(es)	8 ****	8	8	
14.4 Packing group	11	11	II	
14.5 Environmental hazards	Yes. Propylidynetrimethanol, propoxylated, reaction products with ammonia	Yes. Propylidynetrimethanol, propoxylated, reaction products with ammonia	Yes. The environmentally hazardous substance mark is not required.	

Additional information

ADR/RID	:	The environmentally hazardous substance mark is not required when transported in sizes of $\leq 5 \text{ L}$ or $\leq 5 \text{ kg}$. Hazard identification number 80 Limited quantity 1 L Special provisions 274 Tunnel code (E) ADR Classification Code: C7
IMDG	:	The marine pollutant mark is not required when transported in sizes of \leq 5 L or \leq 5 kg. <u>Emergency schedules</u> F-A, S-B <u>Special provisions</u> 274
ΙΑΤΑ	:	The environmentally hazardous substance mark may appear if required by other transportation regulations. Quantity limitation Passenger and Cargo Aircraft: 1 L. Packaging instructions: 851. Cargo Aircraft Only: 30 L. Packaging instructions: 855. Limited Quantities - Passenger Aircraft: 0.5 L. Packaging instructions: Y840. Special provisions A3, A803
14.6 Special precautions for user	:	Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
14.7 Transport in bulk according to IMO instruments	:	Not available.

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 - Germany

WEICON Casting Resin Plus 90 Hardener

SECTION 15: Regulatory information

	·			
15.1 Safety, health and environme	-	s/legislation spec	cific for the subs	stance or mixture
EU Regulation (EC) No. 1907/200 Annex XIV - List of substances		orization		
Annex XIV		ionzation		
None of the components are list	ed			
Substances of very high conc				
None of the components are list				
Annex XVII - Restrictions : N				
on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles				
Restrictions on Manufacture, M	larketing and U	se		
CountryProduct name	-	Conc.	Designation	Usage
Other EU regulations				
	lot listed			
	lot listed			
Ozone depleting substances (1 Not listed.	<u>005/2009/EU)</u>			
Prior Informed Consent (PIC) (6 Not listed.	<u> 49/2012/EU)</u>			
Persistent Organic Pollutants Not listed.				
Seveso Directive				
This product is controlled under the	he Seveso Direc	tive.		
Danger criteria				
Category				
E2				
National regulations				

Storage class (TRGS 510) : 8B

Hazardous incident ordinance

This product is controlled under the Germany Hazardous Incident Ordinance.

Danger criteria

Category				Referenc	e numb	er
E2				1.3.2		
Hazard class for water	: 2					
Technical instruction on air quality control	: TA-Luft Nur	nber 5.2.5: 80-100%				
AOX	•	t does not contain organ in waste water.	ically bound halogen	is which could I	ead to a	an
e of issue/Date of revision	: 10/20/2022	Date of previous issue	: 10/19/2022	Version	: 2.01	13/1

SECTION 15: Regulatory information

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Australia	:	All components are listed or exempted.		
Canada	:	All components are listed or exempted.		
China	:	All components are listed or exempted.		
Eurasian Economic Union	:	Russian Federation inventory: All components are listed or exempted.		
Japan	:	Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined.		
New Zealand	:	All components are listed or exempted.		
Philippines	:	All components are listed or exempted.		
Republic of Korea	:	All components are listed or exempted.		
Taiwan	:	All components are listed or exempted.		
Thailand	:	All components are listed or exempted.		
Turkey	:	Not determined.		
United States	:	All components are active or exempted.		
Viet Nam	:	All components are listed or exempted.		
15.2 Chemical Safety Assessment	:	This product contains substances for which Chemical Safety Assessments are still required.		

SECTION 16: Other information

Indicates information that	at has changed from previously issued version.		
Abbreviations and	: ATE = Acute Toxicity Estimate		
acronyms	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) 1272/2008]		
	DMEL = Derived Minimal Effect Level		
	DNEL = Derived No Effect Level		
	EUH statement = CLP-specific Hazard statement		
	N/A = Not available		
	PBT = Persistent, Bioaccumulative and Toxic		
	PNEC = Predicted No Effect Concentration		
	RRN = REACH Registration Number		
	SGG = Segregation Group		
	vPvB = Very Persistent and Very Bioaccumulative		
Procedure used to derive	the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]		

Date of issue/Date of revision

SECTION 16: Other information				
Classification	Justification			
Acute Tox. 4, H302	On basis of test data			
Acute Tox. 4, H312	On basis of test data			
Skin Corr. 1B, H314	Calculation method			
Eye Dam. 1, H318	Calculation method			
Aquatic Chronic 2, H411	Calculation method			

H302 H312 H314 H318 H411 H412		Harmful if swallowed. Harmful in contact with skin. Causes severe skin burns and eye damage. Causes serious eye damage. Toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects.
Full text of classifications	[CLP/GHS]	
Acute Tox. 4 Aquatic Chronic 2 Aquatic Chronic 3 Eye Dam. 1 Skin Corr. 1B		ACUTE TOXICITY - Category 4 AQUATIC HAZARD (LONG-TERM) - Category 2 AQUATIC HAZARD (LONG-TERM) - Category 3 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 SKIN CORROSION/IRRITATION - Category 1B
Date of printing Date of issue/ Date of revision	: 10/20/2022 : 10/20/2022	

Date of previous issue	: 10/19/2022
Version	: 2.01

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.