# SAFETY DATA SHEET



**Repair Stick Concrete** 

# SECTION 1: Identification of the substance/mixture and of the company/ undertaking

#### 1.1 Product identifier

Product name	: Repair Stick Concrete
UFI	: S4E1-A0J3-700J-UWGV
Product code	: 105370
Color	: White.

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	
Epoxy resins	

#### 1.3 Details of the supplier of the safety data sheet

WEICON GmbH & Co. KG Königsberger Str. 255 48157 Münster Germany Phone: +49 251 93220 Fax: +49(0)251 / 9322 - 244 Internet: www.weicon.de e-mail address of person : msds@weicon.de responsible for this SDS

#### 1.4 Emergency telephone number

Telephone number	: EMERGENCY CONTACT – UK, UAE, South Africa (24h): Tel: ++44 1865 407333
	(English) TRANSPORT EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel: ++44 1865 407333 (English)

# **SECTION 2: Hazards identification**

## 2.1 Classification of the substance or mixture

Product definition : Mixture

## Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

#### 2.2 Label elements

Hazard pictograms



Signal word

: Warning

# SECTION 2: Hazards identification

Hazard statements	H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation. H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements	
Prevention	<ul> <li>P280 - Wear protective gloves. Wear eye or face protection.</li> <li>P273 - Avoid release to the environment.</li> <li>P261 - Avoid breathing dust.</li> <li>P264 - Wash thoroughly after handling.</li> </ul>
Response	<ul> <li>P362 + P364 - Take off contaminated clothing and wash it before reuse.</li> <li>P302 + P352 - IF ON SKIN: Wash with plenty of water.</li> <li>P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention.</li> <li>P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes Remove contact lenses, if present and easy to do. Continue rinsing.</li> <li>P337 + P313 - If eye irritation persists: Get medical advice or attention.</li> </ul>
Storage	Not applicable.
Disposal	P501 - Dispose of waste according to applicable legislation.
Hazardous ingredients	Poly[oxy(methyl-1,2-ethanediyl)], α-hydro-ω-hydroxy-, ether with 2,2-bis (hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) bis-[4-(2,3-epoxipropoxi)phenyl]propane 2,4,6-tris(dimethylaminomethyl)phenol
Supplemental label elements	Contains epoxy constituents. May produce an allergic reaction. Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	Not applicable.
2.3 Other hazards	
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	None known.

# **SECTION 3: Composition/information on ingredients**

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Talc (Mg3H2(SiO3)4)	REACH #: 01-2120140278-58 EC: 238-877-9 CAS: 14807-96-6	≥25 - ≤50	Not classified.	-	[2]
Poly[oxy(methyl- 1,2-ethanediyl)], α-hydro-ω- hydroxy-, ether with 2,2-bis (hydroxymethyl) -1,3-propanediol (4:1), 2-hydroxy-	REACH #: 01-2120118957-46 EC: 615-735-8 CAS: 72244-98-5	≤10	Skin Sens. 1B, H317 Aquatic Chronic 3, H412	-	[1]

# Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 - Germany

Repair Stick Concrete

SECTION 3: Compo	sition/informat	ion on in	gredients		
3-mercaptopropyl ether					
reaction product: bisphenol- A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	REACH #: 01-2119456619-26 EC: 500-033-5 CAS: 25068-38-6 Index: 603-074-00-8	≤10	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	Skin Irrit. 2, H315: C ≥ 5% Eye Irrit. 2, H319: C ≥ 5%	[1]
bis-[4-(2,3-epoxipropoxi) phenyl]propane	REACH #: 01-2119456619-26 EC: 216-823-5 CAS: 1675-54-3 Index: 603-073-00-2	≤10	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	Skin Irrit. 2, H315: C ≥ 5% Eye Irrit. 2, H319: C ≥ 5%	[1] [2]
titanium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7 Index: 022-006-00-2	≤5	Carc. 2, H351 (inhalation)	-	[1] [2] [*]
2,4,6-tris (dimethylaminomethyl) phenol	REACH #: 01-2119560597-27 EC: 202-013-9 CAS: 90-72-2 Index: 603-069-00-0	<1	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1B, H317 See Section 16 for the full text of the H statements declared above.	ATE [Oral] = 500 mg/kg ATE [Dermal] = 1100 mg/kg	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Type</u>

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[\*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter  $\leq$  10 µm not bound within a matrix. Occupational exposure limits, if available, are listed in Section 8.

# **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

#### **SECTION 4: First aid measures**

Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

# Over-exposure signs/symptomsEye contact: Adverse symptoms may include the following:<br/>pain or irritation<br/>watering<br/>rednessInhalation: No specific data.Skin contact: Adverse symptoms may include the following:<br/>irritation<br/>rednessIngestion: No specific data.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>
Specific treatments	: No specific treatment.

# **SECTION 5: Firefighting measures**

E 4 Extinguishing modio	
5.1 Extinguishing media Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
5.2 Special hazards arising f	rom the substance or mixture
Hazards from the substance or mixture	This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide sulfur oxides halogenated compounds metal oxide/oxides
5.3 Advice for firefighters Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

# SECTION 5: Firefighting measures

Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.
---------------------------------------------------	---	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

## **SECTION 6: Accidental release measures**

6.1 Personal precautions, pro	te	ctive equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
6.3 Methods and materials for containment and cleaning up	:	Move containers from spill area. Avoid dust generation. Using a vacuum with HEPA filter will reduce dust dispersal. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

# **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance.

#### 7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

#### 7.3 Specific end use(s)

Recommendations : Not available.

Date of issue/Date of revision

# **SECTION 7: Handling and storage**

Industrial sector specific : Not available. solutions

# **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

#### 8.1 Control parameters

#### **Occupational exposure limits**

Product/ingredient name	Exposure limit values
Talc (Mg3H2(SiO3)4)	<b>TRGS 900 OEL (Germany, 7/2021). []</b> TWA: 1.25 mg/m <sup>3</sup> 8 hours. Form: alveolar fraction PEAK: 2.5 mg/m <sup>3</sup> 15 minutes. Form: alveolar fraction PEAK: 20 mg/m <sup>3</sup> 15 minutes. Form: inhalable fraction TWA: 10 mg/m <sup>3</sup> 8 hours. Form: inhalable fraction
bis-[4-(2,3-epoxipropoxi)phenyl]propane	DFG MAC-values list (Germany, 10/2021). Skin sensitizer.
titanium dioxide	<ul> <li>TRGS 900 OEL (Germany, 7/2021). []</li> <li>TWA: 1.25 mg/m<sup>3</sup> 8 hours. Form: alveolar fraction</li> <li>PEAK: 2.5 mg/m<sup>3</sup> 15 minutes. Form: alveolar fraction</li> <li>PEAK: 20 mg/m<sup>3</sup> 15 minutes. Form: inhalable fraction</li> <li>TWA: 10 mg/m<sup>3</sup> 8 hours. Form: inhalable fraction</li> <li>DFG MAC-values list (Germany, 10/2021).</li> <li>PEAK: 2.4 mg/m<sup>3</sup>, 4 times per shift, 15 minutes. Form: respirable fraction</li> <li>TWA: 0.3 mg/m<sup>3</sup> 8 hours. Form: respirable fraction</li> </ul>
procedures European Stan assessment of values and mer atmospheres - of exposure to (Workplace atmospheres) for the measured	uld be made to monitoring standards, such as the following: dard EN 689 (Workplace atmospheres - Guidance for the exposure by inhalation to chemical agents for comparison with limit asurement strategy) European Standard EN 14042 (Workplace Guide for the application and use of procedures for the assessment chemical and biological agents) European Standard EN 482 nospheres - General requirements for the performance of procedures ement of chemical agents) Reference to national guidance methods for the determination of hazardous substances will also be

#### **DNELs/DMELs**

Product/ingredient name	Туре	Exposure	Value	Population	Effects
Poly[oxy(methyl-1,2-ethanediyl)], α- hydro-ω-hydroxy-, ether with 2,2-bis (hydroxymethyl)-1,3-propanediol (4: 1), 2-hydroxy-3-mercaptopropyl ether	DNEL	Long term Dermal	1.61 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Oral	1.9 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	2.7 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	6.52 mg/m³	General population	Systemic
	DNEL	Long term Inhalation	22 mg/m³	Workers	Systemic
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin	DNEL	Short term Oral	0.75 mg/ kg bw/day	General population	Systemic
te of issue/Date of revision : 3/10	/2023	Date of previous issue	: 10/19/20	l 022 <b>V</b> e	ersion :1

# Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 - Germany

1

pair Stick Concrete								
SECTION 8: Exposure controls/personal protection								
(number average molecular weight ≤ 700)								
	DNEL	Long term Oral	0.75 mg/ kg bw/day	General population	Systemic			
	DNEL	Short term Dermal	3.571 mg/ kg bw/day	General population	Systemic			
	DNEL	Long term Dermal	3.571 mg/ kg bw/day	General population	Systemic			
	DNEL	Short term Dermal	8.33 mg/ kg bw/day	Workers	Systemic			
	DNEL	Long term Dermal	8.33 mg/ kg bw/day	Workers	Systemic			
	DNEL	Short term Inhalation	12.25 mg/ m³	Workers	Systemic			
	DNEL	Long term Inhalation	12.25 mg/ m³	Workers	Systemic			
bis-[4-(2,3-epoxipropoxi)phenyl] propane	DNEL	Long term Dermal	89.3 µg/kg bw/day	General population	Systemic			
	DNEL	Long term Oral	0.5 mg/kg bw/day	General population	Systemic			
	DNEL	Long term Dermal	0.75 mg/ kg bw/day	Workers	Systemic			
	DNEL	Long term Inhalation	0.87 mg/m³	General population	Systemic			
	DNEL	Long term Inhalation	4.93 mg/m <sup>3</sup>	Workers	Systemic			
titanium dioxide	DNEL	Long term Inhalation	10 mg/m³	Workers	Local			
	DNEL	Long term Oral	700 mg/kg bw/day	General population	Systemic			
2,4,6-tris(dimethylaminomethyl) phenol	DNEL	Long term Oral	0.075 mg/ kg bw/day	General population	Systemic			
	DNEL	Short term Dermal	0.075 mg/ kg bw/day	General population	Systemic			
	DNEL	Long term Dermal	0.075 mg/ kg bw/day	General population	Systemic			
	DNEL	Short term Inhalation	0.13 mg/m <sup>3</sup>	General population	Systemic			
	DNEL	Long term Inhalation	0.13 mg/m <sup>3</sup>	General population	Systemic			
	DNEL	Long term Dermal	0.15 mg/ kg bw/day	Workers	Systemic			
	DNEL	Long term Inhalation	0.53 mg/m³	Workers	Systemic			
e of issue/Date of revision : 3/	10/2023	Date of previous issue	: 10/19/2	022	Version :1 7			

SECTION 8: Exposure controls/personal protection								
	DNEL     Short term Dermal     0.6 mg/kg     Workers     Systemic       bw/day     bw/day     Systemic							
	DN	IEL	Short term Inhalation	2.1 mg/m³	Workers	Systemic		

#### **PNECs**

No PNECs available.

8.2 Exposure controls	
Appropriate engineering controls	: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Individual protection mea	<u>sures</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection	
Hand protection	<ul> <li>Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. Recommended : 1 - 4 hours (breakthrough time): nitrile rubber 4 - 8 hours (breakthrough time): Viton®/butyl rubber</li> </ul>
Body protection	<ul> <li>Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Other skin protection	<ul> <li>Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: Respiratory protection is not necessary if room is well ventilated.
Environmental exposure controls	<ul> <li>Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.</li> </ul>

# **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

<u>Appearance</u>	
Physical state	: Solid.
Color	: White.
Odor	: Bland.
Odor threshold	: Not available.
Melting point/freezing point	: Not available.
Initial boiling point and boiling range	: >35°C (>95°F)

Date of issue/Date of revision

# **SECTION 9: Physical and chemical properties**

· · · <b>/</b> ····	
Flammability	: Not available.
Upper/lower flammability or explosive limits	: Not applicable.
Flash point	: Closed cup: >100°C (>212°F)
Auto-ignition temperature	: Not applicable.
Decomposition temperature	: Not available.
рН	: Not applicable.
Viscosity	: Not applicable.
Solubility(ies)	:
Not available.	
Solubility in water	: Not available.
Miscible with water	: No.
Partition coefficient: n-octanol/ water	: Not applicable.
Vapor pressure	: <0 kPa (<0 mm Hg)
Relative density	: Not available.
Density	: 2.03 g/cm³ [20°C (68°F)]
Vapor density	: Not applicable.
Explosive properties	: Not available.
Oxidizing properties	: Not available.
Particle characteristics	
Median particle size	: Not available.
9.2 Other information	
SADT	: Not available.
SAPT	: Not available.
SECTION 10: Stability a	nd reactivity

10.1 Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	:	The product is stable.
10.3 Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	:	No specific data.
10.5 Incompatible materials	:	No specific data.
10.6 Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2,4,6-tris (dimethylaminomethyl) phenol	LD50 Dermal	Rat	1280 mg/kg	-
	LD50 Oral	Rat	1200 mg/kg	-
	LD50 Oral	Rat	1673 mg/kg	-
	LD50 Oral	Rat	2169 mg/kg	-
Conclusion/Summary	Not available.	•	•	•

#### Acute toxicity estimates

	ATE value
Not available.	

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
titanium dioxide	Skin - Mild irritant	Human	-	72 hours 300 ug l	-
2,4,6-tris (dimethylaminomethyl) phenol	Eyes - Severe irritant	Rabbit	-	24 hours 50 ug	-
	Skin - Mild irritant	Rat	-	0.025 MI	-
	Skin - Severe irritant	Rabbit	-	24 hours 2 mg	-
	Skin - Severe irritant	Rat	-	0.25 MI	-
Conclusion/Summary	: Not available.				

Sensitization

**Conclusion/Summary** 

Mutagenicity

**Conclusion/Summary** : Not available.

: Not available.

#### **Carcinogenicity**

It has been observed that the carcinogenic hazard of this product arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung.

<b>Conclusion/Summary</b>	: Not available.
Reproductive toxicity	
<b>Conclusion/Summary</b>	: Not available.
<u>Teratogenicity</u>	
<b>Conclusion/Summary</b>	: Not available.
Specific target organ toxic	<u>ity (single exposure)</u>
Not available.	

Specific target organ toxicity (repeated exposure)

Not available.

#### Aspiration hazard

Not available.

,		
SECTION 11: Toxic	ological information	
Information on the likely routes of exposure	: Not available.	

#### Potential acute health effects

Eye contact	: Causes serious eye irritation.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.

#### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

#### Delayed and immediate effects and also chronic effects from short and long term exposure

	and also entende enceds from short and long term exposure
:	Not available.
:	Not available.
:	Not available.
:	Not available.
ect	<u>S</u>
:	Not available.
:	Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
:	No known significant effects or critical hazards.
:	No known significant effects or critical hazards.
:	No known significant effects or critical hazards.
:	No known significant effects or critical hazards.
:	No known significant effects or critical hazards.
	: : : : : : : : :

#### 11.2 Information on other hazards

11.2.1 Endocrine disrupting properties Not available.11.2.2 Other information Not available.

# **SECTION 12: Ecological information**

#### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
titanium dioxide	Acute EC50 19.3 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 27.8 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 35.306 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 3 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 13.4 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 11 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 3.6 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 15.9 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 6.5 mg/l Fresh water	Daphnia - Daphnia pulex - Neonate	48 hours
	Acute LC50 13 mg/l Fresh water	Daphnia - Daphnia pulex - Neonate	48 hours
	Acute LC50 >1000000 µg/l Marine water	Fish - Fundulus heteroclitus	96 hours
	Acute LC50 >1000 mg/l Fresh water	Fish - Pimephales promelas	96 hours

#### 12.2 Persistence and degradability

**Conclusion/Summary** : Not available.

#### 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
reaction product: bisphenol- A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	2.64 to 3.78	31	low
2,4,6-tris (dimethylaminomethyl) phenol	0.219	-	low

#### 12.4 Mobility in soil

Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

#### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Date of issue/Date of revision	: 3/10/2023	Date of previous issue	: 10/19/2022	Version : 1	12/16	
--------------------------------	-------------	------------------------	--------------	-------------	-------	--

# **SECTION 12: Ecological information**

#### 12.6 Endocrine disrupting properties

Not available.

#### 12.7 Other adverse effects

No known significant effects or critical hazards.

# **SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 13.1 Waste treatment methods

#### Product

Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: The classification of the product may meet the criteria for a hazardous waste.

#### European waste catalogue (EWC)

Waste code	Waste designation
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances

#### Packaging

Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Type of packaging	European waste catalogue (EWC)
15 01 10*	packaging containing residues of or contaminated by hazardous substances
Special precautions	This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# **SECTION 14: Transport information**

	ADR/RID	IMDG	ΙΑΤΑ
14.1 UN number	Not available.	Not available.	Not available.
14.2 UN proper shipping name	Not available.	Not available.	Not available.
14.3 Transport hazard class(es)	Not available.	Not available.	Not available.
14.4 Packing group	-	-	-
14.5 Environmental hazards	No.	No.	No.
Date of issue/Date of re	vision : 3/10/2023 Dat	e of previous issue : 10/19/2	022 Version : 1 13/16

SECTION 14: Transport information			
Not available.	Not available.		

**14.6 Special precautions for user**: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk	: Not available.
according to IMO	
instruments	

# **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH) Annex XIV - List of substances subject to authorization Annex XIV None of the components are listed. Substances of very high concern None of the components are listed. Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles **Restrictions on Manufacture, Marketing and Use** CountryProduct name Designation Conc. Usage **Other EU regulations** Industrial emissions : Not listed (integrated pollution prevention and control) -Air : Not listed Industrial emissions (integrated pollution prevention and control) -Water Ozone depleting substances (1005/2009/EU) Not listed. Prior Informed Consent (PIC) (649/2012/EU) Not listed. Persistent Organic Pollutants Not listed. **Seveso Directive** This product is not controlled under the Seveso Directive. National regulations

# **SECTION 15: Regulatory information**

Product/ingredient name	List name	Name on list	Classification	Notes	
Talc (Mg3H2(SiO3)4)		Talc (without asbestos fibres) (respirable fraction)	К3	-	
titanium dioxide	DFG MAC-values list	Titanium dioxide (inhalable fraction)	K3	-	

#### Storage class (TRGS 510) : 13

#### Hazardous incident ordinance

This product is not controlled under the Germany Hazardous Incident Ordinance.

Hazard class for water	: 2
Technical instruction on air quality control	: TA-Luft Number 5.2.1: 36-80% TA-Luft Number 5.2.5: 16-31%
AOX	: The product contains organically bound halogens and can contribute to the AOX value in waste water.

#### International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals
Not listed.

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

#### **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

#### Inventory list

Australia	:	All components are listed or exempted.
Canada	:	At least one component is not listed in DSL but all such components are listed in NDSL.
China	:	All components are listed or exempted.
Eurasian Economic Union	:	Russian Federation inventory: All components are listed or exempted.
Japan	:	Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined.
New Zealand	:	All components are listed or exempted.
Philippines	:	All components are listed or exempted.
Republic of Korea	:	All components are listed or exempted.
Taiwan	:	All components are listed or exempted.
Thailand	:	All components are listed or exempted.
Turkey	:	Not determined.
United States	:	All components are active or exempted.
Viet Nam	:	All components are listed or exempted.
15.2 Chemical Safety Assessment	:	This product contains substances for which Chemical Safety Assessments are still required.

# **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	<ul> <li>ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic</li> </ul>
	PNEC = Predicted No Effect Concentration RRN = REACH Registration Number SGG = Segregation Group vPvB = Very Persistent and Very Bioaccumulative

#### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
Skin Sens. 1, H317	Calculation method
Aquatic Chronic 3, H412	Calculation method

#### Full text of abbreviated H statements

H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H351	Suspected of causing cancer.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

#### Full text of classifications [CLP/GHS]

/ 2
/ 3
Category 1
Category 2
В
Cat B

revision	
Date of previous issue	: 10/19/2022
Version	: 1

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Date of issue/Date of revision