SAFETY DATA SHEET



Easy-Mix S 50 Epoxy Adhesive Resin

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifie	r
-----------------------	---

Product name	: Easy-Mix S 50 Epoxy Adhesive Resin
UFI	: WKW1-E0SJ-C00N-WCDG
Product code	: 106501
Color	: Colorless to light yellow.
Product type	: Liquid.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	
Epoxy resins	
Uses advised against	Reason
Not applicable.	

1.3 Details of the supplier of the safety data sheet

e-mail address of person	:	msd
URL: www.weicon.de		
email: info@weicon.de,		
phone:+49 251 93220,		
48157 Münster, Germany		
Königsberger Str. 255,		
WEICON GmbH & Co. KG		

ds@weicon.de

responsible for this SDS

1.4 Emergency telephone number

National advisory body/Poison Center

Telephone number	: EMERGENCY CONTACT – UK, UAE, South Africa (24h): Tel: ++44 1865 407333 (English)
	TRĂNSPORT EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel: ++44 1865 407333 (English)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Easy-Mix S 50 Epoxy Adhesive Resin

SECTION 2: Hazards identifi	cation
------------------------------------	--------

Hazard pictograms	
Signal word	: Warning
Hazard statements	 H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation. H411 - Toxic to aquatic life with long lasting effects.
Precautionary statements	
General	: P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children.
Prevention	 P261 - Avoid breathing vapor. P264 - Wash hands thoroughly after handling. P273 - Avoid release to the environment. P280 - Wear protective gloves. Wear eye or face protection.
Response	 P391 - Collect spillage. P362 + P364 - Take off contaminated clothing and wash it before reuse. P302 + P352 - IF ON SKIN: Wash with plenty of water. P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention. P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 - If eye irritation persists: Get medical advice or attention.
Storage	: Not applicable.
Disposal	: P501 - Dispose of waste according to applicable legislation.
Hazardous ingredients	 bis-[4-(2,3-epoxipropoxi)phenyl]propane Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol p-tert-butylphenyl 1-(2,3-epoxy)propyl ether Phenol, polymer with formaldehyde, glycidyl ether
Supplemental label elements	: Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.
2.3 Other hazards	
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	: None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

: Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
bis-[4-(2,3-epoxipropoxi) phenyl]propane	REACH #: 01-2119456619-26 EC: 216-823-5 CAS: 1675-54-3 Index: 603-073-00-2	≥50 - ≤75	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	Skin Irrit. 2, H315: C ≥ 5% Eye Irrit. 2, H319: C ≥ 5%	[1] [2]
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	REACH #: 01-2119454392-40 EC: 701-263-0 CAS: 9003-36-5	≥25 - ≤50	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411	-	[1]
p-tert-butylphenyl 1- (2,3-epoxy)propyl ether	REACH #: 01-2119959496-20 EC: 221-453-2 CAS: 3101-60-8	≥5 - ≤10	Skin Sens. 1, H317 Aquatic Chronic 2, H411	-	[1] [2]
Phenol, polymer with formaldehyde, glycidyl ether	CAS: 28064-14-4	≥5 - ≤10	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	-	[1]
			See Section 16 for the full text of the H statements declared above.		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section. <u>Type</u>

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	 Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

SECTION 4: First aid measures

Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.
4.2 Most important symptor	ns and effects, both acute and delayed
Over-exposure signs/symp	<u>otoms</u>
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	· No specific data

Innalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
5.2 Special hazards arising f	rom the substance or mixture
Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide halogenated compounds
5.3 Advice for firefighters Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

SECTION 5: Firefighting measures

Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure
oquipilion for monginero		mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

brecautionsdrains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.5.3 Methods and materials for containment and cleaning upSmall spill: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.Large spill: Stop leak if without risk. Move containers from spill area. Approach release from up wind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.6.4 Reference to other: See Section 1 for emergency contact information.		
personnelEvacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".S.2 Environmental orecautions: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.S.3 Methods and materials for containment and cleaning up: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate disposal container. Dispose of via a licensed waste disposal contractor.Large spill: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.6.4 Reference to othe	6.1 Personal precautions, pro	ective equipment and emergency procedures
 information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". 5.2 Environmental Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage. 5.3 Methods and materials for containment and cleaning up Small spill Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. Large spill Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into severs, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. 5.4 Reference to other See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. 		Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is
brecautionsdrains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.6.3 Methods and materials for containment and cleaning upSmall spill:Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.Large spill:Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.6.4 Reference to other sections	For emergency responders	information in Section 8 on suitable and unsuitable materials. See also the
 Small spill Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. Large spill Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. 	6.2 Environmental precautions	drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material.
 up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. Large spill Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. 	6.3 Methods and materials fo	containment and cleaning up
 upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. 	Small spill	up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a
See Section 8 for information on appropriate personal protective equipment.	Large spill	upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.
	6.4 Reference to other sections	See Section 8 for information on appropriate personal protective equipment.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Date of issue/Date of revision	: 6/25/2025	Date of previous issue	: 6/15/2025	Version : 4.6	5/16
--------------------------------	-------------	------------------------	-------------	---------------	------

SECTION 7: Handling and storage

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Seveso Directive - Reporting thresholds

Danger criteria

	Notification and MAPP threshold	Safety report threshold
E2	200 tonne	500 tonne

7.3 Specific end use(s)

Recommendations	: Not available.
Industrial sector specific solutions	: Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
bis-[4-(2,3-epoxipropoxi)phenyl]propane	DFG MAC-values list (Germany, 7/2022). Skin sensitizer.
p-tert-butylphenyl 1-(2,3-epoxy)propyl ether	DFG MAC-values list (Germany, 7/2022). Skin sensitizer.

Biological exposure indices

No exposure indices known.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Туре	Exposure	Value	Population	Effects
bis-[4-(2,3-epoxipropoxi)phenyl] propane	DNEL	Long term Dermal	89.3 µg/kg bw/day	General population	Systemic
	DNEL	Long term Oral	0.5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.75 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	0.87 mg/m³	General population	Systemic
	DNEL	Long term Inhalation	4.93 mg/m ³	Workers	Systemic
e of issue/Date of revision : 6//	25/2025	Date of previous issue	: 6/15/202	25 V e	rsion : 4.6 6

Easy-Mix S 50 Epoxy Adhesive Resin

ormaldehyde, oligomeric reaction roducts with 1-chloro- ,3-epoxypropane and phenol	DMEL	Short term Dermal	0.0083 mg/ cm²	Workers	Local
	DNEL	Long term Oral	6.25 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	8.7 mg/m³	General population	Systemic
	DNEL	Long term Inhalation	29.39 mg/ m³	Workers	Systemic
	DNEL	Long term Dermal	62.5 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	104.15 mg/ kg bw/day	Workers	Systemic
o-tert-butylphenyl 1-(2,3-epoxy) propyl ether	DNEL	Short term Dermal	0.95 ng/ cm²	General population	Local
	DNEL	Long term Dermal	0.95 ng/ cm²	General population	Local
	DNEL	Short term Dermal	1.6 ng/cm ²	Workers	Local
	DNEL	Long term Dermal	1.6 ng/cm ²	Workers	Local
	DNEL	Short term Dermal	0.5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.5 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	1 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	1 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.75 mg/m³	General population	Local
	DNEL	Long term Inhalation	1.75 mg/m³	General population	Systemic
	DNEL	Short term Inhalation	3.5 mg/m³	Workers	Local
	DNEL	Long term Inhalation	3.5 mg/m³	Workers	Local
	DNEL	Short term Inhalation	3.5 mg/m³	Workers	Systemic
	DNEL	Long term Inhalation	3.5 mg/m³	Workers	Systemic

PNECs

No PNECs available.

8.2 Exposure controls

Easy-Mix S 50 Epoxy Adhesive Resin

SECTION 8: Exposu	re controls/personal protection
Appropriate engineering controls	: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Individual protection meas	ures
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. Recommended : 1 - 4 hours (breakthrough time): Protective gloves made of nitrile rubber (material thickness of 0,4 mm); EN 374-5 Cat. III ; 4 - 8 hours (breakthrough time): Protective gloves made of Viton®/ butyl rubber (material thickness of 0,7 mm); EN388 Cat.II / EN374 Cat.III / EN374-2
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended : organic vapor (Type AX) and particulate filter
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
OFOTION OF DEVICE	land chamical proportion

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid.
Color	: Colorless to light yellow.
Odor	: Bland.
Odor threshold	: Not available.
Melting point/freezing point	: Not available.
Initial boiling point and boiling range	: Not available.
Flammability	: Not available.
Lower and upper explosion limit	: Not available.
Flash point	:

SECTION 9: Physical and chemical properties

		Closed cup			Open cup		
Ingredient name	°C	°F	Method	°C	°F	Method	
bis-[4-(2,3-epoxipropoxi)phenyl] propane				79	174.2		
Formaldehyde, oligomeric reaction products with 1-chloro- 2,3-epoxypropane and phenol	>93	>199.4	EU A.9				
Phenol, polymer with formaldehyde, glycidyl ether	120	248					
p-tert-butylphenyl 1-(2,3-epoxy) propyl ether				143.3	289.9		
uto-ignition temperature	: N	ot applicable.	•	•	•	•	
ecomposition temperatur	e : N	ot available.					
Н	: N	ot applicable.					
/iscosity		ot available.					

Not available.

Solubility in water : Not available.

Partition coefficient: n-octanol/	:	Not applicable.
water		

2

Vapor pressure

	Vapor Pressure at 20°C			Vapor pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
Formaldehyde, oligomeric reaction products with 1-chloro- 2,3-epoxypropane and phenol	0.62	0.083	EU A.4			
p-tert-butylphenyl 1-(2,3-epoxy) propyl ether	0.00019	0.000025				
Relative density	: Not	available.	•			
Density	: 1.15	5 g/cm³ [20°0	C (68°F)]			
/apor density	: Not	available.				
Particle characteristics						
Median particle size	: Not	applicable.				
9.2.1 Information with rega	rd to physic	al hazard c	lasses			
Explosive properties	: Not	available.				
Oxidizing properties	: Not	available.				
9.2.2 Other safety character	ristics					

SECTION 10: Stability and reactivity

: No.

Miscible with water

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: No specific data.
10.5 Incompatible materials	: No specific data.
Date of issue/Date of revision	: 6/25/2025 Date of previous issue : 6/15/2025 Version : 4.6 9/16

Easy-Mix S 50 Epoxy Adhesive Resin

SECTION 10: Stability and reactivity

10.6 Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Conclusion/Summary : Not available.

Acute toxicity estimates

N/A

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Obse	rvation
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	Skin - Mild irritant	Rabbit	-	24 hours 500 uL	-	
Conclusion/Summary	: Not available.					
<u>Sensitization</u>						
Conclusion/Summary	: Not available.					
<u>Mutagenicity</u>						
Conclusion/Summary	: Not available.					
Carcinogenicity						
Conclusion/Summary	: Not available.					
Reproductive toxicity						
Conclusion/Summary	: Not available.					
<u>Teratogenicity</u>						
Conclusion/Summary	: Not available.					
Specific target organ toxicity Not available.	<u>/ (single exposure)</u>					
<u>Specific target organ toxicity</u> Not available.	<u>/ (repeated exposure)</u>					
Aspiration hazard Not available.						
Information on the likely routes of exposure	: Not available.					
Potential acute health effects						
Eye contact	: Causes serious eye irritation.					
Inhalation	: No known significant effects of	or critical hazar	ds.			
Skin contact	: Causes skin irritation. May ca	ause an allergio	skin rea	iction.		
Ingestion	: No known significant effects of	or critical hazar	ds.			
Symptoms related to the phys	sical, chemical and toxicologic	al characteris	<u>tics</u>			
Eye contact	: Adverse symptoms may inclu pain or irritation watering redness	ide the following	g:			
Inhalation	: No specific data.					
Date of issue/Date of revision	: 6/25/2025 Date of previous is	ssue : 6/1	5/2025	Vers	ion :4.	6 10/16

SECTION 11: Toxicological information						
Skin contact	Adverse symptoms may include the following: irritation redness					
Ingestion	No specific data.					
Delayed and immediate effec	and also chronic effects from short and long term exposure					
<u>Short term exposure</u>						
Potential immediate effects	Not available.					
Potential delayed effects	Not available.					
Long term exposure						
Potential immediate effects	Not available.					
Potential delayed effects	Not available.					
Potential chronic health effe	ž					
Not available.						
Conclusion/Summary	Not available.					
General	Once sensitized, a severe allergic reaction may occur when subsequently exp to very low levels.	osed				
Carcinogenicity	No known significant effects or critical hazards.					
Mutagenicity	No known significant effects or critical hazards.					
Teratogenicity	No known significant effects or critical hazards.					
Developmental effects	No known significant effects or critical hazards.					
Fertility effects	No known significant effects or critical hazards.					
11.2 Information on other has 11.2.1 Endocrine disrupting						

- Not available.
- 11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	2.7	-	Low

12.4 Mobility in soil	
Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

SECTION 12: Ecological information

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: Yes.

European waste catalogue (EWC)

<u></u>	<u>jao (1110)</u>						
Waste code	Waste designation						
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances						
Packaging							
Methods of disposal	packaging sh	ion of waste should be avoided or minimized wherever possible. Waste hould be recycled. Incineration or landfill should only be considered ng is not feasible.					
Type of packaging		European waste catalogue (EWC)					
Can	15 01 10*	packaging containing residues of or contaminated by hazardous substances					
Special precautions	taken when h Empty contai	I and its container must be disposed of in a safe way. Care should be handling emptied containers that have not been cleaned or rinsed out. iners or liners may retain some product residues. Avoid dispersal of rial and runoff and contact with soil, waterways, drains and sewers.					

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	ΙΑΤΑ				
14.1 UN number or ID number	UN3082	UN3082	UN3082	UN3082				
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis- [4-(2,3-epoxipropoxi) phenyl]propane, Formaldehyde, oligomeric reaction products with 1-chloro- 2,3-epoxypropane and phenol)							
Date of issue/Date of rev	ision : 6/25/2025	Date of previous issue	: 6/15/2025	Version : 4.6 12/16				

Easy-Mix S 50 Epoxy Adhesive Resin

Easy-Mix S 50 Epoxy Adi	hesive Resin					
SECTION 14:	Transp	ort inf	ormation			
14.3 Transport hazard class(es)	9		9		9 ***	¥2
14.4 Packing group			111	Ш	111	
14.5 Environmental hazards	Yes.		Yes.	Yes.	Yes.	
Additional informa ADR/RID	<u>ation</u>	or ≤5 and 4			od when transported in eral provisions of 4.1.1	
ADN		or ≤5			od when transported in eral provisions of 4.1.1	
IMDG		or ≤5			od when transported in eral provisions of 4.1.1	
ΙΑΤΑ		or ≤5			od when transported in eral provisions of 5.0.2	
14.6 Special precau user	utions for	uprig		that persons transpo	sport in closed contain rting the product know	
14.7 Maritime trans bulk according to I instruments	•	: Not a	vailable.			

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name%Easy-Mix S 50 Epoxy Adhesive Resin≥90		%	Designation [Usage] 3	
		≥90		
Labeling Other EU regulations	: Not applic	able.		
Industrial emissions (integrated pollution prevention and control) - Air	: Not listed			

ECTION 15: Regulat	tory information	
Industrial emissions (integrated pollution prevention and control) - Water	: Not listed	
Explosive precursors	: Not applicable.	
Ozone depleting substance	<u>es (1005/2009/EU)</u>	
Not listed.		
Prior Informed Consent (Ple Not listed.	<u>C) (649/2012/EU)</u>	
Persistent Organic Pollutar Not listed.	<u>nts</u>	
<u>Seveso Directive</u> This product is controlled unc <u>Danger criteria</u>	der the Seveso Directive.	
Category		
E2		
National regulations		
Storage class (TRGS 510)	: 12	
Hazardous incident ordinar		
This product is controlled unc	der the Germany Hazardous Incident Ordinance.	
Category		Reference number
E2		1.3.2
Hazard class for water	: 2	
Technical instruction on air quality control	: TA-Luft Number 5.2.5: 79.1-100%	
ΑΟΧ	: The product contains organically bound halogens a value in waste water.	nd can contribute to the AOX
International regulations		
<u>-nemical weapon Convention</u>	on List Schedules I, II & III Chemicals	
Not listed.		
Montreal Protocol		
Montreal Protocol Not listed. Stockholm Convention on P	Persistent Organic Pollutants	
Montreal Protocol Not listed. Stockholm Convention on P Not listed.	Persistent Organic Pollutants Prior Informed Consent (PIC)	
Montreal Protocol Not listed. Stockholm Convention on P Not listed. Rotterdam Convention on P		
Montreal Protocol Not listed. Stockholm Convention on P Not listed. Rotterdam Convention on P Not listed.	rior Informed Consent (PIC)	
Montreal Protocol Not listed. Stockholm Convention on P Not listed. Rotterdam Convention on P Not listed. UNECE Aarhus Protocol on	rior Informed Consent (PIC)	
Montreal Protocol Not listed. Stockholm Convention on P Not listed. Rotterdam Convention on P Not listed. UNECE Aarhus Protocol on Not listed.	rior Informed Consent (PIC)	
Montreal Protocol Not listed. Stockholm Convention on P Not listed. Rotterdam Convention on P Not listed. UNECE Aarhus Protocol on Not listed.	Prior Informed Consent (PIC) POPs and Heavy Metals	
Montreal Protocol Not listed. Stockholm Convention on P Not listed. Rotterdam Convention on P Not listed. UNECE Aarhus Protocol on Not listed. Not listed.	Prior Informed Consent (PIC) POPs and Heavy Metals All components are listed or exempted.	
Not listed. Rotterdam Convention on P Not listed. UNECE Aarhus Protocol on Not listed. Inventory list	Prior Informed Consent (PIC) POPs and Heavy Metals	

ous issue : 6/

SECTION 15: Regulatory information

•	•	
Japan	: Japan inventory (CSCL): All components are listed or exempted. Japan inventory (ISHL): Not determined.	
New Zealand	: All components are listed or exempted.	
Philippines	: All components are listed or exempted.	
Republic of Korea	: All components are listed or exempted.	
Taiwan	: All components are listed or exempted.	
Thailand	: Not determined.	
Turkey	: Not determined.	
United States	: All components are active or exempted.	
Viet Nam	: All components are listed or exempted.	
15.2 Chemical Safety Assessment	: This product contains substances for which Chemical Safety Assessments are still required.	

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	 ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number SGG = Segregation Group vPvB = Very Persistent and Very Bioaccumulative
	vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
Skin Sens. 1, H317	Calculation method
Aquatic Chronic 2, H411	Calculation method

Full text of abbreviated H statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

I dir text of classifications		
Aquatic Chronic 2 Eye Irrit. 2 Skin Irrit. 2 Skin Sens. 1		AQUATIC HAZARD (LONG-TERM) - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITIZATION - Category 1
Date of printing	: 6/27/2025	·
Date of issue/ Date of revision	: 6/25/2025	
Date of previous issue	: 6/15/2025	
Version	: 4.6	
Notice to reader		

Easy-Mix S 50 Epoxy Adhesive Resin

SECTION 16: Other information

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.