SAFETY DATA SHEET



Easy-Mix PU-90 Polyurethane Adhesive Resin

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

: Easy-Mix PU-90 Polyurethane Adhesive Resin **Product name**

: GR70-Q0VS-C00R-C5EH UFI

Product code : 107511 Color : Black.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Not available.

1.3 Details of the supplier of the safety data sheet

WEICON GmbH & Co. KG Königsberger Str. 255 48157 Münster Germany

Phone: +49 251 93220 Fax: +49(0)251 / 9322 - 244

Internet: www.weicon.de e-mail address of person

: msds@weicon.de

responsible for this SDS

1.4 Emergency telephone number

Telephone number : EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel: ++44 1865 407333

(English)

TRANSPORT EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel: ++44

1865 407333 (English)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Acute Tox. 4, H332 Skin Irrit, 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 **STOT SE 3, H335**

STOT RE 2, H373

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Date of issue/Date of revision : 10/20/2022 : 10/19/2022 Version : 3.01 1/16 Date of previous issue

SECTION 2: Hazards identification

Hazard pictograms





Signal word : Danger

Hazard statements: H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation.

H332 - Harmful if inhaled.

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 - May cause respiratory irritation. H351 - Suspected of causing cancer.

H373 - May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

Prevention: P201 - Obtain special instructions before use.

P284 - Wear respiratory protection.

P271 - Use only outdoors or in a well-ventilated area.

P260 - Do not breathe vapor.

P264 - Wash thoroughly after handling.

P280 - Wear protective gloves, protective clothing, eye protection, face protection,

or hearing protection.

Response : P308 + P313 - IF exposed or concerned: Get medical advice or attention.

P304 + P340, P312 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. P342 + P311 - If experiencing respiratory symptoms: Call a POISON CENTER or

doctor.

P362 + P364 - Take off contaminated clothing and wash it before reuse.

P302 + P352 - IF ON SKIN: Wash with plenty of water.

P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention. P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 - If eye irritation persists: Get medical advice or attention.

Storage: P405 - Store locked up.

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.

Disposal : P501 - Dispose of waste according to applicable legislation.

Hazardous ingredients : Isocyanic acid, polymethylenepolyphenylene ester

Benzene, 1,1'-methylenebis[4-isocyanato-, homopolymer

4,4'-methylenediphenyl diisocyanate

Supplemental label elements

: Contains isocyanates. May produce an allergic reaction.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Persons already sensitized to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used. As from August 24 2023 adequate training is required before industrial or professional

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification

: None known.

use.

Date of issue/Date of revision : 10/20/2022 Date of previous issue : 10/19/2022 Version : 3.01 2/16

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Isocyanic acid, polymethylenepolyphenylene ester	CAS: 9016-87-9	≥10 - ≤25	Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373	ATE [Inhalation (vapours)] = 11 mg/ I	[1] [2]
Benzene, 1,1'-methylenebis [4-isocyanato-, homopolymer	REACH #: 01-2119457013-49 EC: 500-040-3 CAS: 25686-28-6	≥10 - ≤25	Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373	ATE [Inhalation (dusts and mists)] = 1.5 mg/l	[1]
4,4'-methylenediphenyl diisocyanate	REACH #: 01-2119457014-47 EC: 202-966-0 CAS: 101-68-8 Index: 615-005-00-9	≤10	Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373	ATE [Inhalation (dusts and mists)] = 1.5 mg/l Skin Irrit. 2, H315: C ≥ 5% Eye Irrit. 2, H319: C ≥ 5% Resp. Sens. 1, H334: C ≥ 0.1% STOT SE 3, H335: C ≥ 5%	[1] [2]
			See Section 16 for the full text of the H statements declared above.		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact : Im

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may

Date of issue/Date of revision : 10/20/2022 Date of previous issue : 10/19/2022 Version : 3.01 3/16

Easy-Mix PU-90 Polyurethane Adhesive Resin

SECTION 4: First aid measures

be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. In the event of any complaints or symptoms, avoid further exposure.

Skin contact: Wash with plenty of soap and water. Remove contaminated clothing and shoes.

Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before

reuse. Clean shoes thoroughly before reuse.

Ingestion: Wash out mouth with water. Remove dentures if any. If material has been

swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open

airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it

is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing

thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact: Adverse symptoms may include the following:

pain or irritation

watering redness

Inhalation: Adverse symptoms may include the following:

respiratory tract irritation

coughing

wheezing and breathing difficulties

asthma

Skin contact: Adverse symptoms may include the following:

irritation redness

Ingestion: No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician: In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing

: Use an extinguishing agent suitable for the surrounding fire.

media

Unsuitable extinguishing : None known.

media

5.2 Special hazards arising from the substance or mixture

Hazards from the : In a fire or if heated, a press

substance or mixture

: In a fire or if heated, a pressure increase will occur and the container may burst.

Date of issue/Date of revision : 10/20/2022 Date of previous issue : 10/19/2022 Version : 3.01 4/16

Easy-Mix PU-90 Polyurethane Adhesive Resin

SECTION 5: Firefighting measures

Hazardous combustion products

: Decomposition products may include the following materials: carbon dioxide

carbon monoxide nitrogen oxides

Hydrogen cyanide (HCN).

5.3 Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without

suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and materials for containment and cleaning up

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

6.4 Reference to other sections

: See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

7.1 Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems or asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Date of issue/Date of revision : 10/20/2022 : 10/19/2022 Version : 3.01 5/16 Date of previous issue

Easy-Mix PU-90 Polyurethane Adhesive Resin

SECTION 7: Handling and storage

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific : Not available.

solutions

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
Isocyanic acid, polymethylenepolyphenylene ester	DFG MAC-values list (Germany, 10/2021). Absorbed through skin. Skin sensitizer. Inhalation sensitizer. TWA: 0.05 mg/m³ 8 hours. Form: inhalable fraction PEAK: 0.05 mg/m³, 4 times per shift, 15 minutes. Form: inhalable fraction CEIL: 0.1 mg/m³ TRGS 900 OEL (Germany, 7/2021). Absorbed through skin. Skin sensitizer. Inhalation sensitizer. TWA: 0.05 mg/m³, (calculated as MDI) 8 hours. Form: inhalable fraction PEAK: 0.05 mg/m³, (calculated as MDI) 15 minutes. Form: inhalable fraction CEIL: 0.1 mg/m³, (calculated as MDI) Form: inhalable fraction
4,4'-methylenediphenyl diisocyanate	TRGS 900 OEL (Germany, 7/2021). Absorbed through skin. Skin sensitizer. Inhalation sensitizer. TWA: 0.05 mg/m³ 8 hours. Form: inhalable fraction CEIL: 0.1 mg/m³ Form: inhalable fraction PEAK: 0.05 mg/m³ 15 minutes. Form: inhalable fraction DFG MAC-values list (Germany, 10/2021). Absorbed through skin. Skin sensitizer. Inhalation sensitizer. TWA: 0.05 mg/m³ 8 hours. Form: inhalable fraction PEAK: 0.05 mg/m³, 4 times per shift, 15 minutes. Form: inhalable fraction CEIL: 0.1 mg/m³

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace

Date of issue/Date of revision : 10/20/2022 Date of previous issue : 10/19/2022 Version : 3.01 6/16

SECTION 8: Exposure controls/personal protection

atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
Benzene, 1,1'-methylenebis [4-isocyanato-, homopolymer	DNEL	Long term Inhalation	0.025 mg/ m³	General population	Local
	DNEL	Short term Inhalation	0.05 mg/m ³	General population	Local
	DNEL	Long term Inhalation	0.05 mg/m ³	Workers	Local
	DNEL	Short term Inhalation	0.1 mg/m³	Workers	Local
4,4'-methylenediphenyl diisocyanate	DNEL	Long term Inhalation	0.025 mg/ m³	General population	Local
	DNEL	Short term Inhalation	0.05 mg/m³	General population	Local
	DNEL	Long term Inhalation	0.05 mg/m³	Workers	Local
	DNEL	Short term Inhalation	0.1 mg/m³	Workers	Local

PNECs

No PNECs available.

8.2 Exposure controls

Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. Recommended:; Viton®, Butyl rubber gloves.

Date of issue/Date of revision : 10/20/2022 Date of previous issue : 10/19/2022 Version : 3.01 7/16

Easy-Mix PU-90 Polyurethane Adhesive Resin

SECTION 8: Exposure controls/personal protection

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist

before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be

selected based on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

Based on the hazard and potential for exposure, select a respirator that meets the Respiratory protection

appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important

aspects of use. Recommended: inorganic gases/vapors filter (Type B)

Environmental exposure

controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process

equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid. Color : Black.

Odor : Bland. [Strong] Odor threshold Not available. Melting point/freezing point : Not available. Initial boiling point and : Not available.

boiling range

Flammability : Highly flammable in the presence of the following materials or conditions: acids,

alkalis and moisture.

Upper/lower flammability or

explosive limits

: Not available.

: Closed cup: >93.3°C (>199.9°F) Flash point

Auto-ignition temperature : Not applicable. **Decomposition temperature** : Not available. рΗ : Not applicable.

Viscosity Dynamic: 60000 mPa·s

Solubility(ies)

Not available.

Solubility in water Not available.

Miscible with water : No.

Partition coefficient: n-octanol/ : Not applicable.

water

Vapor pressure :

	Vapor Pressure at 20°C			Vapor pressure at 50°C		e at 50°C
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
4,4'-methylenediphenyl diisocyanate	0	0				

Relative density : Not available.

1.28 g/cm³ [20°C (68°F)] Density

: Not available. Vapor density : Not available. **Explosive properties** Oxidizing properties Not available.

Date of issue/Date of revision : 10/20/2022 : 10/19/2022 Version: 3.01 8/16 Date of previous issue

Easy-Mix PU-90 Polyurethane Adhesive Resin

SECTION 9: Physical and chemical properties

Particle characteristics

Median particle size : Not applicable.

9.2 Other information

SAPT : Not available.
SAPT : Not available.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : No specific data.

10.6 Hazardous decomposition products

Extremely reactive or incompatible with the following materials: moisture.

Will react with water or steam to produce heat and toxic fumes. Reacts violently with

water, especially when water is added to the product.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Isocyanic acid, polymethylenepolyphenylene ester	LC50 Inhalation Dusts and mists	Rat	0.31 mg/l	4 hours
	LC50 Inhalation Vapor	Rat	490 mg/m³	4 hours
	LD50 Dermal	Rabbit	>9400 mg/kg	-
	LD50 Oral	Rat	49 g/kg	-
Benzene, 1,1'-methylenebis [4-isocyanato-, homopolymer	LC50 Inhalation Dusts and mists	Rat	0.49 mg/l	4 hours
4,4'-methylenediphenyl diisocyanate	LC50 Inhalation Dusts and mists	Rat	0.368 mg/l	4 hours
	LD50 Oral	Rat	9200 mg/kg	-

Conclusion/Summary : Not available.

Acute toxicity estimates

Route	ATE value
Inhalation (vapors)	55 mg/l
Inhalation (dusts and mists)	3.55 mg/l

Irritation/Corrosion

Date of issue/Date of revision: 10/20/2022Date of previous issue: 10/19/2022Version: 3.019/16

Easy-Mix PU-90 Polyurethane Adhesive Resin

SECTION 11: Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
Isocyanic acid, polymethylenepolyphenylene ester	Eyes - Mild irritant	Rabbit	-	100 mg	-
4,4'-methylenediphenyl diisocyanate	Eyes - Moderate irritant	Rabbit	-	100 mg	-

Conclusion/Summary: Not available.

Sensitization

Conclusion/Summary: Not available.

Mutagenicity

Conclusion/Summary: Not available.

Carcinogenicity

Conclusion/Summary: Not available.

Reproductive toxicity

Conclusion/Summary: Not available.

Teratogenicity

Conclusion/Summary: Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Isocyanic acid, polymethylenepolyphenylene ester	Category 3	-	Respiratory tract irritation
Benzene, 1,1'-methylenebis[4-isocyanato-, homopolymer	Category 3	-	Respiratory tract irritation
4,4'-methylenediphenyl diisocyanate	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Isocyanic acid, polymethylenepolyphenylene ester	Category 2	-	-
Benzene, 1,1'-methylenebis[4-isocyanato-, homopolymer	Category 2	-	-
4,4'-methylenediphenyl diisocyanate	Category 2	-	-

Aspiration hazard

Not available.

Information on the likely

routes of exposure

: Not available.

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : Harmful if inhaled. May cause respiratory irritation. May cause allergy or asthma

symptoms or breathing difficulties if inhaled.

Skin contact: Causes skin irritation. May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Date of issue/Date of revision : 10/20/2022 Date of previous issue : 10/19/2022 Version : 3.01 10/16

Easy-Mix PU-90 Polyurethane Adhesive Resin

SECTION 11: Toxicological information

Eye contact: Adverse symptoms may include the following:

pain or irritation watering redness

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

wheezing and breathing difficulties

asthma

Skin contact: Adverse symptoms may include the following:

irritation redness

Ingestion: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary: Not available.

General: May cause damage to organs through prolonged or repeated exposure. Once

sensitized, a severe allergic reaction may occur when subsequently exposed to very

low levels

Carcinogenicity : Suspected of causing cancer. Risk of cancer depends on duration and level of

exposure.

Mutagenicity : No known significant effects or critical hazards.
 Teratogenicity : No known significant effects or critical hazards.
 Developmental effects : No known significant effects or critical hazards.
 Fertility effects : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Conclusion/Summary: Not available.

12.3 Bioaccumulative potential

Date of issue/Date of revision : 10/20/2022 Date of previous issue : 10/19/2022 Version : 3.01 11/16

Easy-Mix PU-90 Polyurethane Adhesive Resin

SECTION 12: Ecological information

Product/ingredient name	LogPow	BCF	Potential
Benzene, 1,1'-methylenebis [4-isocyanato-, homopolymer	8.56	200	low
4,4'-methylenediphenyl diisocyanate	4.51	200	low

12.4 Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste

: The classification of the product may meet the criteria for a hazardous waste.

European waste catalogue (EWC)

Waste code	Waste designation
08 05 01*	waste isocyanates

Packaging

Methods of disposal

: The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	European waste catalogue (EWC)
15 01 10*	packaging containing residues of or contaminated by hazardous substances

Special precautions

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Date of issue/Date of revision : 10/20/2022 Date of previous issue : 10/19/2022 Version : 3.01 12/16

SECTION 14: Transport information

	ADR/RID	IMDG	IATA
14.1 UN number	Not available.	Not available.	Not available.
14.2 UN proper shipping name	Not available.	Not available.	Not available.
14.3 Transport hazard class(es)	Not available.	Not available.	Not available.
14.4 Packing group	-	-	-
14.5 Environmental hazards	No. Not available.	No. Not available.	No.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments

: Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Annex XVII - Restrictions : Persons already sensitized to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used. As from August 24 2023 adequate training is required before industrial or professional use.

Restrictions on Manufacture, Marketing and Use

Count	ryProduct name	Conc.	Designation	Usage
EU	4,4'-methylenediphenyl diisocyanate	5 - 10	56	Consumer products
EU	4,4'-methylenediphenyl diisocyanate	5 - 10	74	As from August 24 2023 adequate training is required before industrial or professional use.
GB	4,4'-methylenediphenyl diisocyanate	5 - 10	56	Consumer products
GB	4,4'-methylenediphenyl diisocyanate	5 - 10	74	As from August 24 2023 adequate training is required before industrial or professional use.

Date of issue/Date of revision : 10/20/2022 : 10/19/2022 Version : 3.01 13/16 Date of previous issue

Easy-Mix PU-90 Polyurethane Adhesive Resin

SECTION 15: Regulatory information

Other EU regulations

Industrial emissions : Listed

(integrated pollution prevention and control) -

Air

Industrial emissions : Listed

(integrated pollution prevention and control) -

Water

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

Product/ingredient name	List name	Name on list	Classification	Notes
Isocyanic acid, polymethylenepolyphenylene ester	DFG MAC-values list	polymeric MDI (inhalable fraction); MDI oligomers; pMDI	К3	-
	Germany TRGS905	Techn. ("Polymeres") MDI (in Form atembarer Aerosole, A-Fraktion); pMDI	К3	
4,4'-methylenediphenyl diisocyanate	DFG MAC-values list	Diphenylmethane-4,4'-diisocyanate (inhalable fraction); 4,4'-Methylene diphenyl diisocyanate; MDI	К3	-

Storage class (TRGS 510) : 10

Hazardous incident ordinance

This product is not controlled under the Germany Hazardous Incident Ordinance.

Hazard class for water : 1

Technical instruction on

air quality control

: TA-Luft Class I - Number 5.2.5: 25-70%

: The product does not contain organically bound halogens which could lead to an

AOX value in waste water.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

AOX

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Date of issue/Date of revision : 10/20/2022 Date of previous issue : 10/19/2022 Version : 3.01 14/16

Easy-Mix PU-90 Polyurethane Adhesive Resin

SECTION 15: Regulatory information

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Australia : All components are listed or exempted.

Canada : All components are listed or exempted.

China : All components are listed or exempted.

Eurasian Economic Union: Russian Federation inventory: All components are listed or exempted.

Japan : Japan inventory (CSCL): All components are listed or exempted.

Japan inventory (ISHL): Not determined.All components are listed or exempted.

New Zealand: All components are listed or exempted.Philippines: All components are listed or exempted.Republic of Korea: All components are listed or exempted.Taiwan: All components are listed or exempted.Thailand: All components are listed or exempted.

Turkey : Not determined.

United States : All components are active or exempted.Viet Nam : All components are listed or exempted.

15.2 Chemical Safety

: This product contains substances for which Chemical Safety Assessments are still

Assessment required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and

acronyms

: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

N/A = Not available

PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Acute Tox. 4, H332	Calculation method
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
Resp. Sens. 1, H334	Calculation method
Skin Sens. 1, H317	Calculation method
Carc. 2, H351	Calculation method
STOT SE 3, H335	Calculation method
STOT RE 2, H373	Calculation method

Full text of abbreviated H statements

Date of issue/Date of revision : 10/20/2022 Date of previous issue : 10/19/2022 Version : 3.01 15/16

Easy-Mix PU-90 Polyurethane Adhesive Resin

SECTION 16: Other information

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if
	inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated
	exposure.

Full text of classifications [CLP/GHS]

Acute Tox. 4	ACUTE TOXICITY - Category 4
Carc. 2	CARCINOGENICITY - Category 2
Eye Irrit. 2	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2
Resp. Sens. 1	RESPIRATORY SENSITIZATION - Category 1
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITIZATION - Category 1
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY (REPEATED
	EXPOSURE) - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) -
	Category 3

Date of printing : 10/20/2022 **Date of issue/ Date of** : 10/20/2022

revision

Date of previous issue : 10/19/2022

Version : 3.01

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Date of issue/Date of revision : 10/20/2022 Date of previous issue : 10/19/2022 Version : 3.01 16/16