

# SAFETY DATA SHEET



Zinc Spray bright grade

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : Zinc Spray bright grade  
**UFI** : Q580-80AR-W006-PVAU  
**Product code** : 110010  
**Color** : Silver.  
**Product type** : Aerosol.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

| Identified uses      |        |
|----------------------|--------|
| Aerosol product      |        |
| Uses advised against | Reason |
| Not applicable.      |        |

### 1.3 Details of the supplier of the safety data sheet

WEICON GmbH & Co. KG  
Königsberger Str. 25,  
48157 Münster, Germany  
phone: +49 251 93220,  
Fax: +49 251 932244  
email: [info@weicon.de](mailto:info@weicon.de),  
URL: [www.weicon.de](http://www.weicon.de)

**e-mail address of person responsible for this SDS** : [msds@weicon.de](mailto:msds@weicon.de)

### 1.4 Emergency telephone number

#### National advisory body/Poison Center

**Telephone number** : EMERGENCY CONTACT – UK, UAE, South Africa (24h): Tel: ++44 1865 407333 (English)  
TRANSPORT EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel: ++44 1865 407333 (English)

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Aerosol 1, H222, H229  
Skin Irrit. 2, H315  
Eye Irrit. 2, H319  
Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

## SECTION 2: Hazards identification

### Hazard pictograms

:



### Signal word

: Danger

### Hazard statements

: H222, H229 - Extremely flammable aerosol. Pressurized container: may burst if heated.  
H315 - Causes skin irritation.  
H319 - Causes serious eye irritation.  
H411 - Toxic to aquatic life with long lasting effects.

### Precautionary statements

#### General

: P101 - If medical advice is needed, have product container or label at hand.  
P102 - Keep out of reach of children.

#### Prevention

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 - Do not spray on an open flame or other ignition source.  
P251 - Do not pierce or burn, even after use.  
P264 - Wash thoroughly after handling.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves. Wear eye or face protection.

#### Response

: P391 - Collect spillage.  
P362 + P364 - Take off contaminated clothing and wash it before reuse.  
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337 + P313 - If eye irritation persists: Get medical advice or attention.

#### Storage

: P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

#### Disposal

: P501 - Dispose of waste according to applicable legislation.

### Supplemental label elements

: Not applicable.

### Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

: Not applicable.

### 2.3 Other hazards

#### Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

#### Other hazards which do not result in classification

: Aspiration hazard - Not applicable.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

: Mixture

Zinc Spray bright grade

### SECTION 3: Composition/information on ingredients

| Product/ingredient name  | Identifiers  | %           | Classification   | Specific Conc. Limits, M-factors and ATEs                         | Type    |
|--|--|-------------|--|---|---------|
| dimethyl ether   | REACH #:<br>01-2119472128-37<br>EC: 204-065-8<br>CAS: 115-10-6<br>Index: 603-019-00-8  | ≥50 - ≤75   | Flam. Gas 1A, H220<br>Press. Gas (Comp.), H280   | -   | [2]     |
| xylene   | REACH #:<br>01-2119488216-32<br>EC: 215-535-7<br>CAS: 1330-20-7<br>Index: 601-022-00-9 | ≥5 - <10    | Flam. Liq. 3, H226<br>Acute Tox. 4, H312<br>Acute Tox. 4, H332<br>Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>STOT SE 3, H335<br>STOT RE 2, H373<br>Asp. Tox. 1, H304 | ATE [Dermal] = 1100 mg/kg<br>ATE [Inhalation (vapours)] = 11 mg/l | [1] [2] |
| Zinc powder - zinc dust (stabilized)                                     | REACH #:<br>01-2119467174-37<br>EC: 231-175-3<br>CAS: 7440-66-6<br>Index: 030-001-01-9 | ≥5 - ≤10    | Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410   | M [Acute] = 1<br>M [Chronic] = 1                                  | [1] [2] |
| n-butyl acetate  | REACH #:<br>01-2119485493-29<br>EC: 204-658-1<br>CAS: 123-86-4<br>Index: 607-025-00-1  | ≥5 - ≤5.9   | Flam. Liq. 3, H226<br>STOT SE 3, H336<br>EUH066  | -   | [1] [2] |
| ethyl acetate  | REACH #:<br>01-2119475103-46<br>EC: 205-500-4<br>CAS: 141-78-6<br>Index: 607-022-00-5  | ≥5 - ≤5.9   | Flam. Liq. 2, H225<br>Eye Irrit. 2, H319<br>STOT SE 3, H336<br>EUH066  | -   | [1] [2] |
| acetone  | REACH #:<br>01-2119471330-49<br>EC: 200-662-2<br>CAS: 67-64-1<br>Index: 606-001-00-8   | ≥5 - ≤5.9   | Flam. Liq. 2, H225<br>Eye Irrit. 2, H319<br>STOT SE 3, H336<br>EUH066  | -   | [1] [2] |
| Aluminium powder (stabilized)  | REACH #:<br>01-2119529243-45<br>EC: 231-072-3<br>CAS: 7429-90-5<br>Index: 013-002-00-1 | ≥5 - ≤10    | Flam. Sol. 1, H228<br>Water-react. 2, H261   | -   | [2]     |
| Hydrocarbons, C10-13, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics | REACH #:<br>01-2119457273-39<br>EC: 918-481-9  | ≥5 - ≤10    | Asp. Tox. 1, H304  | -   | [1]     |
| butan-1-ol   | REACH #:<br>01-2119484630-38<br>EC: 200-751-6<br>CAS: 71-36-3<br>Index: 603-004-00-6   | ≥1 - ≤2.1   | Flam. Liq. 3, H226<br>Acute Tox. 4, H302<br>Skin Irrit. 2, H315<br>Eye Dam. 1, H318<br>STOT SE 3, H335<br>STOT SE 3, H336  | ATE [Oral] = 790 mg/kg  | [1] [2] |
| Quaternary ammonium compounds, coco alkylethyldimethyl, Et               | EC: 269-662-8<br>CAS: 68308-64-5   | ≥0.1 - ≤0.2 | Acute Tox. 4, H302<br>Acute Tox. 3, H311<br>Skin Corr. 1C, H314  | ATE [Oral] = 500 mg/kg<br>ATE [Dermal] =                          | [1]     |

Zinc Spray bright grade

### SECTION 3: Composition/information on ingredients

|          |  |  |   |  |  |
|----------|--|--|---|--|--|
| sulfates |  |  | Eye Dam. 1, H318<br>Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410<br><b>See Section 16 for the full text of the H statements declared above.</b> | 300 mg/kg<br>M [Acute] = 10<br>M [Chronic] = 1 |  |
|----------|--|--|---|--|--|

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

#### 4.2 Most important symptoms and effects, both acute and delayed

##### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness
- Ingestion** : No specific data.

Zinc Spray bright grade

## SECTION 4: First aid measures

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

### 5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Extremely flammable aerosol. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
metal oxide/oxides

### 5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

- : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

## SECTION 6: Accidental release measures

### 6.3 Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

- 6.4 Reference to other sections** : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Avoid breathing vapor or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

#### Seveso Directive - Reporting thresholds

##### Danger criteria

| Category  | Notification and MAPP threshold | Safety report threshold |
|-----------|---------------------------------|-------------------------|
| P3a<br>E2 | 150 tonne<br>200 tonne          | 500 tonne<br>500 tonne  |

### 7.3 Specific end use(s)

- Recommendations** : Not available.
- Industrial sector specific solutions** : Not available.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

### 8.1 Control parameters

#### Occupational exposure limits

| Product/ingredient name              | Exposure limit values  |
|--------------------------------------|--|
| dimethyl ether                       | <b>TRGS 900 OEL (Germany, 4/2023).</b><br>TWA: 1900 mg/m <sup>3</sup> 8 hours.<br>PEAK: 15200 mg/m <sup>3</sup> 15 minutes.<br>TWA: 1000 ppm 8 hours.<br>PEAK: 8000 ppm 15 minutes.<br><b>DFG MAC-values list (Germany, 7/2022).</b><br>TWA: 1000 ppm 8 hours.<br>PEAK: 8000 ppm, 4 times per shift, 15 minutes.<br>TWA: 1900 mg/m <sup>3</sup> 8 hours.<br>PEAK: 15200 mg/m <sup>3</sup> , 4 times per shift, 15 minutes.   |
| xylene                               | <b>TRGS 900 OEL (Germany, 4/2023). [xylene] Absorbed through skin.</b><br>TWA: 220 mg/m <sup>3</sup> 8 hours.<br>PEAK: 440 mg/m <sup>3</sup> 15 minutes.<br>TWA: 50 ppm 8 hours.<br>PEAK: 100 ppm 15 minutes.<br><b>DFG MAC-values list (Germany, 7/2022). [Xylene (all isomers)] Absorbed through skin.</b><br>TWA: 50 ppm 8 hours.<br>PEAK: 100 ppm, 4 times per shift, 15 minutes.<br>TWA: 220 mg/m <sup>3</sup> 8 hours.<br>PEAK: 440 mg/m <sup>3</sup> , 4 times per shift, 15 minutes. |
| Zinc powder - zinc dust (stabilized) | <b>DFG MAC-values list (Germany, 10/2021). [Zinc and its inorganic compounds]</b><br>TWA: 2 mg/m <sup>3</sup> 8 hours. Form: inhalable fraction<br>PEAK: 4 mg/m <sup>3</sup> , 4 times per shift, 15 minutes. Form: inhalable fraction<br>PEAK: 0.4 mg/m <sup>3</sup> , 4 times per shift, 15 minutes. Form: respirable fraction<br>TWA: 0.1 mg/m <sup>3</sup> 8 hours. Form: respirable fraction  |
| n-butyl acetate                      | <b>DFG MAC-values list (Germany, 7/2022).</b><br>TWA: 100 ppm 8 hours.<br>PEAK: 200 ppm, 4 times per shift, 15 minutes.<br>TWA: 480 mg/m <sup>3</sup> 8 hours.<br>PEAK: 960 mg/m <sup>3</sup> , 4 times per shift, 15 minutes.<br><b>TRGS 900 OEL (Germany, 4/2023).</b><br>TWA: 300 mg/m <sup>3</sup> 8 hours.<br>TWA: 62 ppm 8 hours.<br>PEAK: 600 mg/m <sup>3</sup> 15 minutes.<br>PEAK: 124 ppm 15 minutes.  |
| ethyl acetate                        | <b>TRGS 900 OEL (Germany, 4/2023).</b><br>TWA: 730 mg/m <sup>3</sup> 8 hours.<br>PEAK: 1460 mg/m <sup>3</sup> 15 minutes.<br>TWA: 200 ppm 8 hours.<br>PEAK: 400 ppm 15 minutes.<br><b>DFG MAC-values list (Germany, 7/2022).</b><br>TWA: 200 ppm 8 hours.<br>PEAK: 400 ppm, 4 times per shift, 15 minutes.<br>TWA: 750 mg/m <sup>3</sup> 8 hours.<br>PEAK: 1500 mg/m <sup>3</sup> , 4 times per shift, 15 minutes.   |

Zinc Spray bright grade

## SECTION 8: Exposure controls/personal protection

acetone

**TRGS 900 OEL (Germany, 4/2023).**

TWA: 1200 mg/m<sup>3</sup> 8 hours.

PEAK: 2400 mg/m<sup>3</sup> 15 minutes.

TWA: 500 ppm 8 hours.

PEAK: 1000 ppm 15 minutes.

**DFG MAC-values list (Germany, 7/2022).**

TWA: 500 ppm 8 hours.

PEAK: 1000 ppm, 4 times per shift, 15 minutes.

TWA: 1200 mg/m<sup>3</sup> 8 hours.

PEAK: 2400 mg/m<sup>3</sup>, 4 times per shift, 15 minutes.

Aluminium powder (stabilized)

**TRGS 900 OEL (Germany, 7/2021). []**

TWA: 1.25 mg/m<sup>3</sup> 8 hours. Form: alveolar fraction

PEAK: 2.5 mg/m<sup>3</sup> 15 minutes. Form: alveolar fraction

PEAK: 20 mg/m<sup>3</sup> 15 minutes. Form: inhalable fraction

TWA: 10 mg/m<sup>3</sup> 8 hours. Form: inhalable fraction

**DFG MAC-values list (Germany, 10/2021). [Aluminium, Aluminium oxide and Aluminium hydroxide, containing dusts]**

TWA: 4 mg/m<sup>3</sup> 8 hours. Form: inhalable dust

TWA: 1.5 mg/m<sup>3</sup> 8 hours. Form: respirable dust

butan-1-ol

**TRGS 900 OEL (Germany, 4/2023).**

TWA: 310 mg/m<sup>3</sup> 8 hours.

PEAK: 310 mg/m<sup>3</sup> 15 minutes.

TWA: 100 ppm 8 hours.

PEAK: 100 ppm 15 minutes.

**DFG MAC-values list (Germany, 7/2022).**

TWA: 100 ppm 8 hours.

PEAK: 100 ppm, 4 times per shift, 15 minutes.

TWA: 310 mg/m<sup>3</sup> 8 hours.

PEAK: 310 mg/m<sup>3</sup>, 4 times per shift, 15 minutes.

### Biological exposure indices

| Product/ingredient name | Exposure indices  |
|-------------------------|---|
| xylene                  | <p><b>DFG BEI-values list (Germany, 7/2022) [Xylene (all isomers)]</b></p> <p><b>Notes: danger from percutaneous absorption (see p. 211 and p. 228).</b></p> <p>BEI: 2000 mg/l, methylhippuric acid (toluric acid) (all isomers) [in urine]. Sampling time: end of exposure or end of shift.</p> <p><b>TRGS 903 - BEI Values (Germany, 2/2022) [Xylene (all isomers)]</b></p> <p>BEI: 2000 mg/l, methylhippuric acid [in urine]. Sampling time: end of exposure or end of shift.</p>  |
| acetone                 | <p><b>DFG BEI-values list (Germany, 7/2022)</b></p> <p>BEI: 50 mg/l, acetone [in urine]. Sampling time: end of exposure or end of shift.</p> <p><b>TRGS 903 - BEI Values (Germany, 2/2022)</b></p> <p>BEI: 80 mg/l, acetone [in urine]. Sampling time: end of exposure or end of shift.</p>   |
| butan-1-ol              | <p><b>DFG BEI-values list (Germany, 7/2022)</b></p> <p>BEI: 2 mg/g creatinine, 1-butanol [in urine]. Sampling time: at the beginning of the next shift.</p> <p>BEI: 10 mg/g creatinine, 1-butanol [in urine]. Sampling time: end of exposure or end of shift.</p> <p><b>TRGS 903 - BEI Values (Germany, 2/2022)</b></p> <p>BEI: 2 mg/g creatinine, butan-1-ol (butanol-1) (after hydrolysis) [in urine]. Sampling time: at the beginning of the next shift.</p> <p>BEI: 10 mg/g creatinine, butan-1-ol (butanol-1) (after hydrolysis)</p> |



Zinc Spray bright grade

## SECTION 8: Exposure controls/personal protection

[in urine]. Sampling time: end of exposure or end of shift.

**Recommended monitoring procedures** : Reference should be made to monitoring standards, such as the following:  
European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### DNELs/DMELs

| Product/ingredient name | Type | Exposure              | Value                  | Population         | Effects  |
|-------------------------|------|-----------------------|------------------------|--------------------|----------|
| dimethyl ether          | DNEL | Long term Inhalation  | 471 mg/m <sup>3</sup>  | General population | Systemic |
|                         | DNEL | Long term Inhalation  | 1894 mg/m <sup>3</sup> | Workers            | Systemic |
| xylene                  | DNEL | Long term Oral        | 12.5 mg/kg bw/day      | General population | Systemic |
|                         | DNEL | Long term Inhalation  | 65.3 mg/m <sup>3</sup> | General population | Local    |
|                         | DNEL | Long term Inhalation  | 65.3 mg/m <sup>3</sup> | General population | Systemic |
|                         | DNEL | Long term Dermal      | 125 mg/kg bw/day       | General population | Systemic |
|                         | DNEL | Long term Dermal      | 212 mg/kg bw/day       | Workers            | Systemic |
|                         | DNEL | Long term Inhalation  | 221 mg/m <sup>3</sup>  | Workers            | Local    |
|                         | DNEL | Long term Inhalation  | 221 mg/m <sup>3</sup>  | Workers            | Systemic |
|                         | DNEL | Short term Inhalation | 260 mg/m <sup>3</sup>  | General population | Local    |
|                         | DNEL | Short term Inhalation | 260 mg/m <sup>3</sup>  | General population | Systemic |
|                         | DNEL | Short term Inhalation | 442 mg/m <sup>3</sup>  | Workers            | Local    |
|                         | DNEL | Short term Inhalation | 442 mg/m <sup>3</sup>  | Workers            | Systemic |
|                         | DNEL | Long term Oral        | 0.83 mg/kg bw/day      | General population | Systemic |
|                         |      | Long term Inhalation  | 2.5 mg/m <sup>3</sup>  | General population | Systemic |
|                         |      | Long term Inhalation  | 5 mg/m <sup>3</sup>    | Workers            | Systemic |
|                         |      | Long term Dermal      | 83 mg/kg bw/day        | General population | Systemic |

Zinc Spray bright grade

## SECTION 8: Exposure controls/personal protection

|                 |      |                       |                        |                    |          |
|-----------------|------|-----------------------|------------------------|--------------------|----------|
| n-butyl acetate | DNEL | Long term Dermal      | 83 mg/kg bw/day        | Workers            | Systemic |
|                 | DNEL | Long term Oral        | 2 mg/kg bw/day         | General population | Systemic |
|                 | DNEL | Short term Oral       | 2 mg/kg bw/day         | General population | Systemic |
|                 | DNEL | Long term Dermal      | 3.4 mg/kg bw/day       | General population | Systemic |
|                 | DNEL | Short term Dermal     | 6 mg/kg bw/day         | General population | Systemic |
|                 | DNEL | Long term Dermal      | 7 mg/kg bw/day         | Workers            | Systemic |
|                 | DNEL | Short term Dermal     | 11 mg/kg bw/day        | Workers            | Systemic |
|                 | DNEL | Long term Inhalation  | 12 mg/m <sup>3</sup>   | General population | Systemic |
|                 | DNEL | Long term Inhalation  | 35.7 mg/m <sup>3</sup> | General population | Local    |
|                 | DNEL | Long term Inhalation  | 48 mg/m <sup>3</sup>   | Workers            | Systemic |
|                 | DNEL | Short term Inhalation | 300 mg/m <sup>3</sup>  | General population | Local    |
|                 | DNEL | Short term Inhalation | 300 mg/m <sup>3</sup>  | General population | Systemic |
|                 | DNEL | Long term Inhalation  | 300 mg/m <sup>3</sup>  | Workers            | Local    |
|                 | DNEL | Short term Inhalation | 600 mg/m <sup>3</sup>  | Workers            | Local    |
|                 | DNEL | Short term Inhalation | 600 mg/m <sup>3</sup>  | Workers            | Systemic |
| ethyl acetate   | DNEL | Long term Oral        | 4.5 mg/kg bw/day       | General population | Systemic |
|                 | DNEL | Long term Dermal      | 37 mg/kg bw/day        | General population | Systemic |
|                 | DNEL | Long term Dermal      | 63 mg/kg bw/day        | Workers            | Systemic |
|                 | DNEL | Long term Inhalation  | 367 mg/m <sup>3</sup>  | General population | Local    |
|                 | DNEL | Long term Inhalation  | 367 mg/m <sup>3</sup>  | General population | Systemic |
|                 | DNEL | Short term Inhalation | 734 mg/m <sup>3</sup>  | General population | Local    |
|                 | DNEL | Short term Inhalation | 734 mg/m <sup>3</sup>  | General population | Systemic |

## SECTION 8: Exposure controls/personal protection

|            |      |                       |                          |                    |          |
|------------|------|-----------------------|--------------------------|--------------------|----------|
| acetone    | DNEL | Long term Inhalation  | 734 mg/m <sup>3</sup>    | Workers            | Local    |
|            | DNEL | Long term Inhalation  | 734 mg/m <sup>3</sup>    | Workers            | Systemic |
|            | DNEL | Short term Inhalation | 1468 mg/m <sup>3</sup>   | Workers            | Local    |
|            | DNEL | Short term Inhalation | 1468 mg/m <sup>3</sup>   | Workers            | Systemic |
|            | DNEL | Long term Oral        | 62 mg/kg bw/day          | General population | Systemic |
|            | DNEL | Long term Dermal      | 62 mg/kg bw/day          | General population | Systemic |
|            | DNEL | Long term Dermal      | 186 mg/kg bw/day         | Workers            | Systemic |
|            | DNEL | Long term Inhalation  | 200 mg/m <sup>3</sup>    | General population | Systemic |
| butan-1-ol | DNEL | Long term Inhalation  | 1210 mg/m <sup>3</sup>   | Workers            | Systemic |
|            | DNEL | Short term Inhalation | 2420 mg/m <sup>3</sup>   | Workers            | Local    |
|            | DNEL | Long term Oral        | 1.5625 mg/kg bw/day      | General population | Systemic |
|            | DNEL | Long term Dermal      | 3.125 mg/kg bw/day       | General population | Systemic |
|            | DNEL | Long term Inhalation  | 55.357 mg/m <sup>3</sup> | General population | Systemic |
|            | DNEL | Long term Inhalation  | 155 mg/m <sup>3</sup>    | General population | Local    |
|            | DNEL | Long term Inhalation  | 310 mg/m <sup>3</sup>    | Workers            | Local    |
|            |      |                       |                          |                    |          |

### PNECs

No PNECs available.

### 8.2 Exposure controls

#### **Appropriate engineering controls**

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

#### **Individual protection measures**

##### **Hygiene measures**

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

## SECTION 8: Exposure controls/personal protection

- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. Recommended : 1 - 4 hours (breakthrough time): Protective gloves made of nitrile rubber (material thickness of 0,4 mm); EN 374-5 Cat. III 4 - 8 hours (breakthrough time): Protective gloves made of Viton®/ butyl rubber (material thickness of 0,7 mm); EN388 Cat.II / EN374 Cat.III / EN374-2
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended : organic vapor (Type AX) and particulate filter
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

#### Appearance

- Physical state** : Gas. [Aerosol]
- Color** : Silver.
- Odor** : Benzene-like.
- Odor threshold** : Not available.
- Melting point/freezing point** : Not applicable.
- Initial boiling point and boiling range** : Not available.
- Flammability** : Highly flammable in the presence of the following materials or conditions: open flames, sparks and static discharge and heat.  
Flammable in the presence of the following materials or conditions: shocks and mechanical impacts.
- Lower and upper explosion limit** : Lower: 3%  
Upper: 18.6%
- Flash point** : Closed cup: Not applicable.
- Auto-ignition temperature** : Not applicable.
- Decomposition temperature** : Not available.

Zinc Spray bright grade

## SECTION 9: Physical and chemical properties

|  |  |
|--|--|
| pH   | : Not applicable.                      |
| Viscosity                                  | : Not applicable.                      |
| Not available.                             |  |
| Solubility in water                        | : Not available.                       |
| Partition coefficient: n-octanol/<br>water | : Not applicable.                      |
| Vapor pressure                             | : Not available.                       |
| Relative density                           | : Not applicable.                      |
| Density                                    | : 0.81 g/cm <sup>3</sup> [20°C (68°F)] |
| Vapor density                              | : Not available.                       |
| <b><u>Particle characteristics</u></b>     |  |
| Median particle size                       | : Not applicable.                      |

### 9.2 Other information

#### 9.2.1 Information with regard to physical hazard classes

|                      |   |
|----------------------|---|
| Fire point           | : >200°C  |
| Heat of combustion   | : 31.78 kJ/g  |
| Explosive properties | : Highly explosive in the presence of the following materials or conditions: open flames, sparks and static discharge and heat.<br>Explosive in the presence of the following materials or conditions: shocks and mechanical impacts. |
| Oxidizing properties | : Not available.  |

#### **Aerosol product**

|                 |         |
|-----------------|---------|
| Type of aerosol | : Spray |
|-----------------|---------|

#### 9.2.2 Other safety characteristics

|                     |       |
|---------------------|-------|
| Miscible with water | : No. |
|---------------------|-------|

## SECTION 10: Stability and reactivity

|   |  |
|---|--|
| 10.1 Reactivity                         | : No specific test data related to reactivity available for this product or its ingredients. |
| 10.2 Chemical stability                 | : The product is stable.   |
| 10.3 Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur.            |
| 10.4 Conditions to avoid                | : Avoid all possible sources of ignition (spark or flame).                                   |
| 10.5 Incompatible materials             | : No specific data.  |
| 10.6 Hazardous decomposition products   | : Forms explosive mixtures with air.   |

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Acute toxicity**

Zinc Spray bright grade

## SECTION 11: Toxicological information

| Product/ingredient name | Result                | Species            | Dose                    | Exposure |
|-------------------------|-----------------------|--------------------|-------------------------|----------|
| dimethyl ether          | LC50 Inhalation Gas.  | Rat                | 164000 ppm              | 4 hours  |
|                         | LC50 Inhalation Vapor | Rat                | 309 g/m <sup>3</sup>    | 4 hours  |
| xylene                  | LD50 Oral             | Mouse              | 2119 mg/kg              | -        |
|                         | LD50 Oral             | Rat                | 4300 mg/kg              | -        |
|                         | LD50 Oral             | Rat                | 4300 mg/kg              | -        |
|                         | LDLo Oral             | Human              | 50 mg/kg                | -        |
|                         | LDLo Oral             | Human              | 50 mg/kg                | -        |
|                         | TDLo Dermal           | Mouse              | 727.3 uL/kg             | -        |
|                         | TDLo Dermal           | Rabbit             | 4300 mg/kg              | -        |
|                         | LD50 Oral             | Rat                | 10768 mg/kg             | -        |
| n-butyl acetate         | LC50 Inhalation Vapor | Rat - Male, Female | >21 mg/l                | 4 hours  |
|                         | LD50 Dermal           | Rabbit             | >17600 mg/kg            | -        |
|                         | LD50 Oral             | Rat                | 5620 mg/kg              | -        |
| ethyl acetate           | LD50 Oral             | Rat                | 5800 mg/kg              | -        |
| acetone                 | LD50 Oral             | Rat                | 24000 mg/m <sup>3</sup> | 4 hours  |
| butan-1-ol              | LC50 Inhalation Vapor | Rat                | 3400 mg/kg              | -        |
|                         | LD50 Dermal           | Rabbit             | 790 mg/kg               | -        |
|                         | LD50 Oral             | Rat                |                         |          |

**Conclusion/Summary** : Not available.

### Acute toxicity estimates

| Product/ingredient name   | Oral (mg/kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapors) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|---|--------------|----------------|--------------------------|----------------------------|-------------------------------------|
| Zinc Spray bright grade   | 41149.1      | 15074.3        | N/A                      | 162.8                      | N/A                                 |
| dimethyl ether  | N/A          | N/A            | 164000                   | 309                        | N/A                                 |
| xylene  | N/A          | 1100           | N/A                      | 11                         | N/A                                 |
| n-butyl acetate   | 10768        | N/A            | N/A                      | N/A                        | N/A                                 |
| ethyl acetate   | 5620         | N/A            | N/A                      | N/A                        | N/A                                 |
| acetone   | 5800         | N/A            | N/A                      | N/A                        | N/A                                 |
| butan-1-ol  | 790          | 3400           | N/A                      | 24                         | N/A                                 |
| Quaternary ammonium compounds, coco alkylethyldimethyl, Et sulfates | 500          | 300            | N/A                      | N/A                        | N/A                                 |

### Irritation/Corrosion

| Product/ingredient name | Result                   | Species | Score | Exposure      | Observation |
|-------------------------|--------------------------|---------|-------|---------------|-------------|
| xylene                  | Eyes - Mild irritant     | Rabbit  | -     | 87 mg         | -           |
|                         | Eyes - Severe irritant   | Rabbit  | -     | 24 hours 5 mg | -           |
|                         | Skin - Mild irritant     | Rat     | -     | 8 hours 60 uL | -           |
|                         | Skin - Moderate irritant | Rabbit  | -     | 100 %         | -           |

Zinc Spray bright grade

## SECTION 11: Toxicological information

|                                    |                          |        |   |                   |   |
|------------------------------------|--------------------------|--------|---|-------------------|---|
| zinc powder zinc dust (stabilised) | Skin - Moderate irritant | Rabbit | - | 24 hours 500 mg   | - |
|                                    | Skin - Mild irritant     | Human  | - | 72 hours 300 ug l | - |
|                                    | Eyes - Mild irritant     | Human  | - | 186300 ppm        | - |
|                                    | Eyes - Mild irritant     | Rabbit | - | 10 uL             | - |
|                                    | Eyes - Moderate irritant | Rabbit | - | 24 hours 20 mg    | - |
|                                    | Eyes - Severe irritant   | Rabbit | - | 20 mg             | - |
|                                    | Skin - Mild irritant     | Rabbit | - | 395 mg            | - |
|                                    | Skin - Mild irritant     | Rabbit | - | 24 hours 500 mg   | - |
|                                    | Eyes - Severe irritant   | Rabbit | - | 0.005 MI          | - |
|                                    | Eyes - Severe irritant   | Rabbit | - | 24 hours 2 mg     | - |
| butan-1-ol                         | Skin - Moderate irritant | Rabbit | - | 24 hours 20 mg    | - |

**Conclusion/Summary** : Not available.

### Sensitization

**Conclusion/Summary** : Not available.

### Mutagenicity

**Conclusion/Summary** : Not available.

### Carcinogenicity

**Conclusion/Summary** : Not available.

### Reproductive toxicity

**Conclusion/Summary** : Not available.

### Teratogenicity

**Conclusion/Summary** : Not available.

### Specific target organ toxicity (single exposure)

| Product/ingredient name | Category   | Route of exposure | Target organs                |
|-------------------------|------------|-------------------|------------------------------|
| xylene                  | Category 3 | -                 | Respiratory tract irritation |
| n-butyl acetate         | Category 3 | -                 | Narcotic effects             |
| ethyl acetate           | Category 3 | -                 | Narcotic effects             |
| acetone                 | Category 3 | -                 | Narcotic effects             |
| butan-1-ol              | Category 3 | -                 | Respiratory tract irritation |
|                         | Category 3 | -                 | Narcotic effects             |

### Specific target organ toxicity (repeated exposure)

| Product/ingredient name | Category   | Route of exposure | Target organs |
|-------------------------|------------|-------------------|---------------|
| xylene                  | Category 2 | -                 | -             |

Zinc Spray bright grade

## SECTION 11: Toxicological information

### Aspiration hazard

| Product/ingredient name  | Result                         |
|--|--------------------------------|
| xylene   | ASPIRATION HAZARD - Category 1 |
| Hydrocarbons, C10-13, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics | ASPIRATION HAZARD - Category 1 |

**Information on the likely routes of exposure** : Not available.

### Potential acute health effects

**Eye contact** : Causes serious eye irritation.  
**Inhalation** : No known significant effects or critical hazards.  
**Skin contact** : Causes skin irritation.  
**Ingestion** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness  
**Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing  
**Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
**Ingestion** : No specific data.

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

**Potential immediate effects** : Not available.  
**Potential delayed effects** : Not available.

#### Long term exposure

**Potential immediate effects** : Not available.  
**Potential delayed effects** : Not available.

### Potential chronic health effects

Not available.

**Conclusion/Summary** : Not available.  
**General** : No known significant effects or critical hazards.  
**Carcinogenicity** : No known significant effects or critical hazards.  
**Mutagenicity** : No known significant effects or critical hazards.  
**Teratogenicity** : No known significant effects or critical hazards.  
**Developmental effects** : No known significant effects or critical hazards.  
**Fertility effects** : No known significant effects or critical hazards.

## 11.2 Information on other hazards

### 11.2.1 Endocrine disrupting properties

Not available.

### 11.2.2 Other information



Zinc Spray bright grade

## SECTION 11: Toxicological information

Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

| Product/ingredient name              | Result                              | Species   | Exposure |
|--------------------------------------|-------------------------------------|---|----------|
| xylene                               | Acute EC50 90 mg/l Fresh water      | Crustaceans - <i>Cypris subglobosa</i>  | 48 hours |
|                                      | Acute LC50 8.5 ppm Marine water     | Crustaceans - <i>Palaemonetes pugio</i> - Adult                               | 48 hours |
|                                      | Acute LC50 8500 µg/l Marine water   | Crustaceans - <i>Palaemonetes pugio</i>                                       | 48 hours |
|                                      | Acute LC50 16940 µg/l Fresh water   | Fish - <i>Carassius auratus</i>   | 96 hours |
|                                      | Acute LC50 15700 µg/l Fresh water   | Fish - <i>Lepomis macrochirus</i> - Juvenile (Fledgling, Hatchling, Weanling) | 96 hours |
|                                      | Acute LC50 20870 µg/l Fresh water   | Fish - <i>Lepomis macrochirus</i>   | 96 hours |
|                                      | Acute LC50 19000 µg/l Fresh water   | Fish - <i>Lepomis macrochirus</i>   | 96 hours |
|                                      | Acute LC50 13400 µg/l Fresh water   | Fish - <i>Pimephales promelas</i>   | 96 hours |
|                                      | Acute EC50 10000 µg/l Fresh water   | Aquatic plants - <i>Lemna minor</i>   | 4 days   |
|                                      | Acute IC50 65 µg/l Marine water     | Algae - <i>Nitzschia closterium</i> - Exponential growth phase                | 4 days   |
| Zinc powder - zinc dust (stabilized) | Acute LC50 65 µg/l Fresh water      | Crustaceans - <i>Ceriodaphnia dubia</i> - Neonate                             | 48 hours |
|                                      | Acute LC50 68 µg/l Fresh water      | Daphnia - <i>Daphnia magna</i>  | 48 hours |
|                                      | Acute LC50 12.21 µg/l Marine water  | Fish - <i>Periophthalmus waltoni</i> - Adult                                  | 96 hours |
|                                      | Chronic EC10 59.2 µg/l Fresh water  | Daphnia - <i>Daphnia magna</i>  | 21 days  |
|                                      | Chronic NOEC 0.25 mg/l Marine water | Algae - <i>Ulva pertusa</i>   | 96 hours |
|                                      | Chronic NOEC 9 mg/l Fresh water     | Aquatic plants - <i>Ceratophyllum demersum</i>                                | 3 days   |
|                                      | Chronic NOEC 178 µg/l Marine water  | Crustaceans - <i>Palaemon elegans</i>   | 21 days  |
|                                      | Chronic NOEC 2.6 µg/l Fresh water   | Fish - <i>Cyprinus carpio</i>   | 4 weeks  |
|                                      | Acute LC50 32 mg/l Marine water     | Crustaceans - <i>Artemia salina</i>   | 48 hours |
|                                      | Acute LC50 62000 µg/l Fresh water   | Fish - <i>Danio rerio</i>   | 96 hours |
| n-butyl acetate                      | Acute LC50 100 ppm Fresh water      | Fish - <i>Lepomis macrochirus</i>   | 96 hours |
|                                      | Acute LC50 18000 µg/l Fresh water   | Fish - <i>Pimephales promelas</i>   | 96 hours |
|                                      | Acute EC50 2500000 µg/l Fresh water | Algae - <i>Selenastrum sp.</i>  | 96 hours |
| ethyl acetate                        | Acute LC50 750000 µg/l Fresh water  | Crustaceans - <i>Gammarus pulex</i>   | 48 hours |

Zinc Spray bright grade

## SECTION 12: Ecological information

|         |                                      |   |          |
|---------|--------------------------------------|---|----------|
| acetone | Acute LC50 154000 µg/l Fresh water   | Daphnia - <i>Daphnia cucullata</i>  | 48 hours |
|         | Acute LC50 212500 µg/l Fresh water   | Fish - <i>Heteropneustes fossilis</i>   | 96 hours |
|         | Chronic NOEC 2.4 mg/l Fresh water    | Daphnia - <i>Daphnia magna</i>  | 21 days  |
|         | Chronic NOEC 75.6 mg/l Fresh water   | Fish - <i>Pimephales promelas</i> - Embryo                                      | 32 days  |
|         | Acute EC50 11493300 µg/l Fresh water | Algae - <i>Navicula seminulum</i>   | 96 hours |
|         | Acute EC50 11727900 µg/l Fresh water | Algae - <i>Navicula seminulum</i>   | 96 hours |
|         | Acute EC50 7200000 µg/l Fresh water  | Algae - <i>Selenastrum sp.</i>  | 96 hours |
|         | Acute EC50 20.565 mg/l Marine water  | Algae - <i>Ulva pertusa</i>   | 96 hours |
|         | Acute EC50 23.5 mg/l Fresh water     | Daphnia - <i>Daphnia magna</i>  | 48 hours |
|         | Acute LC50 4.42589 ml/L Marine water | Crustaceans - <i>Acartia tonsa</i> - Copepodid                                  | 48 hours |
|         | Acute LC50 7550000 µg/l Fresh water  | Crustaceans - <i>Asellus aquaticus</i>  | 48 hours |
|         | Acute LC50 8098000 µg/l Fresh water  | Crustaceans - <i>Ceriodaphnia dubia</i> - Neonate                               | 48 hours |
|         | Acute LC50 11.26487 ml/L Fresh water | Crustaceans - <i>Gammarus pulex</i> - Juvenile (Fledgling, Hatchling, Weanling) | 48 hours |
|         | Acute LC50 6000000 µg/l Fresh water  | Crustaceans - <i>Gammarus pulex</i>   | 48 hours |
|         | Acute LC50 7460000 µg/l Fresh water  | Daphnia - <i>Daphnia cucullata</i>  | 48 hours |
|         | Acute LC50 7810000 µg/l Fresh water  | Daphnia - <i>Daphnia cucullata</i>  | 48 hours |
|         | Acute LC50 10000 µg/l Fresh water    | Daphnia - <i>Daphnia magna</i>  | 48 hours |
|         | Acute LC50 8800000 µg/l Fresh water  | Daphnia - <i>Daphnia pulex</i>  | 48 hours |
|         | Acute LC50 8000 ppm Fresh water      | Fish - <i>Oncorhynchus mykiss</i>   | 96 hours |
|         | Acute LC50 7280000 µg/l Fresh water  | Fish - <i>Pimephales promelas</i>   | 96 hours |
|         | Acute LC50 8120000 µg/l Fresh water  | Fish - <i>Pimephales promelas</i>   | 96 hours |
|         | Acute LC50 6210000 µg/l Fresh water  | Fish - <i>Pimephales promelas</i>   | 96 hours |
|         | Acute LC50 5600 ppm Fresh water      | Fish - <i>Poecilia reticulata</i>   | 96 hours |
|         | Chronic NOEC 0.5 ml/L Marine water   | Algae - <i>Karenia brevis</i>   | 96 hours |
|         | Chronic NOEC 100 µl/L Marine water   | Algae - <i>Skeletonema costatum</i>   | 72 hours |
|         | Chronic NOEC 100 µl/L Marine water   | Algae - <i>Skeletonema costatum</i>   | 96 hours |
|         | Chronic NOEC 4.95 mg/l Marine water  | Algae - <i>Ulva pertusa</i>   | 96 hours |
|         | Chronic NOEC 0.016 ml/L Fresh water  | Crustaceans - <i>Daphniidae</i>   | 21 days  |
|         | Chronic NOEC 0.1 ml/L Fresh water    | Daphnia - <i>Daphnia magna</i> - Neonate  | 21 days  |
|         | Chronic NOEC 5 µg/l Marine water     | Fish - <i>Gasterosteus aculeatus</i> - Larvae                                   | 42 days  |

Zinc Spray bright grade

## SECTION 12: Ecological information

|            |                                     |                                   |          |
|------------|-------------------------------------|-----------------------------------|----------|
| butan-1-ol | Acute EC50 1983 mg/l Fresh water    | Daphnia - <i>Daphnia magna</i>    | 48 hours |
|            | Acute LC50 1730000 µg/l Fresh water | Fish - <i>Pimephales promelas</i> | 96 hours |

**Conclusion/Summary** : Not available.

### 12.2 Persistence and degradability

**Conclusion/Summary** : Not available.

### 12.3 Bioaccumulative potential

| Product/ingredient name | LogP <sub>ow</sub> | BCF         | Potential |
|-------------------------|--------------------|-------------|-----------|
| dimethyl ether          | 0.07               | -           | Low       |
| xylene                  | 3.12               | 8.1 to 25.9 | Low       |
| n-butyl acetate         | 2.3                | -           | Low       |
| ethyl acetate           | 0.68               | 30          | Low       |
| acetone                 | -0.23              | -           | Low       |
| butan-1-ol              | 1                  | -           | Low       |

### 12.4 Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Not available.

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

### 12.6 Endocrine disrupting properties

Not available.

### 12.7 Other adverse effects

No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : Yes.

#### European waste catalogue (EWC)

| Waste code | Waste designation   |
|------------|---|
| 16 05 04*  | gases in pressure containers (including halons) containing hazardous substances |

Zinc Spray bright grade

## SECTION 13: Disposal considerations








### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

| Type of packaging | European waste catalogue (EWC)  |
|-------------------|---|
| Can               | 15 01 10*<br>packaging containing residues of or contaminated by hazardous substances |

**Special precautions** : This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

## SECTION 14: Transport information

|  | ADR/RID  | ADN  | IMDG  | IATA  |
|--|--|--|---|---|
| <b>14.1 UN number or ID number</b>     | UN1950   | UN1950   | UN1950  | UN1950  |
| <b>14.2 UN proper shipping name</b>    | AEROSOLS (dimethyl ether, xylene)  | AEROSOLS (dimethyl ether, xylene)  | AEROSOLS (dimethyl ether, xylene)   | Aerosols, flammable (dimethyl ether, xylene)  |
| <b>14.3 Transport hazard class(es)</b> | 2<br>  | 2<br>  | 2.1<br>  | 2.1<br> |
| <b>14.4 Packing group</b>              | -  | -  | -   | -   |
| <b>14.5 Environmental hazards</b>      | Yes.   | Yes.   | Yes.  | Yes. The environmentally hazardous substance mark is not required.                          |

### Additional information

|                |  |
|----------------|--|
| <b>ADR/RID</b> | : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.<br><b>Limited quantity</b> 1 L<br><b>Special provisions</b> 190, 327, 625, 344<br><b>Tunnel code (D)</b><br><b>ADR Classification Code:</b> 5F  |
| <b>ADN</b>     | : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.<br><b>Special provisions</b> 190, 327, 625, 344   |
| <b>IMDG</b>    | : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.<br><b>Emergency schedules</b> F-D, S-U<br><b>Special provisions</b> 63, 190, 277, 327, 344, 381, 959   |
| <b>IATA</b>    | : The environmentally hazardous substance mark may appear if required by other transportation regulations.<br><b>Quantity limitation</b> Passenger and Cargo Aircraft: 75 kg. Packaging instructions: 203. Cargo Aircraft Only: 150 kg. Packaging instructions: 203. Limited Quantities - Passenger Aircraft: 30 kg. Packaging instructions: Y203.<br><b>Special provisions</b> A145, A167, A802 |

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Zinc Spray bright grade

SECTION 14: Transport information

14.7 Maritime transport in bulk according to IMO instruments : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

No listed substance

Other EU regulations

Industrial emissions (integrated pollution prevention and control) - Air : Listed

Industrial emissions (integrated pollution prevention and control) - Water : Listed

Explosive precursors : Not applicable.

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Aerosol dispensers :

3



Extremely flammable

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

| Category  |
|-----------|
| P3a<br>E2 |

Annex VIIA - Labelling for Contents

Identification

Concentration

Zinc Spray bright grade

## SECTION 15: Regulatory information

aliphatic hydrocarbons

5% or over but less than 15%

**VOC content** : 82.2 %

**VOC (g/L)** : 669.5

### National regulations

| Product/ingredient name | List name           | Name on list | Classification | Notes |
|-------------------------|---------------------|--------------|----------------|-------|
| acetone                 | DFG MAC-values list | Acetone      | RE2            | -     |

**Storage class (TRGS 510)** : 2B

### Hazardous incident ordinance

This product is controlled under the Germany Hazardous Incident Ordinance.

### Danger criteria

| Category | Reference number |
|----------|------------------|
| P3a      | 1.2.3.1          |
| E2       | 1.3.2            |

**Hazard class for water** : 2

**Technical instruction on air quality control** : TA-Luft Number 5.2.5: 63-100%  
TA-Luft Class III - Number 5.2.2: 2.5-10%  
TA-Luft Number 5.2.1: 1.1-10.2%

### International regulations

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

#### UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

### Inventory list

|                                |   |
|--------------------------------|---|
| <b>Australia</b>               | : All components are listed or exempted.  |
| <b>Canada</b>                  | : Not determined.   |
| <b>China</b>                   | : All components are listed or exempted.  |
| <b>Eurasian Economic Union</b> | : <b>Russian Federation inventory</b> : Not determined.   |
| <b>Japan</b>                   | : <b>Japan inventory (CSCL)</b> : All components are listed or exempted.<br><b>Japan inventory (ISHL)</b> : Not determined. |
| <b>New Zealand</b>             | : Not determined.   |
| <b>Philippines</b>             | : Not determined.   |
| <b>Republic of Korea</b>       | : Not determined.   |
| <b>Taiwan</b>                  | : Not determined.   |
| <b>Thailand</b>                | : Not determined.   |
| <b>Turkey</b>                  | : Not determined.   |
| <b>United States</b>           | : All components are active or exempted.  |
| <b>Viet Nam</b>                | : Not determined.   |

**15.2 Chemical Safety Assessment** : This product contains substances for which Chemical Safety Assessments are still required.

Zinc Spray bright grade

## SECTION 16: Other information

Indicates information that has changed from previously issued version.

### Abbreviations and acronyms

: ATE = Acute Toxicity Estimate  
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
 DMEL = Derived Minimal Effect Level  
 DNEL = Derived No Effect Level  
 EUH statement = CLP-specific Hazard statement  
 N/A = Not available  
 PBT = Persistent, Bioaccumulative and Toxic  
 PNEC = Predicted No Effect Concentration  
 RRN = REACH Registration Number  
 SGG = Segregation Group  
 vPvB = Very Persistent and Very Bioaccumulative

### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

| Classification  | Justification   |
|---|---|
| Aerosol 1, H222, H229<br>Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>Aquatic Chronic 2, H411 | On basis of test data<br>Calculation method<br>Calculation method<br>Calculation method |

### Full text of abbreviated H statements

|                                |   |
|--------------------------------|---|
| H220<br>H222, H229             | Extremely flammable gas.<br>Extremely flammable aerosol. Pressurized container: may burst if heated.  |
| H225<br>H226<br>H228           | Highly flammable liquid and vapor.<br>Flammable liquid and vapor.<br>Flammable solid.   |
| H261<br>H280<br>H302           | In contact with water releases flammable gas.<br>Contains gas under pressure; may explode if heated.<br>Harmful if swallowed.   |
| H304<br>H311<br>H312           | May be fatal if swallowed and enters airways.<br>Toxic in contact with skin.<br>Harmful in contact with skin.   |
| H314<br>H315<br>H318           | Causes severe skin burns and eye damage.<br>Causes skin irritation.<br>Causes serious eye damage.   |
| H319<br>H332<br>H335           | Causes serious eye irritation.<br>Harmful if inhaled.<br>May cause respiratory irritation.  |
| H336<br>H373                   | May cause drowsiness or dizziness.<br>May cause damage to organs through prolonged or repeated exposure.  |
| H400<br>H410<br>H411<br>EUH066 | Very toxic to aquatic life.<br>Very toxic to aquatic life with long lasting effects.<br>Toxic to aquatic life with long lasting effects.<br>Repeated exposure may cause skin dryness or cracking. |

### Full text of classifications [CLP/GHS]

|   |   |
|---|---|
| Acute Tox. 3<br>Acute Tox. 4<br>Aerosol 1<br>Aquatic Acute 1<br>Aquatic Chronic 1<br>Aquatic Chronic 2<br>Asp. Tox. 1<br>Eye Dam. 1<br>Eye Irrit. 2<br>Flam. Gas 1A<br>Flam. Liq. 2<br>Flam. Liq. 3 | ACUTE TOXICITY - Category 3<br>ACUTE TOXICITY - Category 4<br>AEROSOLS - Category 1<br>AQUATIC HAZARD (ACUTE) - Category 1<br>AQUATIC HAZARD (LONG-TERM) - Category 1<br>AQUATIC HAZARD (LONG-TERM) - Category 2<br>ASPIRATION HAZARD - Category 1<br>SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1<br>SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2<br>FLAMMABLE GASES - Category 1A<br>FLAMMABLE LIQUIDS - Category 2<br>FLAMMABLE LIQUIDS - Category 3 |
|---|---|

Zinc Spray bright grade

SECTION 16: Other information

|                    |   |
|--------------------|---|
| Flam. Sol. 1       | FLAMMABLE SOLIDS - Category 1   |
| Press. Gas (Comp.) | GASES UNDER PRESSURE - Compressed gas   |
| Skin Corr. 1C      | SKIN CORROSION/IRRITATION - Category 1C   |
| Skin Irrit. 2      | SKIN CORROSION/IRRITATION - Category 2  |
| STOT RE 2          | SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2                         |
| STOT SE 3          | SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 3                           |
| Water-react. 2     | SUBSTANCES AND MIXTURES, WHICH IN CONTACT WITH WATER, EMIT FLAMMABLE GASES - Category 2 |

Date of printing : 5/14/2025

Date of issue/ Date of revision : 5/12/2025

Date of previous issue : 2/19/2025

Version : 4.4

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.