SAFETY DATA SHEET



Multi-Flex Comp. A

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : Multi-Flex Comp. A UFI : JGK0-005D-N00K-2U8K

Product code : 133601 Color : White.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Adhesives-Sealants

Elasticizer

1.3 Details of the supplier of the safety data sheet

WEICON GmbH & Co. KG Königsberger Str. 255 48157 Münster Germany

Phone: +49 251 93220 Fax: +49(0)251 / 9322 - 244 Internet: www.weicon.de

e-mail address of person responsible for this SDS

: msds@weicon.de

1.4 Emergency telephone number

Telephone number : EMERGENCY CONTACT – UK, UAE, South Africa (24h): Tel: ++44 1865 407333

(English)

TRANSPORT EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel: ++44

1865 407333 (English)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Eye Dam. 1, H318

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



Signal word : Danger

Hazard statements : H318 - Causes serious eye damage.

Precautionary statements

Date of issue/Date of revision : 10/20/2022 Date of previous issue : 10/19/2022 Version : 2.04 1/16

Multi-Flex Comp. A

SECTION 2: Hazards identification

: P280 - Wear eye or face protection. Prevention

: P305 + P351 + P338, P310 - IF IN EYES: Rinse cautiously with water for several Response

minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or doctor.

Storage : Not applicable. : Not applicable. Disposal

Hazardous ingredients : N-(3-(trimethoxysilyl)propyl)ethylenediamine

Supplemental label : Contains N-(3-(trimethoxysilyl)propyl)ethylenediamine, trimethoxyvinylsilane and

dioctylbis(pentane-2,4-dionato-O,O')tin. May produce an allergic reaction. elements

: Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

: This mixture does not contain any substances that are assessed to be a PBT or a

Other hazards which do not result in classification : None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
N-(3-(trimethoxysilyl)propyl) ethylenediamine	REACH #: 01-2119970215-39 EC: 217-164-6 CAS: 1760-24-3	≤5	Eye Dam. 1, H318 Skin Sens. 1B, H317 STOT SE 3, H335	-	[1]
3-Aminopropyltrimethoxysilane	REACH #: 01-2119510159-45 EC: 237-511-5 CAS: 13822-56-5	≤3	Skin Irrit. 2, H315 Eye Dam. 1, H318	Skin Irrit. 2, H315: C ≥ 10% Eye Dam. 1, H318: C ≥ 10% Eye Irrit. 2, H319: 5% ≤ C < 10%	[1]
trimethoxyvinylsilane	REACH #: 01-2119513215-52 EC: 220-449-8 CAS: 2768-02-7	<1	Flam. Liq. 3, H226 Acute Tox. 4, H332 Skin Sens. 1B, H317	ATE [Inhalation (vapours)] = 11 mg/	[1]
dioctylbis(pentane- 2,4-dionato-O,O')tin	REACH #: 01-0000020199-67 EC: 483-270-6 CAS: 54068-28-9	≤1	Skin Sens. 1, H317 STOT SE 2, H371	-	[1]
Bis (2,2,6,6-tetramethyl- 4-piperidyl) sebacate	REACH #: 01-2119537297-32 EC: 258-207-9 CAS: 52829-07-9	≤0.3	Eye Dam. 1, H318 Aquatic Acute 1, H400 Aquatic Chronic 2, H411	M [Acute] = 1	[1]

Date of issue/Date of revision : 10/20/2022 2/16 : 10/19/2022 Version: 2.04 Date of previous issue

1	······································
	Multi-Flex Comp. A
	SECTION 3: Composition/information on ingredients
_	See Section 16 for the full text of the H statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact

: Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.

Inhalation

: Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Skin contact

: Get medical attention immediately. Call a poison center or physician. Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact: Adverse symptoms may include the following:

pain watering redness

Inhalation : No specific data.

Date of issue/Date of revision : 10/20/2022 Date of previous issue : 10/19/2022 Version : 2.04 3/16

Multi-Flex Comp. A

SECTION 4: First aid measures

Skin contact : Adverse symptoms may include the following:

> pain or irritation redness

blistering may occur

Ingestion : Adverse symptoms may include the following:

stomach pains

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous combustion

products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides

5.3 Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without

suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Date of issue/Date of revision : 10/20/2022 : 10/19/2022 Version : 2.04 4/16 Date of previous issue

SECTION 6: Accidental release measures

6.3 Methods and materials for containment and cleaning up

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

6.4 Reference to other sections

: See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

7.1 Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific : Not available.

solutions

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
methanol	[Air contaminant - Curing] TRGS 900 OEL (Germany, 7/2021). Absorbed through skin. TWA: 130 mg/m³ 8 hours. PEAK: 260 mg/m³ 15 minutes. TWA: 100 ppm 8 hours. PEAK: 200 ppm 15 minutes. DFG MAC-values list (Germany, 10/2021). Absorbed through skin. TWA: 100 ppm 8 hours. PEAK: 200 ppm, 4 times per shift, 15 minutes. TWA: 130 mg/m³ 8 hours. PEAK: 260 mg/m³, 4 times per shift, 15 minutes.

Date of issue/Date of revision : 10/20/2022 Date of previous issue : 10/19/2022 Version : 2.04 5/16

SECTION 8: Exposure controls/personal protection

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
N-(3-(trimethoxysilyl)propyl) ethylenediamine	DNEL	Long term Oral	2.5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	2.5 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	5 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	5 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	8.7 mg/m³	General population	Systemic
	DNEL	Short term Dermal	17 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	35.3 mg/m³	Workers	Systemic
	DNEL	Long term Inhalation	0.1 mg/m³	General population	Local
	DNEL	Long term Inhalation	0.6 mg/m³	Workers	Local
	DNEL	Short term Inhalation	4 mg/m³	General population	Local
	DNEL	Short term Inhalation	5.36 mg/m³	Workers	Local
	DNEL	Short term Inhalation	50 mg/m³	General population	Systemic
	DNEL	Short term Inhalation	260 mg/m³	Workers	Systemic
3-Aminopropyltrimethoxysilane	DNEL	Long term Oral	5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	1 mg/kg bw/day	Workers	Systemic
	20/2022		. 10/10/2		roion : 2.04 6/46

Date of issue/Date of revision : 10/20/2022 Date of previous issue : 10/19/2022 Version : 2.04 6/16

SECTION 8: Exposure controls/personal protection

<u> </u>					1
	DNEL	Long term Inhalation	1.7 mg/m³	General population	Systemic
	DNEL	Long term Inhalation	7.1 mg/m³	Workers	Systemic
	DNEL	Short term Inhalation	50 mg/m³	General population	Systemic
	DNEL	Short term Inhalation	260 mg/m ³	Workers	Systemic
trimethoxyvinylsilane	DNEL	Long term Oral	0.3 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.3 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.69 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.04 mg/m³	General population	Systemic
	DNEL	Long term Inhalation	4.9 mg/m³	Workers	Systemic
	DNEL	Short term Dermal	26.9 mg/ kg bw/day	General population	Systemic
	DNEL	Short term Inhalation	93.4 mg/m³	General population	Systemic
dioctylbis(pentane-2,4-dionato-O,O') tin	DNEL	Long term Dermal	0.07 mg/ kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	84 mg/m³	Workers	Systemic
Bis (2,2,6,6-tetramethyl-4-piperidyl) sebacate	DNEL	Long term Dermal	0.8 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	1.6 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	2.82 mg/m³	Workers	Systemic
	DNEL	Long term Oral	0.18 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	0.31 mg/m³	General population	Systemic
	DNEL	Long term Inhalation	1.27 mg/m³	Workers	Systemic

PNECs

No PNECs available.

8.2 Exposure controls

Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Date of issue/Date of revision : 10/20/2022 Date of previous issue : 10/19/2022 Version : 2.04 7/16

SECTION 8: Exposure controls/personal protection

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. Recommended: 1 - 4 hours (breakthrough time): nitrile rubber; 4 - 8 hours (breakthrough time): Viton®/butyl rubber

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: organic vapor (Type AX) and particulate filter

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid. Color : White.

Odor Characteristic. **Odor threshold** : Not available. Melting point/freezing point : Not available. Initial boiling point and : Not available.

boiling range

Flammability : Slightly flammable in the presence of the following materials or conditions: heat.

Upper/lower flammability or

explosive limits

: Not available.

: Closed cup: >93.3°C (>199.9°F) Flash point

Auto-ignition temperature : Not applicable. : Not available. **Decomposition temperature** Not applicable. рH **Viscosity** Not available.

Solubility(ies)

Date of issue/Date of revision : 10/20/2022 : 10/19/2022 Version : 2.04 8/16 Date of previous issue

Multi-Flex Comp. A

SECTION 9: Physical and chemical properties

Not available.

Solubility in water : Not available.

Miscible with water : No.

Partition coefficient: n-octanol/ : Not applicable.

water

Vapor pressure :

	Vapor Pressure at 20°C		ure at 20°C	\ \	Vapor pres		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method	
trimethoxyvinylsilane	8.93	1.2	EU A.4				
3-Aminopropyltrimethoxysilane	0.14	0.019					
dioctylbis(pentane-2,4-dionato-O, O')tin	0.05	0.0067	OECD 104				
Bis (2,2,6,6-tetramethyl- 4-piperidyl) sebacate	0	0					

Relative density : Not available.

Density : 1.21 g/cm³ [20°C (68°F)]

Vapor density : Not available.

Explosive properties : Not available.

Oxidizing properties : Not available.

Particle characteristics

Median particle size : Not applicable.

9.2 Other information

SAPT : Not available.
SAPT : Not available.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : No specific data.

10.6 Hazardous : The product hydrolyses quickly in the presence of water to: methanol

decomposition products

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Date of issue/Date of revision : 10/20/2022 Date of previous issue : 10/19/2022 Version : 2.04 9/16

Multi-Flex Comp. A

SECTION 11: Toxicological information

Product/ingredient name	Result	Species	Dose	Exposure
N-(3-(trimethoxysilyl)propyl) ethylenediamine	LD50 Oral	Rat	2413 mg/kg	-
Bis (2,2,6,6-tetramethyl-4-piperidyl) sebacate	LC50 Inhalation Dusts and mists	Rat	500 mg/m³	4 hours

Conclusion/Summary: Not available.

Acute toxicity estimates

	ATE value
Not available.	

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
N-(3-(trimethoxysilyl)propyl) ethylenediamine	Eyes - Severe irritant	Rabbit	-	15 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-

Conclusion/Summary: Not available.

Sensitization

Product/ingredient name	Route of exposure	Species	Result
Flex M Super Fast Comp. A	skin	Guinea pig	Not sensitizing

Conclusion/Summary: Not available.

Mutagenicity

Conclusion/Summary: Not available.

Carcinogenicity

Conclusion/Summary: Not available.

Reproductive toxicity

Conclusion/Summary: Not available.

Teratogenicity

Conclusion/Summary: Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
N-(3-(trimethoxysilyl)propyl)ethylenediamine	Category 3	-	Respiratory tract irritation
dioctylbis(pentane-2,4-dionato-O,O')tin	Category 2	-	-

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely routes of exposure

: Not available.

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation : No known significant effects or critical hazards.Skin contact : No known significant effects or critical hazards.

Date of issue/Date of revision : 10/20/2022 Date of previous issue : 10/19/2022 Version : 2.04 10/16

Multi-Flex Comp. A

SECTION 11: Toxicological information

Ingestion: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:

pain watering redness

Inhalation : No specific data.

Skin contact: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

Ingestion: Adverse symptoms may include the following:

stomach pains

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate

: Not available.

effects

Potential delayed effects :

: Not available.

Long term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary: Not available.

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Teratogenicity : No known significant effects or critical hazards.
 Developmental effects : No known significant effects or critical hazards.
 Fertility effects : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Conclusion/Summary: Not available.

12.2 Persistence and degradability

Conclusion/Summary: Not available.

12.3 Bioaccumulative potential

Date of issue/Date of revision : 10/20/2022 Date of previous issue : 10/19/2022 Version : 2.04 11/16

Multi-Flex Comp. A

SECTION 12: Ecological information

Product/ingredient name	LogP _{ow}	BCF	Potential
3-Aminopropyltrimethoxysilane	0.2	-	low
Bis (2,2,6,6-tetramethyl- 4-piperidyl) sebacate	0.35	-	low

12.4 Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste

: The classification of the product may meet the criteria for a hazardous waste.

European waste catalogue (EWC)

Waste code	Waste designation	
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances	

Packaging

Methods of disposal

: The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	European waste catalogue (EWC)	
15 01 10*	packaging containing residues of or contaminated by hazardous substances	

Special precautions

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Date of issue/Date of revision : 10/20/2022 Date of previous issue : 10/19/2022 Version : 2.04 12/16

SECTION 14: Transport information

	ADR/RID	IMDG	IATA
14.1 UN number	Not available.	Not available.	Not available.
14.2 UN proper shipping name	Not available.	Not available.	Not available.
14.3 Transport hazard class(es)	Not available.	Not available.	Not available.
14.4 Packing group	-	-	-
14.5 Environmental hazards	No. Not available.	No. Not available.	No.

Additional information

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments

: Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions : Not applicable.

on the manufacture, placing on the market and use of certain

dangerous substances,

mixtures and articles

Restrictions on Manufacture, Marketing and Use

CountryProduct name Conc. Designation Usage Dioctylzinnacetylacetonat EU 0.1 - 120 0 **GB** Dioctylzinnacetylacetonat 0.1 - 120 0

Other EU regulations

Industrial emissions : Not listed

(integrated pollution prevention and control) -

Air

Date of issue/Date of revision : 10/19/2022 : 10/20/2022 Version: 2.04 13/16 Date of previous issue

Multi-Flex Comp. A

SECTION 15: Regulatory information

Industrial emissions : Not listed

(integrated pollution prevention and control) -

Water

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

Storage class (TRGS 510) : 10 Hazardous incident ordinance

This product is not controlled under the Germany Hazardous Incident Ordinance.

Hazard class for water : 1

Technical instruction on: TA-Luft Number 5.2.5: 5.6-9%

air quality control TA-Luft Class III - Number 5.2.2: 0.1-1%

TA-Luft Class I - Number 5.2.5: 0-0.2%

AOX : The product does not contain organically bound halogens which could lead to an

AOX value in waste water.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Australia : Not determined.

Canada : Not determined.

China : Not determined.

Eurasian Economic Union: Russian Federation inventory: All components are listed or exempted.

Japan : Japan inventory (CSCL): Not determined.

Japan inventory (ISHL): Not determined.

New Zealand : All components are listed or exempted.

Philippines : Not determined.

Republic of Korea : Not determined.

Taiwan : All components are listed or exempted.

Thailand : Not determined.

Date of issue/Date of revision : 10/20/2022 Date of previous issue : 10/19/2022 Version : 2.04 14/16

Multi-Flex Comp. A

SECTION 15: Regulatory information

Turkey : Not determined. **United States** : Not determined.

Viet Nam : All components are listed or exempted.

15.2 Chemical Safety

Assessment

: This product contains substances for which Chemical Safety Assessments are still

required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and

: ATE = Acute Toxicity Estimate acronyms

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

N/A = Not available

PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Eye Dam. 1, H318	Calculation method

Full text of abbreviated H statements

H226	Flammable liquid and vapor.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H371	May cause damage to organs.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	AQUATIC HAZARD (ACUTE) - Category 1
Aquatic Chronic 2	AQUATIC HAZARD (LONG-TERM) - Category 2
Eye Dam. 1	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITIZATION - Category 1
Skin Sens. 1B	SKIN SENSITIZATION - Category 1B
STOT SE 2	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) -
	Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) -
	Category 3

Date of printing : 10/20/2022 Date of issue/ Date of

revision

: 10/20/2022

Date of previous issue : 10/19/2022 Version : 2.04

Notice to reader

Date of issue/Date of revision : 10/20/2022 : 10/19/2022 Version: 2.04 15/16 Date of previous issue

Multi-Flex Comp. A

SECTION 16: Other information

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Date of issue/Date of revision : 10/20/2022 Date of previous issue : 10/19/2022 Version : 2.04 16/16