SAFETY DATA SHEET



Rust Loosener

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name	: Rust Loosener
UFI	: S6N0-30YA-S00G-9NWV
Product code	: 151502
Color	: Dark. Yellow.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	
_ubricating agent-Release products	

1.3 Details of the supplier of the safety data sheet

WEICON GmbH & Co. KG Königsberger Str. 255 48157 Münster Germany Phone: +49 251 93220 Fax: +49(0)251 / 9322 - 244 Internet: www.weicon.de e-mail address of person : msds@weicon.de responsible for this SDS

1.4 Emergency telephone number

Telephone number	: EMERGENCY CONTACT – UK, UAE, South Africa (24h): Tel: ++44 1865 407333 (English)
	TRANSPORT EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel: ++44 1865 407333 (English)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Asp. Tox. 1, H304 Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



Signal word	: Danger
Hazard statements	: H304 - May be fatal if swallowed and enters airways. H412 - Harmful to aquatic life with long lasting effects.

SECTION 2: Hazards identification

Precautionary statements		
Prevention	:	P273 - Avoid release to the environment.
Response	:	P301 + P310, P331 - IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.
Storage	:	P405 - Store locked up.
Disposal	:	P501 - Dispose of waste according to applicable legislation.
Hazardous ingredients	:	Hydrocarbons, C10-13, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics
Supplemental label elements	:	Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do	:	None known.

not result in classification

SECTION 3: Composition/information on ingredients

3.2 Mixtures	: Mixture				
Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Hydrocarbons, C10-13, n- alkanes, isoalkanes, cycloalkanes, <2% aromatics	REACH #: 01-2119457273-39 EC: 918-481-9 CAS: -	≥10 - ≤25	Asp. Tox. 1, H304	-	[1]
2-(2-heptadec-8-enyl- 2-imidazolin-1-yl)ethanol	REACH #: 01-2119777867-13 EC: 202-414-9 CAS: 95-38-5	<1	Acute Tox. 4, H302 Skin Corr. 1C, H314 Eye Dam. 1, H318 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 500 mg/kg M [Acute] = 10 M [Chronic] = 1	[1]
(Z)-N-methyl-N-(1-oxo- 9-octadecenyl)glycine	REACH #: 01-2119488991-20 EC: 203-749-3 CAS: 110-25-8	<1	Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Acute 1, H400 See Section 16 for the full text of the H statements declared above.	ATE [Inhalation (dusts and mists)] = 1.5 mg/l M [Acute] = 1	[1] [2]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of

equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section. <u>Type</u>

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

Date of issue/Date of revision : 10/20/2022 Date of previous issue	: 10/19/2022	Version : 3.01	2/13
--	--------------	----------------	------

SECTION 4: First aid measures

4.1 Description of first aid n	neasures
Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	 Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: Adverse symptoms may include the following: nausea or vomiting

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
5.2 Special hazards arising	rom the substance or mixture
Hazards from the substance or mixture	In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion	· No specific data

SECTION 5: Firefighting measures

5.3 Advice for firefighters	
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, pro	ote	ctive equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
6.3 Methods and materials for containment and cleaning up	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Do not swallow. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Date of issue/Date of revision

SECTION 7: Handling and storage

7.3 Specific end use(s)

Recommendations

Industrial sector specific :

solutions

: Not available. : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
(Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine	DFG MAC-values list (Germany, 10/2021). PEAK: 0.1 mg/m ³ , 4 times per shift, 15 minutes. Form: inhalable fraction TWA: 0.05 mg/m ³ 8 hours. Form: inhalable fraction TRGS 900 OEL (Germany, 7/2021). PEAK: 0.1 mg/m ³ 15 minutes. Form: inhalable fraction TWA: 0.05 mg/m ³ 8 hours. Form: inhalable fraction
Recommended monitoring : If this product	contains ingredients with exposure limits personal workplace

Recommended monitoring procedures If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Туре	Exposure	Value	Population	Effects
DNEL	Long term Dermal	0.06 mg/ kg bw/day	Workers	Systemic
DNEL	Long term Inhalation	0.46 mg/m ³	Workers	Systemic
DNEL	Short term Dermal	2 mg/kg bw/day	Workers	Systemic
DNEL	Short term Inhalation	14 mg/m³	Workers	Systemic
DNEL	Long term Inhalation	5 µg/m³	General population	Local
DNEL	Long term Inhalation	0.01 mg/m ³	Workers	Local
DNEL	Long term Inhalation	0.1 mg/m³	General population	Systemic
DNEL	Long term Inhalation	0.2 mg/m³	Workers	Systemic
DNEL	Long term Oral	5 mg/kg	General	Systemic
	DNEL DNEL DNEL DNEL DNEL DNEL DNEL	DNELLong term DermalDNELLong term InhalationDNELShort term DermalDNELShort term InhalationDNELLong term InhalationDNELLong term InhalationDNELLong term InhalationDNELLong term InhalationDNELLong term InhalationDNELLong term InhalationDNELLong term InhalationDNELLong term InhalationDNELLong term Inhalation	DNELLong term Dermal0.06 mg/ kg bw/dayDNELLong term Inhalation0.46 mg/m³DNELShort term Dermal2 mg/kg bw/dayDNELShort term Dermal14 mg/m³DNELShort term Inhalation14 mg/m³DNELLong term Inhalation5 µg/m³DNELLong term Inhalation0.01 mg/m³DNELLong term Inhalation0.1 mg/m³DNELLong term Inhalation0.2 mg/m³	DNELLong term Dermal0.06 mg/ kg bw/dayWorkersDNELLong term Inhalation0.46 mg/m³WorkersDNELShort term Dermal2 mg/kg bw/dayWorkersDNELShort term Dermal14 mg/m³WorkersDNELShort term Inhalation14 mg/m³WorkersDNELLong term Inhalation5 µg/m³General populationDNELLong term Inhalation0.01 mg/m³WorkersDNELLong term Inhalation0.1 mg/m³General populationDNELLong term Inhalation0.2 mg/m³Workers

S	ECTION 8: Exposure	controls	/persor	al protection

SECTION 8: Exposure con	1015/1	ersonal prote	CUON		
			bw/day	population	
	DNEL	Long term Dermal	5 mg/kg bw/day	General population	Systemic
	DNEL	Short term Inhalation	9 mg/m³	General population	Local
	DNEL	Short term Inhalation	9 mg/m³	General population	Systemic
	DNEL	Long term Dermal	10 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	18 mg/m³	Workers	Local
	DNEL	Short term Inhalation	18 mg/m³	Workers	Systemic
	DNEL	Short term Dermal	50 mg/kg bw/day	General population	Systemic
	DNEL	Short term Oral	92 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	100 mg/kg bw/day	Workers	Systemic

PNECs

No PNECs available.

8.2 Exposure controls

Appropriate engineering controls: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.Individual protection measures: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.Eye/face protection: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.Skin protection: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the glove are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. Recommended : 1 - 4 hours (breakthrough time): nitrile rubber ; 4 - 8 hours (breakthrough time): Viton®/butyl rubberBody protection: Appropriate footwear and any additional skin protection measures should be approved by a specialist before handling this product.: Appropriate footwear and any additional skin protection measures should be approved by a specialist before handling this product.Date of issue/Date of revision: 10/20/2022<			
Hygiene measures: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.Eye/face protection: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.Skin protection: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. Recommended : 1 - 4 hours (breakthrough time): nitrile rubber ; 4 - 8 hours (breakthrough time): Viton®/butyl rubberBody protection: Personal protective equipment for the body should be approved by a specialist before handling the risks involved and should be approved by a specialist before handling this product.		•	rne
before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.Eye/face protection: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.Skin protection: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. Recommended : 1 - 4 hours (breakthrough time): nitrile rubber ; 4 - 8 hours (breakthrough time): Viton®/butyl rubberBody protection: Personal protective equipment for the body should be approved by a specialist before handling this product.Other skin protection: Appropriate footwear and any additional skin protection measures should be approved by a specialist before handling this product.	Individual protection meas	<u>S</u>	
 assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. Skin protection Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. Recommended : 1 - 4 hours (breakthrough time): nitrile rubber ; 4 - 8 hours (breakthrough time): Viton®/butyl rubber Body protection Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Other skin protection Appropriate footwear and any additional skin protection measures should be approved by a specialist before handling this product. 	Hygiene measures	before eating, smoking and using the lavatory and at the end of the working period Appropriate techniques should be used to remove potentially contaminated cloth Wash contaminated clothing before reusing. Ensure that eyewash stations and	ning.
 Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. Recommended : 1 - 4 hours (breakthrough time): nitrile rubber ; 4 - 8 hours (breakthrough time): Viton®/butyl rubber Body protection Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Other skin protection Appropriate footwear and any additional skin protection measures should be approved by a specialist before handling this product. 	Eye/face protection	assessment indicates this is necessary to avoid exposure to liquid splashes, mis gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses w	sts,
be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. Recommended : 1 - 4 hours (breakthrough time): nitrile rubber ; 4 - 8 hours (breakthrough time): Viton®/butyl rubberBody protection: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.Other skin protection: Appropriate footwear and any additional skin protection measures should be approved by a specialist before handling this product.	Skin protection		
Other skin protectionbeing performed and the risks involved and should be approved by a specialist before handling this product.Other skin protection: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.	Hand protection	be worn at all times when handling chemical products if a risk assessment indicat this is necessary. Considering the parameters specified by the glove manufactur check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. Recommended : 1 - 4 hours (breakthrough time): nitrile rubber ; 4 - 8 hours (breakthrough time): Viton®/bu	ates ırer,
selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.	Body protection	being performed and the risks involved and should be approved by a specialist	ĸ
Date of issue/Date of revision: 10/20/2022Date of previous issue: 10/19/2022Version: 3.016/13	Other skin protection	selected based on the task being performed and the risks involved and should b	e
	Date of issue/Date of revision	: 10/20/2022 Date of previous issue : 10/19/2022 Version : 3.01	6/13

SECTION 8: Exposure controls/personal protection

Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other importan aspects of use. Recommended : organic vapor (Type AX) and particulate filter
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical	and chemical properties
<u>Appearance</u>	
Physical state	: Liquid.
Color	: Dark. Yellow.
Odor	: Characteristic.
Odor threshold	: Not available.
Melting point/freezing point	: Not available.
Initial boiling point and boiling range	: 181°C (357.8°F)
Flammability	: Extremely flammable in the presence of the following materials or conditions: open flames, sparks and static discharge. Highly flammable in the presence of the following materials or conditions: heat.
Upper/lower flammability or explosive limits	: Lower: 0.6% Upper: 6%
Flash point	: Closed cup: 62°C (143.6°F)
Auto-ignition temperature	: Not applicable.
Decomposition temperature	: Not available.
рН	: Not applicable.
Viscosity	: Kinematic (40°C): <20.5 mm ² /s
Solubility(ies)	:
Not available.	
Solubility in water	: Not available.
Miscible with water	: No.
Partition coefficient: n-octanol/ water	: Not applicable.
Vapor pressure	: 0.1 kPa (0.75006 mm Hg)
Relative density	: Not available.
Density	: 0.856 g/cm ³ [20°C (68°F)]
Vapor density	: Not available.
Explosive properties	: Not available.
Oxidizing properties	: Not available.
Particle characteristics	
Median particle size	: Not applicable.
Fire point	: >236°C
SADT	: Not available.
SAPT	: Not available.

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: No specific data.
10.5 Incompatible materials	: No specific data.
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicolo	gical effects
Acute toxicity	
Conclusion/Summary	: Not available.
Acute toxicity estimates	

		ATE value
Not available.		
ritation/Corrosion		
Conclusion/Summary	: Not available.	
Sensitization		
Conclusion/Summary	: Not available.	
lutagenicity		
Conclusion/Summary	: Not available.	
arcinogenicity		
Conclusion/Summary	: Not available.	
eproductive toxicity		
Conclusion/Summary	: Not available.	
eratogenicity		
Conclusion/Summary	: Not available.	
<u>pecific target organ toxi</u>	<u>city (single exposure)</u>	
lot available.		

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Product/ingredient name	Result
Hydrocarbons, C10-13, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics	ASPIRATION HAZARD - Category 1

Information on the likely : Not available. routes of exposure

Potential acute health effects

Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.

SECTION 11: Toxicological information

- Skin contact: No known significant effects or critical hazards.Ingestion: May be fatal if swallowed and enters airways.
- Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: Adverse symptoms may include the following: nausea or vomiting

Delayed and immediate effects and also chronic effects from short and long term exposure

<u>Short term exposure</u>			
Potential immediate effects	: Not available.		
Potential delayed effects	: Not available.		
Long term exposure			
Potential immediate effects	: Not available.		
Potential delayed effects	: Not available.		
Potential chronic health effects			
Not available.			
Conclusion/Summary	: Not available.		
General	: No known significant effects or critical hazards.		
Carcinogenicity	: No known significant effects or critical hazards.		
Mutagenicity	: No known significant effects or critical hazards.		
Teratogenicity	: No known significant effects or critical hazards.		
Developmental effects	: No known significant effects or critical hazards.		
Fertility effects	: No known significant effects or critical hazards.		

11.2 Information on other hazards

11.2.1 Endocrine disrupting propertiesNot available.11.2.2 Other informationNot available.

SECTION 12: Ecological information

12.1 Toxicity

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
(Z)-N-methyl-N-(1-oxo- 9-octadecenyl)glycine	3.5 to 4.2	-	low

12.4 Mobility in soil

Date of issue/Date of revision

SECTION 12: Ecological information

Soil/water partition coefficient (Koc) Mobility

: Not available.

: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

<u>Product</u>	
Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : The classification of the product may meet the criteria for a hazardous waste.

European waste catalogue (EWC)

Waste code	Waste designation	
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances	
Packaging		
Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.	
Type of packaging	European waste catalogue (EWC)	
15 01 10*	packaging containing residues of or contaminated by hazardous substances	
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out	

taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMI	DG	ΙΑΤΑ	
14.1 UN number	Not available.	Not available.		Not available.	
14.2 UN proper shipping name	Not available.	Not available.		Not available.	
Date of issue/Date of re	vision : 10/20/2022	Date of previous issue	: 10/19/2022	Version : 3.01	10/13

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 - Germany

Rust Loosener

14.3 Transport hazard class(es)	Not available.	Not available.	Not available.	
14.4 Packing group	-	-	-	
14.5 Environmental hazards	No.	No. Not available.	No.	
	Not available.			

Additional information

14.6 Special precautions for user	:	Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
14.7 Transport in bulk according to IMO instruments	:	Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization Annex XIV None of the components are listed. Substances of very high concern None of the components are listed. Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles **Restrictions on Manufacture, Marketing and Use** CountryProduct name Conc. Designation Usage **Other EU regulations** Industrial emissions : Not listed (integrated pollution prevention and control) -Air Industrial emissions : Not listed (integrated pollution prevention and control) -Water Ozone depleting substances (1005/2009/EU) Not listed. Prior Informed Consent (PIC) (649/2012/EU) Not listed. Date of issue/Date of revision : 10/20/2022 : 10/19/2022 Date of previous issue

Rust Loosener	
SECTION 15: Regulation	tory information
Persistent Organic Polluta	nts
Not listed.	
VOC content	: 16.9 %
VOC (g/L)	: 144.7
Seveso Directive	
•	d under the Seveso Directive.
National regulations	
Storage class (TRGS 510)	
Hazardous incident ordina	
Hazard class for water	d under the Germany Hazardous Incident Ordinance. : 2
	• Z • TA-Luft Number 5.2.5: 10.2-26%
air quality control	TA-Luft Class I - Number 5.2.5: 0.2-1%
International regulations	
<u>Chemical Weapon Conventi</u>	ion List Schedules I, II & III Chemicals
Not listed.	
Montreal Protocol	
Not listed.	
Stockholm Convention on F	Persistent Organic Pollutants
Not listed.	
Rotterdam Convention on P	Prior Informed Consent (PIC)
Not listed.	
UNECE Aarhus Protocol on	POPs and Heavy Metals
Not listed.	
Inventory list	
Australia	: All components are listed or exempted.
Canada	: Not determined.
China	: All components are listed or exempted.
Eurasian Economic Union	: Russian Federation inventory: Not determined.
Japan	 Japan inventory (CSCL): All components are listed or exempted. Japan inventory (ISHL): Not determined.
New Zealand	: Not determined.
Philippines	: Not determined.
Republic of Korea	: Not determined.
Taiwan	: Not determined.
Thailand	: Not determined.
Turkey	: Not determined.
United States	: All components are active or exempted.
Viet Nam	: Not determined.
15.2 Chemical Safety Assessment	: This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and	: ATE = Acute Toxicity Estimate
acronyms	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = CLP-specific Hazard statement
	N/A = Not available
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
	SGG = Segregation Group
	vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Asp. Tox. 1, H304	Calculation method
Aquatic Chronic 3, H412	Calculation method

Full text of abbreviated H statements

11000	
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

Date of printing	10/20/2022
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C
Eye Dam. 1	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Aquatic Chronic 3	AQUATIC HAZARD (LONG-TERM) - Category 3
Aquatic Chronic 1	AQUATIC HAZARD (LONG-TERM) - Category 1
Aquatic Acute 1	AQUATIC HAZARD (ACUTE) - Category 1
Acute Tox. 4	ACUTE TOXICITY - Category 4

. 10/20/2022
: 10/20/2022
: 10/19/2022
: 3.01

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.