

# SAFETY DATA SHEET



WEICONLOCK AN 305-18

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : WEICONLOCK AN 305-18  
**UFI** : SAV0-4089-600K-6097  
**Product code** : 305180  
**Color** : Red.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses
Adhesives-Anaerobic

### 1.3 Details of the supplier of the safety data sheet

WEICON GmbH & Co. KG  
Königsberger Str. 255  
48157 Münster  
Germany  
Phone: +49 251 93220  
Fax: +49(0)251 / 9322 - 244  
Internet: www.weicon.de

**e-mail address of person responsible for this SDS** : msds@weicon.de

### 1.4 Emergency telephone number

**Telephone number** : EMERGENCY CONTACT – UK, UAE, South Africa (24h): Tel: ++44 1865 407333 (English)  
TRANSPORT EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel: ++44 1865 407333 (English)

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Irrit. 2, H315  
Eye Irrit. 2, H319  
Skin Sens. 1, H317  
STOT SE 3, H335

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

**Hazard pictograms** :



**Signal word** : Warning

## SECTION 2: Hazards identification

<b>Hazard statements</b>	: H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation. H335 - May cause respiratory irritation.
<b>Precautionary statements</b>	
<b>Prevention</b>	: P280 - Wear protective gloves. Wear eye or face protection. P271 - Use only outdoors or in a well-ventilated area. P261 - Avoid breathing vapor. P264 - Wash thoroughly after handling.
<b>Response</b>	: P304 + P312 - IF INHALED: Call a POISON CENTER or doctor if you feel unwell. P362 + P364 - Take off contaminated clothing and wash it before reuse. P302 + P352 - IF ON SKIN: Wash with plenty of water. P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention. P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 - If eye irritation persists: Get medical advice or attention.
<b>Storage</b>	: P405 - Store locked up. P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.
<b>Disposal</b>	: P501 - Dispose of waste according to applicable legislation.
<b>Hazardous ingredients</b>	: 2-hydroxyethyl methacrylate acrylic acid ethylene dimethacrylate
<b>Supplemental label elements</b>	: Not applicable.
<b>Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles</b>	: Not applicable.

### 2.3 Other hazards

<b>Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII</b>	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
<b>Other hazards which do not result in classification</b>	: None known.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
2-hydroxyethyl methacrylate	REACH #: 01-2119490169-29 EC: 212-782-2 CAS: 868-77-9 Index: 607-124-00-X	≥10 - ≤25	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317	-	[1] [2]
2-phenoxyethyl methacrylate	REACH #: 01-2120752383-55 EC: 234-201-1 CAS: 10595-06-9	≥10 - ≤25	Skin Irrit. 2, H315 Eye Irrit. 2, H319	-	[1]
acrylic acid	REACH #: 01-2119452449-31	≤3	Flam. Liq. 3, H226 Acute Tox. 4, H302	ATE [Oral] = 500 mg/kg	[1] [2]

### SECTION 3: Composition/information on ingredients

	EC: 201-177-9 CAS: 79-10-7 Index: 607-061-00-8		Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 1, H400	ATE [Dermal] = 1100 mg/kg ATE [Inhalation (vapours)] = 11 mg/l STOT SE 3, H335: C ≥ 1% M [Acute] = 1	
α,α-dimethylbenzyl hydroperoxide	REACH #: 01-2119475796-19 EC: 201-254-7 CAS: 80-15-9 Index: 617-002-00-8	<1	Org. Perox. E, H242 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 3, H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335 STOT RE 2, H373 Aquatic Chronic 2, H411	ATE [Oral] = 800 mg/kg [1] ATE [Dermal] = 1100 mg/kg ATE [Inhalation (gases)] = 700 ppm Skin Corr. 1B, H314: C ≥ 10% Skin Irrit. 2, H315: 3% ≤ C < 10% Eye Dam. 1, H318: 3% ≤ C < 10% Eye Irrit. 2, H319: 1% ≤ C < 3% STOT SE 3, H335: C ≥ 1% STOT RE 2, H373: C ≥ 3%	
ethylene dimethacrylate	REACH #: 01-2119965172-38 EC: 202-617-2 CAS: 97-90-5 Index: 607-114-00-5	<1	Skin Sens. 1, H317 STOT SE 3, H335	STOT SE 3, H335: C ≥ 10% [1] [2]	
ethanediol	REACH #: 01-2119456816-28 EC: 203-473-3 CAS: 107-21-1 Index: 603-027-00-1	<1	Acute Tox. 4, H302  <b>See Section 16 for the full text of the H statements declared above.</b>	ATE [Oral] = 500 mg/kg [1] [2]	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

**Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

## SECTION 4: First aid measures

- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### 4.2 Most important symptoms and effects, both acute and delayed

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness
- Ingestion** : No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

### 5.2 Special hazards arising from the substance or mixture

## SECTION 5: Firefighting measures

**Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst.

**Hazardous combustion products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide

### 5.3 Advice for firefighters

**Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

**For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### 6.3 Methods and materials for containment and cleaning up

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

### 6.4 Reference to other sections

: See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

### 7.1 Precautions for safe handling

**Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

**Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

## SECTION 7: Handling and storage

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### 7.3 Specific end use(s)

**Recommendations** : Not available.

**Industrial sector specific solutions** : Not available.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

### 8.1 Control parameters

#### Occupational exposure limits

Product/ingredient name	Exposure limit values
2-hydroxyethyl methacrylate	<b>DFG MAC-values list (Germany, 10/2021). Skin sensitizer.</b>
acrylic acid	<b>DFG MAC-values list (Germany, 10/2021).</b> TWA: 30 mg/m <sup>3</sup> 8 hours. TWA: 10 ppm 8 hours. PEAK: 10 ppm, 4 times per shift, 15 minutes. PEAK: 30 mg/m <sup>3</sup> , 4 times per shift, 15 minutes. <b>TRGS 900 OEL (Germany, 7/2021).</b> TWA: 30 mg/m <sup>3</sup> 8 hours. PEAK: 30 mg/m <sup>3</sup> 15 minutes. TWA: 10 ppm 8 hours. PEAK: 10 ppm 15 minutes.
ethylene dimethacrylate	<b>DFG MAC-values list (Germany, 10/2021). Skin sensitizer.</b>
ethanediol	<b>TRGS 900 OEL (Germany, 7/2021). Absorbed through skin.</b> TWA: 26 mg/m <sup>3</sup> 8 hours. PEAK: 52 mg/m <sup>3</sup> 15 minutes. TWA: 10 ppm 8 hours. PEAK: 20 ppm 15 minutes. <b>DFG MAC-values list (Germany, 10/2021). Absorbed through skin.</b> TWA: 10 ppm 8 hours. PEAK: 20 ppm, 4 times per shift, 15 minutes. TWA: 26 mg/m <sup>3</sup> 8 hours. PEAK: 52 mg/m <sup>3</sup> , 4 times per shift, 15 minutes.

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

## SECTION 8: Exposure controls/personal protection

### DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects	
2-hydroxyethyl methacrylate	DNEL	Long term Oral	0.83 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Dermal	0.83 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Dermal	1.3 mg/kg bw/day	Workers	Systemic	
	DNEL	Long term Inhalation	2.9 mg/m <sup>3</sup>	General population	Systemic	
	DNEL	Long term Inhalation	4.9 mg/m <sup>3</sup>	Workers	Systemic	
2-phenoxyethyl methacrylate	DNEL	Long term Dermal	3.5 mg/kg bw/day	Workers	Systemic	
	DNEL	Long term Inhalation	12 mg/m <sup>3</sup>	Workers	Systemic	
	DNEL	Long term Inhalation	84 mg/m <sup>3</sup>	Workers	Local	
acrylic acid	DNEL	Short term Inhalation	3.6 mg/m <sup>3</sup>	General population	Local	
	DNEL	Long term Inhalation	3.6 mg/m <sup>3</sup>	General population	Local	
	DNEL	Short term Dermal	1 mg/cm <sup>2</sup>	General population	Local	
	DNEL	Long term Oral	0.4 mg/kg bw/day	General population	Systemic	
	DNEL	Short term Oral	1.2 mg/kg bw/day	General population	Systemic	
	DNEL	Short term Inhalation	3.6 mg/m <sup>3</sup>	General population	Systemic	
	DNEL	Long term Inhalation	3.6 mg/m <sup>3</sup>	General population	Systemic	
	DNEL	Short term Inhalation	30 mg/m <sup>3</sup>	Workers	Local	
	DNEL	Long term Inhalation	30 mg/m <sup>3</sup>	Workers	Local	
	DNEL	Short term Inhalation	30 mg/m <sup>3</sup>	Workers	Systemic	
	DNEL	Long term Inhalation	30 mg/m <sup>3</sup>	Workers	Systemic	
	α,α-dimethylbenzyl hydroperoxide	DNEL	Long term Inhalation	6 mg/m <sup>3</sup>	Workers	Systemic
	ethylene dimethacrylate	DNEL	Long term Dermal	1.3 mg/kg bw/day	Workers	Systemic

## SECTION 8: Exposure controls/personal protection

ethanediol	DNEL	Long term Inhalation	2.45 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Oral	0.83 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.83 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	1.45 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	7 mg/m <sup>3</sup>	General population	Local
	DNEL	Long term Inhalation	35 mg/m <sup>3</sup>	Workers	Local
	DNEL	Long term Dermal	53 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	106 mg/kg bw/day	Workers	Systemic

### PNECs

No PNECs available.

## 8.2 Exposure controls

**Appropriate engineering controls** : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

### Skin protection

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. Recommended : 1 - 4 hours (breakthrough time): nitrile rubber ; 4 - 8 hours (breakthrough time): Viton®/butyl rubber

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.



## SECTION 8: Exposure controls/personal protection

- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended : organic vapor (Type AX) and particulate filter
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

- Physical state** : Liquid.
- Color** : Red.
- Odor** : Bland.
- Odor threshold** : Not available.
- Melting point/freezing point** : Not available.
- Initial boiling point and boiling range** : Not available.
- Flammability** : Flammable in the presence of the following materials or conditions: open flames, sparks and static discharge.  
Slightly flammable in the presence of the following materials or conditions: heat.
- Upper/lower flammability or explosive limits** : Not available.
- Flash point** : Closed cup: >100°C (>212°F)
- Auto-ignition temperature** : Not applicable.
- Decomposition temperature** : Not available.
- pH** : Not applicable.
- Viscosity** : Dynamic: 105000 mPa·s
- Solubility(ies)** :  
Not available.
- Solubility in water** : Not available.
- Miscible with water** : No.
- Partition coefficient: n-octanol/ water** : Not applicable.
- Vapor pressure** :

Ingredient name	Vapor Pressure at 20 °C			Vapor pressure at 50 °C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
acrylic acid	2.85	0.38	OECD 104			
ethanediol	0.09	0.012				
2-hydroxyethyl methacrylate	0.06	0.008				
ethylene dimethacrylate	0.01	0.0013				
α,α-dimethylbenzyl hydroperoxide	0	0				

- Relative density** : Not available.
- Density** : 1.1 g/cm<sup>3</sup> [20°C (68°F)]
- Vapor density** : Not available.
- Explosive properties** : Not available.
- Oxidizing properties** : Not available.
- Particle characteristics**

WEICONLOCK AN 305-18

## SECTION 9: Physical and chemical properties

Median particle size : Not applicable.

### 9.2 Other information

SADT : Not available.

SAPT : Not available.

## SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : No specific data.

10.6 Hazardous decomposition products : Highly reactive or incompatible with the following materials: metals.  
Reactive or incompatible with the following materials: oxidizing materials and reducing materials.  
Reacts with heavy metals and metallic salts.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2-hydroxyethyl methacrylate	LD50 Oral	Rat	5050 mg/kg	-
acrylic acid	LC50 Inhalation Vapor	Mouse	5300 mg/m <sup>3</sup>	2 hours
	LD50 Dermal	Rabbit	640 mg/kg	-
	LD50 Dermal	Rabbit	280 uL/kg	-
	LD50 Intraperitoneal	Mouse	144 mg/kg	-
	LD50 Intraperitoneal	Rat	22 mg/kg	-
	LD50 Oral	Mouse	2400 mg/kg	-
	LD50 Oral	Rat	1337 mg/kg	-
	LD50 Oral	Rat	33500 µg/kg	-
	LD50 Route of exposure unreported	Mouse	830 mg/kg	-
	LD50 Route of exposure unreported	Rabbit	250 mg/kg	-
	LD50 Route of exposure unreported	Rat	1250 mg/kg	-
	LD50 Subcutaneous	Mouse	1590 mg/kg	-
	α,α-dimethylbenzyl hydroperoxide	LC50 Inhalation Gas.	Rat	220 ppm

WEICONLOCK AN 305-18

## SECTION 11: Toxicological information

ethylene dimethacrylate ethanediol	LD50 Dermal	Rat	500 mg/kg	-
	LD50 Oral	Rat	800 mg/kg	-
	LD50 Oral	Rat	3300 mg/kg	-
	LD50 Oral	Rat	4700 mg/kg	-

**Conclusion/Summary** : Not available.

### Acute toxicity estimates

Route	ATE value
Oral	28571.43 mg/kg
Dermal	62857.14 mg/kg
Inhalation (gases)	127272.73 ppm
Inhalation (vapors)	628.57 mg/l

### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
WEICONLOCK AN 305-18	Eyes - Irritant	Rat	-	-	-
acrylic acid	Eyes - Severe irritant	Rabbit	-	1 mg	-
	Eyes - Severe irritant	Rabbit	-	24 hours 250 ug	-
	Skin - Severe irritant	Rabbit	-	24 hours 5 mg	-
	Skin - Severe irritant	Rabbit	-	500 mg	-
α,α-dimethylbenzyl hydroperoxide	Skin - Mild irritant	Rabbit	-	500 mg	-
ethanediol	Eyes - Mild irritant	Rabbit	-	1 hours 100 mg	-
	Eyes - Mild irritant	Rabbit	-	24 hours 500 mg	-
	Eyes - Moderate irritant	Rabbit	-	6 hours 1440 mg	-
	Skin - Mild irritant	Rabbit	-	555 mg	-

### **Conclusion/Summary**

**Eyes** : Irritating to eyes.

### Sensitization

**Conclusion/Summary** : Not available.

### Mutagenicity

**Conclusion/Summary** : Not available.

### Carcinogenicity

**Conclusion/Summary** : Not available.

### Reproductive toxicity

**Conclusion/Summary** : Not available.

### Teratogenicity

**Conclusion/Summary** : Not available.

## SECTION 11: Toxicological information

### Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
acrylic acid	Category 3	-	Respiratory tract irritation
$\alpha,\alpha$ -dimethylbenzyl hydroperoxide	Category 3	-	Respiratory tract irritation
ethylene dimethacrylate	Category 3	-	Respiratory tract irritation

### Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
$\alpha,\alpha$ -dimethylbenzyl hydroperoxide	Category 2	-	-

### Aspiration hazard

Not available.

**Information on the likely routes of exposure** : Not available.

### Potential acute health effects

**Eye contact** : Causes serious eye irritation.  
**Inhalation** : May cause respiratory irritation.  
**Skin contact** : Causes skin irritation. May cause an allergic skin reaction.  
**Ingestion** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness  
**Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing  
**Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
**Ingestion** : No specific data.

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

**Potential immediate effects** : Not available.  
**Potential delayed effects** : Not available.

#### Long term exposure

**Potential immediate effects** : Not available.  
**Potential delayed effects** : Not available.

### Potential chronic health effects

Not available.

**Conclusion/Summary** : Not available.

## SECTION 11: Toxicological information

<b>General</b>	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
<b>Carcinogenicity</b>	: No known significant effects or critical hazards.
<b>Mutagenicity</b>	: No known significant effects or critical hazards.
<b>Teratogenicity</b>	: No known significant effects or critical hazards.
<b>Developmental effects</b>	: No known significant effects or critical hazards.
<b>Fertility effects</b>	: No known significant effects or critical hazards.

### 11.2 Information on other hazards

#### 11.2.1 Endocrine disrupting properties

Not available.

#### 11.2.2 Other information

Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
2-hydroxyethyl methacrylate	Acute LC50 227000 µg/l Fresh water	Fish - Pimephales promelas - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
acrylic acid	Chronic NOEC 3.8 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	21 days
α,α-dimethylbenzyl hydroperoxide	Acute LC50 12.7 mg/l Fresh water	Fish - Pimephales promelas - Larvae	96 hours
ethanediol	Acute LC50 6900000 µg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 41000 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 8050000 µg/l Fresh water	Fish - Pimephales promelas	96 hours

**Conclusion/Summary** : Not available.

### 12.2 Persistence and degradability

**Conclusion/Summary** : Not available.

### 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
2-hydroxyethyl methacrylate	0.42	-	low
acrylic acid	0.38	3.162	low
α,α-dimethylbenzyl hydroperoxide	1.6	9	low
ethylene dimethacrylate	1.87	-	low
ethanediol	-1.36	-	low

### 12.4 Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

## SECTION 12: Ecological information

**Mobility** : Not available.

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

### 12.6 Endocrine disrupting properties

Not available.

### 12.7 Other adverse effects

No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : The classification of the product may meet the criteria for a hazardous waste.

#### European waste catalogue (EWC)

Waste code	Waste designation
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances

#### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	European waste catalogue (EWC)
15 01 10*	packaging containing residues of or contaminated by hazardous substances

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

	ADR/RID	IMDG	IATA
<b>14.1 UN number</b>	Not available.	Not available.	Not available.
<b>14.2 UN proper shipping name</b>	Not available.	Not available.	Not available.
<b>14.3 Transport hazard class(es)</b>	Not available.	Not available.	Not available.

WEICONLOCK AN 305-18

## SECTION 14: Transport information

<b>14.4 Packing group</b>	-	-	-
<b>14.5 Environmental hazards</b>	No.  Not available.	No.  Not available.	No.

### Additional information

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Transport in bulk according to IMO instruments** : Not available.

## SECTION 15: Regulatory information

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

### EU Regulation (EC) No. 1907/2006 (REACH)

#### Annex XIV - List of substances subject to authorization

##### Annex XIV

None of the components are listed.

##### Substances of very high concern

None of the components are listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

#### Restrictions on Manufacture, Marketing and Use

Country	Product name	Conc.	Designation	Usage
---------	--------------	-------	-------------	-------

#### Other EU regulations

**Industrial emissions (integrated pollution prevention and control) - Air** : Not listed

**Industrial emissions (integrated pollution prevention and control) - Water** : Not listed

#### Ozone depleting substances (1005/2009/EU)

Not listed.

#### Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

#### Persistent Organic Pollutants

Not listed.

**VOC content** : ca. 5 %

## SECTION 15: Regulatory information

VOC (g/L) : 2

### Seveso Directive

This product is not controlled under the Seveso Directive.

### National regulations

Storage class (TRGS 510) : 10

### Hazardous incident ordinance

This product is not controlled under the Germany Hazardous Incident Ordinance.

Hazard class for water : 1

Technical instruction on air quality control : TA-Luft Number 5.2.5: 20.2-62%  
TA-Luft Class I - Number 5.2.5: 1.1-3.5%

AOX : The product does not contain organically bound halogens which could lead to an AOX value in waste water.

### International regulations

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

#### UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

### Inventory list

<b>Australia</b>	: All components are listed or exempted.
<b>Canada</b>	: At least one component is not listed in DSL but all such components are listed in NDSL.
<b>China</b>	: All components are listed or exempted.
<b>Eurasian Economic Union</b>	: <b>Russian Federation inventory</b> : All components are listed or exempted.
<b>Japan</b>	: <b>Japan inventory (CSCL)</b> : All components are listed or exempted. <b>Japan inventory (ISHL)</b> : Not determined.
<b>New Zealand</b>	: All components are listed or exempted.
<b>Philippines</b>	: All components are listed or exempted.
<b>Republic of Korea</b>	: Not determined.
<b>Taiwan</b>	: All components are listed or exempted.
<b>Thailand</b>	: All components are listed or exempted.
<b>Turkey</b>	: Not determined.
<b>United States</b>	: All components are active or exempted.
<b>Viet Nam</b>	: Not determined.
<b>15.2 Chemical Safety Assessment</b>	: This product contains substances for which Chemical Safety Assessments are still required.



## SECTION 16: Other information

Indicates information that has changed from previously issued version.

### Abbreviations and acronyms

: ATE = Acute Toxicity Estimate  
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
 DMEL = Derived Minimal Effect Level  
 DNEL = Derived No Effect Level  
 EUH statement = CLP-specific Hazard statement  
 N/A = Not available  
 PBT = Persistent, Bioaccumulative and Toxic  
 PNEC = Predicted No Effect Concentration  
 RRN = REACH Registration Number  
 SGG = Segregation Group  
 vPvB = Very Persistent and Very Bioaccumulative

### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT SE 3, H335	Calculation method On basis of test data Calculation method Calculation method

### Full text of abbreviated H statements

H226	Flammable liquid and vapor.
H242	Heating may cause a fire.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

### Full text of classifications [CLP/GHS]

Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	AQUATIC HAZARD (ACUTE) - Category 1
Aquatic Chronic 2	AQUATIC HAZARD (LONG-TERM) - Category 2
Eye Dam. 1	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Org. Perox. E	ORGANIC PEROXIDES - Type E
Skin Corr. 1A	SKIN CORROSION/IRRITATION - Category 1A
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITIZATION - Category 1
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 3

Date of printing : 10/20/2022

Date of issue/ Date of revision : 10/20/2022

Date of previous issue : 10/19/2022

WEICONLOCK AN 305-18

## SECTION 16: Other information

Version : 3.01

### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.