SAFETY DATA SHEET



Cleaner Spray S

Section 1. Identification				
Product identifier	: Cleaner Spray S			
Product code	: 112025			
Relevant identified uses of the Identified uses	e substance or mixture and uses advised against			
Aerosol product-Cleaning ager	t			
Supplier's details	: WEICON GmbH & Co. KG Königsberger Str. 25, 48157 Münster, Germany phone: +49 251 93220, Fax: +49 251 9322244 email: info@weicon.de, URL: www.weicon.de			
e-mail address of person responsible for this SDS	: msds@weicon.de			
National contact WEICON Canada Inc. 20 Steckle Place, Unit 20 Kitchener, Ontario N2E 2C3, C/ www.weicon.ca E-mail: info@weicon.ca Telephone: +1-519-896-5252 Telefax: +1-519-896-5254	Ą			
Emergency telephone number	: +1 866 928 0789 (24h - Toll free) TRANSPORT EMERGENCY CONTACT :+1 866 928 0789 ((24h - Toll free)			
Section 2. Hazard	dentification			
Classification of the substance or mixture	: FLAMMABLE AEROSOLS - Category 1 GASES UNDER PRESSURE - Compressed gas SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3			
GHS label elements				
Hazard pictograms				
Signal word	: Danger			
Hazard statements	 H222 - Extremely flammable aerosol. H280 - Contains gas under pressure; may explode if heated. H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation. H336 - May cause drowsiness or dizziness. 			
Precautionary statements				

: 4/24/2025

Version : 3.3

1/14

Date of issue/Date of revision

: 5/12/2025

Date of previous issue

Section 2. Hazard identification

Prevention	, D210. Keen away from best bet surfaces aparks open flames and other ignition
Prevention	: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition
	sources. No smoking.
	P211 - Do not spray on an open flame or other ignition source.
	P251 - Do not pierce or burn, even after use.
	P261 - Avoid breathing dust or mist.
	P264 - Wash thoroughly after handling.
	P271 - Use only outdoors or in a well-ventilated area.
	P280 - Wear protective gloves. Wear eye or face protection.
Response	: P304 + P340, P312 - IF INHALED: Remove person to fresh air and keep
•	comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.
	P362 + P364 - Take off contaminated clothing and wash it before reuse.
	P302 + P352 - IF ON SKIN: Wash with plenty of water.
	P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention.
	P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes.
	Remove contact lenses, if present and easy to do. Continue rinsing.
	P337 + P313 - If eye irritation persists: Get medical advice or attention.
Storage	: P405 - Store locked up.
Storage	P410 + P403 - Protect from sunlight.
	P410 + P412 - Do not expose to temperatures exceeding 50 °C/122 °F.
	P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.
Disposal	: P501 - Dispose of waste according to applicable legislation.
Section 2 Co	mposition/information on ingradiants

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of	: Not available.
identification	

Ingredient name	Synonyms	% (v/v)	CAS number
Hydrocarbons, C7, n-alkanes, iso- alkanes, cyclic		≥60 - ≤80	64742-49-0
acetone	propan-2-one; propanone; 2-Propanone; Ketone propane; Dimethyl ketone; β-ketonepropane; acetonum; dimethylketone; methyl ketone; propanone; pyroacetic acid; pyroacetic ether; dimethylformaldehyde; methyl ketone; Acetone (I); 2-Propanone (I); DIMETHYLFORMALDEHYDE; 2-OXOPROPANE	≥10 - ≤30	67-64-1
propan-2-ol	isopropanol; 2-Propanol	≥1 - ≤5	67-63-0
Orange, sweet, ext.	Orange, sweet, extract; Sweet orange, peel, tincture; Oils, orange; orange, sweet; Orange peel, sweet, extract (Citrus Sinensis (L.) Osbeck); Blood orange oil (Citrus sinensis (L.) Osbeck 'Blood orange'); Citrus sinensis (L.) Osbeck 'Blood orange' oil; Sweet orange peel tincture; CITRUS AURANTIUM DULCIS PEEL EXTRACT; CITRUS AURANTIUM DULCIS SEED EXTRACT; CITRUS AURANTIUM DULCIS FLOWER EXTRACT	≥0.1 - ≤1	8028-48-6

Ranges if listed above for hazardous ingredient(s) are prescribed ranges. The actual concentration(s) or actual concentration range(s) are being withheld as a trade secret.

2/14

Section 3. Composition/information on ingredients

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-aid measures

Description of necessary first aid measures		
Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.	
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.	
Skin contact	: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.	
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.	

Most important symptoms/effects, acute and delayed

Potential acute health effect	ts	
Eye contact	:	Causes serious eye irritation.
Inhalation	:	Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
Skin contact	:	Causes skin irritation. May cause an allergic skin reaction.
Ingestion	:	Can cause central nervous system (CNS) depression.
Over-exposure signs/sympt	or	<u>15</u>
Eye contact	:	Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	:	Adverse symptoms may include the following: respiratory tract irritation coughing nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
Skin contact	:	Adverse symptoms may include the following: irritation redness
Date of issue/Date of revision		: 5/12/2025 Date of previous issue : 4/24/2025 Version : 3.3 3/1

Section 4. First-aid measures

Ingestion	:	No specific data.
Indication of immediate me	dica	l attention and special treatment needed, if necessary
Notes to physician	:	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	:	No specific treatment.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

: Use an extinguishing agent suitable for the surrounding fire.
: None known.
: Extremely flammable aerosol. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed.
: Decomposition products may include the following materials: carbon dioxide carbon monoxide
: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures				
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.		
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".		
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).		

 Date of issue/Date of revision
 : 5/12/2025
 Date of previous issue
 : 4/24/2025
 Version
 : 3.3
 4/14

Section 6. Accidental release measures

Methods and materials for containment and cleaning up

Small sp	ill
----------	-----

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Section 7. Handling and storage

Precautions for safe handling	g	
Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing gas. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Protect from sunlight. Store locked up. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name			Exposure limits
acetone			 CA Alberta Provincial (Canada, 6/2018). OEL: 1200 mg/m³ 8 hours. OEL: 1800 mg/m³ 15 minutes. OEL: 500 ppm 8 hours. OEL: 750 ppm 15 minutes. CA British Columbia Provincial (Canada, 6/2022). TWA: 250 ppm 8 hours. STEL: 500 ppm 15 minutes. CA Ontario Provincial (Canada, 6/2019). TWA: 250 ppm 8 hours. STEL: 500 ppm 15 minutes. CA Quebec Provincial (Canada, 6/2022). TWAEV: 250 ppm 8 hours. STEL: 500 ppm 15 minutes. CA Quebec Provincial (Canada, 6/2022). TWAEV: 250 ppm 8 hours. STEV: 500 ppm 15 minutes. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 750 ppm 15 minutes. TWA: 500 ppm 8 hours.
propan-2-ol			CA Alberta Provincial (Canada, 6/2018). OEL: 984 mg/m ³ 15 minutes. OEL: 200 ppm 8 hours.
ate of issue/Date of revision	: 5/12/2025	Date of previous issue	: 4/24/2025 Version : 3.3 5/14

Section 8. Exposure controls/personal protection

OEL: 400 ppm 15 minutes.
OEL: 492 mg/m³ 8 hours.
CA British Columbia Provincial (Canada,
6/2022).
TWA: 200 ppm 8 hours.
STEL: 400 ppm 15 minutes.
CA Ontario Provincial (Canada, 6/2019).
TWA: 200 ppm 8 hours.
STEL: 400 ppm 15 minutes.
CA Quebec Provincial (Canada, 6/2022).
TWAEV: 200 ppm 8 hours.
STEV: 400 ppm 15 minutes.
CA Saskatchewan Provincial (Canada,
7/2013).
STEL: 400 ppm 15 minutes.
TWA: 200 ppm 8 hours.

Biological exposure indices

No exposure indices known.

Appropriate engineering controls	: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measur	<u>s</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. Recommended : 1 - 4 hours (breakthrough time): Protective gloves made of nitrile rubber (material thickness of 0,4 mm); EN 374-5 Cat. III 4 - 8 hours (breakthrough time): Protective gloves made of Viton®/ butyl rubber (material thickness of 0,7 mm); EN388 Cat.II / EN374 Cat.III / EN374-2
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Section 8. Exposure controls/personal protection

Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended : organic vapor (Type AX) and particulate filter

Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

<u>Appearance</u>		
Physical state	:	Aerosol.
Color	:	Colorless.
Odor	:	Characteristic.
Odor threshold	:	Not available.
рН	:	Not applicable.
Melting point/freezing point	:	Not applicable.
Boiling point, initial boiling point, and boiling range	:	Not available.
Flash point	:	Closed cup: Not applicable.
Fire point	:	>200°C (>392°F)
Evaporation rate	:	Not available.
Flammability	:	Highly flammable in the presence of the following materials or conditions: open flames, sparks and static discharge and heat. Flammable in the presence of the following materials or conditions: shocks and mechanical impacts.
Lower and upper explosion limit/flammability limit	:	Not available.
Vapor pressure	:	Not available.
Relative vapor density	:	Not available.
Relative density	:	Not applicable.
Density	:	0.699 g/cm ³
Solubility(ies) Not available.		:
Solubility in water	:	Not available.
Miscible with water	:	No.
Partition coefficient: n- octanol/water	:	Not applicable.
Auto-ignition temperature	:	Not applicable.
Decomposition temperature	:	Not available.
Heat of combustion	:	6.49 kJ/g
Viscosity	:	Kinematic: Not applicable.
Flow time (ISO 2431)	:	Not available.
Particle characteristics		
Median particle size	:	Not applicable.
Aerosol product		
Type of aerosol	:	Spray

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame).
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
acetone	LD50 Oral	Rat	5800 mg/kg	-
propan-2-ol	LD50 Dermal	Rabbit	12800 mg/kg	-
	LD50 Oral	Rat	5000 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
acetone	Eyes - Mild irritant	Human	-	186300 ppm	-
	Eyes - Mild irritant	Rabbit	-	10 uL	-
	Eyes - Moderate irritant	Rabbit	-	24 hours 20 mg	-
	Eyes - Severe irritant	Rabbit	-	20 mg	-
	Skin - Mild irritant	Rabbit	-	395 mg	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 mg	-
propan-2-ol	Eyes - Moderate irritant	Rabbit	-	10 mg	-
	Eyes - Moderate irritant	Rabbit	-	24 hours 100 mg	-
	Eyes - Severe irritant	Rabbit	-	100 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Section 11. Toxicological information

Product/ingredient name	IARC	NTP	ACGIH
acetone	-	-	A4
propan-2-ol	3		A4

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Hydrocarbons, C7, n-alkanes, iso-alkanes, cyclic	Category 3	-	Narcotic effects
acetone	Category 3	-	Narcotic effects
propan-2-ol	Category 3	-	Narcotic effects

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Product/ingredient name	Result
Hydrocarbons, C7, n-alkanes, iso-alkanes, cyclic	ASPIRATION HAZARD - Category 1
Orange, sweet, ext.	ASPIRATION HAZARD - Category 1

Information on the likely : Not available.

routes of exposure

Potential acute health effects

Eye contact	: Causes serious eye irritation.
Inhalation	: Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Ingestion	: Can cause central nervous system (CNS) depression.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure Short term exposure

UNDUGUIU	
-	
	<u>oxpoouro</u>

Date of issue/Date of revision	: 5/12/2025	Date of previous issue	: 4/24/2025	Version : 3.3	9/14
--------------------------------	-------------	------------------------	-------------	---------------	------

Section 11. Toxicological information

Potential immediate effects	t available.	
Potential delayed effects	t available.	
Long term exposure		
Potential immediate effects	t available.	
Potential delayed effects	t available.	
Potential chronic health eff		
Not available.		
General	ce sensitized, a severe allergic reaction may occur when subsequently e very low levels.	xposed
Carcinogenicity	known significant effects or critical hazards.	
Mutagenicity	known significant effects or critical hazards.	
Reproductive toxicity	known significant effects or critical hazards.	

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	(vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
acetone	5800	N/A	N/A	N/A	N/A
propan-2-ol	5000	12800	N/A	N/A	N/A

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
acetone	Acute EC50 11493300 µg/l Fresh water	Algae - Navicula seminulum	96 hours
	Acute EC50 11727900 µg/l Fresh water	Algae - Navicula seminulum	96 hours
	Acute EC50 7200000 μg/l Fresh water	Algae - Selenastrum sp.	96 hours
	Acute EC50 20.565 mg/l Marine water	Algae - <i>Ulva pertusa</i>	96 hours
	Acute EC50 23.5 mg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
	Acute LC50 4.42589 ml/L Marine water	Crustaceans - <i>Acartia tonsa</i> - Copepodid	48 hours
	Acute LC50 7550000 µg/l Fresh water	Crustaceans - Asellus aquaticus	48 hours
	Acute LC50 8098000 µg/l Fresh water	Crustaceans - <i>Ceriodaphnia dubia</i> - Neonate	48 hours
	Acute LC50 11.26487 ml/L Fresh water	Crustaceans - <i>Gammarus pulex</i> - Juvenile (Fledgling, Hatchling, Weanling)	48 hours
	Acute LC50 6000000 µg/l Fresh water	Crustaceans - Gammarus pulex	48 hours
	Acute LC50 7460000 µg/l Fresh water	Daphnia - <i>Daphnia cucullata</i>	48 hours
	Acute LC50 7810000 µg/l Fresh water	Daphnia - <i>Daphnia cucullata</i>	48 hours
Date of issue/Date of revision	: 5/12/2025 Date of previous issue	: 4/24/2025 Version	: 3.3 10/1

Section 12. Ecological information

	Acute LC50 10000 µg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
	Acute LC50 8800000 µg/l Fresh water	Daphnia - <i>Daphnia pulex</i>	48 hours
	Acute LC50 8000 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 7280000 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	Acute LC50 8120000 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	Acute LC50 6210000 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	Acute LC50 5600 ppm Fresh water	Fish - Poecilia reticulata	96 hours
	Chronic NOEC 0.5 ml/L Marine water	Algae - <i>Karenia brevis</i>	96 hours
	Chronic NOEC 100 ul/L Marine water	Algae - Skeletonema costatum	72 hours
	Chronic NOEC 100 ul/L Marine water	Algae - Skeletonema costatum	96 hours
	Chronic NOEC 4.95 mg/l Marine water	Algae - <i>Ulva pertusa</i>	96 hours
	Chronic NOEC 0.016 ml/L Fresh water	Crustaceans - Daphniidae	21 days
	Chronic NOEC 0.1 ml/L Fresh water	Daphnia - <i>Daphnia magna</i> - Neonate	21 days
	Chronic NOEC 5 µg/l Marine water	Fish - <i>Gasterosteus aculeatus</i> - Larvae	42 days
propan-2-ol	Acute EC50 7550 mg/l Fresh water	Daphnia - <i>Daphnia magna</i> - Neonate	48 hours
	Acute LC50 1400000 µg/l Marine water	Crustaceans - Crangon crangon	48 hours
	Acute LC50 4200 mg/l Fresh water	Fish - Rasbora heteromorpha	96 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
acetone	-0.23	-	Low
propan-2-ol	0.05	-	Low
Orange, sweet, ext.	2.78 to 4.88	1.502 to 2.597	Low

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

Section 14. Transport information

	TDG Classification	DOT Classification	IMDG	ΙΑΤΑ
UN number	UN1950	UN1950	UN1950	UN1950
UN proper shipping name	AEROSOLS	Aerosols	AEROSOLS (acetone, butane)	Rerosols, flammable (acetone, butane)
Transport hazard class(es)	2.1	2.1	2.1	2.1
Packing group	-	-	-	-
Environmental hazards	Yes.	No.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Additional inform	ation			
DOT Classificatio	on : <u>Reportal</u> less than quantity) <u>Limited</u> Quantity	the product reportable q transportation requireme quantity Yes. ng instruction Exception	<u>il Index</u> 75 / 15133.3 kg. Package s uantity are not subject to	the RQ (reportable Bulk: None.
IMDG	 The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg <u>Emergency schedules</u> F-D, S-U Special provisions 63, 190, 277, 327, 344, 381, 959 			
ΙΑΤΑ	 The environmentally hazardous substance mark may appear if required by other transportation regulations. <u>Quantity limitation</u> Passenger and Cargo Aircraft: 75 kg. Packaging instructions 203. Cargo Aircraft Only: 150 kg. Packaging instructions: 203. Limited Quantities Passenger Aircraft: 30 kg. Packaging instructions: Y203. <u>Special provisions</u> A145, A167, A802 			Packaging instructions:
Special precaution	upright a		es: always transport in clo ersons transporting the pl e.	

Section 14. Transport information

Transport in bulk according : Not available. to IMO instruments

Section 15. Regulatory information

Canadian lists

Canadian NPRI	: The following components are listed: isopropyl alcohol; ethanol; butane (all isomers);
	butane (all isomers)

CEPA Toxic substances	: The following components are listed: carbon dioxide

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

<u>Interiory net</u>	
Australia	: Not determined.
Canada	: Not determined.
China	: Not determined.
Eurasian Economic Union	: Russian Federation inventory: Not determined.
Japan	: Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined.
New Zealand	: Not determined.
Philippines	: Not determined.
Republic of Korea	: Not determined.
Taiwan	: Not determined.
Thailand	: Not determined.
Turkey	: Not determined.
United States	: Not determined.
Viet Nam	: Not determined.

: 5/12/2025

Section 16. Other information

Date of issue/Date of revision

History	
Date of printing	: 5/14/2025
Date of issue/Date of revision	: 5/12/2025
Date of previous issue	: 4/24/2025
Version	: 3.3
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals HPR = Hazardous Products Regulations IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods

Date of previous issue

: 4/24/2025

Version : 3.3

13/14

Section 16. Other information

LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations

Procedure used to derive the classification

Classification	Justification
FLAMMABLE AEROSOLS - Category 1 GASES UNDER PRESSURE - Compressed gas SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3	On basis of test data On basis of test data Calculation method Calculation method Calculation method Calculation method

References

: Not available.

Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.