

# Cleaners and Degreasers

## Bike Cleaner

### powerful all-purpose material-neutral

The Bike Cleaner removes dirt, degreases and is suitable for all surfaces made of metal, plastic, rubber, carbon, and aluminium. The effective power-cleaner removes even stubborn dirt, such as oil, dried mud, dust, grease, and resin. With the help of the cleaner, the entire bike can be cleaned - from the handlebar to the gears, frame, tyres, spokes, pedals, saddle, and cargo rack. The Bike Cleaner is highly concentrated and can be diluted with water in a ratio of up to 1:40. In addition to manual cleaning, it can also be used in high-pressure cleaners and sprayers. The Bike Cleaner is suitable for all types of bicycles: e-bike, mountain bike, gravel bike, racing bike, trekking bike, city bike, Dutch bike, folding bike, and many more.

#### Technical Data

Specific properties	solvent-free, compatible with oil separators	
Odour	nearly odourless	
Temperature resistance	+5°C to +90°C	
Minimum shelf life at room temperature	24 mon.	

#### Approvals / Guidelines

MIL-Spec	complies with	A-A-59281
----------	---------------	-----------

#### Surface Pre-Treatment

Remove coarse dirt.

#### Application

- rinse the bike thoroughly with clean water
- apply cleaner to the entire bike
- allow to take effect for 3-5 minutes
- wipe with a clean sponge
- treat stubborn dirt repeatedly with Bike Cleaner
- rinse the bike thoroughly with fresh, clean water

#### Storage

Container is pressurised. Protect from direct sunlight and temperatures above +50 °C.

#### Instructions for use

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our EC safety data sheets ([www.weicon.com](http://www.weicon.com)) must be observed.

#### Available sizes

10058947 Bike Cleaner, 500 ml  
10059048 Bike Cleaner, 500 ml

#### Conversion table

(°C x 1.8) + 32 = °F	Nm x 8.851 = lb-in
mm/25.4 = inch	Nm x 0.738 = lb·ft
µm/25.4 = mil	Nm x 141.62 = oz·in
N x 0.225 = lb	mPa·s = cP
N/mm² x 145 = psi	N/cm x 0.571 = lb/in
MPa x 145 = psi	kV/mm x 25.4 = V/mil

To the product detail page:



#### Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON Middle East L.L.C.  
United Arab Emirates  
phone +971 4 880 25 05  
info@weicon.ae

WEICON Inc.  
Canada  
phone +1 877 620 8889  
info@weicon.ca

WEICON Czech Republic s.r.o.  
Czech Republic  
phone +42 (0) 417 533 013  
info@weicon.cz

WEICON Ibérica S.L.  
Spain  
phone +34 (0) 914 7997 34  
info@weicon.es

WEICON GmbH & Co. KG  
(Headquarters) Germany  
phone +49 (0) 251 9322 0  
info@weicon.de

WEICON Italia S.r.l.  
Italy  
phone +39 (0) 010 2924 871  
info@weicon.it

WEICON Romania SRL  
Romania  
phone +40 (0) 3 65 730 763  
office@weicon.com

WEICON SA (Pty) Ltd  
South Africa  
phone +27 (0) 21 709 0088  
info@weicon.co.za

WEICON South East Asia Pte Ltd  
Singapore  
Phone (+65) 6710 7671  
info@weicon.com.sg

WEICON Kimya Sanayi Tic. Ltd. Şti.  
Türkiye  
phone +90 (0) 212 465 33 65  
info@weicon.com.tr