

## Bike Drive Cleaner

### cleans and degreases material-friendly

The Bike Drive Cleaner improves the smooth running of the bicycle chain and the basic lubrication of rear derailleur, chain and sprocket stays intact. The efficient special cleaner is suitable for all-purpose use and cleans, degreases and evaporates without leaving residues. The spray removes dirt from bike chains, chain rings, sprockets, rear derailleur, rims, etc., removes leaked bearing grease, is acid-free, and does not attack the treated surfaces. The cleaner is suitable even for sensitive surfaces, like plastics, rubber materials or carbon. Thanks to its residue-free evaporation, the Bike Drive Cleaner can also be used to remove dirt from brakes and brake surfaces. The cleaner is suitable for all types of bicycles: e-bike, mountain bike, gravel bike, racing bike, trekking bike, city bike, Dutch bike, folding bike, and many more.

#### Technical Data

Specific properties	Eficiente, 95 % contenido de sustancia activa
Odour	solvent
Minimum shelf life at room temperature	24 mon.

#### Approvals / Guidelines

MIL-Spec	complies with	A-A-59281
----------	---------------	-----------

### Application

- spray the part to be cleaned thoroughly from a distance of 5 cm
- allow the cleaner to take effect for a few minutes
- remove coarse dirt with the included brush or with a clean cloth

In case of stubborn dirt, repeat the procedure.

### Storage

Container is pressurised. Protect from direct sunlight and temperatures above +50 °C.

### Instructions for use

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our EC safety data sheets ([www.weicon.com](http://www.weicon.com)) must be observed.

### Available sizes

10058809	Bike Drive Cleaner, 500 ml
10058954	Bike Drive Cleaner, 500 ml

### Conversion table

(°C x 1.8) + 32 = °F	Nm x 8.851 = lb·in
mm/25.4 = inch	Nm x 0.738 = lb·ft
µm/25.4 = mil	Nm x 141.62 = oz·in
N x 0.225 = lb	mPa·s = cP
N/mm² x 145 = psi	N/cm x 0.571 = lb/in
MPa x 145 = psi	kV/mm x 25.4 = V/mil

To the product detail page:



#### Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.