

Care Spray PTFE



4-in-1: cleaner, corrosion protection, lubricant and contact spray special PTFE formulaweather-resistant

With this care product, you can clean your bike and bring back its former shine! The spray serves as cleaner, corrosion protection, lubricant, and contact spray, all rolled into one product, and thanks to its special PTFE formula, it maintains all surfaces on your bike (e.g. frame, spokes, mudguards) gently and reliably. At the same time, the care product leaves a shiny, whether-resistant, non-sticky protective coat. The spray is also suitable for lubricating mechanical components or for maintaining electrical contacts.

The perfect protection for your bike - even in winter!

The Care Spray PTFE is suitable for all types of bicycles: e-bike, mountain bike, gravel bike, racing bike, trekking bike, city bike, Dutch bike, folding bike, and many more.

Note: Do not use on brake discs/brake linings or on tyres!

Technical Data

Specific properties	with PTFE	
Odour	vanilla	
Temperature resistance	-50°C to +210°C	
Minimum shelf life	at room temperature	24 mon.

Surface Pre-Treatment

Pretreat surfaces with WEICON Bike Cleaner or WEICON Bike Drive Cleaner

Application

- shake spray well before use and only apply to dry surfaces
- apply the spray evenly and polish with a soft cloth
- prior to winter storage, apply the spray generously and do not wipe off

Storage

Container is pressurised. Protect from direct sunlight and temperatures above +50 °C.

Instructions for use

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

Available sizes

- 10058805 Care Spray PTFE, 150 ml
- 10058962 Care Spray PTFE, 150 ml

Conversion table

$(^{\circ}\text{C} \times 1.8) + 32 = ^{\circ}\text{F}$
 $\text{mm}/25.4 = \text{inch}$
 $\mu\text{m}/25.4 = \text{mil}$
 $\text{N} \times 0.225 = \text{lb}$
 $\text{N}/\text{mm}^2 \times 145 = \text{psi}$
 $\text{MPa} \times 145 = \text{psi}$

$\text{Nm} \times 8.851 = \text{lb}\cdot\text{in}$
 $\text{Nm} \times 0.738 = \text{lb}\cdot\text{ft}$
 $\text{Nm} \times 141.62 = \text{oz}\cdot\text{in}$
 $\text{mPa}\cdot\text{s} = \text{cP}$
 $\text{N}/\text{cm} \times 0.571 = \text{lb}/\text{in}$
 $\text{kV}/\text{mm} \times 25.4 = \text{V}/\text{mil}$

To the product detail page:



Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON Middle East L.L.C.
United Arab Emirates
phone +971 4 880 25 05
info@weicon.ae

WEICON Czech Republic s.r.o.
Czech Republic
phone +42 (0) 417 533 013
info@weicon.cz

WEICON GmbH & Co. KG
(Headquarters) Germany
phone +49 (0) 251 9322 0
info@weicon.de

WEICON Romania SRL
Romania
phone +40 (0) 3 65 730 763
office@weicon.com

WEICON South East Asia Pte Ltd
Singapore
Phone (+65) 6710 7671
info@weicon.com.sg

WEICON Inc.
Canada
phone +1 877 620 8889
info@weicon.ca

WEICON Ibérica S.L.
Spain
phone +34 (0) 914 7997 34
info@weicon.es

WEICON Italia S.r.l.
Italy
phone +39 (0) 010 2924 871
info@weicon.it

WEICON SA (Pty) Ltd
South Africa
phone +27 (0) 21 709 0088
info@weicon.co.za

WEICON Kimya Sanayi Tic. Ltd. Şti.
Türkiye
phone +90 (0) 212 465 33 65
info@weicon.com.tr