

## Lubricating and Multifunctional Oils

# Fitting Spray

### Free of silicones and resins

WEICON Fitting Spray is a maintenance and care product with high adhesive strength, which contains no silicone, resin, acid or solvents. Thanks to its excellent capillary action and water-rejecting properties, WEICON Fitting Spray reduces friction and wear and suppresses squeaky noises. WEICON Fitting Spray is weather-resistant, protects against corrosion and loosens dirt. It can be used for the lubrication, servicing and maintenance of fittings on windows, doors, gates, garages, tilt-and-turn and shear fittings as well as on hinges and locking mechanisms.

#### Technical data

Odour	odourless
Colour	transparent
Specific properties	resin- and acid-free
Minimum shelf life	at room temperature 24 mon.
Kinematic viscosity (40°C)	70 mm²/s
Kinematic viscosity (100°C)	8 mm²/s
Temperature resistance	-25°C to +120°C

#### Approvals / Guidelines

ISSA Code	53.402.26
IMPA Code	450816
MIL-Spec	complies with MIL-C-1258

### Application

Clean and degrease surfaces. For a better spray function, warm the product up to room temperature. Shake can before use. Spray on from a distance of approx. 15 cm.

### Storage

Container is pressurised. Protect from direct sunlight and temperatures above +50 °C.

### Instructions for use

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our EC safety data sheets ([www.weicon.com](http://www.weicon.com)) must be observed.

### Available sizes

10028235 Fitting Spray, 200 ml, transparent

To the product detail page:



#### Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON Middle East L.L.C.  
United Arab Emirates  
phone +971 4 880 25 05  
[info@weicon.ae](mailto:info@weicon.ae)

WEICON Czech Republic s.r.o.  
Czech Republic  
phone +42 (0) 417 533 013  
[info@weicon.cz](mailto:info@weicon.cz)

WEICON GmbH & Co. KG  
(Headquarters) Germany  
phone +49 (0) 251 9322 0  
[info@weicon.de](mailto:info@weicon.de)

WEICON Romania SRL  
Romania  
phone +40 (0) 3 65 730 763  
[office@weicon.com](mailto:office@weicon.com)

WEICON South East Asia Pte Ltd  
Singapore  
Phone (+65) 6710 7671  
[info@weicon.com.sg](mailto:info@weicon.com.sg)

WEICON Inc.  
Canada  
phone +1 877 620 8889  
[info@weicon.ca](mailto:info@weicon.ca)

WEICON Ibérica S.L.  
Spain  
phone +34 (0) 914 7997 34  
[info@weicon.es](mailto:info@weicon.es)

WEICON Italia S.r.l.  
Italy  
phone +39 (0) 010 2924 871  
[info@weicon.it](mailto:info@weicon.it)

WEICON SA (Pty) Ltd  
South Africa  
phone +27 (0) 21 709 0088  
[info@weicon.co.za](mailto:info@weicon.co.za)

WEICON Kimya Sanayi Tic. Ltd. Şti.  
Türkiye  
phone +90 (0) 212 465 33 65  
[info@weicon.com.tr](mailto:info@weicon.com.tr)