

**Technical Sprays** 

# Release Agents

## **Mould Release Agent**



### Silicone-free sliding and release agent

The high-quality combination of active ingredients consisting of pure natural products has a high sliding effect, which prevents its adhesion to plastics, moulds, metals and tools. WEICON Mould Release Agent can be used in plastic processing and for spraying, pressing, and vacuum deforming.

#### Technical data

Odour		solvent
Colour		colourless, transparent
Specific properties		silicone-free
Silicone-free		yes
Minimum shelf life	at room temperature	24 mon.
Temperature resistance		-20°C to +130°C

#### **Processing**

The surfaces to be treated must be free of grease, dry and clean (Spray Cleaner S). Shake can and spray at a distance of approx. 25 cm.

The special valve makes it possible to work in any position.

#### Storage

Container is pressurised. Protect from direct sunlight and temperatures above +50 °C.

#### Instructions for use

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

#### **Available sizes**

10000154 Mould Release Agent, 400 ml, colourless, transparent



The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the requested properties are recommended. A claim cannot be derived from them.