

## Lubricating and Multifunctional Oils

# Pneuma-Lube

### Lubricant for pneumatic equipment | high content of PTFE

As a lubricating and corrosion protection agent, WEICON Pneuma-Lube is the universal problemsolver for all moving parts in pneumatic equipment and accessories. Its special product formula with a high content of PTFE makes it a multi-purpose product for: lubrication, corrosion protection, cleaning, water displacing and conservation. The product can not only be used in installation or maintenance of pneumatic equipment and accessories, but also on pneumatic tools in operation. Its excellent weathering resistance allows its use in other sectors as well, e.g. in the on- and offshore industry.

#### Technical data

Odour	vanilla
Colour	yellowish
Specific properties	with PTFE
Silicone-free	yes
Minimum shelf life	at room temperature 24 mon.
Kinematic viscosity (40°C)	21 mm <sup>2</sup> /s
Kinematic viscosity (100°C)	4 mm <sup>2</sup> /s
Temperature resistance	-50°C to +210°C

#### Approvals / Guidelines

IMPA Code	450825
MIL-Spec	complies with MIL-C-1258

#### Application

Shake can well and apply from a distance of approx. 5 cm, then allow to take effect for approx. 30 seconds.

#### Storage

Container is pressurised. Protect from direct sunlight and temperatures above +50 °C.

#### Instructions for use

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our EC safety data sheets ([www.weicon.com](http://www.weicon.com)) must be observed.

#### Available sizes

10010547 Pneuma-Lube, 400 ml, yellowish

To the product detail page:



#### Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON Middle East L.L.C.  
United Arab Emirates  
phone +971 4 880 25 05  
[info@weicon.ae](mailto:info@weicon.ae)

WEICON Czech Republic s.r.o.  
Czech Republic  
phone +42 (0) 417 533 013  
[info@weicon.cz](mailto:info@weicon.cz)

WEICON GmbH & Co. KG  
(Headquarters) Germany  
phone +49 (0) 251 9322 0  
[info@weicon.de](mailto:info@weicon.de)

WEICON Romania SRL  
Romania  
phone +40 (0) 3 65 730 763  
[office@weicon.com](mailto:office@weicon.com)

WEICON South East Asia Pte Ltd  
Singapore  
Phone (+65) 6710 7671  
[info@weicon.com.sg](mailto:info@weicon.com.sg)

WEICON Inc.  
Canada  
phone +1 877 620 8889  
[info@weicon.ca](mailto:info@weicon.ca)

WEICON Ibérica S.L.  
Spain  
phone +34 (0) 914 7997 34  
[info@weicon.es](mailto:info@weicon.es)

WEICON Italia S.r.l.  
Italy  
phone +39 (0) 010 2924 871  
[info@weicon.it](mailto:info@weicon.it)

WEICON SA (Pty) Ltd  
South Africa  
phone +27 (0) 21 709 0088  
[info@weicon.co.za](mailto:info@weicon.co.za)

WEICON Kimya Sanayi Tic. Ltd. Şti.  
Türkiye  
phone +90 (0) 212 465 33 65  
[info@weicon.com.tr](mailto:info@weicon.com.tr)