Technical Sprays
Adhesive Lubricants

Top-Lube-Fluid



Nonfood Compounds
Program Listed H2
Registration 152617
NO FOOD CONTACT

Adhesive Lubricant for sensitive areas | NSF registration

WEICON Top-Lube-Fluid is a special adhesive lubricant and has an NSF registration for the foodstuffs sector, which means it can be used in the food and beverage industry and in the pharmaceuticals and cosmetics industries. Top-Lube-Fluid is strongly adherent and pressure-resistant, with excellent capillary action, and is also noise-damping and water-repellent. The spray prevents elongation, friction and wear. Due to its special formula and the resulting NSF registration, WEICON Top-Lube-Fluid can contribute towards the improvement of workplace safety and health protection. The spray can be used on toothed wheels and worm gears, on joints and couplings, on rollers and bearings, on chains and wire cables or on spring assemblies as well as in numerous industrial areas.

Technical data

Odour		neutral
Colour		pale yellow, transparent
Specific properties		synthetic, transparent
Silicone-free		yes
Minimum shelf life	at room temperature	24 mon.
Kinematic viscosity (40°C)		97 mm²/s
Kinematic viscosity (100°C)		13 mm²/s
Temperature resistance		-20°C to +250°C
Compatible with Double Nozzle		no

Approvals / Guidelines

NSF	H2 (FDA 21 CFR)

Application

Spray in sufficient quantity onto the part to be treated and allow to react. If necessary, wipe off with a clean cloth. Repeat process as required. Avoid contact with plastic and varnished surfaces.

Storage

Container is pressurised. Protect from direct sunlight and temperatures above +50 °C.

Instructions for use

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

Available sizes

10039117 Top-Lube-Fluid, 400 ml, pale yellow, transparent

To the product detail page:

Note
The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON Middle East L.L.C.
United Arab Emirates
phone +971 4 880 25 05
info@weicon.ae

WEICON Czech Republic s.r.o.
Czech Republic
phone +42 (0) 417 533 013
info@weicon.cz

WEICON GmbH & Co. KG
(Headquaters) Germany
phone +49 (0) 251 9322 0
info@weicon.de

WEICON Romania SRL
Romania
phone +40 (0) 3 65 730 763
office@weicon.com

WEICON South East Asia Pte Ltd
Singapore
Phone (+65) 6710 7671
info@weicon.com.sg

WEICON Colombia S.A.S
Colombia
Phone: +57 314 793 86 06
Email: info@weicon.co

WEICON Inc.
Canada
phone +1 877 620 8889
info@weicon.ca

WEICON Ibérica S.L.
Spain
phone +34 (0) 914 7997 34
info@weicon.es

WEICON Italia S.r.L.
Italy
phone +39 (0) 010 2924 871
info@weicon.it

WEICON SA (Pty) Ltd
South Africa
phone +27 (0) 21 709 0088
info@weicon.co.za

WEICON Kimya Sanayi Tic. Ltd. Şti.
Türkiye
phone +90 (0) 212 465 33 65
info@weicon.com.tr