

MINIMUM SHELF LIFE

(from date of delivery)

Product	Months	Storage temperature	
2-Component Adhesives and Sealants			
Plastic Metal			
WEICON A; B; Ceramic HC 220; HT 111; WR; WR2; HP; Ceramic BL; ST; BR; TI; UW; HB 300; Ceramic W; WAL 04; WAL 06; WP; GL-S; Casting Resin MS 1000; Epoxy Resin Putty; Balancing Putty	36	Room temperature	●
C; CBC; F; F2; SF; WL; GL; Pipe Repair-Kit; Fire Safe; Food Grade, Anti-Static; Anti-Stick; Casting Resin Plus 90	24	Room temperature	●
Repair Kits			
Belt Repair-Kit, Belt Repair-Kit SF	6	Room temperature	●
Pipe Repair-Kit	24	Room temperature	●
Emergency Repair Kits	see individual products		●
Repair Tapes	24	Room temperature	●
Repair Sticks			
Repair Stick (all types)	24	Room temperature	●
Epoxy Adhesives			
Epoxy Minute Adhesive / Set; Aluminium Minute Adhesive / Set; Epoxy Minute Adhesive yellow / Set; Easy-Mix S 50; Easy-Mix N 50; Easy-Mix N 5000; Easy-Mix HT 250; Easy-Mix S 50 yellow; Easy-Mix Metal	18	Room temperature	●
Fast-Metal Minute Adhesive / Set	12	Room temperature	●
Easy-Mix HT 180	24	Room temperature	●
Polyurethane Systems			
Urethane 45; 60; 80; 85; 85 SF; 90 SF	12	Room temperature Air humidity <70 %	●
Easy-Mix PU 90; Easy-Mix PU 240	18	Room temperature Air humidity <70 %	●
Easy-Mix PU Crystal	12	Room temperature Air humidity <70 %	●
Primer G	6	Room temperature Air humidity <70 %	●
Structural Acrylic Adhesives			
RK-1300; RK-1500 Adhesive	12	Room temperature	●
	24	+2°C to +7°C	
Activator for RK-1300 & RK-1500	6	Room temperature	●
	12	+2°C to +7°C	
RK-1300, RK-1500 complete package	6	Room temperature	●
	12	+2°C to +7°C	
RK-7000; RK-7100; RK-7100 black	12	Room temperature	●
	3	Room temperature	
Easy-Mix RK-7200	6	+2°C to +7°C	●
	6	Room temperature	
Easy-Mix RK-7300	6	Room temperature	●
Plastic-Bond / Set	12	Room temperature	●
Easy-Mix PE-PP 45	3	Room temperature	●
	6	+2°C to +7°C	
Easy-Mix PE-PP 50 / Set	3	Room temperature	●
	12	+2°C to +7°C	

*Storage conditions::

● = must be stored refrigerated ● = should be stored refrigerated ● = does not need to be stored refrigerated

Product	Months	Storage temperature	
1-Component Adhesives and Sealants			
WEICONLOCK			
WEICONLOCK (all types with the following exceptions)	24	Room temperature	●
WEICONLOCK® SI 303-31 Pipe and thread sealing	12	Room temperature	●
Gasket Maker	12	Room temperature	●
Plast-o-Seal®	24	Room temperature	●
Thread Sealing Cord DF 175	unlimited	Room temperature	●
Threadlocking Varnish	12	Room temperature	●
Contact Cyanoacrylate Adhesives			
WEICON Contact Cyanoacrylate Adhesives (all types with the following exceptions)	9	Room temperature	●
	12	+2°C to +7°C	
O-Ring Bonding Set	9	Room temperature	●
	12	+2°C to +7°C	
Contact-Filler Set transparent and black	9	Room temperature	●
	12	+2°C to +7°C	
Contact-Filler transparent and black	unlimited	Room temperature	●
Elastic Adhesives			
WEICON Silicones (all types with the following exceptions)	12	Room temperature	●
Silicone A	15	Room temperature	●
WEICON MS Polymers (all types with the following exceptions)	12	Room temperature	●
Flex 310 M® ProSeal	18	Room temperature	●
Flex 310 M® FireSeal	18	Room temperature	●
Flex 310 PU	12	Room temperature	●
Flex+bond®	18	Room temperature	●
Fast-Bond Assembly Adhesive	12	Room temperature	●
Mounting Tape			
Mounting Tape Grey; transparent	12	Room temperature	●
Rubber-Metal Adhesives			
GMK 2410; 2510	12	Room temperature	●
Assembly Adhesive	12	Room temperature	●
Technical Sprays			
WEICON Sprays (all types with the following exceptions)	24	Room temperature	●
Adhesive Spray; removable, extra strong	12	Room temperature	●

*Storage conditions::



● = must be stored refrigerated

● = should be stored refrigerated

● = does not need to be stored refrigerated

Product	Months	Storage temperature	
Technical Liquids			
WEICON Technical Liquids (all types except the following)	24	Room temperature	
All WEICON metal colours	12	Room temperature	
Cleaner M; Adhesive Spray technical liquid	12	Room temperature	
Anti-Seize Assembly Pastes			
WEICON Anti-Seize (all types and containers)	24	Room temperature	
High-Performance Greases			
WEICON Allround Lubricant (all types and containers)	24	Room temperature	
WEICON Silicone Grease	24	Room temperature	
Surface Pre-Treatment			
Activator F	24	Room temperature	
CA-Activator; CA-Activator AC; CA-Activator PS	12	Room temperature	
Primer M 100; Primer K 200	12	Room temperature	
Primer S 300; Primer P 400; Primer E 500	6	Room temperature	
Primer E 73	12	Room temperature	
Contact Primer for Polyolefins	12	Room temperature	
Activating Cleaner	24	Room temperature	
Release Agents			
Mould Release Agent Liquid F 1000; P 500	24	Room temperature	
Auxiliary Materials			
Colour Paste Black	12	Room temperature	
CA-Remover	12	Room temperature	
Smoothing Agent	24	Room temperature	

Date: 10/03/2025

*Storage conditions:



- = must be stored refrigerated
- = should be stored refrigerated
- = does not need to be stored refrigerated

Any specifications and recommendations given in this document do not represent guaranteed characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.