# SAFETY DATA SHEET



According to Work Health and Safety (WHS) Australia

Contact VM 2000 Cyanoacrylate Adhesive

### Section 1. Identification

Product identifier : Contact VM 2000 Cyanoacrylate Adhesive

**Product code** : 124000

#### Relevant identified uses of the substance or mixture and uses advised against

Adhesives

: WEICON GmbH & Co. KG Supplier's details

> Königsberger Str. 25, 48157 Münster, Germany phone:+49 251 93220, email: info@weicon.de, URL: www.weicon.de

e-mail address of person responsible for this SDS

: msds@weicon.de

#### **National contact**

WEICON Australia Pty. Ltd

1/55-65 Christensen Road, Stapylton QLD 4207

Phone: +61 493473383 E-Mail: info@weicon.com.au website: www.weicon.com.au

**Emergency telephone** 

number

: National Poison Information Center: Tel: 131126

TRANSPORT / EMERGENCY CONTACT (24h): Tel: +61 2 8014 4558 (English) TRANSPORT / EMERGENCY CONTACT (24h): Tel.: 1800 074 234 (English)

## Section 2. Hazard(s) identification

Classification of the

substance or mixture

: SKIN CORROSION/IRRITATION - Category 2

SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract

irritation) - Category 3

#### **GHS label elements**

Hazard pictograms



Signal word : WARNING

**Hazard statements** : H315 - Causes skin irritation.

> H319 - Causes serious eye irritation. H335 - May cause respiratory irritation.

**Precautionary statements** 

Prevention : P261 - Avoid breathing vapor.

P264 - Wash thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area. P280 - Wear protective gloves. Wear eye or face protection.

: P304 + P312 - IF INHALED: Call a POISON CENTER or doctor if you feel unwell. Response

P362 + P364 - Take off contaminated clothing and wash it before reuse.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 - If eye irritation persists: Get medical advice or attention.

: P405 - Store locked up. Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.

Disposal : P501 - Dispose of waste according to applicable legislation.

Contact VM 2000 Cyanoacrylate Adhesive

### Section 2. Hazard(s) identification

Supplemental label elements

: Not applicable.

Other hazards which do not : None known.

result in classification

## Section 3. Composition and ingredient information

: Mixture Substance/mixture

Ingredient name	% (w/w)	CAS number	Classification
ethyl 2-cyanoacrylate	≥90	7085-85-0	FLAMMABLE LIQUIDS - Category 4 ACUTE TOXICITY (inhalation) - Category 4 SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
1,4-dihydroxybenzene	<1	123-31-9	ACUTE TOXICITY (oral) - Category 4 SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 SKIN SENSITIZATION - Category 1 GERM CELL MUTAGENICITY - Category 2 CARCINOGENICITY - Category 2

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

The total concentration of ingredients in this product, reported or not in this section, is 100%.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

#### **Description of necessary first aid measures**

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Skin contact

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

### Section 4. First aid measures

#### Ingestion

: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

Eye contactInhalationCauses serious eye irritation.May cause respiratory irritation.

**Skin contact**: Causes skin irritation.

**Ingestion**: No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

**Eye contact**: Adverse symptoms may include the following:

pain or irritation

watering redness

**Inhalation** : Adverse symptoms may include the following:

respiratory tract irritation

coughing

**Skin contact**: Adverse symptoms may include the following:

irritation redness

**Ingestion**: No specific data.

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments**: No specific treatment.

**Protection of first-aiders**: No action shall be taken involving any personal risk or without suitable training. If it

is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person

providing aid to give mouth-to-mouth resuscitation.

#### See toxicological information (Section 11)

### Section 5. Fire-fighting measures

#### **Extinguishing media**

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous thermal decomposition products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide nitrogen oxides

### Section 5. Fire-fighting measures

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure

### Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** 

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

### Section 7. Handling and storage

#### Precautions for safe handling

**Protective measures** 

Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

including any incompatibilities

Conditions for safe storage, : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls and personal protection

#### **Control parameters**

Occupational exposure limits

## Section 8. Exposure controls and personal protection

Ingredient name	Exposure limits
ethyl 2-cyanoacrylate	Safe Work Australia (Australia, 10/2022). [Cyanides (as CN)] Absorbed through skin. TWA: 5 mg/m³, (as CN) 8 hours.
1,4-dihydroxybenzene	Safe Work Australia (Australia, 10/2022). TWA: 2 mg/m³ 8 hours.

# Appropriate engineering controls

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

# Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

### Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. Recommended: 1 - 4 hours (breakthrough time): Protective gloves made of nitrile rubber (material thickness of 0,4 mm); EN 374-5 Cat. III; 4 - 8 hours (breakthrough time): Protective gloves made of Viton®/ butyl rubber (material thickness of 0,7 mm); EN388 Cat.II / EN374 Cat.III / EN374-2

#### **Body protection**

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

#### Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

#### Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: organic vapor (Type AX) and particulate filter

## Section 9. Physical and chemical properties

**Appearance** 

Physical state : Liquid. Color : Colorless. : Characteristic. Odor Odor threshold : Not available. рΗ : Not applicable. Melting point : Not available.

Boiling point, initial boiling point, and boiling range

: >150°C (>302°F)

Flash point : Closed cup: >85°C (>185°F)

Fire point : >100°C (>212°F) : Not available. **Evaporation rate** : Not available. **Flammability** Lower and upper explosion

limit/flammability limit

: Not available.

Vapor pressure : 0.0053 kPa (0.03975 mm Hg) [50°C (122°F)]

Relative vapor density : Not available. Relative density : Not available.

: 1.04 g/cm³ [20°C (68°F)] Density

Solubility(ies)

Not available.

Solubility in water : Not applicable. Partition coefficient: n-: Not applicable.

octanol/water

Auto-ignition temperature

Ingredient name	°C	°F	Method
ethyl 2-cyanoacrylate	480	896	EU A.15
1,4-dihydroxybenzene	515	959	

: Not available. **Decomposition temperature** 

: Dynamic: 1500 mPa·s (1500 cP) Viscosity

Flow time (ISO 2431) : Not available.

**Particle characteristics** 

Median particle size : Not applicable.

## Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous

reactions

: Hazardous reactions or instability may occur under certain conditions of storage or

use.

Conditions to avoid : No specific data.

Incompatible materials : No specific data.

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

# **Section 11. Toxicological information**

#### Information on toxicological effects

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
ethyl 2-cyanoacrylate	LC50 Inhalation Vapor	Rat	21110 mg/m <sup>3</sup>	1 hours
1,4-dihydroxybenzene	LD50 Oral	Rat	302 mg/kg	-

#### **Acute toxicity estimates**

	ATE value
Not available.	

#### **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
ethyl 2-cyanoacrylate	Skin - Mild irritant	Rabbit	-	0.5 gm	-
	Skin - Mild irritant	Rabbit	-	24 hours 500	-
				uL	
1,4-dihydroxybenzene	Skin - Mild irritant	Human	-	2 %	-
	Skin - Severe irritant	Human	-	5 %	-

#### **Conclusion/Summary**

Skin : Irritating to skin.

Eyes : Irritating to eyes.

**Respiratory**: May cause respiratory irritation.

**Sensitization** 

Not available.

#### **Mutagenicity**

Not available.

#### **Carcinogenicity**

Not available.

#### **Reproductive toxicity**

Not available.

#### **Teratogenicity**

Not available.

#### Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
ethyl 2-cyanoacrylate	Category 3	-	Respiratory tract irritation

#### Specific target organ toxicity (repeated exposure)

Not available.

#### **Aspiration hazard**

Not available.

Information on the likely routes of exposure

: Not available.

#### Potential acute health effects

Eye contact : Causes serious eye irritation.Inhalation : May cause respiratory irritation.

**Skin contact**: Causes skin irritation.

# **Section 11. Toxicological information**

**Ingestion** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact**: Adverse symptoms may include the following:

pain or irritation watering redness

**Inhalation** : Adverse symptoms may include the following:

respiratory tract irritation

coughing

**Skin contact**: Adverse symptoms may include the following:

irritation redness

**Ingestion**: No specific data.

#### Delayed and immediate effects and also chronic effects from short and long term exposure

#### **Short term exposure**

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

#### Potential chronic health effects

Not available.

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Teratogenicity : No known significant effects or critical hazards.
 Developmental effects : No known significant effects or critical hazards.
 Fertility effects : No known significant effects or critical hazards.

#### Numerical measures of toxicity

#### **Acute toxicity estimates**

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
ethyl 2-cyanoacrylate	N/A	N/A	N/A	10.555	N/A
1,4-dihydroxybenzene	302	N/A	N/A	N/A	N/A

## **Section 12. Ecological information**

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
1,4-dihydroxybenzene	Acute EC50 130 μg/l Fresh water	Daphnia - <i>Daphnia magna</i> - Larvae	48 hours
	Acute LC50 44 μg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours

Date of issue/Date of revision	: 2/19/2025	Date of previous issue	: 1/9/2025	Version : 3.3	8/11
--------------------------------	-------------	------------------------	------------	---------------	------

Contact VM 2000 Cyanoacrylate Adhesive

# Section 12. Ecological information

#### Persistence and degradability

Not available.

#### Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
1,4-dihydroxybenzene	0.59	3.162	Low

#### **Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

### Section 13. Disposal considerations

**Disposal methods** 

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# **Section 14. Transport information**

	ADG	ADR/RID	IMDG	IATA
UN number	Not available.	Not available.	Not available.	Not available.
UN proper shipping name	Not available.	Not available.	Not available.	Not available.
Transport hazard class(es)	Not available.	Not available.	Not available.	Not available.
Packing group	-	-	-	-
Environmental hazards	No.	No.	No.	No.

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Transport in bulk according : Not available.

to IMO instruments

### Section 15. Regulatory information

#### Standard for the Uniform Scheduling of Medicines and Poisons

Not regulated.

#### Model Work Health and Safety Regulations - Scheduled Substances

No listed substance

#### International regulations

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### **Montreal Protocol**

Not listed.

#### **Stockholm Convention on Persistent Organic Pollutants**

Not listed.

#### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

#### **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

#### **Inventory list**

**Australia** : All components are listed or exempted.

Canada : Not determined.

**China** : All components are listed or exempted.

**Eurasian Economic Union**: Russian Federation inventory: All components are listed or exempted.

Japan : Japan inventory (CSCL): All components are listed or exempted.

Japan inventory (ISHL): Not determined.

**New Zealand** : All components are listed or exempted. **Philippines** : All components are listed or exempted. Republic of Korea : All components are listed or exempted. **Taiwan** : All components are listed or exempted. **Thailand** : All components are listed or exempted. **Turkey** : All components are listed or exempted. **United States** : All components are active or exempted. **Viet Nam** : All components are listed or exempted.

### Section 16. Any other relevant information

<u>History</u>

Date of printing : 2/20/2025 Date of issue/Date of : 2/19/2025

revision

Date of previous issue : 1/9/2025 Version : 3.3

**Key to abbreviations** : ADG = Australian Dangerous Goods

ADR = The European Agreement concerning the International Carriage of

Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

Contact VM 2000 Cyanoacrylate Adhesive

# Section 16. Any other relevant information

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group SUSMP = Standard Uniform Schedule of Medicine and Poisons UN = United Nations

#### Procedure used to derive the classification

Classification	Justification
SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3	Calculation method Calculation method Calculation method

**References**: Not available.

▼ Indicates information that has changed from previously issued version.

#### **Notice to reader**

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.