SAFETY DATA SHEET



According to Work Health and Safety (WHS) Australia

CA-Primer for Polyolefines

Section 1. Identification

Product identifier : CA-Primer for Polyolefines

Product code : 124500

Relevant identified uses of the substance or mixture and uses advised against

Adhesion promotor

Supplier's details : WEICON GmbH & Co. KG

Königsberger Str. 25, 48157 Münster, Germany phone:+49 251 93220, email: info@weicon.de, URL: www.weicon.de

e-mail address of person responsible for this SDS

: msds@weicon.de

National contact

WEICON Australia Pty. Ltd

1/55-65 Christensen Road, Stapylton QLD 4207

Phone: +61 493473383 E-Mail: info@weicon.com.au website: www.weicon.com.au

Emergency telephone

number

: National Poison Information Center: Tel: 131126

TRANSPORT / EMERGENCY CONTACT (24h): Tel: +61 2 8014 4558 (English) TRANSPORT / EMERGENCY CONTACT (24h): Tel.: 1800 074 234 (English)

Section 2. Hazard(s) identification

Classification of the substance or mixture : FLAMMABLE LIQUIDS - Category 2 ACUTE TOXICITY (oral) - Category 3

SKIN CORROSION/IRRITATION - Category 1B

SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1

GERM CELL MUTAGENICITY - Category 1

CARCINOGENICITY - Category 1

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

ASPIRATION HAZARD - Category 1

GHS label elements

Hazard pictograms :









Signal word : DANGER

Hazard statements : H225 - Highly flammable liquid and vapor.

H301 - Toxic if swallowed.

H304 - May be fatal if swallowed and enters airways. H314 - Causes severe skin burns and eye damage.

H340 - May cause genetic defects.

H350 - May cause cancer.

H372 - Causes damage to organs through prolonged or repeated exposure.

Precautionary statements

Date of issue/Date of revision : 2/19/2025 Date of previous issue : 1/9/2025 Version : 4.3 1/12

Section 2. Hazard(s) identification

Prevention : P201 - Obtain special instructions before use.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P260 - Do not breathe vapor.

P264 - Wash thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P280 - Wear protective gloves, protective clothing and eye or face protection.

: P308 + P313 - IF exposed or concerned: Get medical advice or attention. Response

> P304 + P340, P310 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor. P301 + P310, P330, P331 - IF SWALLOWED: Immediately call a POISON

CENTER or doctor. Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353, P310 - IF ON SKIN (or hair): Take off immediately all

contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER

or doctor.

P363 - Wash contaminated clothing before reuse.

P305 + P351 + P338, P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or doctor.

: P405 - Store locked up. Storage

: P501 - Dispose of waste according to applicable legislation. Disposal

Supplemental label

elements

: Not applicable.

Other hazards which do not : None known.

result in classification

Section 3. Composition and ingredient information

Substance/mixture : Mixture

Ingredient name	% (w/w)	CAS number	Classification
Naphtha (petroleum), hydrotreated light A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C4 through C11 and boiling in the range of approximately minus 20C to 190C (-4F to 374F).	≥90	64742-49-0	FLAMMABLE LIQUIDS - Category 3 SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A GERM CELL MUTAGENICITY - Category 1B CARCINOGENICITY - Category 1A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1 ASPIRATION HAZARD - Category 1
1,8-diazabicyclo[5.4.0]undec-7-ene	≤3	6674-22-2	CORROSIVE TO METALS - Category 1 ACUTE TOXICITY (oral) - Category 3 SKIN CORROSION/IRRITATION - Category 1B SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

The total concentration of ingredients in this product, reported or not in this section, is 100%.

Occupational exposure limits, if available, are listed in Section 8.

Date of issue/Date of revision : 2/19/2025 Date of previous issue : 1/9/2025 Version: 4.3

Section 4. First aid measures

Description of necessary first aid measures

Eye contact : Get medica

: Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes.

Chemical burns must be treated promptly by a physician.

Inhalation : Get medical attention immediately. Call a poison center or physician. Remove

victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention

immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under

medical surveillance for 48 hours.

Skin contact: Get medical attention immediately. Call a poison center or physician. Flush

contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly

before reuse.

Ingestion : Get medical attention immediately. Call a poison center or physician. Wash out

mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such

as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation : No known significant effects or critical hazards.

Skin contact: Causes severe burns.

Ingestion: Toxic if swallowed. May be fatal if swallowed and enters airways.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:

pain watering redness

Inhalation : No specific data.

Skin contact: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

Ingestion: Adverse symptoms may include the following:

stomach pains nausea or vomiting

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments: No specific treatment.

Date of issue/Date of revision : 2/19/2025 Date of previous issue : 1/9/2025 Version : 4.3 3/12

Section 4. First aid measures

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

media

: Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media

: Do not use water jet.

Specific hazards arising

from the chemical

: Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.

Hazardous thermal decomposition products

: Decomposition products may include the following materials: carbon dioxide

carbon dioxide carbon monoxide nitrogen oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Date of issue/Date of revision : 2/19/2025 Date of previous issue : 1/9/2025 Version : 4.3 4/12

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Avoid exposure obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not swallow. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

: Do not store above the following temperature: 25°C (77°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls and personal protection

Control parameters

Occupational exposure limits

None.

Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection

Date of issue/Date of revision : 2/19/2025 Date of previous issue : 1/9/2025 Version : 4.3 5/12

Section 8. Exposure controls and personal protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. Recommended: 1 - 4 hours (breakthrough time): Protective gloves made of nitrile rubber (material thickness of 0,4 mm); EN 374-5 Cat. III; 4 - 8 hours (breakthrough time): Protective gloves made of Viton®/ butyl rubber (material thickness of 0,7 mm); EN388 Cat.II / EN374 Cat.III / EN374-2

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended : organic vapor (Type AX) and particulate filter

Section 9. Physical and chemical properties

Appearance

Flash point

Physical state : Liquid.

Color : Colorless. [Light]
Odor : Characteristic. [Strong]

Odor threshold : Not available.

pH : Not applicable.

Melting point : Not available.

Boiling point, initial boiling : >80°C (>176°F)

point, and boiling range

: Closed cup: -4°C (24.8°F)

Fire point : >200°C (>392°F)

Evaporation rate : Not available.

Flammability : Extremely flammable in the presence of the following materials or conditions: open

flames, sparks and static discharge and heat.

Lower and upper explosion limit/flammability limit

: Lower: 1% Upper: 6.7%

Vapor pressure :

	Vapor Pressure at 20°C		V	Vapor pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
Naphtha (petroleum), hydrotreated light A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C4 through C11 and boiling in the range of approximately minus 20C to 190C (-4F to 374F).	42.15358	5.6	OECD 104	357.48039	47.7	OECD 104

Relative vapor density : Not available.

Relative density : Not available.

Date of issue/Date of revision: 2/19/2025Date of previous issue: 1/9/2025Version: 4.36/12

CA-Primer for Polyolefines

Section 9. Physical and chemical properties

Density : 0.7 g/cm³ [15°C (59°F)]

Solubility(ies)

Not available.

Solubility in water : Not available.

Miscible with water : No.

Partition coefficient: n-

octanol/water

: Not applicable.

Auto-ignition temperature :

Ingredient name	°C	°F	Method
Naphtha (petroleum), hydrotreated light A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C4 through C11 and boiling in the range of approximately minus 20C to 190C (-4F to 374F).	280 to 470	536 to 878	DIN EN 14522

Decomposition temperature: Not available.

Viscosity : Kinematic (40°C (104°F)): <20.5 mm²/s (<20.5 cSt)

Flow time (ISO 2431) : Not available.

Particle characteristics

Median particle size : Not applicable.

Section 10. Stability and reactivity

Reactivity: No specific test data related to reactivity available for this product or its ingredients.

Chemical stability: The product is stable.

Possibility of hazardous

reactions

: Hazardous reactions or instability may occur under certain conditions of storage or

use.

Conditions to avoid : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld,

braze, solder, drill, grind or expose containers to heat or sources of ignition.

Incompatible materials: Reactive or incompatible with the following materials:

oxidizing materials

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Not available.

Acute toxicity estimates

Route	ATE value
Oral	100 mg/kg

Irritation/Corrosion

Not available.

Sensitization

Not available.

Date of issue/Date of revision: 2/19/2025Date of previous issue: 1/9/2025Version: 4.37/12

Section 11. Toxicological information

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
Naphtha (petroleum), hydrotreated light A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C4 through C11 and boiling in the range of approximately minus 20C to 190C (-4F to 374F).	Category 1	-	-

Aspiration hazard

Name	Result
Naphtha (petroleum), hydrotreated light A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C4 through C11 and boiling in the range of approximately minus 20C to 190C (-4F to 374F).	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure

: Not available.

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation : No known significant effects or critical hazards.

Skin contact: Causes severe burns.

Ingestion: Toxic if swallowed. May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact: Adverse symptoms may include the following:

pain watering redness

Inhalation : No specific data.

Skin contact: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

Ingestion: Adverse symptoms may include the following:

stomach pains nausea or vomiting

Delayed and immediate effects and also chronic effects from short and long term exposure

Date of issue/Date of revision: 2/19/2025Date of previous issue: 1/9/2025Version: 4.38/12

Section 11. Toxicological information

Short term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General: Causes damage to organs through prolonged or repeated exposure.

Carcinogenicity: May cause cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity: May cause genetic defects.

Teratogenicity : No known significant effects or critical hazards.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
CA-Primer for Polyolefines 1,8-diazabicyclo[5.4.0]undec-7-ene	100 100			N/A N/A	N/A N/A

Section 12. Ecological information

Toxicity

Not available.

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
hydrotreated light A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C4 through C11 and boiling in the range of approximately minus 20C to 190C (-4F to 374F).	2.2 to 5.2	10 to 2500	High
1,8-diazabicyclo[5.4.0]undec-	1.38	<3.6	Low

Date of issue/Date of revision: 2/19/2025Date of previous issue: 1/9/2025Version: 4.39/12

CA-Primer for Polyolefines

Section 12. Ecological information

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and

Section 14. Transport information

	ADG	ADR/RID	IMDG	IATA
UN number	UN1993	UN2924	UN2924	UN2924
UN proper shipping name	FLAMMABLE LIQUID, N.O.S. (Naphtha (petroleum), hydrotreated light)	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Naphtha (petroleum), hydrotreated light, 1,8-diazabicyclo[5.4.0] undec-7-ene)	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Naphtha (petroleum), hydrotreated light, 1,8-diazabicyclo[5.4.0] undec-7-ene)	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Naphtha (petroleum), hydrotreated light, 1,8-diazabicyclo[5.4.0] undec-7-ene)
Transport hazard class(es)	3	3 (8)	3 (8)	3 (8)
Packing group	II	II	II	II
Environmental hazards	Yes. The environmentally hazardous substance mark is not required.	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.

Additional information

ADR/RID

: The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.

Tunnel code (D/E)

IMDG

The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.

IATA

The environmentally hazardous substance mark may appear if required by other

transportation regulations.

Date of issue/Date of revision : 2/19/2025 Date of previous issue : 1/9/2025 Version: 4.3 10/12

Section 14. Transport information

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Transport in bulk according : Not available.

to IMO instruments

Section 15. Regulatory information

Standard for the Uniform Scheduling of Medicines and Poisons

Not regulated.

Model Work Health and Safety Regulations - Scheduled Substances

No listed substance

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Australia : All components are listed or exempted.

Canada : All components are listed or exempted.

China : All components are listed or exempted.

Eurasian Economic Union: Russian Federation inventory: All components are listed or exempted.

Japan : Japan inventory (CSCL): All components are listed or exempted.

Japan inventory (ISHL): Not determined.

New Zealand : All components are listed or exempted.
Philippines : All components are listed or exempted.
Republic of Korea : All components are listed or exempted.
Taiwan : All components are listed or exempted.
Thailand : All components are listed or exempted.

Turkey: Not determined.

United States : All components are active or exempted.Viet Nam : All components are listed or exempted.

Section 16. Any other relevant information

History

Date of printing : 2/20/2025

Date of issue/Date of : 2/19/2025

revision

Date of previous issue : 1/9/2025 Version : 4.3

Date of issue/Date of revision: 2/19/2025Date of previous issue: 1/9/2025Version: 4.311/12

Section 16. Any other relevant information

Key to abbreviations

: ADG = Australian Dangerous Goods

ADR = The European Agreement concerning the International Carriage of

Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available

SGG = Segregation Group

SUSMP = Standard Uniform Schedule of Medicine and Poisons

UN = United Nations

Procedure used to derive the classification

Classification	Justification
FLAMMABLE LIQUIDS - Category 2 ACUTE TOXICITY (oral) - Category 3 SKIN CORROSION/IRRITATION - Category 1B SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 GERM CELL MUTAGENICITY - Category 1 CARCINOGENICITY - Category 1 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1 ASPIRATION HAZARD - Category 1	On basis of test data Calculation method

References: Not available.

✓ Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Date of issue/Date of revision: 2/19/2025Date of previous issue: 1/9/2025Version: 4.312/12