# SAFETY DATA SHEET



#### According to Work Health and Safety (WHS) Australia

Label Remover

## **Section 1. Identification**

Product identifier	:	Label Remover
Product code	:	152060

#### Relevant identified uses of the substance or mixture and uses advised against

Cleaning agent-Industrial application.-Organic solvents

Supplier's details	: WEICON GmbH & Co. KG Königsberger Str. 25, 48157 Münster, Germany phone:+49 251 93220, email: info@weicon.de, URL: www.weicon.de
e-mail address of person	: msds@weicon.de

e-mail address of person responsible for this SDS

#### National contact

WEICON Australia Pty. Ltd 1/55-65 Christensen Road, Stapylton QLD 4207 Phone: +61 493473383 E-Mail: info@weicon.com.au website: www.weicon.com.au

# Emergency telephone number

: National Poison Information Center: Tel: 131126 TRANSPORT / EMERGENCY CONTACT (24h): Tel: +61 2 8014 4558 (English) TRANSPORT / EMERGENCY CONTACT (24h): Tel.: 1800 074 234 (English)

etien O Herend(e) identification

## Section 2. Hazard(s) identification

Classification of the substance or mixture	: FLAMMABLE LIQUIDS - Category 2 SKIN CORROSION/IRRITATION - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 ASPIRATION HAZARD - Category 1
	ASPIRATION HAZARD - Calegoly T

GHS label elements Hazard pictograms	
Signal word	: DANGER
Hazard statements	<ul> <li>H225 - Highly flammable liquid and vapor.</li> <li>H304 - May be fatal if swallowed and enters airways.</li> <li>H315 - Causes skin irritation.</li> <li>H336 - May cause drowsiness or dizziness.</li> </ul>
Precautionary statements	
Prevention	<ul> <li>P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</li> <li>P261 - Avoid breathing vapor.</li> <li>P264 - Wash thoroughly after handling.</li> <li>P271 - Use only outdoors or in a well-ventilated area.</li> <li>P280 - Wear protective gloves.</li> </ul>
Response	<ul> <li>P304 + P312 - IF INHALED: Call a POISON CENTER or doctor if you feel unwell.</li> <li>P301 + P310, P331 - IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.</li> <li>P362 + P364 - Take off contaminated clothing and wash it before reuse.</li> </ul>

Date of issue/Date of revision	***	Date of previous issue	: 1/9/2025	Version : 5.3 1/12

## Section 2. Hazard(s) identification

Storage	<ul> <li>P405 - Store locked up.</li> <li>P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.</li> </ul>
Disposal	: P501 - Dispose of waste according to applicable legislation.
Supplemental label elements	: Not applicable.

Other hazards which do not : None known. result in classification

## Section 3. Composition and ingredient information

Substance/mixture

: Mixture

Ingredient name	% (w/w)	CAS number	Classification
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	≥75 - ≤90	-	FLAMMABLE LIQUIDS - Category 2 SKIN CORROSION/IRRITATION - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 ASPIRATION HAZARD - Category 1
ethanol	<10	64-17-5	FLAMMABLE LIQUIDS - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

The total concentration of ingredients in this product, reported or not in this section, is 100%.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

#### Description of necessary first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Date of issue/Date of revision	***	Date of previous issue	: 1/9/2025	Version : 5.3 2/12

# Section 4. First aid measures

## Most important symptoms/effects, acute and delayed

Folential acule health enects	3	
Eye contact	:	No known significant effects or critical hazards.
Inhalation	:	Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
Skin contact	:	Causes skin irritation.
Ingestion	:	Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.
Over-exposure signs/sympto	om	<u>IS</u>
Eye contact	:	Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	:	Adverse symptoms may include the following: nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
Skin contact	:	Adverse symptoms may include the following: irritation redness
Ingestion	>	Adverse symptoms may include the following: nausea or vomiting attention and special treatment needed, if necessary
Notes to physician		Treat symptomatically. Contact poison treatment specialist immediately if large
	•	quantities have been ingested or inhaled.
Specific treatments	:	No specific treatment.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

## See toxicological information (Section 11)

## Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use dry chemical, CO <sub>2</sub> , water spray (fog) or foam.
Unsuitable extinguishing media	: Do not use water jet.
Specific hazards arising from the chemical	<ul> <li>Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.</li> </ul>
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Date of issue/Date of revision	***	Date of previous issue	: 1/9/2025	Version : 5.3 3/12

## Section 5. Fire-fighting measures

Special protective	: Fire-fighters should wear appropriate protective equipment and self-contained
equipment for fire-fighters	breathing apparatus (SCBA) with a full face-piece operated in positive pressure
	mode.
Hazchem code	: •3YE

## Section 6. Accidental release measures

Personal precautions, protect	ctive equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	ontainment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble.

explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

## Section 7. Handling and storage

#### Precautions for safe handling

Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Do not swallow. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

# Section 8. Exposure controls and personal protection

#### **Control parameters**

## **Occupational exposure limits**

Ingredient name		Exposure limits
ethanol		Safe Work Australia (Australia, 10/2022). TWA: 1880 mg/m³ 8 hours. TWA: 1000 ppm 8 hours.
Appropriate engineering controls	ventilation or other engineering contaminants below any recom	tion. Use process enclosures, local exhaust controls to keep worker exposure to airborne mended or statutory limits. The engineering controls or dust concentrations below any lower explosive ntilation equipment.
Environmental exposure controls	they comply with the requireme cases, fume scrubbers, filters o	vork process equipment should be checked to ensure ents of environmental protection legislation. In some or engineering modifications to the process reduce emissions to acceptable levels.
Individual protection measur	es	
Hygiene measures	: Wash hands, forearms and fac eating, smoking and using the Appropriate techniques should	e thoroughly after handling chemical products, before lavatory and at the end of the working period. be used to remove potentially contaminated clothing. efore reusing. Ensure that eyewash stations and workstation location.
Eye/face protection	assessment indicates this is ne gases or dusts. If contact is po	an approved standard should be used when a risk ecessary to avoid exposure to liquid splashes, mists, ossible, the following protection should be worn, es a higher degree of protection: chemical splash
Skin protection		
Hand protection	be worn at all times when hand this is necessary. Considering check during use that the glove should be noted that the time to different for different glove man (breakthrough time): Protective 0,4 mm); EN 374-5 Cat. III ; 4	a gloves complying with an approved standard should lling chemical products if a risk assessment indicates the parameters specified by the glove manufacturer, as are still retaining their protective properties. It to breakthrough for any glove material may be nufacturers. Recommended : 1 - 4 hours the gloves made of nitrile rubber (material thickness of a - 8 hours (breakthrough time): Protective gloves material thickness of 0,7 mm); EN388 Cat.II / EN374
Body protection	being performed and the risks before handling this product. V wear anti-static protective cloth	for the body should be selected based on the task involved and should be approved by a specialist Vhen there is a risk of ignition from static electricity, ing. For the greatest protection from static lude anti-static overalls, boots and gloves.
Other skin protection		additional skin protection measures should be ng performed and the risks involved and should be handling this product.
Respiratory protection	appropriate standard or certific respiratory protection program	ntial for exposure, select a respirator that meets the ation. Respirators must be used according to a to ensure proper fitting, training, and other important d : organic vapor (Type AX) and particulate filter

# Section 9. Physical and chemical properties

<u>Appearance</u>		
Physical state	Liquid.	
Color	Colorless.	
Odor	Benzene-like.	
Odor threshold	Not available.	
рН	Not applicable.	
Melting point	<-20°C (<-4°F)	
Boiling point, initial boiling point, and boiling range	78°C (172.4°F)	
Flash point	Closed cup: -9°C (15.8°F)	
Fire point	>200°C (>392°F)	
Evaporation rate	Not available.	
Flammability	Extremely flammable in the presence of the following materials or conditions: ope flames, sparks and static discharge. Highly flammable in the presence of the following materials or conditions: heat.	n
Lower and upper explosion limit/flammability limit	Lower: 0.8% Upper: 7.7%	
Vapor pressure	57.3 kPa (429.79 mm Hg)	
Relative vapor density	Not available.	
Relative density	Not available.	
Density	0.78 g/cm³ [20°C (68°F)]	
Solubility(ies)		
Not available.	* draft aply ***	
Solubility in water	Not available.	
Miscible with water	Not available. Alt ONIV ***	
Partition coefficient: n- octanol/water	Not applicable.	
Auto-ignition temperature	Not applicable.	
Decomposition temperature	Not available.	
Viscosity	Kinematic (room temperature): 0.38 mm²/s (0.38 cSt) Kinematic (40°C (104°F)): <20.5 mm²/s (<20.5 cSt)	
Flow time (ISO 2431)	Not available.	
Particle characteristics		
Median particle size	Not applicable.	
Section 10 Stabili	and reactivity	

## Section 10. Stability and reactivity

Date of issue/Date of revision	**	Date of previous issue : 1/9/2025 Version : 5.3 6/12
Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Incompatible materials	:	Reactive or incompatible with the following materials: oxidizing materials
Conditions to avoid	:	Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Chemical stability	:	The product is stable.
Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.

# Section 11. Toxicological information

#### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
ethanol	LC50 Inhalation Vapor	Rat	124700 mg/m <sup>3</sup>	4 hours
	LD50 Oral	Rat	7 g/kg	-

#### Acute toxicity estimates

Not available.

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
ethanol	Eyes - Mild irritant	Rabbit	-	24 hours 500 mg	-

#### Sensitization

Not available.

#### **Mutagenicity**

Not available.

#### **Carcinogenicity**

Not available.

#### Reproductive toxicity

Not available.

#### **Teratogenicity**

Not available.

# draft only \*\*\*

#### Specific target organ toxicity (single exposure)

\*\*\*

Name	Category	Route of exposure	Target organs
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	Category 3	-	Narcotic effects

#### Specific target organ toxicity (repeated exposure)

Not available.

#### Aspiration hazard

Name	Result
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	ASPIRATION HAZARD - Category 1

# Information on the likely : Not available. routes of exposure

## Potential acute health effects

Eye contact	: No known significant effects or critical hazards.
Inhalation	: Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
Skin contact	: Causes skin irritation.
Ingestion	: Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

#### Symptoms related to the physical, chemical and toxicological characteristics

Date of issue/Date of revision	***
--------------------------------	-----

# Section 11. Toxicological information

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: Adverse symptoms may include the following: nausea or vomiting

#### Delayed and immediate effects and also chronic effects from short and long term exposure

	<u> </u>	
<u>Short term exposure</u>		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Long term exposure		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Potential chronic health effe	ect	s drott oply **
Not available.		
General	:	No known significant effects or critical hazards.
Carcinogenicity	:	No known significant effects or critical hazards.
Mutagenicity	:	No known significant effects or critical hazards.
Teratogenicity	:	No known significant effects or critical hazards.
Developmental effects	:	No known significant effects or critical hazards.
Fertility effects	:	No known significant effects or critical hazards.

#### Numerical measures of toxicity

#### Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	(mg/kg)	Inhalation (gases) (ppm)	(vapors)	Inhalation (dusts and mists) (mg/l)
ethanol	7000	N/A	N/A	124.7	N/A

# Section 12. Ecological information

## **Toxicity**

\*

# Section 12. Ecological information

Product/ingredient name	Result	Species	Exposure
ethanol	Acute EC50 17.921 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute EC50 3306 mg/l Marine water	Algae - <i>Ulva pertusa</i>	96 hours
	Acute EC50 1074 mg/l Fresh water	Crustaceans - <i>Cypris</i> subglobosa	48 hours
	Acute EC50 2 mg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
	Acute EC50 7640 mg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
	Acute EC50 12.9 g/L Fresh water	Fish - Pimephales promelas	96 hours
	Acute EC50 12800 mg/l Fresh water	Fish - Pimephales promelas	96 hours
	Acute LC50 25500 μg/l Marine water	Crustaceans - <i>Artemia</i> <i>franciscana</i> - Larvae	48 hours
	Acute LC50 5577000 μg/l Fresh water	Crustaceans - <i>Ceriodaphnia dubia</i> - Neonate	48 hours
	Acute LC50 3715000 µg/l Fresh water	Crustaceans - <i>Ceriodaphnia dubia</i> - Neonate	48 hours
	Acute LC50 6076000 μg/l Fresh water	Crustaceans - <i>Ceriodaphnia dubia</i> - Neonate	48 hours
*:	Acute LC50 5680 mg/l Fresh water	Daphnia - <i>Daphnia magna</i> - Neonate	48 hours
	Acute LC50 9248000 µg/l Fresh water	Daphnia - <i>Daphnia magna -</i> Neonate	48 hours
	Acute LC50 11000000 µg/l Marine water	Fish - Alburnus alburnus	96 hours
	Acute LC50 42000 μg/l Fresh water	Fish - Oncorhynchus mykiss	4 days
	Acute LC50 12720 ppm Fresh water	Fish - Pimephales promelas	96 hours
	Chronic NOEC 14 ppm Fresh water	Algae - <i>Eutreptiella sp.</i>	96 hours
	Chronic NOEC 350 ppm Fresh water	Algae - Heterosigma akashiwo	96 hours
	Chronic NOEC 50 ul/L Marine water	Algae - <i>Hormosira banksii -</i> Gamete	72 hours
	Chronic NOEC 20 ppm Fresh water	Algae - Prorocentrum minimum	96 hours
	Chronic NOEC 4.995 mg/l Marine water	Algae - <i>Ulva pertusa</i>	96 hours
	Chronic NOEC 100 ul/L Fresh water	Daphnia - <i>Daphnia magna -</i> Neonate	21 days
	Chronic NOEC 0.375 ul/L Fresh water	Fish - <i>Gambusia holbrooki -</i> Larvae	12 weeks

#### Persistence and degradability

Not available.

#### **Bioaccumulative potential**

## Section 12. Ecological information

Product/ingredient name	LogPow	BCF	Potential
ethanol	-0.35	-	Low

Mobility in soil

Soil/water partition : Not available. coefficient (Koc)

Other adverse effects

: No known significant effects or critical hazards.

## Section 13. Disposal considerations

**Disposal methods** 

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

n

## Section 14. Transport information

	ADG	ADR/RID	IMDG	ΙΑΤΑ
UN number	UN1993	UN1993	UN1993	UN1993
UN proper shipping name	FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane, ethanol)	FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane, ethanol)		Flammable liquid, n.o. s. (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane, ethanol)
Transport hazard class(es)	3	3	3	3
Packing group	11	11	11	П
Environmental hazards	Yes. The environmentally hazardous substance mark is not required.	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.

Additional information ADG

: <u>Hazchem code</u> •3YE <u>Special provisions</u> 274 Label Remover

## Section 14. Transport information

ADR/RID	:	The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg. Hazard identification number 33 Limited quantity 1 L Special provisions 601, 274, 640D Tunnel code (D/E) ADR Classification Code: F1
IMDG	:	The marine pollutant mark is not required when transported in sizes of $\leq 5 \text{ L}$ or $\leq 5 \text{ kg}$ . <u>Emergency schedules</u> F-E, _S-E_ <u>Special provisions</u> 274
ΙΑΤΑ	:	The environmentally hazardous substance mark may appear if required by other transportation regulations. <b>Quantity limitation</b> Passenger and Cargo Aircraft: 5 L. Packaging instructions: 353. Cargo Aircraft Only: 60 L. Packaging instructions: 364. Limited Quantities - Passenger Aircraft: 1 L. Packaging instructions: Y341. <b>Special provisions</b> A3
Special precautions for user	:	<b>Transport within user's premises:</b> always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
Transport in bulk according to IMO instruments	:	Not available.

# Section 15. Regulatory information

Standard for the Uniform Scheduling of Medicines and Poisons Not regulated.

Model Work Health and Safety Regulations - Scheduled Substances

No listed substance

#### International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals Not listed.

#### **Montreal Protocol**

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

## Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

## **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

## **Inventory list**

Australia Canada China Eurasian Economic Union Japan	<ul> <li>All components are listed or exempted.</li> <li>All components are listed or exempted.</li> <li>All components are listed or exempted.</li> <li>Russian Federation inventory: Not determined.</li> <li>Japan inventory (CSCL): All components are listed or exempted. Japan inventory (ISHL): Not determined.</li> </ul>
New Zealand Philippines Republic of Korea	<ul> <li>Not determined.</li> <li>Not determined.</li> <li>Not determined.</li> </ul>

\*\*\*

## Section 15. Regulatory information

Taiwan	: Not determined.
Thailand	: Not determined.
Turkey	: All components are listed or exempted.
United States	: Not determined.
Viet Nam	: Not determined.

## Section 16. Any other relevant information

<u>History</u>	
Date of printing	: 2/20/2025
Date of issue/Date of revision	• *** •
Date of previous issue	: 1/9/2025
Version	: 5.3
Key to abbreviations	: ADG = Australian Dangerous Goods ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group SUSMP = Standard Uniform Schedule of Medicine and Poisons UN = United Nations

#### Procedure used to derive the classification

Classification	Justification
FLAMMABLE LIQUIDS - Category 2	On basis of test data
SKIN CORROSION/IRRITATION - Category 2	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) -	Calculation method
Category 3	
ASPIRATION HAZARD - Category 1	Calculation method

References

: Not available.

✓ Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.