# SAFETY DATA SHEET



according to 29 CFR 1910.1200 and ANSI standard Z400.1-2010

WEICON Ceramic HC 220 Epoxy Resin

# Section 1. Identification

GHS product identifier	:	WEICON Ceramic HC 220 Epoxy Resin
Product code	:	105232

Relevant identified uses of the substance or mixture and uses advised against

Epoxy resins

Supplier's details	: WEICON Canada Inc. 20 Steckle Place, Unit 20 Kitchener, Ontario N2E 2C3, CA www.weicon.ca E-mail: info@weicon.ca Telephone: +1-519-896-5252 Telefax: +1-519-896-5254
e-mail address of person responsible for this SDS	: msds@weicon.de
Emergency telephone number	: +1 202 464 2554 / TRANSPORT EMERGENCY CONTACT - USA (24h): Tel: +1 202 464 2554

# Section 2. Hazards identification

OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	: SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A
	SKIN SENSITIZATION - Category 1
GHS label elements	
Hazard pictograms	
Signal word	: Warning
Hazard statements	: H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation.
Precautionary statements	
Prevention	<ul> <li>P280 - Wear protective gloves. Wear eye or face protection.</li> <li>P261 - Avoid breathing vapor.</li> <li>P264 - Wash thoroughly after handling.</li> </ul>
Response	<ul> <li>P362 + P364 - Take off contaminated clothing and wash it before reuse.</li> <li>P363 - Wash contaminated clothing before reuse.</li> </ul>
Storage	: Not applicable.
Disposal	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazards not otherwise classified	: None known.

# Section 3. Composition/information on ingredients

#### Substance/mixture

: Mixture

%	CAS number
≥10 - ≤25	9003-36-5
≥10 - ≤25	1675-54-3
≤10	28768-32-3
≤5	-
<0.1	108-31-6
1.4 1.4	≥10 - ≤25 ≤10 ≤5

## Section 4. First aid measures

#### Description of necessary first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

Potential acute health	<u>n effects</u>
Eye contact	: Causes serious eye irritation.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/	/symptoms
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: No specific data.

# Section 4. First aid measures

Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### See toxicological information (Section 11)

# Section 5. Fire-fighting measures

	•
Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides halogenated compounds
Special protective actions for fire-fighters	<ul> <li>Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.</li> </ul>
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

Personal precautions, protect	iv	e equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for containment and cleaning up	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Date of issue/Date of revision	: 11/21/2023	Date of previous issue	:10/20/2022	Version : 1.03
--------------------------------	--------------	------------------------	-------------	----------------

## Section 6. Accidental release measures

#### Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

# Section 7. Handling and storage

Precautions for safe handling	
Protective measures	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

#### **Control parameters**

#### Occupational exposure limits

Ingredient name	Exposure limits
Formaldehyde, oligomeric reaction products with 1-chloro- 2,3-epoxypropane and phenol	None.
bis-[4-(2,3-epoxipropoxi)phenyl]propane	None.
4,4'-methylenebis[N,N-bis(2,3-epoxypropyl)aniline]	None.
Polyamine amides salts	None.
maleic anhydride	ACGIH TLV (United States, 1/2021). Skin sensitizer. Inhalation sensitizer. TWA: 0.01 mg/m <sup>3</sup> 8 hours. Form: Inhalable fraction and vapor OSHA PEL 1989 (United States, 3/1989). TWA: 0.25 ppm 8 hours. TWA: 1 mg/m <sup>3</sup> 8 hours. NIOSH REL (United States, 10/2020). TWA: 1 mg/m <sup>3</sup> 10 hours. TWA: 0.25 ppm 10 hours. OSHA PEL (United States, 5/2018). TWA: 0.25 ppm 8 hours. TWA: 1 mg/m <sup>3</sup> 8 hours.

# Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

# Section 8. Exposure controls/personal protection

Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection meas	sures
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. Recommended : 1 - 4 hours (breakthrough time): nitrile rubber ; 4 - 8 hours (breakthrough time): Viton®/butyl rubber
Body protection	<ul> <li>Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Other skin protection	<ul> <li>Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended : organic vapor (Type AX) and particulate filter

# Section 9. Physical and chemical properties

#### **Appearance**

Physical state	: Liquid.
Color	: Dark grey.
Odor	: Bland.
Odor threshold	: Not available.
рН	: Not applicable.
Melting point/freezing point	: Not available.
Boiling point, initial boiling point, and boiling range	: >200°C (>392°F)
Flash point	: Closed cup: >200°C (>392°F)
Evaporation rate	: Not available.
Flammability	: Not available.
Lower and upper explosion limit/flammability limit	: Not available.
Vapor pressure	:

# Section 9. Physical and chemical properties

		Vapor Press	sure at 20°C	\ \	/apor pres	sure at 50°C
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
Formaldehyde, oligomeric reaction products with 1-chloro- 2,3-epoxypropane and phenol	0.62	0.083	EU A.4			
maleic anhydride	0.25	0.033				
Relative vapor density	: Not availa	ble.				
Relative density	: Not availa	ble.				
Density	: 1.8 g/cm <sup>3</sup>	[20°C (68°F	)]			
Solubility(ies)	:					
Not available.						
olubility in water	: Not availa	ble.				
liscible with water	: No.					
Partition coefficient: n- octanol/water	: Not applic	able.				
uto-ignition temperature	: Not applic	able.				
Decomposition temperature	: Not availa	ble.				
/iscosity	: Dynamic:	153000 mPa	a·s (153000 cP)			
low time (ISO 2431)	: Not availa	ble.				
Particle characteristics						
Median particle size	: Not applic	able.				

# Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# Section 11. Toxicological information

#### Information on toxicological effects

Acute	<u>toxicity</u>
-------	-----------------

Product/ingredient name	Result	Species	Dose	Exposure
maleic anhydride	LD50 Dermal	Rabbit	2620 mg/kg	-
	LD50 Oral	Rat	400 mg/kg	-

#### Acute toxicity estimates

Not available.

#### Irritation/Corrosion

# Section 11. Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
maleic anhydride	Eyes - Severe irritant	Rabbit	-	1 %	-

#### Sensitization

Not available.

#### **Mutagenicity**

Not available.

#### **Carcinogenicity**

Not available.

#### **Classification**

Product/ingredient name	OSHA	IARC	NTP
bis-[4-(2,3-epoxipropoxi) phenyl]propane	-	3	-

#### Reproductive toxicity

Not available.

#### **Teratogenicity**

Not available.

#### Specific target organ toxicity (single exposure)

Not available.

#### Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
maleic anhydride	Category 1	inhalation	respiratory system

#### Aspiration hazard

Not available.

Information on the likely routes of exposure	: Not available.
Potential acute health effect	t <u>s</u>
Eye contact	: Causes serious eye irritation.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
Symptoms related to the ph	vsical, chemical and toxicological characteristics
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: No specific data.

# Skin contact : Adverse symptoms may include the following: irritation redness Ingestion : No specific data.

#### Delayed and immediate effects and also chronic effects from short and long term exposure Short term exposure

Date of issue/Date of revision: 11/21/2023Date of previous issue: 10/20/2022Version: 1.03

# Section 11. Toxicological information

Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health eff	ects
Not available.	
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.

# Section 12. Ecological information

<u>Toxicity</u>

Product/ingredient name	Result	Species	Exposure
maleic anhydride	Acute LC50 230 ppm Fresh water	Fish - <i>Gambusia affinis</i> - Adult	96 hours

#### Persistence and degradability

Not available.

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	2.7	-	Low
4,4'-methylenebis[N,N-bis (2,3-epoxypropyl)aniline]	2.12	-	Low
maleic anhydride	-2.78	-	Low

#### Mobility in soil

Soil/water partition coefficient (Koc)	: Not available.
Other adverse effects	: No known significant effects or critical hazards.

# Section 13. Disposal considerations

**Disposal methods** 

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

	-		-	-	
	DOT Classification	TDG Classification	Mexico Classification	IMDG	ΙΑΤΑ
UN number	UN3082	UN3082	UN3082	UN3082	UN3082
UN proper shipping name	Environmentally hazardous substance, liquid, n.o.s.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis-[4- (2,3-epoxipropoxi) phenyl]propane, Formaldehyde, oligomeric reaction products with 1-chloro- 2,3-epoxypropane and phenol)	SUBSTANCIA LIQUIDA POTENCIALMENTE PELIGROSA PARA EL MEDIO AMBIENTE, N.E. P. (bis-[4- (2,3-epoxipropoxi) phenyl]propane, Formaldehyde, oligomeric reaction products with 1-chloro- 2,3-epoxypropane and phenol)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis-[4- (2,3-epoxipropoxi) phenyl]propane, Formaldehyde, oligomeric reaction products with 1-chloro- 2,3-epoxypropane and phenol)	Environmentally hazardous substance, liquid, n.o.s. (bis-[4- (2,3-epoxipropoxi) phenyl]propane, Formaldehyde, oligomeric reaction products with 1-chloro- 2,3-epoxypropane and phenol)
Transport hazard class(es)	9	9	9	9	9
Packing group	ш	111	ш	111	Ш
Environmental hazards	Yes.	Yes.	Yes.	Yes.	Yes.

Additional information

DOT Classification	<ul> <li>Non-bulk packages of this product are not regulated as hazardous materials unless transported by inland waterway. This product is not regulated as a hazardous material when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of §§ 173.24 and 173.24a.</li> <li><u>Limited quantity</u> Yes.</li> <li><u>Packaging instruction</u> Exceptions: 155. Non-bulk: 203. Bulk: 241.</li> <li><u>Special provisions</u> 8, 146, 173, 335, IB3, T4, TP1, TP29</li> </ul>
TDG Classification	<ul> <li>Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.43-2.45 (Class 9), 2.7 (Marine pollutant mark). Non-bulk packages of this product are not regulated as dangerous goods when transported by road or rail.</li> <li><u>Explosive Limit and Limited Quantity Index</u> 5 <u>Special provisions</u> 16, 99</li> </ul>

# Section 14. Transport information

•		
Mexico Classification	:	The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg. Special provisions 274, 331, 335
IMDG	:	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. Emergency schedules F-A, S-F Special provisions 274, 335, 969
ΙΑΤΑ	:	This product is not regulated as a dangerous good when transported in sizes of $\leq 5$ L or $\leq 5$ kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8. <b>Quantity limitation</b> Passenger and Cargo Aircraft: 450 L. Packaging instructions: 964. Cargo Aircraft Only: 450 L. Packaging instructions: 964. Limited Quantities - Passenger Aircraft: 30 kg. Packaging instructions: Y964. <b>Special provisions</b> A97, A158, A197
Special precautions for user	:	<b>Transport within user's premises:</b> always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
Transport in bulk according to IMO instruments	:	Not available.

# Section 15. Regulatory information

U.S. Federal regulations	: TSCA 8(a) CDR Exempt/Partial exemption: Not determined
	Clean Water Act (CWA) 311: maleic anhydride
Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)	: Listed
Clean Air Act Section 602 Class I Substances	: Not listed
Clean Air Act Section 602 Class II Substances	: Not listed
DEA List I Chemicals (Precursor Chemicals)	: Not listed
DEA List II Chemicals (Essential Chemicals)	: Not listed
<u>SARA 302/304</u>	
Composition/information	on ingredients
No products were found.	
SARA 304 RQ	: Not applicable.
<u>SARA 311/312</u>	
Classification	: SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1
Composition/information	on ingredients

# Section 15. Regulatory information

	<u>ye</u>	
Name	%	Classification
Formaldehyde, oligomeric reaction products with 1-chloro- 2,3-epoxypropane and phenol	≥10 - ≤25	SKIN IRRITATION - Category 2 SKIN SENSITIZATION - Category 1
bis-[4-(2,3-epoxipropoxi)phenyl] propane	≥10 - ≤25	SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1
4,4'-methylenebis[N,N-bis (2,3-epoxypropyl)aniline]	≤10	SKIN SENSITIZATION - Category 1
Polyamine amides salts	≤5	SKIN IRRITATION - Category 2
maleic anhydride	<0.1	ACUTE TOXICITY (oral) - Category 4 SKIN CORROSION - Category 1B SERIOUS EYE DAMAGE - Category 1 RESPIRATORY SENSITIZATION - Category 1 SKIN SENSITIZATION - Category 1A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

#### State regulations

Massachusetts	:	None of the components are listed.
New York	:	None of the components are listed.
New Jersey	:	None of the components are listed.
Pennsylvania	:	None of the components are listed.
<u>California Prop. 65</u>		

This product does not require a Safe Harbor warning under California Prop. 65.

#### International regulations

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

#### UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

#### Inventory list

:	Not determined. Not determined. Not determined.	
:	Not determined.	
-		
•		
•	Not determined.	
:	Not determined.	
:	Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined.	
:	Russian Federation inventory: Not determined.	
:	Not determined.	
:	Not determined.	
:	Not determined.	
	:	<ul> <li>Not determined.</li> <li>Not determined.</li> <li>Not determined.</li> <li>Russian Federation inventory: Not determined.</li> <li>Japan inventory (CSCL): Not determined.</li> <li>Japan inventory (ISHL): Not determined.</li> <li>Not determined.</li> </ul>

:1.03


# Section 15. Regulatory information

Turkey

- : Not determined.
- United States
- : Not determined.
- Viet Nam
- : Not determined.

## Section 16. Other information

#### Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

#### National Fire Protection Association (U.S.A.)



#### Procedure used to derive the classification

	Classification	Justification
SKIN IRRITATION - Catego EYE IRRITATION - Catego SKIN SENSITIZATION - Ca	ry 2A	Calculation method Calculation method Calculation method
History		
Date of printing	: 11/28/2023	
Date of issue/Date of revision	: 11/21/2023	
Date of previous issue	: 10/20/2022	
Version	: 1.03	
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classificatio IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition co MARPOL = International Convention for the Prevent as modified by the Protocol of 1978. ("Marpol" = ma N/A = Not available SGG = Segregation Group UN = United Nations	efficient ion of Pollution From Ships, 1973
References	: Not available.	

Indicates information that has changed from previously issued version.

#### Notice to reader

## Section 16. Other information

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.