# SAFETY DATA SHEET



according to 29 CFR 1910.1200 and ANSI standard Z400.1-2010

WEICON GL Epoxy Resin

## **Section 1. Identification**

GHS product identifier : WEICON GL Epoxy Resin

Product code : 107001

Relevant identified uses of the substance or mixture and uses advised against

**Epoxy resins** 

Supplier's details : WEICON Canada Inc.

20 Steckle Place, Unit 20

Kitchener, Ontario N2E 2C3, CA

www.weicon.ca

E-mail: info@weicon.ca Telephone: +1-519-896-5252 Telefax: +1-519-896-5254

e-mail address of person responsible for this SDS

: msds@weicon.de

**Emergency telephone** 

: +1 202 464 2554 / TRANSPORT EMERGENCY CONTACT - USA (24h): Tel: +1 202 464 2554

number

### Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard

(29 CFR 1910.1200).

Classification of the

substance or mixture

: SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1

**GHS label elements** 

Hazard pictograms



Signal word : Warning

**Hazard statements** : H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation.

**Precautionary statements** 

**Prevention**: P280 - Wear protective gloves. Wear eye or face protection.

P261 - Avoid breathing vapor.

P264 - Wash thoroughly after handling.

**Response** : P362 + P364 - Take off contaminated clothing and wash it before reuse.

P363 - Wash contaminated clothing before reuse.

**Storage** : Not applicable.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional, national

and international regulations.

Hazards not otherwise

classified

: None known.

Date of issue/Date of revision: 10/20/2022Date of previous issue: 10/19/2022Version: 1.031/12

# Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	%	CAS number
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	≥25 - ≤50	9003-36-5
4,4'-methylenebis[N,N-bis(2,3-epoxypropyl)aniline]	≥10 - ≤25	28768-32-3
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	≤10	25068-38-6
1,6-bis(2,3-epoxypropoxy)hexane	≤10	16096-31-4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

## Section 4. First aid measures

### **Description of necessary first aid measures**

**Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10

minutes. Get medical attention.

**Inhalation**: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If

not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical

attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical

surveillance for 48 hours.

**Skin contact**: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash

contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean

shoes thoroughly before reuse.

**Ingestion**: Wash out mouth with water. Remove dentures if any. If material has been swallowed

and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately.

Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact**: Causes skin irritation. May cause an allergic skin reaction.

**Ingestion**: No known significant effects or critical hazards.

Over-exposure signs/symptoms

**Eye contact**: Adverse symptoms may include the following:

pain or irritation watering redness

**Inhalation** : No specific data.

Date of issue/Date of revision : 10/20/2022 Date of previous issue : 10/19/2022 Version : 1.03 2/12

## Section 4. First aid measures

: Adverse symptoms may include the following:

irritation redness

Ingestion : No specific data.

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

: No specific treatment. Specific treatments

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It may

be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash

contaminated clothing thoroughly with water before removing it, or wear gloves.

### See toxicological information (Section 11)

## Section 5. Fire-fighting measures

### **Extinguishing media**

Suitable extinguishing

media

Unsuitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

: None known.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst.

**Hazardous thermal** decomposition products : Decomposition products may include the following materials:

carbon dioxide carbon monoxide nitrogen oxides

halogenated compounds

Special protective actions

for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is

inadequate. Put on appropriate personal protective equipment.

For emergency responders:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

**Environmental precautions** 

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Date of issue/Date of revision : 10/20/2022 Date of previous issue :10/19/2022 Version: 1.03

## Section 6. Accidental release measures

#### Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

## Section 7. Handling and storage

#### Precautions for safe handling

#### **Protective measures**

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

### Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating. drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

# including any incompatibilities

Conditions for safe storage, : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

#### **Control parameters**

#### Occupational exposure limits

Ingredient name	Exposure limits	
Formaldehyde, oligomeric reaction products with 1-chloro- 2,3-epoxypropane and phenol	None.	
4,4'-methylenebis[N,N-bis(2,3-epoxypropyl)aniline]	None.	
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	None.	
1,6-bis(2,3-epoxypropoxy)hexane	None.	

#### Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

#### **Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

#### Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Date of issue/Date of revision : 10/20/2022 Date of previous issue :10/19/2022 Version: 1.03

# Section 8. Exposure controls/personal protection

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

#### Skin protection

**Hand protection** 

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. Recommended: 1 - 4 hours (breakthrough time): nitrile rubber; 4 - 8 hours (breakthrough time): Viton®/butyl rubber

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** 

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: organic vapor (Type AX) and particulate filter

# Section 9. Physical and chemical properties

**Appearance** 

Physical state: Liquid.Color: Green.Odor: Bland.

Odor threshold : Not available.

pH : Not applicable.

Melting point/freezing point : Not available.

Boiling point, initial boiling : >200°C (>392°F)

point, and boiling range

Flash point : Closed cup: >100°C (>212°F)

**Evaporation rate** : Not available.

**Flammability** : Flammable in the presence of the following materials or conditions: open flames, sparks

and static discharge and heat.

Lower and upper explosion limit/flammability limit

initional initial inity initial

: Not available.

Vapor pressure : 0.01 kPa (0.075006 mm Hg)

**Relative vapor density** : Not available. **Relative density** : Not available.

**Density** : 1.31 g/cm³ [25°C (77°F)]

Solubility(ies) :

Not available.

Solubility in water : Not available.

Miscible with water : No

Partition coefficient: n-

: Not applicable.

octanol/water

Auto-ignition temperature : Not applicable.

Decomposition temperature : Not available.

Viscosity : Dynamic: 70000 to 100000 mPa·s (70000 to 100000 cP)

Flow time (ISO 2431) : Not available.

Date of issue/Date of revision: 10/20/2022Date of previous issue: 10/19/2022Version: 1.035/12

# Section 9. Physical and chemical properties

#### **Particle characteristics**

Median particle size : Not applicable.

# Section 10. Stability and reactivity

**Reactivity**: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability**: The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : No specific data.

**Incompatible materials** : No specific data.

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products should

not be produced.

# Section 11. Toxicological information

#### Information on toxicological effects

#### **Acute toxicity**

Not available.

#### **Acute toxicity estimates**

Not available.

### Irritation/Corrosion

Not available.

#### Sensitization

Not available.

#### **Mutagenicity**

Not available.

#### Carcinogenicity

Not available.

#### Reproductive toxicity

Not available.

#### **Teratogenicity**

Not available.

#### Specific target organ toxicity (single exposure)

Not available.

#### Specific target organ toxicity (repeated exposure)

Not available.

### **Aspiration hazard**

Not available.

Information on the likely routes of exposure

: Not available.

Date of issue/Date of revision: 10/20/2022Date of previous issue: 10/19/2022Version: 1.036/12

# Section 11. Toxicological information

### Potential acute health effects

**Eye contact**: Causes serious eye irritation.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact**: Causes skin irritation. May cause an allergic skin reaction.

**Ingestion**: No known significant effects or critical hazards.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact**: Adverse symptoms may include the following:

pain or irritation watering

watering redness

**Inhalation** : No specific data.

**Skin contact**: Adverse symptoms may include the following:

irritation redness

**Ingestion**: No specific data.

#### Delayed and immediate effects and also chronic effects from short and long term exposure

#### **Short term exposure**

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

#### Potential chronic health effects

Not available.

**General** : Once sensitized, a severe allergic reaction may occur when subsequently exposed to

very low levels.

Carcinogenicity
 Mutagenicity
 No known significant effects or critical hazards.
 Teratogenicity
 No known significant effects or critical hazards.
 Developmental effects
 No known significant effects or critical hazards.
 Fertility effects
 No known significant effects or critical hazards.
 No known significant effects or critical hazards.

# **Section 12. Ecological information**

#### **Toxicity**

Not available.

#### Persistence and degradability

Not available.

### **Bioaccumulative potential**

Date of issue/Date of revision: 10/20/2022Date of previous issue: 10/19/2022Version: 1.037/12

# Section 12. Ecological information

Product/ingredient name	LogPow	BCF	Potential
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	2.7	-	Low
4,4'-methylenebis[N,N-bis (2,3-epoxypropyl)aniline]	2.12	-	Low
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	2.64 to 3.78	31	Low
1,6-bis(2,3-epoxypropoxy) hexane	0.822	-	Low

#### **Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

## Section 13. Disposal considerations

#### Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# **Section 14. Transport information**

	<u> </u>				
	DOT Classification	TDG Classification	Mexico Classification	IMDG	IATA
UN number	UN3082	UN3082	UN3082	UN3082	UN3082
UN proper shipping name	Environmentally hazardous substance, liquid, n.o.s.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Formaldehyde, oligomeric reaction products with 1-chloro- 2,3-epoxypropane and phenol, 4,4'- methylenebis[N,N- bis (2,3-epoxypropyl) aniline])	SUBSTANCIA LIQUIDA POTENCIALMENTE PELIGROSA PARA EL MEDIO AMBIENTE, N.E. P. (Formaldehyde, oligomeric reaction products with 1-chloro- 2,3-epoxypropane and phenol, 4,4'- methylenebis[N,N- bis (2,3-epoxypropyl) aniline])	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Formaldehyde, oligomeric reaction products with 1-chloro- 2,3-epoxypropane and phenol, 4,4'- methylenebis[N,N- bis (2,3-epoxypropyl) aniline])	Environmentally hazardous substance, liquid, n.o.s. (Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol, 4,4'-methylenebis[N,N-bis (2,3-epoxypropyl) aniline])
	1	†	1	1	

Date of issue/Date of revision: 10/20/2022Date of previous issue: 10/19/2022Version: 1.038/12

# **Section 14. Transport information**

Transport hazard class(es)	9	9	9	9	9
Packing group	III	III	III	III	III
Environmental hazards	Yes.	Yes.	Yes.	Yes.	Yes.

#### **Additional information**

**DOT Classification** 

: Non-bulk packages of this product are not regulated as hazardous materials unless transported by inland waterway. This product is not regulated as a hazardous material when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of §§ 173.24 and 173.24a.

Limited quantity Yes.

Packaging instruction Exceptions: 155. Non-bulk: 203. Bulk: 241.

Special provisions 8, 146, 173, 335, IB3, T4, TP1, TP29

**TDG Classification** : Product classified as per the following sections of the Transportation of Dangerous

Goods Regulations: 2.43-2.45 (Class 9), 2.7 (Marine pollutant mark).

Non-bulk packages of this product are not regulated as dangerous goods when

transported by road or rail.

**Explosive Limit and Limited Quantity Index** 5

Special provisions 16, 99

**Mexico Classification** : The environmentally hazardous substance mark is not required when transported in

sizes of ≤5 L or ≤5 kg.

Special provisions 274, 331, 335

**IMDG** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or

≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and

4.1.1.4 to 4.1.1.8.

Emergency schedules F-A, S-F Special provisions 274, 335, 969

**IATA** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or

≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and

5.0.2.8.

Quantity limitation Passenger and Cargo Aircraft: 450 L. Packaging instructions: 964. Cargo Aircraft Only: 450 L. Packaging instructions: 964. Limited Quantities - Passenger

Aircraft: 30 kg. Packaging instructions: Y964.

Special provisions A97, A158, A197

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in the

event of an accident or spillage.

Transport in bulk according : Not available.

to IMO instruments

# Section 15. Regulatory information

U.S. Federal regulations

: TSCA 5(a)2 final significant new use rules: 1,6-bis(2,3-epoxypropoxy)hexane

TSCA 5(e) substance consent order: 1,6-bis(2,3-epoxypropoxy)hexane

TSCA 8(a) CDR Exempt/Partial exemption: Not determined TSCA 12(b) one-time export: 1,6-bis(2,3-epoxypropoxy)hexane

Clean Air Act Section 112

(b) Hazardous Air Pollutants (HAPs) : Not listed

Clean Air Act Section 602 Class I Substances

: Not listed

Date of issue/Date of revision

: 10/20/2022

Date of previous issue

:10/19/2022

Version: 1.03

# Section 15. Regulatory information

Clean Air Act Section 602

**Class II Substances** 

: Not listed

**DEA List I Chemicals** 

: Not listed

(Precursor Chemicals)

**DEA List II Chemicals** 

: Not listed

(Essential Chemicals)

**SARA 302/304** 

**Composition/information on ingredients** 

No products were found.

SARA 304 RQ : Not applicable.

**SARA 311/312** 

Classification : SKIN IRRITATION - Category 2

> EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1

#### **Composition/information on ingredients**

Name	%	Classification
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	≥25 - ≤50	SKIN IRRITATION - Category 2 SKIN SENSITIZATION - Category 1
4,4'-methylenebis[N,N-bis (2,3-epoxypropyl)aniline]	≥10 - ≤25	SKIN SENSITIZATION - Category 1
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	≤10	SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1
1,6-bis(2,3-epoxypropoxy) hexane	≤10	SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1

#### State regulations

**Massachusetts** : None of the components are listed. **New York** : None of the components are listed. **New Jersey** : None of the components are listed. Pennsylvania : None of the components are listed.

California Prop. 65

This product does not require a Safe Harbor warning under California Prop. 65.

### **International regulations**

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### **Montreal Protocol**

Not listed.

### Stockholm Convention on Persistent Organic Pollutants

Not listed.

### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

### **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

Date of issue/Date of revision : 10/20/2022 Date of previous issue :10/19/2022 Version: 1.03 10/12

# Section 15. Regulatory information

#### **Inventory list**

Australia : All components are listed or exempted.

Canada : All components are listed or exempted.

China : All components are listed or exempted.

**Eurasian Economic Union**: Russian Federation inventory: All components are listed or exempted.

**Japan** : **Japan inventory (CSCL)**: All components are listed or exempted.

Japan inventory (ISHL): Not determined.

**New Zealand** : All components are listed or exempted.

Philippines : Not determined.

Republic of Korea: All components are listed or exempted.Taiwan: All components are listed or exempted.Thailand: All components are listed or exempted.

Turkev : Not determined.

United States : All components are active or exempted.Viet Nam : All components are listed or exempted.

### **Section 16. Other information**

### **Hazardous Material Information System (U.S.A.)**



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

#### **National Fire Protection Association (U.S.A.)**



#### Procedure used to derive the classification

Classification	Justification
EYE IRRITATION - Category 2A	Calculation method Calculation method Calculation method

#### **History**

Date of printing : 11/28/2023 Date of issue/Date of : 10/20/2022

revision

Date of previous issue : 10/19/2022

Version : 1.03

Date of issue/Date of revision: 10/20/2022Date of previous issue: 10/19/2022Version: 1.0311/12

## Section 16. Other information

#### Key to abbreviations

: ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available SGG = Segregation Group

UN = United Nations

**References** : Not available.

Indicates information that has changed from previously issued version.

#### **Notice to reader**

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.



Date of issue/Date of revision : 10/20/2022 Date of previous issue : 10/19/2022 Version : 1.03 12/12